

POWER ENTRY, LOGIC SUPPLY, GROUNDS, DECOUPLING



MOTHERLOOM (Delta pinout, CN1 = in, CN2 = out, wired in parallel)



LINE INPUT — ground-compensated differential receiver



INSERT (send = tip, return = ring, ring normalled to send) + post-insert buffer




OVERLOAD DETECTOR (-+18 dBu)



PFL (pre-fade) SW3: A-B = ON



SOFT MUTE (2x J112 shunt, ~20 ms ramp) SW4: A-B = MUTE



FADER + POST-AMP (+10 dB; omit R38 for unity) JP1 = VCA bypass



AUX SENDS (JP2: 1-2 = PRE; JP3, JP4: 1-2 = POST)



PAN + PAN BUFFERS (AC-coupled outputs)



ROUTING MATRIX (A-B = assigned; off grounds the resistor) 4K7 summing



Nets joined by labels: tidy wiring in Eeschema as needed
Generated from channel_strip_schematic_spec.md v3.0

Sheet: /	
File: channel_strip.kicad_sch	
Title: Channel strip — goa console (Delta-style motherloom)	
Size: A1	Date: 2026-10-19
KiCad E.D.A. 10.0.7	Id: 1/1
	Rev: 3.0