POWER ENTRY (7-pin XLR NC7MD-LX on the rear panel. two 5 A contacts per rail. 18 AWG to this terminal: +-17 V PSU)
MAIN OUTPUTS: DRA134 -> 1Ω NP in the Sense loop -> mute relay (NO) -> XLR mate. pin 2 hot
HEADPHONES: PHONES dual A10K. CPA1612 + LME49600 composite (+9.9 dB). 2R2 out. PHONESGND
REMOTE METER HEADER (for a meter bridge)
METER L: full-wave rectifier. precision peak / average. follower (TL072). 2 dB ladder. 2 x 10-LED strings
METER R: full-wave rectifier. precision peak / average. follower (TL072). 2 dB ladder. 2 x 10-LED strings
AUX MASTER 6: OPA1656 sum (2X || 100Ω) + re-invert. buffer. DRV134 out. AFL
AUX MASTER 5: OPA1656 sum (2X || 100Ω) + re-invert. level. buffer. DRV134 out. AFL
AUX MASTER 6: OPA1656 sum (2X || 100Ω) + re-invert. level. buffer. DRV134 out. AFL
EXT INPUT (2-track / DAW) and MIX / EXT monitor select (SW latched = EXT)
PFL / AFL: OPA1656 sum (2X || 100Ω) + re-invert. SOLO LEVEL. follower
PFL DETECT (1.5 V per press vs 0.7+ V). complementary ramps. rude-solo flasher
PFL SWITCHER: series J112 (Delta E0Z7B0 sh.1) -> CR5 L/R followers
CONTROL ROOM: C/ROOM dual A10K. followers. DRV134. mute relays. TRS outs
MASTER FADER (dual 100 mm A10K. pin 1 = GNDA) + post-amps +10 dB
MIX R: summing amp (GCANCEL-referenced). re-inverter. master insert
MIX L: summing amp (GCANCEL-referenced). re-inverter. master insert
GROUND CANCEL BUFFER (feeds every re-inverter summing amps use the raw GCANCEL line)
MOTHERLOOM (master in the center: CN1 = left wing. CN2 = right wing: Delta pinout)
DISTRIBUTION (PTC per wing per rail. 1.6 A hold. 72 V. local branches VA audio. VP phones. VM meters. VL logic)
MAIN OUTPUTS: DRA134 -> 1Ω NP in the Sense loop -> mute relay (NO) -> XLR mate. pin 2 hot
MONO: inverting sum of POST L+R. re-inverter
MASTER FADER (dual 100 mm A10K. pin 1 = GNDA) + post-amps +10 dB
MIX R: summing amp (GCANCEL-referenced). re-inverter. master insert
MIX L: summing amp (GCANCEL-referenced). re-inverter. master insert
GROUND CANCEL BUFFER (feeds every re-inverter summing amps use the raw GCANCEL line)
MOTHERLOOM (master in the center: CN1 = left wing. CN2 = right wing: Delta pinout)
DISTRIBUTION (PTC per wing per rail. 1.6 A hold. 72 V. local branches VA audio. VP phones. VM meters. VL logic)