Hyperlocal Air Quality Mapping in Chicago

A Citizen Science Project in Urban Aerosol Transport

PhD Research Project | Northwestern University

Department of Physics | Soft Condensed Matter & Fluid Dynamics

2026 – 2027

Hardware instrumentation · Open dataset · Urban aerosol physics · Citizen science

Contents

1 Project Summary **3**

2 Scientific Goals and Hypotheses **4**
2.1 H1 — Street Canyon Recirculation . . . 4
2.2 H2 — Gaussian Plume Dispersion from Highway Line Sources . . . 4
2.3 H3 — Stokes-Number-Dependent Particle Separation . . . 5
2.4 H4 — Lake Breeze Effects on Near-Surface Pollutant Concentrations . . . 5
2.5 Ancillary Goal — Open Dataset Publication . . . 5

3 Hardware Build List **6**

4 Step-by-Step Build Instructions **8**
4.1 Hardware Assembly . . . 8
4.1.1 Step 1 — Prepare the Raspberry Pi Zero 2W . . . 8
4.1.2 Step 2 — Wire the SEN54 via I^2C . . . 8
4.1.3 Step 3 — Wire the GPS Module via UART . . . 8
4.1.4 Step 4 — Enclosure and Weatherproofing . . . 8
4.2 Software Setup . . . 8
4.2.1 Step 1 — Install Raspberry Pi OS Lite . . . 8
4.2.2 Step 2 — Enable Interfaces . . . 9
4.2.3 Step 3 — Install Python Dependencies . . . 9
4.2.4 Step 4 — Configure `gpsd` . . . 9
4.2.5 Step 5 — Deploy the Logging Script . . . 9
4.2.6 Step 6 — Auto-Start on Boot . . . 9
4.2.7 Step 7 — Pre-Run Calibration . . . 9

5 Data Collection Protocol **10**
5.1 Route Design Strategy . . . 10
5.1.1 Route Family 1 — Street Orientation Transects (for H1) . . . 10
5.1.2 Route Family 2 — Highway Plume Transects (for H2) . . . 10
5.1.3 Route Family 3 — Lakefront Gradient (for H4) . . . 10
5.1.4 Route Family 4 — Point Source Transects (for H3) . . . 10
5.2 Flagging Wind and Weather Conditions . . . 10
5.3 Statistical Power and Required Sample Size . . . 11

6 Data Pipeline **12**
6.0.1 Step 1 — Ingest and Concatenate . . . 12
6.0.2 Step 2 — GPS Quality Filter . . . 12
6.0.3 Step 3 — Sensor Quality Control . . . 12
6.0.4 Step 4 — Time Synchronization . . . 12
6.0.5 Step 5 — Meteorological Data Merge . . . 12
6.0.6 Step 6 — Spatial Binning . . . 12
6.0.7 Step 7 — Final Dataset Schema . . . 13

7 Analysis Roadmap **14**
7.1 Level 1 — Exploratory Spatial Analysis . . . 14

7.2 Level 2 — Statistical Testing of Core Hypotheses 14
7.3 Level 3 — Gaussian Plume Fitting (H2) 14
7.4 Level 4 — Stokes Number Analysis (H3) 15
7.5 Level 5 — Data-Driven Spatial Modeling 15
7.6 Level 6 — Community Impact Map 15

8 Milestone Timeline (6–12 Months) 16

9 How to Present the Final Result 18
9.1 GitHub Repository (Public Portfolio Piece) 18
9.2 Dataset Publication 18
9.3 Blog Post / Public Communication 18
9.4 Conference Presentations 18
9.5 Potential Journal Venues 19

1. Project Summary

Chicago has just five EPA air quality monitoring stations for a city of 2.7 million people—a spatial resolution of roughly one sensor per 540,000 residents. This project deploys a lightweight, wearable sensor package on everyday running and cycling routes to collect fine-grained measurements of particulate matter ($PM_{2.5}$, PM_{10}), volatile organic compounds (VOCs), temperature, humidity, and pressure, each paired with a GPS coordinate and timestamp.

The result will be an open dataset of street-level air quality at spatial resolutions of 5–10 m and time resolutions of 1 s—roughly 100× finer than anything currently publicly available for Chicago. On top of that dataset, the project applies established fluid mechanics and atmospheric physics models (Gaussian plume dispersion, street canyon recirculation, Stokes-number particle sorting, lake breeze dynamics) to turn casual outdoor exercise into a genuine scientific investigation of urban air quality.

This is a solo, end-to-end project: you design the hardware, collect every data point yourself, build the analysis pipeline, and tell the final scientific story—from sensor to published result.

2. Scientific Goals and Hypotheses

Each hypothesis below is specific, directional, and testable with the dataset you will collect. They are ordered from most tractable (large expected signal, few confounders) to most ambitious.

2.1 H1 — Street Canyon Recirculation

When wind blows perpendicular to a row of buildings (a "street canyon"), fluid mechanics predicts that a recirculation vortex forms inside the canyon, trapping pollutants rather than flushing them. Streets parallel to the wind experience ventilation; perpendicular streets do not. This is one of the most robust phenomena in urban meteorology and should produce a large, detectable signal even with modest sampling.

Testable Hypothesis

$PM_{2.5}$ concentrations on streets oriented **perpendicular** to the prevailing wind will be 30–50% higher than on parallel streets of similar traffic density, measured during steady winds $\geq 3\,\mathrm{m\,s^{-1}}$.

Method: Bin routes by street–wind angle (0–30°, 31–60°, 61–90°). One-way ANOVA + Tukey HSD post-hoc test. Report Cohen's d as effect size.
Control variable: Annual average daily traffic (AADT) from IDOT open data.

2.2 H2 — Gaussian Plume Dispersion from Highway Line Sources

A highway acts as a continuous line source of $PM_{2.5}$ and NO_x. Classical atmospheric dispersion theory (Gaussian plume model) predicts that, for a line source long compared with the sampling distance, concentration is uniform *along* the road and falls off with *downwind* distance x through the growth of the vertical dispersion parameter $\sigma_z(x)$, governed by Pasquill–Gifford (PG) atmospheric stability classes. (There is no cross-wind fall-off to fit: an infinite line source is translation-invariant along its own axis, so the perpendicular-transect decay is a σ_z measurement, not a σ_y one.) This is the most directly quantitative hypothesis—fitting the plume model yields physically interpretable parameters (σ_z, line emission rate Q_L) that can be compared to published values.

Testable Hypothesis

$PM_{2.5}$ concentrations on repeated transects across I-90/94 and I-290 will decay with downwind distance in a manner consistent with a ground-level line source whose $\sigma_z(x)$ matches Pasquill–Gifford class D (neutral) stability at the measured wind speeds.

Method: 20+ perpendicular transects per highway. Nonlinear least-squares fit of the ground-level infinite-line-source relation

$$C(x) = \sqrt{\frac{2}{\pi}}\,\frac{Q_L}{\sigma_z(x)\,u}, \qquad \sigma_z(x) = a\,x^b$$

where Q_L is the emission rate *per unit length of road* and u the transport wind speed. Extract $\sigma_z(x)$; compare the exponent b and prefactor a to PG class-D σ_z power-law curves. Estimate Q_L; compare to USEPA NEI emission factors (per-vehicle factor × measured traffic count per unit length). Report the wind angle relative to the road and restrict fits to near-perpendicular transport, since the line-source form assumes flow across the road rather than along it.

2.3 H3 — Stokes-Number-Dependent Particle Separation

Coarse particles (PM_{10} but not $PM_{2.5}$) have a larger Stokes number $\mathrm{St} = \tau_p/\tau_f$, where the particle relaxation time is $\tau_p = \rho_p d_p^2/18\mu$. High-St particles cannot follow rapid changes in airflow and preferentially deposit near their source. Fine particles ($PM_{2.5}$) track the flow and travel farther. This predicts that the $PM_{10}/PM_{2.5}$ mass ratio should decrease with distance from a coarse-particle source and increase with wind speed at fixed distance.

Testable Hypothesis

The $PM_{10}/PM_{2.5}$ mass concentration ratio will decrease monotonically with distance from identified coarse-particle sources (construction sites, unsealed lots) at a rate consistent with Stokes-number-predicted settling velocities for 2.5–10 μm diameter particles.

Method: Characterize 3–5 point sources. Run 10+ transects per source at distances 20, 50, 100, 200 m. Fit exponential decay: $R(r) = R_0 \exp(-\lambda r)$. Interpret λ via theoretical settling velocity $v_s = \rho_p d_p^2 g/18\mu$.

2.4 H4 — Lake Breeze Effects on Near-Surface Pollutant Concentrations

Lake Michigan drives a mesoscale lake breeze circulation on summer afternoons: cool, relatively clean air advects inland, deepening the atmospheric boundary layer (ABL) and diluting near-surface pollutants. This effect should be detectable as a spatial gradient in $PM_{2.5}$ along an east–west transect, conditional on confirmed lake breeze events.

Testable Hypothesis

On confirmed lake breeze days (easterly surface wind, KMDW vs. KORD wind speed divergence), $PM_{2.5}$ concentrations within 1 km of Lake Michigan will be $\geq 20\%$ lower than on matched non-lake-breeze days with similar traffic and time-of-day conditions.

Method: Composite analysis. Lake breeze days identified via NOAA ISD + surface analysis. Matched-pair design (same day-of-week, time-of-day, season). Mann–Whitney U test; effect size $r = Z/\sqrt{N}$.

2.5 Ancillary Goal — Open Dataset Publication

Regardless of hypothesis outcomes, the spatial dataset itself is a novel contribution. No open, street-level, multi-parameter air quality dataset at cycling/running resolution ($\sim$10 m) exists for Chicago. The dataset will be published to Zenodo under a CC-BY 4.0 license with a DOI, and a Data Descriptor submitted to *Earth System Science Data*.

3. Hardware Build List

Total estimated cost: **$165–$185 USD**. All components are commercially available; no specialized lab equipment is required. The Sensirion SEN54 is the non-negotiable core sensor—it combines five measurements into a single factory-calibrated unit with peer-reviewed validation against federal reference instruments (Zimmerman et al., 2018; Tryner et al., 2020).

Component	Notes	Cost	Source
Raspberry Pi Zero 2W	Quad-core 1 GHz, 512 MB RAM. Low-power Linux SBC.	$15	Adafruit, PiShop.us
Sensirion SEN54	$PM_{1/2.5/4/10}$, VOC, T, RH on one I^2C board. Factory-calibrated laser counter.	$45	Mouser, DigiKey
u-blox NEO-M9N GPS	10 Hz, 2.5 m CEP. NMEA over UART. Strong urban canyon performance.	$30	SparkFun #GPS-17285
MicroSD card, 64 GB U3 A2	Class-10 write speed avoids I/O bottlenecks during 1 Hz logging.	$10	Amazon (Samsung Endurance)
USB-C battery, 10,000 mAh	Powers Pi + sensors for 8–10 hrs continuously.	$25	Amazon (Anker PowerCore)
USB-C cable + splitter	Power routing from pack to Pi.	$8	Amazon
JST-SH / Qwiic cable (4-pin)	I^2C connection SEN54 → Pi GPIO.	$5	SparkFun, Adafruit
CP2102 USB–UART adapter	UART connection for GPS; doubles as debug serial port.	$8	Amazon
ABS enclosure 120×80×55 mm	Protects from sweat, rain, condensation. Hammond 1554A or similar.	$12	Amazon
Silica gel packets	Humidity control inside sealed enclosure.	$3	Amazon
40-pin GPIO header	Required for Pi Zero 2W (ships unsoldered).	$3	Adafruit
Jumper wires, heat shrink, tape	Wiring and strain relief.	$8	Amazon / local shop
3D-printed vest/handlebar mount	Attach enclosure to running vest or bike bar. STL files on Thingiverse.	$5	Self-print
Total		**$177**	

Why the SEN54 specifically?

Sensirion's SEN5x series uses a calibrated laser-diffraction optical particle counter with on-board signal processing. Independent laboratory evaluations show $PM_{2.5}$ $R^2 > 0.95$ against FEM reference instruments under most atmospheric conditions. The VOC index is a qualitative relative metric (scale 1–500), not absolute ppb—useful for detecting emission events but not for regulatory comparison.

4. Step-by-Step Build Instructions

4.1 Hardware Assembly

4.1.1 Step 1 — Prepare the Raspberry Pi Zero 2W

1. Solder or press-fit the 40-pin GPIO header if not pre-soldered.
2. Insert a formatted 64 GB microSD card (will be overwritten in §4.2).
3. Do not power on until software is fully installed.

4.1.2 Step 2 — Wire the SEN54 via I^2C

The SEN54 communicates over I^2C at 3.3 V logic. Use 4 wires:

1. **VDD** → Pi GPIO Pin 1 (3.3 V). SEN54 operates at 3.3 V—confirmed safe.
2. **GND** → Pi GPIO Pin 6 (GND).
3. **SDA** → Pi GPIO Pin 3 (I^2C SDA, BCM GPIO2).
4. **SCL** → Pi GPIO Pin 5 (I^2C SCL, BCM GPIO3).
5. Leave the `SEL` pin floating or tie to GND (selects I^2C mode). Default address: `0x69`.
6. Use a Qwiic/JST-SH cable for a secure, rattle-free connection. Protect both ends with heat shrink.

4.1.3 Step 3 — Wire the GPS Module via UART

1. TX (GPS) → RX (Pi GPIO Pin 10, BCM GPIO15).
2. RX (GPS) → TX (Pi GPIO Pin 8, BCM GPIO14).
3. VCC (GPS) → 5 V or 3.3 V depending on your module—check the datasheet.
4. GND (GPS) → Pi GPIO Pin 14.
5. *Note:* Disable the Pi's serial console via `raspi-config` before using UART for GPS.

4.1.4 Step 4 — Enclosure and Weatherproofing

1. Drill two holes in the ABS lid: one for the SEN54 inlet/outlet ports (must be open to air flow), one for the USB-C power cable.
2. Use M12 weatherproof cable glands at all entry points.
3. Place silica gel packets inside to control interior humidity.
4. Mount Pi, battery, and sensors with double-sided foam tape or M2.5 standoffs.
5. Test fit: all cables should have slack; no stress on connectors when lid is closed.
6. Attach to running vest or handlebar with zip ties or outdoor-rated Velcro. Orient so the SEN54 inlet faces into oncoming airflow.

4.2 Software Setup

4.2.1 Step 1 — Install Raspberry Pi OS Lite

1. Download Raspberry Pi OS Lite (64-bit, Bookworm) from `https://raspberrypi.com`.
2. Flash to microSD using Raspberry Pi Imager. In Advanced Options: set hostname, enable SSH, set home WiFi credentials.
3. Boot, SSH in: `ssh pi@<hostname>.local`

4.2.2 Step 2 — Enable Interfaces

1. Run `sudo raspi-config`
2. Interface Options → I^{2}C: **Enable**.
3. Interface Options → Serial Port: disable the login shell; enable the hardware serial port.
4. Reboot. Verify with `i2cdetect -y 1`—you should see `0x69` (SEN54).

4.2.3 Step 3 — Install Python Dependencies

1. `sudo apt update && sudo apt install -y python3-pip python3-serial gpsd gpsd-clients`
2. `pip3 install sensirion-i2c-driver sensirion-i2c-sen5x pynmea2`
3. `pip3 install pandas pyserial`

4.2.4 Step 4 — Configure gpsd

1. Edit `/etc/default/gpsd`: set `DEVICES="/dev/ttyS0"` and `GPSD_OPTIONS="-n"`.
2. `sudo systemctl enable gpsd && sudo systemctl start gpsd`
3. Test: `cgps -s`—should show lat/lon within 60 s in open sky.

4.2.5 Step 5 — Deploy the Logging Script

Create `/home/pi/airlog/logger.py`. The core loop reads sensor and GPS at 1 Hz and writes one row per second to a date-stamped CSV:

Logger Script—Core Logic (Python pseudocode)

```
sensor = Sen5xI2cDevice(I2cConnection(i2c_transceiver))
sensor.start_measurement()
gps_ser = serial.Serial('/dev/ttyS0', 9600, timeout=1)

with open(f'/data/airlog_{date.today()}.csv', 'w') as f:
writer.writerow(['timestamp','lat','lon','pm1','pm25',
'pm4','pm10','voc_index','temp_c',
'rh_pct','fix_quality','n_sats'])
while True:
parse $GNGGA NMEA sentence → lat, lon, fix, sats
read sensor → pm1, pm25, pm4, pm10, rh, temp, voc
write row with datetime.utcnow().isoformat()
time.sleep(1) # 1 Hz sampling rate
```

4.2.6 Step 6 — Auto-Start on Boot

1. Create `/etc/systemd/system/airlog.service` with `ExecStart` pointing to `logger.py`.
2. `sudo systemctl enable airlog && sudo systemctl start airlog`
3. Reboot; verify CSVs appear in `/data/` within 30 s.

4.2.7 Step 7 — Pre-Run Calibration

- Co-locate the SEN54 beside a PurpleAir or IQAir AirVisual for 24 hrs. Record any systematic $PM_{2.5}$ offset. If offset $> 15\%$, document a correction factor.
- Verify GPS cold-start time < 90 s in open sky.
- Log a 10-minute stationary test. Verify timestamps are UTC, lat/lon stable, all columns populated.

5. Data Collection Protocol

5.1 Route Design Strategy

Routes are designed to isolate specific independent variables, not chosen at random. Build four route families:

5.1.1 Route Family 1 — Street Orientation Transects (for H1)

- Design 3–5 matched pairs: one block running N–S, one E–W, within 200 m of each other with comparable building height and traffic density.
- Target Chicago's grid: Wacker, Michigan Ave, State St vs. adjacent cross-streets.
- Run each pair on the same day within 30 min so meteorological conditions are identical.
- **Go/no-go condition:** steady wind $\geq 3\,\mathrm{m\,s^{-1}}$. Check ASOS KMDW before leaving.

5.1.2 Route Family 2 — Highway Plume Transects (for H2)

- Target two highways: I-90/94 (Dan Ryan Expressway) and I-290 (Eisenhower Expressway).
- Design perpendicular transects at 25, 50, 100, 200, and 400 m downwind from the highway centerline.
- A transect is only valid when wind is blowing from the highway toward you (confirmed from KMDW obs.).
- Run consistently at 7–9 AM (peak traffic) for comparability across dates.

5.1.3 Route Family 3 — Lakefront Gradient (for H4)

- Design an E–W transect from the lakefront (e.g., Montrose Beach, 41.96° N) inland ~ 5 km.
- Collect data on lake breeze days and non-lake-breeze days; label using NOAA ISD wind records.
- Minimum 10 lake breeze runs and 10 matched control runs for adequate comparison.

5.1.4 Route Family 4 — Point Source Transects (for H3)

- Identify 3–5 active construction sites or unsealed lots. Confirm still active before each run.
- Run at 20, 50, 100, and 200 m from the source boundary on concentric arcs.
- Target steady moderate winds ($\geq 4\,\mathrm{m\,s^{-1}}$, from source toward runner).

5.2 Flagging Wind and Weather Conditions

For every run, record the following alongside the sensor data:

Variable	Source	How to Record
Wind speed (10 m)	NOAA ASOS KMDW or KORD	Iowa State Mesonet API; log obs. at start and end of run
Wind direction	Same ASOS station	Bin into 8 cardinal directions. Flag runs with variable wind ($> 45°$ std. dev.)
Stability class	Wind speed + cloud cover + solar elevation	Pasquill–Gifford table (Seinfeld & Pandis, Table 4.2)
Precipitation	NWS observed	Exclude runs during or within 2 hrs of rain (wet deposition removes PM)
Mixing layer height	NOAA HRRR model (hourly)	AWS Open Data. Low MLH ($\leq$ 500 m) = pollution trapping event
Lake breeze flag	KMDW vs. KORD wind divergence	Binary yes/no per run; confidence notes in field log
Traffic proxy	Time of day + day of week	AM peak (7–9), midday (10–15), PM peak (16–19), off-peak

5.3 Statistical Power and Required Sample Size

Estimates assume $\alpha = 0.05$, power $= 0.80$, effect sizes from published urban air quality literature.

Hypothesis	Expected Effect	Runs Needed	Running Total
H1: Street canyon	Cohen's $d \approx 0.8$, 30–50% $PM_{2.5}$ difference	~60 route segments	60
H2: Highway plume	Gaussian fit $R^2 > 0.7$	40 transects (2 highways)	100
H3: Particle separation	Moderate effect, high variability	40 transects (4 sources)	140
H4: Lake breeze	20–30% PM reduction	20 runs	160
Buffer / exploratory	Opportunistic repeats	+40 runs	**200**

Bottom line: ~200 total logged runs over 6–12 months. At 3–4 runs per week (integrated into your normal exercise habit), this is achievable in 50–67 weeks. Prioritize H1 and H2 first—they are weather-gated and cannot be rescheduled freely.

6. Data Pipeline

The pipeline transforms raw, messy SD-card CSVs into a clean, analysis-ready dataset. Every step should be scripted and fully reproducible. Use Python with `pandas`, `geopandas`, and `pyarrow`.

6.0.1 Step 1 — Ingest and Concatenate

- Read all per-run CSV files. Tag each row with `run_id`, `route_family`, and `run_date`.
- Assert the column schema on read—fail loudly on any missing column rather than silently dropping data.
- Save concatenated raw data to `raw_combined.parquet` (preserves dtypes, much faster than CSV for repeated reads).

6.0.2 Step 2 — GPS Quality Filter

- Drop rows where `fix_quality == 0` (no GPS fix) or `n_sats < 4`.
- Flag rows where implied speed between consecutive positions exceeds physically plausible values ($> 35\,\mathrm{km\,h^{-1}}$ running, $> 60\,\mathrm{km\,h^{-1}}$ cycling).
- Apply a Hampel identifier (5-point median filter, threshold $= 3\sigma$) to `lat` and `lon` separately to remove spike outliers.
- Report fraction of data dropped per run; flag any run losing $> 10\%$ of rows.

6.0.3 Step 3 — Sensor Quality Control

- $PM_{2.5}$, PM_{10}: physical range 0–1000 $\mu\mathrm{g\,m^{-3}}$. Flag out-of-range values as instrument errors.
- Temperature: flag values outside -20 to $50°C$.
- RH $> 85\%$: flag as high-humidity condition. Optical particle counters overcount $PM_{2.5}$ at high RH due to hygroscopic particle growth; exclude these rows from plume fitting or analyze separately.
- VOC index: qualitative scale 1–500. Use only for event detection, not absolute comparison.
- Sensor warm-up artifact: SEN54 requires $\sim$30 s to stabilize. Drop the first 60 s of every run.

6.0.4 Step 4 — Time Synchronization

- Verify Pi clock was NTP-synced before each run (add NTP check to logger startup script).
- GPS NMEA sentences carry UTC time—use this as the master clock, not the Pi system clock.
- Interpolate GPS position to 1 Hz if GPS dropouts create sub-second gaps.

6.0.5 Step 5 — Meteorological Data Merge

- Download hourly ASOS observations for KMDW and KORD from the Iowa State Mesonet API (`https://mesonet.agron.iastate.edu`).
- For each run, assign the ASOS observation nearest in time (± 30 min) as the meteorological context.
- Compute PG stability class: wind speed + cloud cover + solar elevation angle (Seinfeld & Pandis, Eq. 4.7).

6.0.6 Step 6 — Spatial Binning

- Project GPS coordinates to Illinois State Plane (EPSG:3435) for accurate metric distance calculations.
- Snap each measurement to a 10×10 m grid cell using a `geopandas` spatial join.

- Per cell compute: mean $PM_{2.5}$, std $PM_{2.5}$, n_{obs}, n_{runs}. Flag cells with $n_{obs} < 5$ as low-confidence.

6.0.7 Step 7 — Final Dataset Schema

Two output tables:

- `observations.parquet`: one row per 1-second sensor reading, all quality flags applied.
- `grid_summary.parquet`: one row per 10 m grid cell, aggregated statistics across all runs.

Column	Type	Description
`run_id`	`str`	Unique ID per run (`YYYYMMDD_routeID`)
`timestamp_utc`	`datetime64[ns,UTC]`	GPS-anchored UTC timestamp
`lat` / `lon`	`float64`	WGS84 decimal degrees, Hampel-filtered
`easting` / `northing`	`float64`	Illinois State Plane (m)
`pm1`, `pm25`, `pm4`, `pm10`	`float32`	Particle mass concentration ($\mu g\,m^{-3}$)
`voc_index`	`int16`	Sensirion VOC index (1–500, dimensionless)
`temp_c`, `rh_pct`	`float32`	Ambient temperature (°C) and relative humidity (%)
`wind_speed_ms`, `wind_dir_deg`	`float32`	From nearest ASOS obs., interpolated to run time
`stability_class`	`str`	Pasquill–Gifford A–F
`lake_breeze_flag`	`bool`	`True` if run tagged as lake breeze event
`route_family`	`categorical`	`canyon / plume / lakefront / point_source / exploratory`
`qc_flag`	`int8`	Bitmask: bit0=GPS drop, bit1=high RH, bit2=warm-up, bit3=range

7. Analysis Roadmap

Work through these levels in order. Each one builds on the previous and serves as a sanity check that the data are behaving physically before you commit to model fitting.

7.1 Level 1 — Exploratory Spatial Analysis

- **Spatial heatmap:** Plot all $PM_{2.5}$ measurements on an interactive Chicago basemap using `folium` or `kepler.gl`. This is your first look at whether the data make physical sense—hot spots should correspond to highways, industrial zones, and street canyons, not random locations.
- **Time-of-day profiles:** Boxplot $PM_{2.5}$ by hour of day. Expect morning and evening peaks corresponding to commuter traffic; clean midday if winds are strong.
- **Seasonal decomposition:** Compare summer vs. winter runs. Winter temperature inversions trap boundary-layer pollutants and should produce dramatically higher concentrations than summer runs on the same routes.
- **Sensor self-consistency:** Scatter $PM_{2.5}$ vs. PM_{10}. Expect $R^2 > 0.7$. Points far off the regression line (anomalously high $PM_{10}/PM_{2.5}$) signal coarse-particle events worth investigating.
- **Wind rose of polluted runs:** 90th-percentile $PM_{2.5}$ binned by wind sector. A quick qualitative check on dominant source directions before any model fitting.

7.2 Level 2 — Statistical Testing of Core Hypotheses

- **H1 (Street canyon):** One-way ANOVA across street–wind angle bins. Tukey HSD post-hoc test. Report Cohen's d as effect size. Visualize as mean ± 95% CI bar chart.
- **H4 (Lake breeze):** Mann–Whitney U test (non-parametric; PM distributions are right-skewed). Effect size $r = Z/\sqrt{N}$.
- **For both:** Bootstrap confidence intervals ($n = 10{,}000$ resamples) on group means; this requires no distributional assumptions and is straightforward to implement with `scipy.stats` or `numpy`.

7.3 Level 3 — Gaussian Plume Fitting (H2)

- For each highway transect, bin $PM_{2.5}$ by *downwind* distance x from the highway edge (10 m bins). Record the wind angle relative to the road and keep only near-perpendicular transport.
- Fit the ground-level line-source decay

$$C(x) = \frac{C_0}{\sigma_z(x)}, \qquad \sigma_z(x) = a\,x^b \quad \Longrightarrow \quad C(x) = C_0\,a^{-1}x^{-b}$$

  using `scipy.optimize.curve_fit` (fit in log–log space, where the model is linear and the fit is well conditioned). Extract a, b and their uncertainties.
- Compare the exponent b to PG stability-class σ_z predictions (class D neutral: $b \approx 0.7$–0.8 over the 10–300 m range; verify against the specific PG parameterisation used).
- Estimate the per-unit-length emission rate Q_L from the fitted prefactor via $C(x) = \sqrt{2/\pi}\,Q_L/(\sigma_z(x)u)$ with measured u. Convert to a per-vehicle factor using the traffic count and compare to USEPA National Emissions Inventory (NEI) highway emission factors.
- **Background subtraction:** fit $C(x) = C_{\text{bg}} + C_0 a^{-1}x^{-b}$, or subtract a control-site background first — a power-law decay fitted without a background term will bias b low.

7.4 Level 4 — Stokes Number Analysis (H3)

- Compute particle relaxation time: $\tau_p = \rho_p d_p^2 / 18\mu$ for $d_p = 2.5$ and $10\,\mu$m. Use $\rho_p = 1500\,\mathrm{kg\,m^{-3}}$ (typical urban aerosol), $\mu = 1.81 \times 10^{-5}\,\mathrm{Pa\,s}$.
- Compute $\mathrm{St} = \tau_p U / L$ where U is measured wind speed and L is a characteristic building scale ($\sim$20 m).
- Plot $PM_{10}/PM_{2.5}$ ratio vs. distance from each point source. Fit exponential decay $R(r) = R_0 e^{-\lambda r}$.
- Interpret λ via theoretical settling velocity $v_s = \rho_p d_p^2 g / 18\mu$. *This level is the most original physics in the project—in-situ Stokes analysis at street scale is genuinely novel in the literature.*

7.5 Level 5 — Data-Driven Spatial Modeling

- Train a random forest regressor to predict $PM_{2.5}$ at any (lat, lon) given: wind speed, wind direction, time of day, day of week, proximity to roads/highways (OpenStreetMap network), land use (NLCD), and season.
- Evaluate with RMSE and spatial cross-validation (leave-one-neighborhood-out), to prevent inflated performance from spatial autocorrelation.
- Extract feature importances to quantify which variables dominate $PM_{2.5}$ predictions across Chicago.
- Compare to a kriging interpolation (geostatistical baseline).

7.6 Level 6 — Community Impact Map

- Join `grid_summary` with the Chicago Community Areas shapefile (City of Chicago Open Data Portal).
- Compute mean and 90th-percentile $PM_{2.5}$ per community area.
- Overlay with demographic data (ACS 5-year estimates: % below poverty line, % non-white residents, % under 5 and over 65 years).
- Report Pearson correlation between socioeconomic indicators and mean $PM_{2.5}$. This is the public-facing story and the most immediately communicable result.

8. Milestone Timeline (6–12 Months)

Designed to be completed alongside a full PhD workload—roughly 5–10 hours per week of project time (including the runs themselves).

Period	Phase	Key Deliverables and Actions
Month 1	Hardware	Order all components. Assemble Pi + SEN54 + GPS. Verify I^2C and UART. Log first 30-min stationary test file. Confirm GPS cold-start time.
Months 1–2	Software	Deploy `logger.py` with systemd auto-start. Build pre-run health check script. 24-hr co-location calibration vs. PurpleAir or IQAir. Document any correction factors.
Months 2–3	Pilot Runs	20 exploratory runs across all route families to shake out hardware and logging issues. Build v1 data pipeline. Fix systematic errors. Refine enclosure weatherproofing.
Months 3–6	Systematic Collection	**Priority phase.** Focus on weather-gated H1 and H2 runs. Target 3–4 runs/week. Reach ∼100 runs by month 6. Build met. merge pipeline in parallel.
Months 6–7	Pipeline & QC	Run full data pipeline on all collected data. Generate QC report (flag drop rates, RH exceedances, GPS quality). Produce first spatial heatmap. Identify gaps; plan fill runs.
Months 7–8	Exploratory Analysis	Complete Level 1 and Level 2 analyses. Run all 4 hypothesis tests. Share informal update with advisor or lab group. Refine collection strategy based on power analysis of real data.
Months 8–10	Advanced Analysis	Gaussian plume fitting (Level 3). Stokes analysis (Level 4). ML spatial model (Level 5). Freeze dataset for publication.
Months 10–11	Write-Up	Write dataset descriptor paper (*ESSD* target). Write main results paper or technical report. Produce blog post and GitHub repository.
Months 11–12	Dissemination	Submit dataset to Zenodo. Post to personal site. Submit abstract to AGU or AAAR. Consider journal submission (see §9).

PhD Compatibility Notes

- Data collection = 45–90 min per run, integrated into exercise you would do anyway.
- Analysis is modular: each Level in §7 is a self-contained Jupyter notebook.
- Hardware is passive once deployed—no babysitting required during runs.

- Build pipeline and analysis during slower PhD periods (between semesters, post-quals).
- A 3-month delay in any phase is recoverable without compromising scientific quality.

9. How to Present the Final Result

9.1 GitHub Repository (Public Portfolio Piece)

- **Repository structure:** `/hardware` (wiring diagrams, enclosure CAD), `/firmware` (logger.py, systemd config), `/pipeline` (data cleaning notebooks), `/analysis` (one notebook per hypothesis), `/data` (Zenodo links), `/docs` (rendered GitHub Pages site).
- Write a thorough `README.md` with photos of the hardware setup, example output maps, and one-sentence plain-language summaries of each finding.
- Use DVC (Data Version Control) or Git LFS to track large data files without bloating the repo.
- **Target:** full reproducibility—a collaborator should be able to `git clone`, download the Zenodo dataset, run `make analysis`, and reproduce every figure.

9.2 Dataset Publication

- Publish the clean dataset to Zenodo (`https://zenodo.org`) under CC-BY 4.0. Free, issues a DOI, indexed by Google Scholar and OpenAIRE.
- Consider a Data Descriptor submission to *Earth System Science Data* (ESSD)—a peer-reviewed EGU journal for novel environmental datasets (IF ≈ 12). An ESSD paper is a standalone, citable publication even if it precedes the main analysis paper.
- Minimum metadata: sensor make/model/firmware version, calibration protocol and correction factors, GPS accuracy characterization, route family definitions, and meteorological data sources.

9.3 Blog Post / Public Communication

- Write one 2,000-word accessible post for a technically curious general audience. Suggested platforms: Towards Data Science, a personal Hugo/Jekyll site, or Substack.
- Suggested structure: (1) Chicago's monitoring gap, (2) the hardware you built and why, (3) one striking map or chart, (4) what the physics tells us, (5) what you'll do next.
- Cross-post on Twitter/X, LinkedIn, and Reddit (`r/dataisbeautiful`, `r/chicago`, `r/STEM`). This is how citizen science projects get noticed by journalists and environmental agencies.

9.4 Conference Presentations

- **AAAR Annual Conference** (American Association for Aerosol Research): ideal venue. Abstract deadline typically April for October conference. Target session: Urban Aerosols / Low-Cost Sensors.
- **AGU Fall Meeting**: large atmospheric science community. Target session: Atmospheric Composition / Air Quality.
- **AMS Annual Meeting**: good fit for the lake breeze and Gaussian dispersion components.
- **Northwestern Graduate Research Symposium**: low-stakes entry point to practice your talk. Present there first.

9.5 Potential Journal Venues

Journal	Fit	Notes
Atmospheric Measurement Techniques (EGU)	Excellent	Best fit if sensor validation + novel dataset is the primary contribution. Open access.
Atmospheric Environment	Excellent	Best fit if main findings are the urban aerosol physics results (H1–H4). Broad readership.
npj Climate and Atmospheric Science (Nature)	Strong	High-impact. Requires novel, broadly significant findings. Good if equity/lake breeze results are striking.
Environmental Science & Technology (ACS)	Good	Well-regarded applied urban air quality journal; strong policy-community readership.
Earth System Science Data (EGU)	Excellent (dataset)	Peer-reviewed data descriptor. Citable standalone publication; does not require full analysis.
PLOS ONE	Fallback	Accepts well-executed work regardless of novelty threshold. Good if hypothesis results are mixed.

Final Advice

Start writing before the analysis is done. Write the Introduction and Methods sections while you are still collecting data—the Methods section is fully knowable right now.

The dataset is the guaranteed deliverable. Even if every hypothesis yields a null result, a publicly released, GPS-tagged, street-level air quality dataset for Chicago is a genuine scientific contribution.

This project demonstrates, in one package: hardware design, experimental protocol, data engineering, statistical analysis, and physical modeling. For a physics PhD, that range of demonstrated skills is rare and impressive to future employers in academia, national labs, and industry alike.