Friday Experiments: Novel Free-Surface Configurations for Probing Shear-Thickening Suspension Dynamics

C. Burton[1]

[1]*Department of Mechanical Engineering,*

Northwestern University, Evanston, IL 60208, USA

(Dated: July 6, 2026)

Abstract

We propose five preliminary experimental programs—"Friday experiments"— motivated by two recent landmark papers on shear-thickening ("oobleck") flows: Darbois Texier *et al.* [1, 2], who identified and characterized the inertia-free surface-wave instability of dense cornstarch suspensions on inclined planes, and Bougouin *et al.* [3], who discovered the "liquid dam"—a constant-speed gravity-driven front arising from a jammed, load-bearing structure at the advancing edge. Each proposed experiment targets a gap that is clearly open in the literature and feasibly addressable with existing high-speed photography and a modest laser-based velocimetry system. The five programs are: (1) a three-dimensional radial free-surface dam break that removes the quasi-two-dimensional channel constraint of all prior liquid-dam work and probes azimuthal stability of the jammed front; (2) upward elastic-membrane forcing of a resting suspension layer ("reverse impact"), providing a controlled, inertia-free route to jamming-front nucleation and propagation; (3) quantitative mapping of the oobleck-wave dispersion relation via controlled sinusoidal inlet perturbations, providing the first systematic experimental test of the linear stability theory using only side-view imaging; (4) stairwave wavelength selection under a programmable tilt-rate protocol; and (5) liquid-dam interaction with a geometric step discontinuity, testing the intrinsic character of U^{LD} and providing the first direct measurement of the overflow-layer thickness δ. For each experiment we derive the relevant scalings, identify the decisive observables, and discuss measurement strategy.

I. INTRODUCTION AND LITERATURE LANDSCAPE

Dense suspensions of hard particles near the jamming transition exhibit a remarkably rich class of free-surface flow phenomena absent in Newtonian or conventional non-Newtonian fluids. The physical origin lies in the Wyart–Cates (WC) model of discontinuous shear thickening (DST): a smooth crossover from a frictionless viscosity $\eta_0(\phi) = \eta_s(\phi_0-\phi)^{-2}$ at low stress to a frictional, near-divergent viscosity at stresses above a concentration-dependent critical stress $\tau_c(\phi)$, with a fully re-entrant (backward-bending) constitutive curve in the shear-jamming (SJ) regime $\phi_1 < \phi < \phi_0$ [5].

a. Oobleck waves. Darbois Texier *et al.* [1] reported that dense cornstarch suspensions flowing down an inclined channel spontaneously develop prominent, regular surface waves at volume fractions $\phi \gtrsim 0.38$. Unlike the classical Kapitza (roll-wave) instability

of Newtonian thin films, which requires a finite Reynolds number, oobleck waves appear at vanishingly small Re and are entirely inertia-free. Their origin is the coupling between the free surface and the backward-bending branch of the constitutive curve: an increase in surface stress reduces flow velocity, which raises the local free-surface height, which further amplifies the stress—a self-sustaining feedback [2, 8]. Darbois Texier *et al.* [2] subsequently provided a quantitative linear stability theory spanning the full Kapitza-to-Oobleck range, and Balmforth [6] extended this to nonlinear saturation, predicting that finite-amplitude waves steepen into staircase fronts—precisely the "stairwaves" subsequently observed by Bougouin *et al.* [3].

b. Liquid dam. Bougouin *et al.* [3] showed that when a DST suspension in the SJ regime is released in a dam-break geometry, it spreads not by decelerating like any known fluid but instead with a nearly vertical front—a "liquid dam"—that advances at a constant speed

$$U^{\mathrm{LD}}(\phi) = 2k\,\frac{\tau_c(\phi)^2}{\rho g\,\eta_0(\phi)}, \tag{1}$$

independent of released volume, flow height, and channel slope. The mechanism is a jammed, frictional front of length $\ell \sim kH/k_0$ (where $k = 10$ and $k_0 \approx 2$–3 from their model, consistent with $\ell/H \approx 3$–5 observed in their surface velocimetry) above which a thin frictionless overflow layer of thickness δ carries the mass flux. Equation (1) is validated across nearly two decades in speed by varying ϕ, solvent viscosity, and particle type. Related localized jammed structures—frictional solitons—had previously been identified in pipe flow [4] and Couette cells [7], establishing a generic picture of stress-localization in DST systems.

c. Open questions. The liquid-dam experiments are all performed in quasi-two-dimensional channels; the three-dimensional geometry is completely unexplored. The overflow-layer thickness δ and jammed-front length ℓ appear in the model but have not been directly measured; the paper explicitly calls for future internal imaging [3]. The linear stability theory for oobleck waves has been tested only against naturally arising waves; no controlled-perturbation experiment has mapped the dispersion relation $\omega(k)$ or growth rate $\sigma(k)$. The stairwave wavelength formula $\lambda \approx 2h_{\mathrm{ini}}/\sin\theta$ has not been tested against a controlled tilt protocol. And the behavior of the liquid dam upon encountering a geometric discontinuity is entirely unexplored. The five experiments proposed below address these gaps one by one.

Throughout, we characterize the system by: particle volume fraction ϕ (corrected for

cornstarch porosity via $\phi_{\text{eff}} = 1.136\,\phi_{\text{nom}}$ [11]), critical stress $\tau_c(\phi)$ and frictionless viscosity $\eta_0(\phi)$ from WC fits to Couette rheometry (representative values for cornstarch-water in the SJ regime: $\tau_c \approx 2$–4 Pa, $\eta_0 \approx 0.2$–1.5 Pa·s [3]), layer thickness H, jammed-front length $\ell \approx 4H$ (from surface velocimetry of Bougouin *et al.*), and suspension density $\rho \approx \rho_w\,[1 + (\rho_p/\rho_w - 1)\phi]$.

II. EXPERIMENT 1: THREE-DIMENSIONAL RADIAL FREE-SURFACE DAM BREAK

A. Physical motivation and gap

Every existing liquid-dam experiment confines the suspension between parallel channel walls, reducing the problem to one spatial dimension. Real gravity-driven flows of DST suspensions—lava analogues, slurry spills, concrete placement—are three-dimensional. When the advancing front is a growing annulus (radius $R(t)$), azimuthal perturbations of the jammed ring experience a qualitatively different geometry than the flat channel case. In standard viscous spreading, the 3D (axisymmetric) Newtonian gravity current follows $R \propto t^{1/8}$ (Huppert 1982 [14]), with a qualitatively different height evolution than the 2D case ($X \propto t^{1/5}$). Whether the liquid-dam regime persists in 3D, and how the transition to Newtonian spreading is modified, are both unexplored.

A further question is azimuthal stability. In the channel, the jammed front is a rectangle driven forward by the frictionless pool. In the radial geometry, the frictionless pool (viscosity η_0) drives the jammed annulus (effective viscosity $\gg \eta_0$) outward. This configuration—a less-viscous fluid displacing a more-viscous one in radial outward spreading—is the same orientation as the Saffman–Taylor instability in a Hele-Shaw cell, raising the possibility that fingers of the frictionless pool penetrate the jammed ring. Whether this analogy carries over quantitatively is unknown: the jammed front is not a passive fluid but a self-sustaining frictional structure. Determining whether the front fingers or remains azimuthally uniform is a key open question.

Key questions. (1) Does $U^{\text{LD}} = dR/dt$ remain constant and consistent with Eq. (1) in radial 3D spreading? (2) Is the liquid dam azimuthally uniform, or do fingers of

the frictionless pool penetrate the jammed annulus? (3) How does the height evolution $H(t)$ differ from the 2D case, and where does the transition to Newtonian axisymmetric spreading ($R \propto t^{1/8}$) occur?

B. Geometry and scaling

Consider a cylindrical release of volume $V = \pi R_0^2 H_0$ spreading radially on a horizontal surface. If the flat-top liquid-dam morphology holds in 3D (as it does in 2D), volume conservation with $h(r,t) \approx H(t)$ for $r < R(t)$ gives

$$H(t) = \frac{V}{\pi R(t)^2}. \tag{2}$$

The front mass balance is local: a cross-section of the annular front at any azimuthal position still satisfies $H\,U^{\mathrm{LD}} \sim \delta\bar{u}$ (the same relation as in 2D), provided the overflow remains frictionless and $\ell \sim H$. If these conditions hold, the front speed in 3D is still $U^{\mathrm{LD}}(\phi)$ from Eq. (1), giving

$$R(t) \approx U^{\mathrm{LD}}(\phi)\, t, \qquad H(t) \approx \frac{V}{\pi\, U^{\mathrm{LD}2}\, t^2}. \tag{3}$$

The $H \sim t^{-2}$ decay in 3D is qualitatively faster than the $H \sim t^{-1/5}$ decay in the 2D Newtonian case and represents a clean, falsifiable difference from any existing spreading model.

The transition to Newtonian spreading occurs when the Newtonian axisymmetric front speed overtakes U^{LD}. For the axisymmetric viscous gravity current (Huppert 1982 [14]), the lubrication scaling gives $\dot{R}_{\mathrm{Newt}} \sim \rho g H^3/(\eta_0 R)$, so the transition condition $U^{\mathrm{LD}} = \dot{R}_{\mathrm{Newt}}$ yields

$$U^{\mathrm{LD}} \sim \frac{\rho g H_c^3}{\eta_0 R_c}, \tag{4}$$

where R_c and H_c are simultaneously constrained by $H_c = V/(\pi R_c^2)$. Unlike the 2D case—where H_c depends only on ϕ and A—in 3D the transition height and radius depend on V as well. The coupled system of Eq. (4) and volume conservation must be solved numerically for each V and ϕ; subsequent spreading after the transition follows $R \propto t^{1/8}$ (Huppert 1982 [14]).

Proposed setup. A Plexiglas cylinder ($R_0 = 4$–6 cm, $H_0 = 3$–8 cm) is filled with a DST cornstarch suspension at $\phi \in \{0.43, 0.45, 0.46\}$ and placed on a flat, hydrophobic-coated

acrylic sheet. The cylinder is lifted rapidly ($\Delta t \lesssim 0.1\, H_0/U^{\mathrm{LD}} \sim 0.1$ s) by a pneumatic actuator, releasing the suspension to spread freely. Top-view high-speed photography (1000–3000 fps) records $R(\theta, t)$ where θ is the azimuthal angle. A synchronized side-view camera at 500–1000 fps tracks $H(t)$ and verifies the flat-top morphology. Surface PTV: the free surface is seeded with 50–100 µm hollow glass microspheres; a horizontal CW 532 nm laser sheet illuminates the surface, and the top-view camera (with long-pass filter) records particle tracks at 1000–2000 fps for radial velocity mapping.

C. Observables and expected results

From top-view imagery: mean radius $\bar{R}(t)$ tests Eq. (3); a log-log plot of $\bar{R}$ vs. t should show slope 1 during the liquid-dam phase, transitioning to slope 1/2 after t_c. The rms azimuthal fluctuation $\sigma_R(t) = \langle [R(\theta, t) - \bar{R}]^2 \rangle^{1/2}$ quantifies any fingering instability. If fingers grow, their count m and growth rate can be extracted by azimuthal Fourier decomposition.

From surface PTV: the radial velocity profile $u_r(r, t)$ should exhibit a localized overspeed near the front (analogous to the 2D signature of Bougouin *et al.* [3]) with azimuthal modulation if fingers are present.

Novelty and publishability. This is the first liquid-dam experiment without lateral confinement. It tests whether Eq. (1) is a genuinely local, geometry-independent constitutive law, reveals whether the jammed annulus is azimuthally stable, and provides the first experimental measurement of the 3D height evolution $H(t) \sim t^{-2}$. A clean result—stability or instability—is a natural *Physical Review Letters* paper; a full dataset mapping R_c, H_c, and $R(\theta, t)$ as functions of V and ϕ suits *Physical Review Fluids*.

III. EXPERIMENT 2: ELASTIC MEMBRANE UPWARD FORCING ("REVERSE IMPACT")

A. Physical motivation and gap

Work from the Driscoll laboratory on drop impact of DST suspensions onto compliant (PEGDA/PEGMEA gel) substrates has established that the elastic wave reflection timescale $t_r = 2h/c_s$ competes with jamming front propagation and strongly alters impact morphol-

ogy [12, 13]. In all of this work, the suspension is the impactor and the elastic substrate is the target; the jammed region nucleates at the impact interface and propagates upward through the suspension.

Here we propose to invert this geometry: a thin elastic membrane (stretched latex or PDMS sheet) is clamped over a rigid frame and loaded from above with a layer of DST suspension of height h_0. A rod pushes upward through the frame at controlled velocity v_{rod}. There is no impact—the forcing is slow and controlled—so inertia plays no role. The free surface of the suspension (the top surface) is unconfined. This provides a clean way to study jamming-front nucleation and propagation in the quasi-static limit, which is inaccessible in drop-impact experiments where inertia and stress localization are entangled.

Key questions. (1) At what critical velocity v_c does a jammed patch nucleate above the rod contact, and does $v_c \sim \tau_c h_0/\eta_0$ (the WC-based threshold)? (2) Does a radially propagating jamming front appear above this threshold, and how does its speed depend on v_{rod} and ϕ? (3) How does the elastic restoring force of the membrane modify the spatial extent of the jammed region compared to the rigid-substrate impact case? (4) Does the free surface deform upward ("dome") above the jammed patch, and at what height does the dome arrest?

B. Geometry and scaling

When the rod tip (radius a_{rod}) pushes up at speed v_{rod}, the suspension layer is compressed vertically at a strain rate $\dot{\varepsilon} \approx v_{\mathrm{rod}}/h_0$. For a suspension layer with free-slip at the top surface and no-slip at the membrane, the resulting shear rate is of the same order, $\dot{\gamma} \sim v_{\mathrm{rod}}/h_0$. Jamming nucleates when the local stress exceeds τ_c:

$$v_{\mathrm{rod}} \geq v_c \equiv \frac{\tau_c(\phi)\, h_0}{\eta_0(\phi)}. \tag{5}$$

For cornstarch-water in the SJ regime ($\tau_c \sim$ 2–4 Pa, $\eta_0 \sim$ 0.2–1.5 Pa·s) with $h_0 = 1$ cm, this gives $v_c \sim$ 10–100 mm/s, accessible with a standard lead-screw actuator or pneumatic piston. The elastic membrane contributes a spatially varying upward normal stress $\sigma_{\mathrm{mem}}(r) \approx T\,\nabla^2 w(r)$ (where T is membrane tension and w is the deflection profile), which partially offsets the rod forcing away from the contact point. As a result, the jammed region may arrest at a finite radius R_{jam} before the rod is withdrawn, allowing one to map

$R_{\text{jam}}(v_{\text{rod}}, T, \phi)$.

Once a jammed front nucleates, its radial propagation speed c_f in the drop-impact geometry has been shown to scale with the impact velocity and current front radius [7, 10]. Whether the same scaling holds in the quasi-static, upward-forcing geometry—where neither the forcing velocity nor the stress distribution are the same as in impact—is an open question.

Proposed setup. A circular latex membrane ($R_{\text{frame}} = 10$ cm, thickness 0.3–1 mm, pretension T set by a calibrated tightening ring; T measured via the fundamental drum frequency with a microphone) is clamped over a rigid acrylic support with a central hole (diameter $2a_{\text{frame}} = 1$ cm). A suspension layer ($h_0 = 0.5$–2 cm, $\phi = 0.43$–0.46) is loaded on top. A rounded Delrin rod ($a_{\text{rod}} = 2$–5 mm tip radius) is driven from below by a stepper-motor lead screw at controlled $v_{\text{rod}} = 1$–200 mm/s. Top-view high-speed camera (500–2000 fps) images plan-view jamming front growth. Side-view camera records free-surface dome profile $h(r, t)$. Surface PTV (seeded free surface, horizontal CW laser sheet, top-view camera with long-pass filter) provides radial velocity $u_r(r, t)$.

C. Observables and expected results

Vary v_{rod} from well below to well above $v_c(\phi)$ at fixed h_0 and ϕ: the onset of visible jamming (central dark rigid patch in top-view) defines v_c experimentally. Plotting v_c vs. $\tau_c h_0/\eta_0$ across multiple ϕ tests Eq. (5). Above threshold: track $R_{\text{jam}}(t)$ to extract the front propagation speed $c_f(v_{\text{rod}}, \phi)$ and compare with the drop-impact scaling [10]. Vary T at fixed v_{rod} and ϕ: if membrane tension halts front growth at $R_{\text{jam}} < R_{\text{frame}}$, this directly reveals the length scale over which the elastic restoring stress becomes comparable to τ_c. The dome height $h_{\text{dome}}(R_{\text{jam}}, T, \phi)$ from the side-view camera provides a complementary observable.

Novelty and publishability. This is the first experiment in which an elastic substrate drives jamming in a resting suspension from below. By removing impact inertia entirely, it isolates the quasi-static stress-localization mechanism and provides a direct, parameter-free test of the WC nucleation threshold v_c. The dependence of R_{jam} on membrane tension T introduces a new length scale with no analogue in the rigid-substrate impact literature, and connects directly to the Driscoll-lab program on compliance effects in

DST impact. Target: *Physical Review Letters* or *Soft Matter*.

IV. EXPERIMENT 3: OOBLECK-WAVE DISPERSION RELATION VIA CONTROLLED INLET PERTURBATION

A. Physical motivation and gap

Darbois Texier *et al.* [2] derived the full linear stability problem for a WC suspension on an inclined plane, predicting the spatial growth rate $\sigma(k;\,\phi,\theta)$ and phase speed $c(k;\,\phi,\theta)$ as functions of streamwise wavenumber k. Depoilly *et al.* [8] generalized this to an arbitrary generalized-Newtonian rheology, unifying the Kapitza and Oobleck branches. These theories make quantitative, parameter-free predictions (all inputs come from rheometry): the neutral stability curve $k_{\mathrm{neutral}}(\phi,\theta)$, the wavenumber of maximum growth $k_{\max}$, and the sign of the group velocity $c_g = \partial\omega/\partial k$.

Experimentally, only naturally arising waves have been studied. Darbois Texier *et al.* [1] detected waves by laser profilometry but did not control the perturbation wavenumber and did not measure $\sigma(k)$. No experimental dispersion relation for oobleck waves exists. This is a remarkable gap given the maturity of the theory.

Key questions. (1) Does $\sigma(k)$ from experiment agree with the WC-based linear stability theory [2], with no free parameters? (2) Is the neutral stability wavenumber $k_{\mathrm{neutral}}(\phi,\theta)$ consistent with the predicted band of unstable modes? (3) Does the measured phase speed $c(k)$ match theory, including the sign of c_g?

B. Geometry, perturbation scheme, and scaling

A steady base flow at controlled thickness h_0 and mean velocity $\bar{U}$ is established in a recirculating inclined-plane channel (length $L = 80$–150 cm, width $W = 10$–15 cm, slope θ adjustable from 0° to 30°; pump with PID-controlled flow rate). A thin Teflon paddle ($\sim$2 mm height, spanning W) at the inlet is driven sinusoidally at frequency f_0 by a voice-coil actuator. This imposes a surface-height perturbation of dominant wavenumber $k_0 = 2\pi f_0/\bar{U}$ at $x = 0$. Sweeping f_0 at fixed base-flow conditions maps the full $\sigma(k)$ curve.

C. Free-surface height measurement

Darbois Texier *et al.* [1] measured $h(x,t)$ using a Keyence laser line profilometer, which resolves the opaque suspension-air interface by triangulation. A simpler and equally effective approach for our setup is backlit side-view imaging: a diffuse LED panel behind the channel provides high-contrast silhouettes of the opaque suspension, and the high-speed camera positioned at the side records $h(x,t)$ directly at each frame. This method requires no additional instrumentation beyond the existing camera. The free-surface perturbation $\eta(x,t) = h(x,t) - h_0$ is extracted by edge detection.

The amplitude $|\hat{\eta}(x, f_0)|$ at the forcing frequency is extracted at multiple streamwise positions $x_1, \ldots, x_n$ by lock-in analysis, yielding the spatial growth rate

$$\sigma(k_0) = \frac{1}{\Delta x} \ln \frac{|\hat{\eta}(x_2)|}{|\hat{\eta}(x_1)|}. \tag{6}$$

The phase velocity $c(k_0)$ is obtained by cross-correlating $\eta(x_1,t)$ and $\eta(x_2,t)$ to find the propagation delay.

D. Practical constraints

Cornstarch suspensions are optically opaque at $\phi \gtrsim 0.40$; a laser sheet cannot penetrate the bulk. The primary measurement is therefore the free-surface profile $h(x,t)$ from side-view imaging, not interior velocity fields. Cross-sectional PIV inside the flow would require either (a) an ultrasound velocimetry system or (b) a fully transparent index-matched suspension (e.g., PMMA beads in water–DMSO or silica beads in a refractive-index-matched glycerol–water mixture); both are reserved for future work. The surface-height measurement alone is sufficient to map $\sigma(k)$ and $c(k)$, which are the primary deliverables of this experiment.

Sedimentation: cornstarch suspensions at $\phi < 0.43$ can sediment on the timescale of an experiment. The Bougouin group discards flows with $H < 7.5$ mm for this reason [3]; we apply the same criterion. Recirculating the suspension through a pump continuously re-mixes it.

Proposed setup. Recirculating channel (acrylic, $150 \times 12 \times 5$ cm, variable slope mount); gear pump with PID flow control; inlet paddle voice-coil (0.1–50 Hz). Backlit LED panel + side-view high-speed camera at 2000–5000 fps for $h(x,t)$ over a 60 cm window.

Cornstarch-water at $\phi = 0.40,\ 0.43,\ 0.45,\ 0.46$; $\theta = 5°$–$25°$; $h_0 = 5$–15 mm. Lock-in analysis of $\eta(x,t)$ at each (f_0, ϕ, θ).

E. Observables and expected results

Plot σ vs. k_0 for each (ϕ, θ): expect a band of unstable wavenumbers $k_{\min} < k_0 < k_{\max}$ with a peak at $k_{\max}$. Compare directly with the Darbois Texier (2023) predictions using $\tau_c(\phi)$ and $\eta_0(\phi)$ from independent rheometry. Plot $c(k_0)$ vs. k_0: theory predicts $c > \bar{U}$ in the oobleck-wave regime (waves travel faster than mean flow).

Novelty and publishability. This is the first experimental measurement of the oobleck-wave dispersion relation. The controlled-perturbation protocol distinguishes stable from unstable wavenumbers and measures growth rates without free parameters, providing a stringent quantitative test of the WC-based stability theory that the existing literature cannot supply. A clean $\sigma(k)$ curve across two or three volume fractions constitutes a full *Journal of Fluid Mechanics* or *Physical Review Fluids* paper. Extension to interior velocity measurement (via index-matched transparent system or ultrasound velocimetry) is a natural second phase.

V. EXPERIMENT 4: STAIRWAVE WAVELENGTH SELECTION UNDER CONTROLLED TILT RATE

A. Physical motivation and gap

Balmforth [6] showed theoretically that the nonlinear saturation of oobleck waves produces steadily propagating, finite-amplitude stairwaves: steep fronts separated by nearly flat regions at the base-flow thickness. Bougouin *et al.* [3] subsequently observed stairwaves when a horizontal layer of DST suspension was abruptly tilted. The observed wavelength agrees with a geometric mass-conservation argument:

$$\lambda \approx \frac{2\, h_{\mathrm{ini}}}{\sin\theta}, \tag{7}$$

which contains no rheological parameters and predicts λ independent of ϕ.

Two questions remain open. First, in the Bougouin experiments the tilt was rapid but not controlled; whether λ depends on the tilt rate Ω is unknown. Balmforth's theory connects

stairwaves to the nonlinear saturation of the fastest-growing oobleck wave mode, which has a wavenumber $k_{\max}$ that depends on ϕ and θ; if the tilt is slow enough that the suspension evolves quasi-statically through the Oobleck-unstable regime, it is plausible that the selected λ differs from Eq. (7). Whether and how this occurs is an empirical question that the theory does not yet prescribe analytically. Second, how quickly do stairwaves form from an initially flat layer, and does this timescale scale with the oobleck-wave e-folding time?

Key questions. (1) Does λ depend on Ω, or is Eq. (7) exact regardless of tilt rate? (2) Does λ depend on ϕ at fixed (h_{ini}, θ)? (If yes, rheology matters; Eq. (7) is incomplete.) (3) Is there a minimum Ω below which stairwaves do not form? (4) What is the stairwave formation time $t_{\text{stair}}(\phi, \theta, \Omega)$?

B. Geometry, protocol, and scaling

A flat acrylic tray (40×15 cm, depth 2 cm) is mounted on a motorized hinge (stepper motor, angular resolution 0.05°, range 0.1–90°/s) and filled with a suspension layer of thickness h_{ini} at rest. The motor tilts the tray to a target angle θ_f at rate Ω.

A natural timescale for comparing the tilt to the wave dynamics is $\Omega^* \sim \theta_f \cdot \sigma_{\max}(\phi, \theta_f)$, where $\sigma_{\max}$ is the peak temporal growth rate of the oobleck instability (dimension s^{-1}). Roughly, if $\Omega \gg \Omega^*$ the tray reaches its final angle before Oobleck waves can grow; if $\Omega \ll \Omega^*$ the waves begin growing during the tilt transient. From the linear stability theory of Darbois-Texier *et al.* [2], $\sigma_{\max}$ at $\phi = 0.45$ and $\theta \sim 15°$ is of order 10^{-2} s^{-1}, giving $\Omega^* \sim 10^{-2} \times 15° \sim 0.15°$–$1°$/s (the range reflects uncertainty in the exact $\sigma_{\max}$ without running the full linear stability code). The motor range (0.1–90°/s) straddles this estimate by over two decades in either direction, which is the essential experimental requirement.

Proposed setup. Motorized tray as described; $\phi \in \{0.43, 0.45, 0.46\}$; $h_{\text{ini}} \in \{3, 5, 7, 10\}$ mm; $\theta_f \in \{10°, 15°, 20°, 25°\}$; $\Omega \in \{0.1, 0.5, 2, 10, 50\}°$/s. Side-view high-speed camera (2000 fps) for $h(x, t)$ via backlit LED; spatiotemporal diagrams $h(x, t)$ reveal stairwave nucleation time and speed. Top-view camera for plan-view stairwave geometry near sidewalls. No laser or PIV required.

C. Observables and expected results

Primary observable: spatiotemporal diagram $h(x,t)$ from side-view footage. Stairwaves appear as diagonal stripes with slope $dx/dt = U^{\mathrm{LD}}$; their spatial spacing gives λ. Plot $\lambda(\Omega)$ at fixed $(\phi, \theta_f, h_{\mathrm{ini}})$.

If Eq. (7) is exact, λ is independent of Ω and ϕ—a clean null result that itself confirms the geometric picture and the universality of the liquid-dam speed. If $\lambda(\Omega)$ shows a trend, the crossover rate Ω^* provides a direct empirical measurement of the oobleck-wave growth rate without a separate perturbation experiment. Measuring $\lambda(\phi)$ at fixed $(\Omega, \theta_f, h_{\mathrm{ini}})$ tests whether the rheological parameters enter the wavelength selection at all.

Novelty and publishability. Stairwaves were first reported by Bougouin *et al.* [3]; this would be the first controlled study of their formation. The experiment requires only a motorized tray and existing camera, is executable within 2–3 weeks, and the cleanest outcome—λ independent of Ω and ϕ—is itself publishable as a concise confirmation of the Balmforth–Bougouin picture. A ϕ-dependent or Ω-dependent λ is a more striking result and would motivate a direct comparison with Balmforth's nonlinear theory. Target: *Physical Review Letters* or *Physical Review Fluids*.

VI. EXPERIMENT 5: LIQUID DAM ARREST AND REFORMATION AT A STEP DISCONTINUITY

A. Physical motivation and gap

The gravito-rheological model of Bougouin *et al.* [3] predicts that U^{LD} is an intrinsic material property: it depends only on $\tau_c(\phi)$, $\eta_0(\phi)$, ρ, and g, with no sensitivity to geometry, released volume, or surface topography. This has been tested only on smooth, flat surfaces. A step discontinuity provides a decisive test: if U^{LD} is truly intrinsic, the dam should arrest at the step, undergo a transient, and then re-establish at exactly U^{LD} below the step. Beyond this falsification test, an upward step (barrier) of carefully chosen height can arrest the frictionless overflow layer, providing the first indirect measurement of the overflow-layer thickness δ—the one quantity in the Bougouin model never directly observed.

Key questions. (1) Does the liquid dam reform at $U^{\mathrm{LD}}(\phi)$ after a downward step, confirming the intrinsic character of the gravito-rheological speed? (2) What is the transient length $\Delta x_{\mathrm{trans}}$ over which the dam re-establishes, and how does it scale with ℓ and $\Delta z/H$? (3) What is the critical barrier height b^* above which the jammed front is permanently arrested, and does it scale as predicted from the overflow thickness δ? (4) Is there an upstream-propagating disturbance when the front is arrested?

B. Geometry and scaling

a. Downward step. The jammed front arrives at the step with speed U^{LD} and height H_1. Below the step, the hydrostatic driving increases by $\rho g \Delta z$. Since U^{LD} is set by local rheology alone (independent of Δz), the dam must reform at the same speed below the step. The reformation involves a transient in which the overflow layer re-equilibrates to its original thickness δ. We do not make a detailed analytical prediction for $\Delta x_{\mathrm{trans}}$—the model of Bougouin *et al.* is not derived for this configuration—but parametrically, the relevant scales are ℓ (the jammed-front length) and $\Delta z/\delta$ (the step height normalized by the overflow thickness).

b. Upward barrier (measurement of δ). An upward barrier of height b blocks the jammed front but allows the thin frictionless overflow to pass over if $b < \delta$. The critical barrier height that just arrests the overflow is $b^* \approx \delta$. From the model, the overflow thickness is set by the DST onset condition on the overflow shear stress: the shear stress at the base of the overflow equals τ_c, giving

$$\frac{\rho g\, \delta^2}{2\ell} \sim \tau_c(\phi), \qquad \Rightarrow \qquad \delta \sim \left(\frac{2\ell\, \tau_c}{\rho g}\right)^{1/2}, \tag{8}$$

and hence $b^* \sim \delta$. With $\ell \approx 4H$ (from the Bougouin surface velocimetry), $H = 3$ cm, $\tau_c = 3$ Pa, and $\rho g = 11{,}760$ N/m^3,

$$\delta \approx \left(\frac{2 \times 0.12\,\mathrm{m} \times 3\,\mathrm{Pa}}{11{,}760\,\mathrm{N/m^3}}\right)^{1/2} \approx 8\,\mathrm{mm}. \tag{9}$$

This estimate uses $\ell = 4H$ from the $\ell/H \approx 3$–5 range reported by Bougouin *et al.* Steps in the range 3–15 mm comfortably bracket b^*. Equation (8) predicts $b^* \propto (H\tau_c)^{1/2}$, which can be tested by varying H and ϕ independently.

We note that Eq. (8) is derived from the Bougouin model and involves ℓ, which is itself uncertain by a factor of ~ 2. The numerical estimate in Eq. (9) should be treated as an order-of-magnitude guide for step sizing, not a precise prediction.

Proposed setup. Primary channel ($100 \times 12 \times 6$ cm acrylic, horizontal). Modular acrylic floor inserts, shimmed to precise heights, provide steps of $\Delta z \in \{-10, -5, -3, +1, +3, +5, +8, +12\}$ mm at $x_s = 30$ cm from the release point. Dam-break release: acrylic wedge ($A = 50$–200 cm^2) initially at 45°, tilted to horizontal (identical to the Bougouin protocol). Side-view high-speed camera (500–2000 fps) images the full channel. Spatiotemporal diagram $X(t)$ extracted by front-edge detection. Surface PTV (seeded surface, horizontal laser sheet) for overflow velocity profile before and after step.

C. Observables and expected results

Downward step: Spatiotemporal plot $X(t)$ shows a possible kink when the front crosses x_s, followed by recovery to slope U^{LD}. The recovery length $\Delta x_{\mathrm{trans}}$ vs. Δz and H characterizes the jammed-front relaxation.

Upward barrier: Front speed $U_{\mathrm{post}}(b)$ measured for each b. For $b \ll b^*$: dam passes with no speed change. For $b \sim b^*$: dam slows or arrests. For $b \gg b^*$: front permanently arrested. The threshold $b^*(\phi, H)$ tests Eq. (8). Surface PTV at the step: for $b < b^*$, the overflow-layer velocity profile above the step directly reveals the overflow dynamics; comparing $u_r(r)$ just upstream and downstream of the barrier provides the most direct evidence of the overflow layer in either configuration.

Novelty and publishability. The step provides a decisive, falsifiable test of the intrinsic character of U^{LD}—something no existing liquid-dam experiment has done. The barrier threshold b^* gives the first indirect measurement of δ, closing the last major gap in the Bougouin model. Both sub-experiments are low-cost (acrylic shims, existing channel, existing camera) and executable within a few weeks. The combination of model falsification and internal-structure measurement in a single experiment makes this a strong *Physical Review Letters* candidate.

VII. INSTRUMENTATION NOTES

A. High-speed photography

All five experiments use a single side-view or top-view high-speed camera as the primary diagnostic. Frame rates of 500–2000 fps are sufficient for all proposed flow velocities ($U^{\mathrm{LD}} \sim$ 5–50 mm/s) and length scales ($H \sim$ 5–30 mm). Backlit LED panel illumination provides excellent contrast at the jammed front (the opacity change between flowing and jammed cornstarch is visible to the naked eye and is stark in high-speed images).

B. Laser PIV / PTV

Experiments 1, 2, and 5 use surface PTV: a CW 532 nm DPSS laser ($\geq$ 300 mW) expanded to a $\sim$1 mm horizontal sheet illuminates hollow glass microspheres (50–100 µm) floating at the free surface. The top-view high-speed camera (with a 550 nm long-pass filter to reject scattered laser light) records particle tracks. This requires no additional hardware beyond a CW laser, cylindrical lens, and band-pass filter—all items available from standard optics suppliers.

Cross-sectional (volumetric) PIV inside the bulk of an opaque cornstarch suspension is not possible with visible-light laser sheets and is not proposed here. Any future requirement for interior velocity fields should be addressed by (a) acoustic velocimetry (ultrasound Doppler), (b) an index-matched transparent particle system, or (c) high-resolution x-ray imaging, as suggested by Bougouin *et al.* [3].

C. Rheological characterization

Independent Couette rheometry ($\dot{\gamma}$-sweep at controlled rate) provides $\tau_c(\phi)$ and $\eta_0(\phi)$ via WC fits. The Han–van Ha–Jaeger cornstarch correction $\phi_{\mathrm{eff}} = 1.136\,\phi_{\mathrm{nom}}$ [11] is applied throughout. Moisture content is controlled by preparing suspensions in a humidity-controlled environment ($65 \pm 5\%$ RH) and measuring suspension density before each run. Validating key results in a second particle system (polystyrene beads in water, or cornstarch in water–glycerol) confirms generality, following the Bougouin protocol [3].

D. Prioritization

Table I summarizes the estimated setup complexity and time to first publishable figure for each experiment.

TABLE I. Prioritization of proposed experiments. Setup complexity: L = low (stock parts + machine shop), M = medium (1–2 weeks fabrication + alignment). Time to result: elapsed time from start to first publication-quality figure.

Exp.	Topic	Complexity	Time	Primary target
4	Stairwave tilt-rate	L	2–3 weeks	*PRL* / *PRF*
5	Step discontinuity	L	3–5 weeks	*PRL*
1	3D radial dam break	L	3–5 weeks	*PRL* / *PRF*
2	Elastic membrane	M	4–8 weeks	*PRL* / *SM*
3	Wave dispersion mapping	M	8–16 weeks	*JFM* / *PRF*

Experiments 4, 5, and 1 can be started immediately with stock acrylic, a motorized hinge, and the existing high-speed camera. They share no hardware and can run in parallel. Experiments 2 and 3 require additional fabrication (membrane frame and actuator; recirculating channel) but are the highest-impact targets and should be designed concurrently with the first three.

VIII. DISCUSSION

The five experiments collectively address three open questions in the liquid-dam and oobleck-wave literature as of early 2026.

(i) *Three-dimensionality* (Experiment 1): All existing theory and experiment is quasi-2D. The 3D case modifies the height dynamics from $H \sim t^{-1/5}$ (Newtonian 2D) to the clean $H \sim t^{-2}$ during the liquid-dam phase, with a subsequent transition to the Huppert axisymmetric regime. The azimuthal stability of the jammed front is entirely open.

(ii) *Internal flow structure and model validation* (Experiments 3, 5): The overflow thickness δ and jammed-front length ℓ enter the Bougouin model but have not been directly measured. Experiment 5 measures δ indirectly via the barrier threshold; Experiment 3 maps

$\sigma(k)$ with no free parameters, providing the first quantitative test of the Darbois Texier stability theory.

(iii) *Controlled dynamics* (Experiments 4, 2): Stairwave formation has only been observed under abrupt tilt; controlling Ω converts an observation into a measurement. Experiment 2 similarly converts the impact scenario (impulsive, inertia-dominated) into a controlled quasi-static forcing, isolating the WC nucleation mechanism.

Any publishable result from these experiments should include validation in a second particle system (polystyrene–water or cornstarch–glycerol) to confirm that the observed behavior is generic to DST suspensions rather than specific to cornstarch.

ACKNOWLEDGMENTS

This work is supported by [grant details]. The author thanks the Driscoll Laboratory and the Cheng Laboratory (Northwestern University) for access to equipment and discussion.

---

[1] B. Darbois Texier, H. Lhuissier, Y. Forterre, and B. Metzger, *Surface-wave instability without inertia in shear-thickening suspensions*, Commun. Phys. **3**, 232 (2020).

[2] B. Darbois-Texier, H. Lhuissier, B. Metzger, and Y. Forterre, *Shear-thickening suspensions down inclines: from Kapitza to Oobleck waves*, J. Fluid Mech. **959**, A27 (2023).

[3] A. Bougouin, H. Lhuissier, Y. Forterre, and B. Metzger, *Liquid Dam: A Constant-Speed Regime in Gravity-Driven Shear-Thickening Suspensions*, Phys. Rev. Lett. **136**, 158202 (2026).

[4] A. Bougouin, B. Metzger, Y. Forterre, P. Boustingorry, and H. Lhuissier, *A frictional soliton controls the resistance law of shear-thickening suspensions in pipes*, Proc. Natl. Acad. Sci. U.S.A. **121**, e2321581121 (2024).

[5] M. Wyart and M. E. Cates, *Discontinuous shear thickening without inertia in dense non-Brownian suspensions*, Phys. Rev. Lett. **112**, 098302 (2014).

[6] N. J. Balmforth, *Nonlinear Oobleck waves*, J. Fluid Mech. **1002**, A34 (2025).

[7] V. Rathee, J. Miller, D. Blair, and J. Urbach, *Structure of propagating high-stress fronts in a shear-thickening suspension*, Proc. Natl. Acad. Sci. U.S.A. **119**, e2203795119 (2022).

[8] F. Depoilly, S. Millet, H. Ben Hadid, S. Dagois-Bohy, and F. Rousset, *Unifying the roll waves*, PLoS One **19**, e0310805 (2024).

[9] F. Rocha, Y. Forterre, B. Metzger, and H. Lhuissier, *Drag of a shear-thickening suspension on a rotating cylinder*, J. Fluid Mech. **970**, A35 (2023).

[10] S. R. Waitukaitis and H. M. Jaeger, *Impact-activated solidification of dense suspensions via dynamic jamming fronts*, Nature **487**, 205 (2012).

[11] E. Han, N. Van Ha, and H. M. Jaeger, *Measuring the porosity and compressibility of liquid-suspended solids using ultrasound*, Soft Matter **13**, 3506 (2017).

[12] S. Mobaseri *et al.*, Proc. Natl. Acad. Sci. U.S.A. (2025).

[13] S. Mobaseri *et al.*, arXiv:2601.12642 (2026).

[14] H. E. Huppert, *The propagation of two-dimensional and axisymmetric viscous gravity currents over a rigid horizontal surface*, J. Fluid Mech. **121**, 43 (1982).