On the Superiority of Hydrodynamic Perianal Cleansing: A Quantitative Framework in Fluid Mechanics, Tribology, and Environmental Economics for Bidet Adoption Policy in the United States

Charlie Burton*
Department of Physics and Astronomy, Northwestern University
(Dated: March 22, 2026)

The United States remains an international outlier in its near-universal reliance on dry toilet paper (TP) for perianal hygiene, consuming 141 rolls/person/year, the highest per-capita rate on Earth, while countries such as Japan have achieved 80 % household bidet penetration. This paper constructs a rigorous, quantitative argument for bidet adoption in American residential and commercial buildings across four domains. Using Watson's (1964) radial wall-jet solution augmented by a curvature-perturbation expansion, we model the nozzle as a turbulent circular free jet (Re ≈ 10,000–18,000) and derive wall shear stress distributions $\tau_w(r)$; peak values $\tau_{w,\max} \approx 100$–$1{,}000\,\mathrm{Pa}$ exceed the critical detachment threshold for fecal biofilm ($\tau_{\mathrm{crit}} \approx 1$–$10\,\mathrm{Pa}$) by one to two orders of magnitude. A Péclet-number analysis ($\mathrm{Pe} \sim 10^9$) confirms that advective transport in the spreading water film eliminates dislodged material in a single pass, whereas dry wiping redistributes rather than removes debris. Tribological analysis of toilet paper on moist perianal skin yields contact shear stresses of 1–30 kPa, two to three orders of magnitude above the bidet's hydrodynamic shear, providing a mechanistic basis for stratum corneum disruption and the associated clinical spectrum of pruritus ani, anal fissures, and hemorrhoidal exacerbation. An environmental lifecycle and economic analysis shows that national bidet adoption would eliminate the harvest of 15–31 million trees annually, reduce embedded water consumption by ∼ 98 %, and pay back household installation costs within 3–15 months. A targeted policy proposal modeled on the EPA WaterSense rebate framework is presented.

I. INTRODUCTION

The act of perianal cleansing following defecation is performed by nearly every human being on the planet multiple times daily, yet the dominant American method (dry mechanical wiping with cellulose paper) has received almost no formal engineering scrutiny. The bidet employs a directed water jet to accomplish the same task through different physics: convective mass transfer rather than frictional contact, hydrodynamic shear rather than tribological abrasion, and advective removal rather than smearing. These differences are quantitative, spanning two to three orders of magnitude in the mechanical stress delivered to perianal tissue.

The public health stakes are substantial. Hemorrhoidal disease affects an estimated 10 million Americans annually, generating $770 million in documented employer-insured healthcare costs [14]. Pruritus ani has a population prevalence of 1–5%, with mechanical irritation from wiping identified as a primary or exacerbating factor in a significant fraction of cases [3]. The environmental costs are no less significant: American toilet paper consumption accounts for approximately 20% of global supply [18], with 80% manufactured from virgin forest fiber [13].

* cpb@u.northwestern.edu

II. ANATOMICAL GEOMETRY: THE HEMI-CYLINDER MODEL

A. Geometric Idealization

The perianal anatomy presents a concave ellipsoidal cleft whose local geometry near the anal verge is well approximated, for the purpose of fluid mechanical analysis, by a hemi-cylindrical surface. We define the *effective cleft radius* R as the radius of curvature of the inter-gluteal fold at the level of the anus, measured in the sagittal plane. From anthropometric data, $R \approx 15$–$25\,\mathrm{mm}$ for the seated adult posture relevant to bidet use.

We introduce cylindrical coordinates (r, ϕ, z) with z directed along the jet axis (vertically downward from the nozzle), the apex of the concave surface located at the origin, and r measuring radial distance from the stagnation point on the surface. The concave surface profile is described by

$$z_s(r) = \frac{r^2}{2R} + \mathcal{O}\left(\frac{r^4}{R^3}\right), \qquad r \ll R, \tag{1}$$

i.e., a paraboloid of revolution to leading order. The flat-plate limit corresponds to $R \to \infty$, and curvature effects enter at $\mathcal{O}(r^2/R^2)$.

The *curvature parameter* is defined as

$$\epsilon \equiv \frac{d}{R}, \tag{2}$$

where d is the nozzle diameter. For typical values $d \approx 1$–$2\,\mathrm{mm}$ and $R \approx 20\,\mathrm{mm}$, we have $\epsilon \approx 0.05$–0.10, confirming

that curvature is a small but non-negligible perturbation. The analysis of Sections III–IV proceeds by (i) solving the flat-plate impinging jet problem exactly, and (ii) incorporating curvature effects via a systematic perturbation expansion in ϵ.

B. Debris Distribution and the Cleaning Criterion

Fecal residue is deposited on the concave surface as a thin layer of shear-thinning viscoplastic material. Let $\Sigma(r)$ denote the areal density of adhered material (kg/m^2) as a function of radial position. The cleaning criterion requires that the wall shear stress delivered by the bidet jet exceed the adhesive yield stress of the fecal layer at every point:

$$\tau_w(r) \geq \tau_{\text{crit}}(r) \quad \forall\, r \in [0, r_{\max}], \tag{3}$$

where $r_{\max}$ is the maximum radial extent of contamination (estimated at 10–20 mm based on anatomical considerations).

The effective angular cleaning coverage on the hemi-cylinder is bounded by the angle $\theta_{\max}$ at which the jet's normal velocity component drops below the cleaning threshold:

$$V_n(\theta) = V_0 \cos\theta \geq \left(\frac{2\tau_{\text{crit}}}{\rho}\right)^{1/2} \text{Re}_d^{1/4}, \tag{4}$$

where θ is the polar angle from the apex. For $\tau_{\text{crit}} \approx 5$ Pa, $V_0 \approx 10$ m/s, and $\text{Re}_d \approx 14{,}000$, equation (4) yields $\theta_{\max} \approx 82°$, indicating that effective cleaning extends over essentially the entire hemi-cylindrical surface.

III. FLUID MECHANICS OF THE IMPINGING BIDET JET

A. Nozzle Conditions and Free-Jet Parameters

A modern bidet nozzle delivers a coherent circular jet through a circular orifice of diameter $d = 1$–2 mm at a supply gauge pressure $\Delta P = 0.05$–0.1 MPa. The jet exit velocity follows from the Torricelli relation with a velocity coefficient $C_v \approx 0.97$:

$$V_0 = C_v \sqrt{\frac{2\,\Delta P}{\rho}}, \tag{5}$$

yielding $V_0 \approx 8$–14 m/s across the operating envelope. The volumetric flow rate and mass-flux Reynolds number are, respectively,

$$Q = \frac{\pi d^2}{4} V_0, \qquad \text{Re}_d = \frac{V_0\, d}{\nu}, \tag{6}$$

with $\nu = 8.9 \times 10^{-7}$ m^2/s for water at $T = 25\,°$C. For $V_0 = 10$ m/s and $d = 1.3$ mm:

$$\text{Re}_d = \frac{(10)(1.3 \times 10^{-3})}{8.9 \times 10^{-7}} \approx 14{,}600, \tag{7}$$

placing the exit flow in the fully turbulent regime ($\text{Re}_d > 3{,}000$ for a pipe, $> 4{,}000$ for a free jet [23]).

1. Jet Coherence: Weber Number Analysis

The Weber number governs whether surface tension can break the jet into droplets via Rayleigh–Plateau instability:

$$\text{We} = \frac{\rho V_0^2\, d}{\sigma}, \tag{8}$$

where $\sigma = 0.072$ N/m for water–air at 25 °C. For the nominal parameters, We $\approx 1{,}400$–$2{,}800$, indicating that inertia overwhelmingly dominates surface tension. The axisymmetric Rayleigh breakup length, accounting for the turbulent perturbation spectrum [10], scales as

$$L_{\text{break}} \approx 12\,\text{We}^{1/2}\, d \approx 450\,\text{mm}. \tag{9}$$

Since the nozzle-to-skin standoff H is typically $H \approx 50$–150 mm, the condition $L_{\text{break}} \gg H$ is satisfied comfortably. The jet therefore arrives at the skin surface as a continuous liquid column of nearly uniform velocity V_0, not as a dispersed spray. A spray carries less momentum per unit area and generates lower wall shear stress.

2. Free-Jet Velocity Decay

Beyond the potential core, which extends to $z/d \approx 4$–6 [16], the centreline velocity of a turbulent axisymmetric jet decays as

$$\frac{V_c(z)}{V_0} = \frac{B}{z/d}, \qquad B \approx 6.3, \tag{10}$$

with a self-similar Gaussian radial profile $V(r,z) = V_c(z)\exp\!\left(-r^2/(2\sigma_j^2 z^2)\right)$, where $\sigma_j \approx 0.094$.

For a standoff of $H = 80$ mm and $d = 1.3$ mm, we have $H/d \approx 62$, so the impinging centreline velocity is $V_c(H) = V_0\, B/(H/d) = 10 \times 6.3/62 \approx 1$ m/s. At first glance this appears to substantially reduce impingement effectiveness. However, the relevant quantity for wall shear stress is not the centreline velocity but the *radial velocity* in the spreading wall jet, which is set by momentum conservation rather than direct jet velocity. The total axial momentum flux $J = \rho Q V_0 = \pi\rho d^2 V_0^2/4$ is conserved throughout the free-jet region (in the absence of co-flow), and it is J that drives the wall-jet spreading and generates the cleaning shear stress. Thus the effective cleaning capacity scales as $\tau \sim J^{1/2}/(\nu^{1/2} r)$ and is relatively insensitive to jet decay at moderate standoffs.

B. Impingement Zone: Stagnation Flow Analysis

In the immediate vicinity of the stagnation point ($r \lesssim d/2$), the flow is described by axisymmetric stagnation-

point theory. Along the stagnation streamline, the continuity equation requires the radial velocity to grow linearly with r:

$$u_r(r,0) = a\,r + \mathcal{O}(r^3), \tag{11}$$

where a is the *strain rate* at the stagnation point. For an impinging jet, Schlichting's boundary-layer analysis gives $a \approx V_c(H)/l_{\text{imp}}$, with the impingement length scale $l_{\text{imp}} \sim d/2$. The Bernoulli equation applied along the stagnation streamline yields the *stagnation pressure*:

$$P_s = P_\infty + \frac{1}{2}\rho V_c^2(H). \tag{12}$$

For $V_c(H) \approx 10\,\text{m/s}$ (short standoff) to $1\,\text{m/s}$ (long standoff):

$$P_s - P_\infty \approx \frac{1}{2}(1000)(10)^2 = 50\,\text{kPa} \quad \text{(short standoff)}. \tag{13}$$

Although 50 kPa exceeds atmospheric by roughly half, this pressure is compressive (normal to the surface), acts over a very small contact area $A_{\text{stag}} \sim \pi d^2/4 \approx 1.3\,\text{mm}^2$, and produces no frictional shear. The stagnation region therefore poses no abrasive risk to the skin; the loading is purely hydrostatic.

The pressure distribution along the surface decays from the stagnation value as (from Bernoulli and the radial acceleration in equation 11)

$$P(r) = P_s - \frac{1}{2}\rho a^2 r^2. \tag{14}$$

The radial pressure gradient $\partial P/\partial r = -\rho a^2 r < 0$ drives the flow outward into the spreading wall jet.

C. Wall Jet Region: Watson's Solution for the Flat-Plate Baseline

Beyond the stagnation zone ($r > d/2$), the flow transitions into a thin radially spreading *wall jet* governed by the Prandtl boundary-layer equations. Following Watson (1964) [21], we consider the axisymmetric spreading of a circular liquid jet on a horizontal plate under the assumptions: (i) the outer flow is inviscid with uniform surface velocity $U_s \approx V_0$; (ii) a viscous boundary layer of thickness $\delta(r)$ grows from the plate upward; and (iii) the pressure is atmospheric throughout (no streamwise adverse pressure gradient in the outer film, as verified by the decay of equation 14).

The governing equations in the boundary layer are

$$\frac{\partial(r\,u_r)}{\partial r} + \frac{\partial(r\,u_z)}{\partial z} = 0, \qquad u_r\frac{\partial u_r}{\partial r} + u_z\frac{\partial u_r}{\partial z} = \nu\frac{\partial^2 u_r}{\partial z^2}, \tag{15}$$

with boundary conditions

$$u_r(r,0) = 0 \qquad \text{(no-slip)}, \tag{16}$$

$$\left.\frac{\partial u_r}{\partial z}\right|_{z=h(r)} = 0 \qquad \text{(zero shear at free surface)}, \tag{17}$$

$$u_r(r,h) = U_s = V_0 \qquad \text{(matching outer inviscid flow)}, \tag{18}$$

where $h(r) = Q/(2\pi r V_0) = a^2 V_0/(2rV_0) = a^2/(2r)$ is the local film thickness (volume conservation, $a \equiv d/2$).

Watson introduces the similarity variable $\eta = z/\delta(r)$ and assumes a cubic velocity profile within the boundary layer:

$$\frac{u_r}{V_0} = \frac{3}{2}\eta - \frac{1}{2}\eta^3, \qquad 0 \le \eta \le 1, \tag{19}$$

which satisfies both (16) and (17). The von Kármán momentum integral equation then gives the boundary-layer growth law:

$$\frac{d}{dr}\left(r\int_0^\delta u_r(U_s - u_r)\,dz\right) = -r\,\nu\left.\frac{\partial u_r}{\partial z}\right|_{z=0}, \tag{20}$$

which, upon substituting equation (19), yields

$$r\,\frac{d}{dr}\left(\frac{r\,\delta}{h}\right) = \frac{3\,r^2}{h^2}\cdot\frac{\nu}{V_0\,\delta}, \tag{21}$$

solved by Watson as

$$\frac{\delta}{a} = \frac{\sqrt{3}\,\Gamma(1/3)}{2^{2/3}\,\Gamma(2/3)}\left(\frac{r}{a}\right)^3 \text{Re}_a^{-1}, \qquad r \le r_0, \tag{22}$$

where $a = d/2$, $\text{Re}_a = V_0 a/\nu$, and the numerical prefactor evaluates to approximately 0.5757.

The *transition radius* r_0, at which the boundary layer spans the entire film ($\delta = h$), is

$$\frac{r_0}{a} = \left[\frac{a^2/2}{a\,C_W\,\text{Re}_a^{-1}}\right]^{1/3} = (0.3536\,\text{Re}_a)^{1/3}, \tag{23}$$

where $C_W = 0.5757$. For $\text{Re}_a = V_0(d/2)/\nu = 7{,}300$ (half the jet Re_d):

$$r_0 = a\,(0.3536{\times}7300)^{1/3} \approx a{\times}13.5 \approx 8.8\,\text{mm} \quad (d = 1.3\,\text{mm}). \tag{24}$$

1. *Wall Shear Stress Distribution*

The wall shear stress in Watson's Region I ($r \le r_0$) follows directly from the cubic velocity profile (19):

$$\tau_w(r) = \mu\left.\frac{\partial u_r}{\partial z}\right|_{z=0} = \mu\,V_0\,\frac{3}{2\delta(r)}, \tag{25}$$

and substituting equation (22):

$$\boxed{\tau_w(r) = \frac{3\mu\, V_0}{2\, a\, C_W}\, \mathrm{Re}_a \left(\frac{a}{r}\right)^3, \qquad r \le r_0.} \tag{26}$$

Several features of this result merit discussion:

(i) The shear stress scales as r^{-3}: extremely concentrated near the impingement point and decaying rapidly.

(ii) $\tau_w \propto \mathrm{Re}_a$: higher jet velocity yields linearly higher shear stress (since $\mathrm{Re}_a = V_0 a/\nu$ and $\mu V_0 \cdot \mathrm{Re}_a = \rho V_0^2 a$, giving $\tau_w \propto \rho V_0^2$, i.e., the dynamic pressure).

(iii) At $r = a$ (the edge of the jet footprint):

$$\tau_w(a) = \frac{3\rho\nu V_0}{2\, C_W} \cdot \frac{\mathrm{Re}_a}{a} = \frac{3\rho V_0^2}{2\, C_W} \approx 2.6\, \rho V_0^2. \tag{27}$$

For $V_0 = 10\,\mathrm{m/s}$, this gives $\tau_w(a) \approx 2.6 \times 10^3 \times 10^2 = 260\,\mathrm{kPa}$, a value that substantially exceeds any adhesive threshold but is concentrated over a tiny area ($r \sim a \sim 0.65\,\mathrm{mm}$).

(iv) The peak shear stress relevant for practical cleaning, averaged over the inner cleaning zone $r \le 5\,\mathrm{mm}$:

$$\langle \tau_w \rangle_{r \le 5\,\mathrm{mm}} = \frac{3\rho\nu V_0\, \mathrm{Re}_a}{2\, a^2\, C_W} \int_a^{5a} \frac{r\, dr}{r^3} \approx 100\text{–}1{,}000\,\mathrm{Pa}. \tag{28}$$

In Watson's Region II ($r > r_0$), the boundary layer spans the full film and the governing physics changes. The shear stress drops more steeply, approximated by [15]:

$$\tau_w(r) \propto r^{-5/3}, \qquad r > r_0. \tag{29}$$

2. Hydraulic Jump

At a radial distance r_h determined by the momentum-gravity balance, the thin high-velocity film undergoes a *hydraulic jump*: an abrupt thickening accompanied by a rapid velocity decrease. Using Watson's result, r_h satisfies

$$\frac{3Q^2}{8\pi^2 g}\, r_h^{-3} = r_h\, h_H^2, \tag{30}$$

where h_H is the post-jump film thickness. For typical bidet parameters, $r_h \approx 15$–$30\,\mathrm{mm}$, coincidentally close to the anatomical boundary of the contaminated region $r_{\max}$. The hydraulic jump thus serves a natural confinement function, preventing dilute contaminated water from spreading beyond the cleft onto dry perianal skin.

D. Curvature Effects: Concave-Surface Perturbation

We now generalize the Watson solution to the concave surface geometry. Define the arc-length coordinate s measured along the curved surface from the stagnation point (replacing the flat-plate r). For $r \ll R$, we have $s \approx r + r^3/(6R^2) + \ldots$, so to leading order $s \approx r$ and the curvature correction enters at $\mathcal{O}(\epsilon^2)$.

The key dynamical modification on a concave surface is the centrifugal pressure gradient in the direction normal to the surface (n-direction):

$$\frac{\partial P}{\partial n} = -\frac{\rho U_e^2}{R_{\mathrm{eff}}}, \tag{31}$$

where U_e is the outer edge velocity and $R_{\mathrm{eff}}(s)$ is the local surface radius of curvature. This creates an *adverse normal pressure gradient* (pressure decreasing away from the surface) that *inhibits boundary-layer growth* on a concave wall, thickening it less rapidly than on a flat plate. The net effect on wall shear stress is a positive correction:

$$\tau_w^{\mathrm{concave}}(r) = \tau_w^{\mathrm{flat}}(r) \left[1 + \frac{\alpha_c\, \delta(r)}{R} + \mathcal{O}(\epsilon^2)\right], \tag{32}$$

where $\alpha_c = \mathcal{O}(1)$ is a positive numerical constant (typically 0.5–1.5 from boundary-layer stability analyses [6]). For $\delta \approx 0.1\,\mathrm{mm}$ and $R = 20\,\mathrm{mm}$, the first-order correction is $\delta/R \approx 0.005$, a 0.5% enhancement over the flat-plate value, confirming that the flat-plate Watson solution is a conservative (under-)estimate of cleaning effectiveness on the concave anatomy.

1. Taylor–Görtler Vortex Instability

Concave boundary layers are subject to the centrifugal *Taylor–Görtler* instability, which generates counter-rotating streamwise vortex pairs and substantially enhances turbulent mixing and surface transport. The criterion for onset is [6]:

$$\mathrm{Gö} \equiv \frac{U_e\, \theta}{\nu} \sqrt{\frac{\theta}{R}} > \mathrm{Gö}_{\mathrm{crit}} \approx 0.3, \tag{33}$$

where θ is the momentum thickness of the boundary layer. For the spreading water film at $r \approx r_0 \approx 9\,\mathrm{mm}$, the momentum thickness $\theta \approx \delta/6 \approx 15\,\mu\mathrm{m}$ and $U_e \approx V_0$, giving $\mathrm{Gö} \approx 0.03$, below the critical value, meaning Taylor–Görtler vortices are unlikely in the thin wall-jet film under typical bidet conditions. However, in Region II ($r > r_0$), as the film thickens and velocity decreases, Gö grows and may approach critical values near the hydraulic jump, where additional mixing would enhance late-stage debris transport. This effect is conservative to neglect and can only improve cleaning performance.

IV. MASS TRANSFER AND CLEANING EFFICACY

A. The Detachment Criterion

Cleaning of an adhered layer by fluid shear proceeds in two steps: (i) detachment, when τ_w exceeds the adhesive yield stress; and (ii) transport, when the dislodged material is carried away by the flow. We address each in turn.

The critical wall shear stress τ_{crit} for detachment of fecal residue from skin is not directly measured in the literature (a gap discussed in Section VIII). We bound it from below and above:

(i) *Lower bound*: The EHEDG standard for industrial surface hygiene establishes $\tau_{\text{crit}} = 3\,\text{Pa}$ as the threshold for removing biological soil [5]. Biofilm detachment studies find $\tau_{\text{crit}} \approx 0.3$–$4.7\,\text{Pa}$ [19].

(ii) *Upper bound*: Fecal material has a measured dynamic yield stress of approximately $\sigma_y \approx 10\,\text{Pa}$ at physiologically relevant moisture contents [22]. The mucus-encapsulation model of Hu et al. (2017) further suggests that residual fecal adhesion to skin is mediated by a mucus interlayer with viscosity $100\times$ lower than bulk feces, which would reduce effective adhesive shear to $\tau_{\text{crit}} \approx 1$–$10\,\text{Pa}$.

We therefore adopt $\tau_{\text{crit}} = 1$–$10\,\text{Pa}$ as the operative range. From equation (26), the *cleaning radius* r_{clean} where $\tau_w = \tau_{\text{crit}}$ is

$$r_{\text{clean}} = a\left(\frac{3\,\rho V_0^2}{2\,C_W\,\tau_{\text{crit}}}\right)^{1/3} \qquad (r_{\text{clean}} \le r_0). \tag{34}$$

For $\tau_{\text{crit}} = 5\,\text{Pa}$, $\rho V_0^2 = 100\,\text{kPa}$:

$$r_{\text{clean}} = (0.65\,\text{mm})\left(\frac{3\times10^5}{2\times0.58\times5}\right)^{1/3} \approx (0.65\,\text{mm})\,(17{,}000)^{1/3} \approx (0.65\,\text{mm})(26) \approx 17\,\text{mm}. \tag{35}$$

This value ($r_{\text{clean}} \approx 17\,\text{mm}$) comfortably encloses the anatomical contamination zone ($r_{\max} \approx 10$–$20\,\text{mm}$), confirming that the bidet jet delivers sufficient shear to remove fecal residue across the entire relevant surface. Moreover, since $r_{\text{clean}} \approx r_0$, cleaning occurs primarily in Watson's Region I where the r^{-3} shear stress is highest; the jet operates in the regime where it is most effective.

The margin of safety is defined as

$$\mathcal{M} = \frac{\langle\tau_w\rangle}{\tau_{\text{crit}}} \approx \frac{100\text{–}1000\,\text{Pa}}{1\text{–}10\,\text{Pa}} = 10\text{–}1000, \tag{36}$$

a safety margin of one to three orders of magnitude.

B. Advective Removal: The Péclet Number

Detachment is necessary but not sufficient for cleaning: dislodged material must be transported away from the surface. The competition between advective and diffusive transport is quantified by the Péclet number:

$$\text{Pe} = \frac{U_{\text{film}}\,L}{\mathcal{D}}, \tag{37}$$

where $U_{\text{film}} \approx 5\,\text{m/s}$ is a representative film velocity in the cleaning zone, $L \approx r_{\text{clean}} \approx 0.017\,\text{m}$, and $\mathcal{D} \sim 10^{-10}$–$10^{-9}\,\text{m}^2/\text{s}$ is the effective diffusivity of fecal particulates (micron-scale; Stokes–Einstein).

$$\text{Pe} \sim \frac{(5)(0.017)}{10^{-10}} = 8.5\times10^8 \approx 10^9. \tag{38}$$

Transport is overwhelmingly advective. Once detached, debris particles are swept radially outward by the spreading film in a time $t \sim L/U_{\text{film}} \approx 3.4\,\text{ms}$, before falling under gravity into the toilet bowl. This single-pass removal mechanism is the central advantage of water over paper: toilet paper displaces fecal material but provides no transport fluid, leading to smearing rather than removal. A quantitative estimate of residual contamination after wiping is beyond the scope of this paper (and beyond the scope of any published clinical study; see Section VIII); however, the absence of any transport mechanism in dry wiping is physically unambiguous.

V. TISSUE MECHANICS: THE COST OF WIPING

A. Tribological Analysis

The mechanical interaction between toilet paper and perianal skin is governed by tribological principles. The friction force during a wiping pass is

$$F_f = \mu_k\,N, \tag{39}$$

where N is the normal load and μ_k is the kinetic friction coefficient. The resulting contact shear stress is

$$\tau_{\text{wipe}} = \frac{F_f}{A_c} = \mu_k\,P_c, \tag{40}$$

where $P_c = N/A_c$ is the contact pressure.

Derler and Gerhardt [4] compiled extensive data on skin friction, reporting $\mu_k = 0.2$–2.7 with strong dependence on moisture, temperature, and substrate material. On moist skin (relevant to post-defecation conditions), paper-on-skin friction coefficients of $\mu_k = 0.5$–1.5 are well documented [20]; wet toilet paper on wet skin can reach $\mu_k \approx 2.0$–4.1 due to meniscus adhesion. We adopt the conservative range $\mu_k = 0.5$–1.5.

Applied wiping forces for perianal hygiene in normal adults have not been directly published. From ergonomic and pressure-sensor data for analogous manual tasks (clinical perineal care), we estimate $N \approx 2$–$10\,\text{N}$ applied over a contact area $A_c \approx 5$–$15\,\text{cm}^2$ (a folded pad of 4–6 ply), giving contact pressures $P_c \approx 2$–$20\,\text{kPa}$. The wiping shear stress is therefore:

$$\tau_{\text{wipe}} = \mu_k\,P_c \approx (0.5\text{–}1.5)\times(2{,}000\text{–}20{,}000\,\text{Pa}) = 1{,}000\text{–}30{,}000\,\text{Pa}. \tag{41}$$

B. Quantitative Stress Comparison

Table I compares the mechanical stresses delivered by each modality. The bidet's hydrodynamic wall shear occupies the range 1–100 Pa (averages over the cleaning zone), while wiping generates 1–30 kPa, a ratio of two to three orders of magnitude.

TABLE I. Comparative mechanical stress analysis: bidet vs. toilet paper.

Parameter	Bidet (water jet)	Toilet paper	Ratio (TP/Bidet)
Shear stress on tissue	1–100 Pa	1,000 Pa–30,000 Pa	10–1000×
Normal contact pressure	0.4–2 kPa (stagnation)	2–20 kPa	5–50×
Contact type	Non-contact (hydrodynamic)	Solid friction (abrasive)	N/A
Transport mechanism	Advective (Pe $\sim 10^9$)	None (smearing)	N/A
Friction coefficient	0 (no solid contact)	$\mu_k = 0.5$–1.5	N/A

C. Stratum Corneum Disruption

The perianal stratum corneum (SC) is the outermost, rate-limiting barrier of the skin, comprising 10–20 corneocyte layers at a total thickness of $\sim 15\,\mu$m [11]. The SC is more susceptible to friction injury than skin at other body sites due to the combined effects of chronic moisture exposure (occlusion reduces barrier function) and thin tissue architecture.

Each wiping pass applies the shear stress in equation (41) over the SC, progressively disrupting the intercorneocyte lipid lamellae. Löffler *et al.* [12] demonstrated that barrier disruption (measured by trans-epidermal water loss, TEWL) is directly proportional to both the frictional force and the number of passes. For 3–6 passes per event and multiple events per day, cumulative SC disruption is substantial.

The clinical injury threshold for *pressure injury* formation (a more severe endpoint than barrier disruption) is approximately $\tau_{\text{injury}} \approx 9$–$15$ kPa [2]. Vigorous wiping ($\tau_{\text{wipe}} \approx 10$ kPa) reaches this threshold, particularly in elderly or immunocompromised patients.

The bidet delivers no solid-contact stress. The hydrodynamic wall shear ($\tau_w \approx 10$–100 Pa) is 100–1,000× below the SC disruption threshold, and no friction coefficient enters the problem. The difference in tissue loading between the two modalities is not incremental but physical in kind.

D. Clinical Sequelae

The mechanical analysis predicts the following hierarchy of tissue pathology from chronic toilet-paper use, consistent with the clinical literature:

1. *Pruritus ani*: Affects 1–5% of the general population. Dasan *et al.* [3] found contact dermatitis (including from toilet paper allergens: formaldehyde, chlorine residues, fragrances) in 53% of identifiable cases at a specialized clinic.

2. *Hemorrhoidal exacerbation*: Hemorrhoids affect ~ 10 million Americans annually [14]. Ryoo *et al.* [17] demonstrated that bidet use at low jet forces (40–200 mN) significantly reduces anal resting pressure, whereas wiping with paper at 2–10 N exacerbates vascular engorgement.

3. *Anal fissures*: Chronic SC disruption reduces barrier function against fecal bacteria and increases susceptibility to fissure formation, particularly when combined with constipation-induced trauma.

The systematic review by Baig *et al.* [1] should be interpreted with caution; their finding of elevated bidet use among subjects with perianal pathology most likely reflects reverse causation (patients adopt bidets *because* of symptoms), confirmed by the prospective study of Kiuchi *et al.* [9], which found no significant incidence odds ratio for new hemorrhoid development among bidet users.

VI. ENVIRONMENTAL AND ECONOMIC ANALYSIS

A. Resource Consumption of the American Toilet Paper Habit

The United States consumes approximately 36.5 billion rolls of toilet paper annually, representing $\sim 20\%$ of the global supply from $\sim 4\%$ of the world's population [18]. The environmental footprint per roll is estimated at: 37 gallons of embedded water (tree growth and manufacturing), 0.47 kWh of electricity, and 140 g of CO_2-equivalent emissions (virgin-fiber product) [13]. Aggregated to national scale:

- Embedded water: ∼473 billion gallons per year;
- Virgin trees harvested: 15–31 million annually, sourced disproportionately from Canada's boreal forest;
- Carbon emissions from production and deforestation: ∼26 million metric tons CO_2-equivalent per year.

B. Lifecycle Comparison

A single bidet use consumes $Q_{\text{bidet}} \approx 0.5$ L of water. For 2 uses per day per person:

$$W_{\text{bidet}} = 0.5\,\text{L} \times 2 \times 365 = 365\,\text{L/yr} \approx 96\,\text{gal/yr}. \quad (42)$$

Compared to the 5,200 gal/yr in embedded TP water, the bidet uses $\sim 1.8\%$ of the water budget. The net embedded-water reduction from national adoption would be $\sim$5,100 gal yr^{-1} person^{-1}, or $\sim$1.7 trillion gallons nationally.

Non-electric bidet attachments carry a manufacturing carbon footprint of $\sim$3–6 lbs CO_2e (embodied in $\sim$200 g of plastic), amortized over a 5–10 year lifespan: negligible compared to the annual avoided carbon footprint of $\sim$ 50 lbs CO_2e yr^{-1} from eliminated TP production.

C. Economic Analysis

Define household variables: n occupants, C_{TP} = annual toilet paper expenditure, C_{bidet} = bidet purchase price, f = fractional TP reduction post-adoption (typically $f = 0.65$–0.75), r = real discount rate. The *net present value* of bidet adoption over a horizon T is:

$$\mathrm{NPV} = -C_{\mathrm{bidet}} + \sum_{t=1}^{T} \frac{f\, C_{\mathrm{TP}}}{(1+r)^t} = -C_{\mathrm{bidet}} + f\, C_{\mathrm{TP}}\, \frac{1-(1+r)^{-T}}{r}. \tag{43}$$

For $C_{\mathrm{bidet}} = \$50$ (attachment), $C_{\mathrm{TP}} = \$200$/yr (4-person household), $f = 0.70$, $r = 0.05$, $T = 10$ yr:

$$\mathrm{NPV} = -50 + (0.70)(200)\,(7.72) = -50 + 1{,}081 = \$1{,}031. \tag{44}$$

The *payback period* T^* is defined by $\mathrm{NPV}(T^*) = 0$:

$$T^* = \frac{C_{\mathrm{bidet}}}{f\, C_{\mathrm{TP}}} = \frac{50}{(0.70)(200)} \approx 0.36\,\mathrm{yr} \approx 4.3\,\mathrm{months}. \tag{45}$$

At the national scale, if 50% of 130 million US households adopted a bidet attachment:

$$\text{Annual savings} = 0.50 \times 1.3 \times 10^8 \times \$140 \approx \$9.1\,\text{billion/yr}. \tag{46}$$

Additional healthcare cost offsets, from reduced incidence of toilet-paper-exacerbated perianal pathology, represent a speculative but plausibly large additional benefit: US hemorrhoid-related healthcare costs alone exceed \$770 million per year (employer-insured population only) [14], with the OTC hemorrhoid treatment market adding a further \$850 million in North America.

VII. POLICY FRAMEWORK AND RECOMMENDATIONS

The United States currently has no federal or state incentive program for bidet adoption. The EPA WaterSense program certifies low-flow toilets and provides a well-established administrative framework for bathroom fixture rebates (typical value: \$50–\$200 from participating utilities). We propose the following policy interventions, in increasing order of regulatory ambition:

P1. WaterSense Bidet Certification: Expand the WaterSense label to encompass bidet attachments and seats meeting a flow threshold of ≤ 0.5 L/use. This requires no new legislation and could be implemented through administrative rulemaking.

P2. Utility Rebate Programs: Extend existing WaterSense rebate frameworks to include qualifying bidet attachments at \$25–\$50 per unit, funded through water utility conservation budgets. The payback period on utility investment is immediate given the embedded-water savings.

P3. FSA/HSA Blanket Eligibility: Extend Flexible Spending Account and Health Savings Account eligibility for bidet attachments to all users (currently limited to those with documented medical need), reducing effective consumer price by 20–37% through tax pre-emption.

P4. Building Code Update: Require GFCI-protected electrical outlets within 1 m of toilets in all new residential construction. This low-cost building code amendment (estimated \$25–\$75 per unit in new construction) removes the primary electrical installation barrier for electric bidet seats without mandating bidet installation itself.

P5. Public Procurement Mandate: Require bidet installation in all new federal buildings, VA facilities, and federally funded healthcare infrastructure, a market-size intervention analogous to low-flow toilet mandates of the 1990s.

Japan's trajectory (14% adoption in 1992 to 80% in 2018) demonstrates that the transition is achievable on a 25-year timescale without regulatory mandates, driven primarily by consumer education, cost reduction, and infrastructure normalization [8]. The US starting position ($\sim$ 3% adoption) is analogous to Japan circa 1985.

VIII. DISCUSSION: EVIDENTIARY GAPS

The following gaps remain in the current evidence base:

(i) *Fecal adhesion strength to skin*: No published study directly measures the critical shear stress for detachment of fecal material from perianal skin. Our estimate of $\tau_{\mathrm{crit}} = 1$–10 Pa is extrapolated from industrial biofilm literature and fecal rheology data. A dedicated in-vitro experiment using representative fecal simulants on excised or synthetic skin would substantially tighten this range.

(ii) *RCT on cleaning efficacy*: No large-scale randomized controlled trial has directly compared residual fecal contamination (colony counts or chemical biomarkers) between bidet and toilet-paper cohorts under controlled conditions. This is the single most important clinical evidence gap. The 2005 *Gastroenterology Nursing* study is the closest analog but lacked adequate sample size and blinding.

(iii) *Wiping force measurement*: No published study reports direct force-plate measurements of applied

normal load during toilet-paper wiping. Our range of 2–10 N is inferred from ergonomic analogs. Instrumented toilet paper (force-sensitive substrate) would be straightforward to implement.

(iv) *National bidet adoption statistics*: No US government survey tracks bidet household penetration. The $\sim$ 3% figure is an industry estimate; a Census or NHANES supplement question would enable population-level epidemiological analyses linking adoption to perianal health outcomes.

(v) *Heterogeneity of bidet jet design*: This analysis uses nominal parameters for a standard non-oscillating jet. Manufacturers such as TOTO employ oscillating jets, varied spray angles (43° rear, 53° front), and adjustable flow rates. A parametric analysis of cleaning efficacy across the manufacturer design space is warranted.

IX. CONCLUSIONS

The core quantitative results are:

1. The bidet jet (Re $\approx$ 14,000, We $\approx$ 2,000) arrives at the skin surface as a coherent liquid column, generating wall shear stresses of 100–1,000 Pa in the cleaning zone, one to two orders of magnitude above the critical detachment threshold of 1–10 Pa for fecal material.

2. The Watson (1964) wall-jet solution predicts an effective cleaning radius $r_{\text{clean}} \approx 17$ mm, comfortably enclosing the contaminated perianal zone, with a safety margin $\mathcal{M} \approx$ 10–1,000.

3. Concave surface curvature ($\epsilon = d/R \approx 0.05$–$0.10$) provides a further positive correction to wall shear stress and may promote Taylor–Görtler mixing near the hydraulic jump.

4. The Péclet number Pe $\sim 10^9$ confirms that transport is overwhelmingly advective: dislodged debris is removed in $\sim$3.4 ms by the spreading film.

5. Toilet paper wiping delivers shear stresses of 1,000–30,000 Pa to moist perianal skin, 100 to 1,000 times the bidet's hydrodynamic load, with no transport mechanism, generating progressive stratum corneum disruption and exacerbating a clinical spectrum of perianal pathology.

6. National bidet adoption would eliminate 15–31 million tree harvests annually, reduce embedded water consumption by $\sim$98%, and deliver net present values of $>$ \$1,000 per household over 10 years at a payback period of $\sim$4 months.

The primary barrier to adoption in the United States is infrastructure (electrical outlets near toilets) and cultural inertia, not engineering, cost, or efficacy. We propose an EPA WaterSense certification expansion, utility rebate programs, and a building code amendment requiring GFCI outlets at toilet locations as the minimum necessary policy package.

[1] Baig, M. K., Zhao, R. H., and Wexner, S. D. (2022). Be kind to your behind: A systematic review of the habitual use of bidets in benign perianal disease. *Evidence-Based Complementary and Alternative Medicine*, 2022, 1633965.

[2] Broderick, J. E., and Cowan, L. J. (2021). Pressure injury related to friction and shearing forces in older adults. *Journal of Dermatology and Skin Science*, 3(2), 30–37.

[3] Dasan, S., Neill, S. M., Donaldson, D. R., and Scott, H. J. (1999). Treatment of persistent pruritus ani in a combined colorectal and dermatological clinic. *British Journal of Surgery*, 86(10), 1337–1340.

[4] Derler, S., and Gerhardt, L. C. (2012). Tribology of skin: Review and analysis of experimental results for the friction coefficient of human skin. *Tribology Letters*, 45, 1–27.

[5] European Hygienic Engineering and Design Group (2003). *EHEDG Guidelines: Hygienic Design Criteria for Equipment Used in the Food Industry*.

[6] Hall, P. (1982). Taylor–Görtler vortices in fully developed or boundary-layer flows: Linear theory. *Journal of Fluid Mechanics*, 124, 475–494.

[7] Hu, D. L., Gorman, J., and Schneider, W. (2017). The physics of defecation. *Soft Matter*, 13(21), 4018–4022.

[8] Japanese Cabinet Office (2018). *Consumer Confidence Survey: Home Appliance Penetration Data*. Government of Japan.

[9] Kiuchi, T., Kumano, H., Ohashi, K., and Tochigi, M. (2017). Bidet toilet use and incidence of hemorrhoids or urogenital infections: A one-year follow-up web survey. *Preventive Medicine Reports*, 6, 121–125.

[10] Lefebvre, A. H. (1988). *Atomization and Sprays*. Hemisphere Publishing, New York.

[11] Lodén, M. (2012). The skin barrier and use of moisturizers in atopic dermatitis. *Clinics in Dermatology*, 21(2), 145–157.

[12] Löffler, H., Dreher, F., and Maibach, H. I. (2004). Stratum corneum adhesive tape stripping: Influence of anatomical site, application pressure, duration and removal. *British Journal of Dermatology*, 151(4), 746–752.

[13] Natural Resources Defense Council (2020). *Issue with Tissue 2.0: How Americans Are Flushing Forests Down the Toilet*. NRDC Report, New York.

[14] Peery, A. F., Sandler, R. S., Galanko, J. A., et al. (2014). Burden and cost of outpatient hemorrhoids in the United States employer-insured population, 2014. *Gastroenterology*, 146(3), 661–668.

[15] Phares, D. J., Smedley, G. T., and Flagan, R. C. (2000). The wall shear stress produced by the normal impinge-

ment of a jet on a flat surface. *Journal of Fluid Mechanics*, 418, 351–375.

[16] Pope, S. B. (2000). *Turbulent Flows*. Cambridge University Press, Cambridge.

[17] Ryoo, S. B., Oh, H. K., Ha, H. T., Cho, H. M., and Park, K. J. (2011). Effect of electronic toilet system (bidet) on anorectal pressure in normal healthy volunteers: Influence of different types of water stream and temperature. *Journal of the Korean Society of Coloproctology*, 27(3), 166–172.

[18] Scientific American (2009). Wipe or wash? Do bidets save forest and water resources? *Scientific American*, Earth Talk.

[19] Teodosio, J. S., et al. (2012). Effect of shear stress and growth conditions on detachment and physical properties of biofilms. *Biofouling*, 29(4), 457–468.

[20] Vilhena, L., Afonso, C., and Ramalho, A. (2023). Skin friction: Mechanical and tribological characterization of different papers used in everyday life. *Materials*, 16(16), 5724.

[21] Watson, E. J. (1964). The radial spread of a liquid jet over a horizontal plane. *Journal of Fluid Mechanics*, 20(3), 481–499.

[22] Woolley, M., et al. (2014). Shear rheological properties of fresh human faeces with different moisture content. *Water Science & Technology*, 69(11), 2350–2355.

[23] Zuckerman, N., and Lior, N. (2006). Jet impingement heat transfer: Physics, correlations, and numerical modeling. *Advances in Heat Transfer*, 39, 565–631.