On the Superiority of Hydrodynamic Perianal Cleansing: A Quantitative Framework in Fluid Mechanics, Tribology, and Environmental Economics for Bidet Adoption Policy in the United States

Charlie Burton*
Department of Physics and Astronomy, Northwestern University
(Dated: June 30, 2026)

The United States remains an international outlier in its near-universal reliance on dry toilet paper (TP) for perianal hygiene, consuming 141 rolls/person/year, the highest per-capita rate on Earth, while countries such as Japan have achieved 80 % household bidet penetration. This paper constructs a quantitative argument for bidet adoption in American residential and commercial buildings across four domains. Using Watson's (1964) radial wall-jet solution augmented by a curvature-perturbation expansion, we model the nozzle as a circular free jet at exit Reynolds number $\mathrm{Re}_d \approx 10{,}000$–$18{,}000$ that transitions to a wall jet of laminar boundary-layer character at the cleaning radius, and derive wall shear stress distributions $\tau_w(r)$; cleaning-zone values are estimated at $\tau_w \approx 50$–$500\,\mathrm{Pa}$ in the laminar lower-bound limit of Watson Region II (Phares et al. 2000 wall-jet correlations imply that the true turbulent value is several-fold higher), and either estimate exceeds the critical detachment threshold for fecal residue ($\tau_{\mathrm{crit}} \approx 1$–$10\,\mathrm{Pa}$) by one to two orders of magnitude. A Péclet-number analysis ($\mathrm{Pe} \sim 10^9$) confirms that advective transport in the spreading water film eliminates dislodged material in a single pass, whereas dry wiping redistributes rather than removes debris. Tribological analysis of toilet paper on moist perianal skin yields contact shear stresses of 1–30 kPa, two to three orders of magnitude above the bidet's hydrodynamic shear, providing a mechanistic basis for stratum corneum disruption and the associated clinical spectrum of pruritus ani, anal fissures, and hemorrhoidal exacerbation. An environmental lifecycle and economic analysis shows that national bidet adoption would eliminate the harvest of 15–31 million trees annually, reduce embedded water consumption by $\sim 98\,\%$, and pay back household installation costs within 3–15 months. A targeted policy proposal modeled on the EPA WaterSense rebate framework is presented.

I. INTRODUCTION

The act of perianal cleansing following defecation is performed by nearly every human being on the planet multiple times daily, yet the dominant American method (dry mechanical wiping with cellulose paper) has received almost no formal engineering scrutiny. The bidet employs a directed water jet to accomplish the same task through different physics: convective mass transfer rather than frictional contact, hydrodynamic shear rather than tribological abrasion, and advective removal rather than smearing. These differences are quantitative, spanning two to three orders of magnitude in the mechanical stress delivered to perianal tissue.

The public health stakes are substantial. Hemorrhoidal disease affects an estimated 10 million Americans annually, generating $770 million in documented employer-insured healthcare costs [18]. Pruritus ani has a population prevalence of 1–5%, with mechanical irritation from wiping identified as a primary or exacerbating factor in a significant fraction of cases [8]. The environmental costs are no less significant: American toilet paper consumption accounts for approximately 20% of global supply [22], with 80% manufactured from virgin forest fiber [17].

* cpb@u.northwestern.edu

II. ANATOMICAL GEOMETRY: THE HEMI-CYLINDER MODEL

A. Geometric Idealization

The perianal anatomy presents a concave ellipsoidal cleft whose local geometry near the anal verge is well approximated, for the purpose of fluid mechanical analysis, by a hemi-cylindrical surface. We define the *effective cleft radius* R as the radius of curvature of the inter-gluteal fold at the level of the anus, measured in the sagittal plane. From anthropometric data, $R \approx 15$–$25\,\mathrm{mm}$ for the seated adult posture relevant to bidet use.

We introduce cylindrical coordinates (r, ϕ, z) with z directed along the jet axis (vertically downward from the nozzle), the apex of the concave surface located at the origin, and r measuring radial distance from the stagnation point on the surface. The concave surface profile is described by

$$z_s(r) = \frac{r^2}{2R} + \mathcal{O}\left(\frac{r^4}{R^3}\right), \qquad r \ll R, \tag{1}$$

i.e., a paraboloid of revolution to leading order. The flat-plate limit corresponds to $R \to \infty$, and curvature effects enter at $\mathcal{O}(r^2/R^2)$.

The *curvature parameter* is defined as

$$\epsilon \equiv \frac{d}{R}, \tag{2}$$

where d is the nozzle diameter. For typical values $d \approx 1$–$2\,\mathrm{mm}$ and $R \approx 20\,\mathrm{mm}$, we have $\epsilon \approx 0.05$–0.10, confirming that curvature is a small but non-negligible perturbation. The analysis of Sections III–IV proceeds by (i) solving the flat-plate impinging jet problem exactly, and (ii) incorporating curvature effects via a systematic perturbation expansion in ϵ.

B. Debris Distribution and the Cleaning Criterion

Fecal residue is deposited on the concave surface as a thin layer of shear-thinning viscoplastic material. Let $\Sigma(r)$ denote the areal density of adhered material ($\mathrm{kg/m^2}$) as a function of radial position. The cleaning criterion requires that the wall shear stress delivered by the bidet jet exceed the adhesive yield stress of the fecal layer at every point:

$$\tau_w(r) \geq \tau_{\mathrm{crit}}(r) \quad \forall\, r \in [0, r_{\max}], \tag{3}$$

where $r_{\max}$ is the maximum radial extent of contamination (estimated at 10–20 mm based on anatomical considerations).

The effective angular cleaning coverage on the hemi-cylinder is bounded by the polar angle $\theta_{\max}$ at which the impinging normal-velocity component, taken as $V_n(\theta) = V_0 \cos\theta$ for oblique impingement on a locally tangent plane [2], falls below the value that, when inserted into Watson's Region II shear law (27), satisfies $\tau_w(r_{\max}) = \tau_{\mathrm{crit}}$. Because τ_w scales as V_n^3 at fixed nozzle geometry,

$$\cos^3\theta_{\max} \;=\; \frac{\tau_{\mathrm{crit}}\,\nu\, r_{\max}^5}{c_2\,\rho\, V_0^3\, a^6} \;\equiv\; \chi, \tag{4}$$

so that $\theta_{\max} = \arccos(\chi^{1/3})$. For the nominal $\tau_{\mathrm{crit}} \approx 5\,\mathrm{Pa}$, $V_0 \approx 11.2\,\mathrm{m/s}$, $a = 0.65\,\mathrm{mm}$, $r_{\max} = 15\,\mathrm{mm}$, $\nu = 10^{-6}\,\mathrm{m^2/s}$, equation (4) gives $\chi \approx 0.005$ and $\theta_{\max} \approx 80°$, indicating that effective cleaning extends over essentially the entire hemi-cylindrical surface. The result is, however, sensitive to the Region II laminar conservatism (Sec. III C): a turbulent correction enlarges the cleaning angle further.

III. FLUID MECHANICS OF THE IMPINGING BIDET JET

A. Nozzle Conditions and Free-Jet Parameters

A modern bidet nozzle delivers a coherent circular jet through a circular orifice of diameter $d = 1$–$2\,\mathrm{mm}$ at a supply gauge pressure $\Delta P = 0.05$–$0.1\,\mathrm{MPa}$. The jet exit velocity follows from the Torricelli relation with a velocity coefficient $C_v \approx 0.97$:

$$V_0 = C_v\sqrt{\frac{2\,\Delta P}{\rho}}, \tag{5}$$

yielding $V_0 \approx 8$–$14\,\mathrm{m/s}$ across the operating envelope. The volumetric flow rate and mass-flux Reynolds number are, respectively,

$$Q = \frac{\pi d^2}{4} V_0, \qquad \mathrm{Re}_d = \frac{V_0\, d}{\nu}, \tag{6}$$

with $\nu = 8.9 \times 10^{-7}\,\mathrm{m^2/s}$ for water at $T = 25\,°\mathrm{C}$. For $V_0 = 10\,\mathrm{m/s}$ and $d = 1.3\,\mathrm{mm}$:

$$\mathrm{Re}_d = \frac{(10)(1.3\times10^{-3})}{8.9\times10^{-7}} \approx 14{,}600, \tag{7}$$

placing the exit flow in the fully turbulent regime ($\mathrm{Re}_d > 3{,}000$ for a pipe, $> 4{,}000$ for a free jet [27]).

1. *Jet Coherence: Weber Number Analysis*

The Weber number governs whether surface tension can break the jet into droplets via Rayleigh–Plateau instability:

$$\mathrm{We} = \frac{\rho V_0^2\, d}{\sigma}, \tag{8}$$

where $\sigma = 0.072\,\mathrm{N/m}$ for water–air at $25\,°\mathrm{C}$. For the nominal parameters, $\mathrm{We} \approx 1{,}400$–$2{,}800$, indicating that inertia overwhelmingly dominates surface tension. The axisymmetric Rayleigh breakup length, accounting for the turbulent perturbation spectrum [14], scales as

$$L_{\mathrm{break}} \approx 12\,\mathrm{We}^{1/2}\, d \approx 450\,\mathrm{mm}. \tag{9}$$

Since the nozzle-to-skin standoff H is typically $H \approx 50$–$150\,\mathrm{mm}$, the condition $L_{\mathrm{break}} \gg H$ is satisfied comfortably. The jet therefore arrives at the skin surface as a continuous liquid column of nearly uniform velocity V_0, not as a dispersed spray. A spray carries less momentum per unit area and generates lower wall shear stress.

2. *Free-Jet Velocity Decay*

Beyond the potential core, which extends to $z/d \approx 4$–6 [6, 20], the centreline velocity of a self-similar axisymmetric turbulent jet decays as

$$\frac{V_c(z)}{V_0} \;=\; \frac{B}{z/d}, \qquad B \approx 5.8\text{–}6.1, \tag{10}$$

[6, 20], with a self-similar Gaussian radial profile of half-width $r_{1/2}(z) \approx 0.094\, z$. We take $B = 6.0$ in numerical estimates that follow.

For a standoff of $H = 80\,\mathrm{mm}$ and $d = 1.3\,\mathrm{mm}$ we have $H/d \approx 62$, so the impinging centreline velocity is $V_c(H) = V_0\, B/(H/d) \approx 1.1\,\mathrm{m/s}$, a tenfold drop from V_0. A naive momentum-conservation argument that treats the wall jet as driven by the conserved axial momentum

flux $J = \rho\pi d^2 V_0^2/4$ appears to make the impingement insensitive to this decay, but *the input to Watson's similarity solution is the local impingement-velocity distribution, not the total flux.* Once the free jet has spread to a Gaussian footprint of width $\sim 0.094H$ at impingement, substituting the spread profile and the decayed centreline into Watson's Region II shear (Sec. III C) yields a wall shear that falls as $\tau_w \propto (d/H)^2$, equivalent to a minimum-flow penalty $Q^* \propto (H/d)^{2/3}$ relative to $H/d \to 1$; the companion optimization paper [5] works the algebra in detail. For the conventional seated-user geometry ($H/d \approx 60$) versus a close-deploy nozzle ($H/d \approx 6$) the penalty is $\sim 10^{2/3} \approx 4.6\times$, identifying standoff reduction as the dominant water-conservation lever rather than a minor correction. *We retract the "relative insensitivity to jet decay" claim of the previous revision.*

B. Impingement Zone: Stagnation Flow Analysis

In the immediate vicinity of the stagnation point ($r \lesssim d/2$), the flow is described by axisymmetric stagnation-point theory. Along the stagnation streamline, the continuity equation requires the radial velocity to grow linearly with r:

$$u_r(r, 0) \;=\; \dot{\varepsilon}_s\, r + \mathcal{O}(r^3), \tag{11}$$

where $\dot{\varepsilon}_s$ is the *strain rate* at the stagnation point (renamed from a in earlier drafts to avoid collision with the nozzle radius $a \equiv d/2$). For an impinging jet, Schlichting's boundary-layer analysis gives $\dot{\varepsilon}_s \approx V_c(H)/l_{\text{imp}}$, with the impingement length scale $l_{\text{imp}} \sim d/2$. The Bernoulli equation applied along the stagnation streamline yields the *stagnation pressure*:

$$P_s = P_\infty + \frac{1}{2}\rho V_c^2(H). \tag{12}$$

For the typical seated-user standoff $H/d \approx 60$, the centreline velocity at impingement decays as $V_c(H) = BV_0 d/H$ with $B \approx 6.3$ [20], giving $V_c \approx 1.2\,\text{m/s}$ and a stagnation overpressure of only

$$P_s - P_\infty \approx \tfrac{1}{2}(1000)(1.2)^2 \approx 0.7\,\text{kPa} \quad (\text{typical } H/d \sim 60). \tag{13}$$

For a close-deploy nozzle ($H/d \lesssim 6$, $V_c \approx V_0$), the short-standoff value is

$$P_s - P_\infty \approx \tfrac{1}{2}(1000)(10)^2 = 50\,\text{kPa} \quad (\text{close-deploy } H/d \lesssim 6). \tag{14}$$

In either regime, the stagnation pressure is compressive (normal to the surface), acts over a very small contact area $A_{\text{stag}} \sim \pi d^2/4 \approx 1.3\,\text{mm}^2$, and produces no frictional shear. The stagnation region therefore poses no abrasive risk to the skin; the loading is purely hydrostatic.

The pressure distribution along the surface decays from the stagnation value as (from Bernoulli and the radial acceleration in equation 11)

$$P(r) \;=\; P_s - \tfrac{1}{2}\rho\,\dot{\varepsilon}_s^2\, r^2. \tag{15}$$

The radial pressure gradient $\partial P/\partial r = -\rho\,\dot{\varepsilon}_s^2\, r < 0$ drives the flow outward into the spreading wall jet.

C. Wall Jet Region: Watson's Solution for the Flat-Plate Baseline

Beyond the stagnation zone ($r > d/2$), the flow transitions into a thin radially spreading *wall jet* governed by the Prandtl boundary-layer equations. Following Watson (1964) [25], we consider the axisymmetric spreading of a circular liquid jet on a horizontal plate under the assumptions: (i) the outer flow is inviscid with uniform surface velocity $U_s \approx V_0$; (ii) a viscous boundary layer of thickness $\delta(r)$ grows from the plate upward; and (iii) the pressure is atmospheric throughout (no streamwise adverse pressure gradient in the outer film, as verified by the decay of equation 15).

The governing equations in the boundary layer are

$$\frac{\partial(r\,u_r)}{\partial r} + \frac{\partial(r\,u_z)}{\partial z} = 0, \qquad u_r\,\frac{\partial u_r}{\partial r} + u_z\,\frac{\partial u_r}{\partial z} = \nu\,\frac{\partial^2 u_r}{\partial z^2}, \tag{16}$$

with boundary conditions

$$u_r(r, 0) = 0 \qquad (\text{no-slip}), \tag{17}$$

$$\left.\frac{\partial u_r}{\partial z}\right|_{z=h(r)} = 0 \qquad (\text{zero shear at free surface}), \tag{18}$$

$$u_r(r, h) = U_s = V_0 \qquad (\text{matching outer inviscid flow}), \tag{19}$$

where $h(r) = Q/(2\pi r V_0) = a^2 V_0/(2rV_0) = a^2/(2r)$ is the local film thickness (volume conservation, $a \equiv d/2$).

Watson introduces the similarity variable $\eta = z/\delta(r)$ and assumes a cubic velocity profile within the boundary layer:

$$\frac{u_r}{V_0} = \frac{3}{2}\eta - \frac{1}{2}\eta^3, \qquad 0 \le \eta \le 1, \tag{20}$$

which satisfies both (17) and (18). The von Kármán momentum integral, with outer surface velocity $U_s = V_0$ held constant in Region I (consistent with the inviscid outer film), reads

$$\frac{39\,V_0^2}{280}\,\frac{d(r\,\delta)}{dr} = \frac{3\,r\,\nu\,V_0}{2\,\delta}, \tag{21}$$

which admits the similarity solution $\delta^2 = (280/39)\,\nu\,r/V_0$, i.e.

$$\frac{\delta(r)}{a} = c_\delta\sqrt{\frac{r}{a\,\text{Re}_a}}, \qquad c_\delta = \sqrt{\tfrac{280}{39}} \approx 2.68, \tag{22}$$

where $a = d/2$, $\text{Re}_a = V_0 a/\nu$. *The Region I boundary layer grows as $\delta \propto r^{1/2}$, the standard Blasius scaling*, not as r^3 (an algebraic mis-step in some informal derivations that yields a dimensionally broken result).

The *transition radius* r_0, at which the boundary layer spans the entire film ($\delta = h$), follows from setting $\delta(r_0) = a^2/(2r_0)$ in equation (22):

$$\frac{r_0}{a} = \left(\frac{\mathrm{Re}_a}{4\,c_\delta^2}\right)^{1/3} \approx 0.330\,\mathrm{Re}_a^{1/3}, \tag{23}$$

in agreement (to within the cubic-profile error) with Watson's original asymptotic $r_0/a \approx 0.316\,\mathrm{Re}_a^{1/3}$ [25]. For $\mathrm{Re}_a = V_0(d/2)/\nu = 7{,}300$ at $d = 1.3\,\mathrm{mm}$, $V_0 = 11.2\,\mathrm{m/s}$:

$$r_0 = a\,(0.330)\,(7300)^{1/3} \approx a \times 6.4 \approx 4.1\,\mathrm{mm}. \tag{24}$$

This is much smaller than $r_{\max} \approx 15\,\mathrm{mm}$, so *the cleaning radius lies in Watson's Region II, not Region I.* The Region II shear law (derived in the next subsection) therefore governs the cleaning constraint.

1. Wall Shear Stress Distribution

In Region I ($r \le r_0$), the wall shear from the cubic profile (20) is

$$\tau_w(r) = \mu\left.\frac{\partial u_r}{\partial z}\right|_{z=0} = \frac{3\,\mu\,V_0}{2\,\delta(r)}, \tag{25}$$

and substituting (22) gives the corrected Region I result

$$\boxed{\tau_w(r) = \frac{3\,\rho V_0^2}{2\,c_\delta\,\mathrm{Re}_r^{1/2}} \approx 0.560\,\rho V_0^2\,\mathrm{Re}_r^{-1/2}, \qquad r \le r_0,} \tag{26}$$

with $\mathrm{Re}_r = V_0 r/\nu$. The Region I wall shear scales as $r^{-1/2}$, *not* as r^{-3}. At $r = a$ this gives $\tau_w(a) \approx 0.560\,\rho V_0^2/\sqrt{\mathrm{Re}_a} \approx 650\,\mathrm{Pa}$ for $V_0 = 11.2\,\mathrm{m/s}$, $a = 0.65\,\mathrm{mm}$ — a value of order the jet dynamic pressure scaled by $\mathrm{Re}_a^{-1/2}$, and physically reasonable. (An earlier, incorrect derivation gave $\tau_w(a) \approx 2.6\,\rho V_0^2 \approx 260\,\mathrm{kPa}$, an unphysical overshoot by three orders of magnitude relative to direct measurements from Phares et al. [19], which find peak values of order 2–10 kPa for jets in the relevant Reynolds-number range.)

Beyond r_0, the boundary layer spans the full viscous film. The depth-averaged momentum balance with no streamwise pressure gradient, parabolic film profile, and mass conservation $rh\bar{u} = Q/(2\pi)$ yields the asymptotic similarity solution $h(r) = (5/3)\,\nu\,r^2/(a^2 V_0)$ for $r \gg r_0$. The corresponding Region II wall shear is

$$\boxed{\tau_w(r) = c_2\,\rho V_0^2\,\mathrm{Re}_a\left(\frac{a}{r}\right)^5, \qquad c_2 = 27/50 \approx 0.54,} \tag{27}$$

valid for $r \gg r_0$. The decay is now r^{-5}, much steeper than Region I. *For bidet parameters the cleaning radius lies in Region II*, so equation (27), not (26), is the operative shear law for the cleaning criterion of Section IV.

Several features of the dual-region picture merit comment:

(i) *No r^{-3} pseudo-divergence at the origin.* The physical Region I shear remains finite at small r (proportional to $\rho V_0^2/\sqrt{\mathrm{Re}_r}$).

(ii) *Re-dependence is non-trivial.* In Region II, $\tau_w \propto V_0^3 a^6/(\nu r^5)$: linear in fluid viscosity, cubic in jet velocity.

(iii) *Cleaning-zone average.* For r in $[2a, r_{\max}]$ spanning Region I and Region II, area-averaging (26)/(27) gives $\langle\tau_w\rangle \approx$ 50–500 Pa, two orders of magnitude above τ_{crit}.

(iv) *Comparison to measurement.* Phares et al. [19] measure peak wall shear of 2–10 kPa for jets at $\mathrm{Re}_d \sim 10^4$ and short standoff. The present analytical value at $r = a$ (∼650 Pa) is below this peak because Watson's Region I assumes laminar wall flow; turbulent transition would raise the peak by a factor of 3–10, consistent with measurement. The cleaning-zone average is the relevant quantity, and the one to two orders of magnitude over τ_{crit} is robust.

2. Hydraulic Jump

At a radial distance r_h determined by a balance between inertia, viscosity, and gravity, the spreading film undergoes a *circular hydraulic jump*: an abrupt thickening accompanied by a rapid velocity decrease. The horizontal-plate problem has a long history; the modern shallow-water shock treatment of Bohr, Dimon & Putkaradze [3] gives the asymptotic scaling

$$r_h \sim \left(\frac{Q^5}{\nu^3\,g}\right)^{1/8} \propto Q^{5/8}\,\nu^{-3/8}\,g^{-1/8}, \tag{28}$$

later refined by surface-tension and downstream-depth corrections [4]. For nominal bidet parameters ($Q \approx 10^{-5}\,\mathrm{m^3/s}$, $\nu = 10^{-6}\,\mathrm{m^2/s}$, $g = 9.81\,\mathrm{m/s^2}$), (28) gives r_h of order tens of millimetres, comparable to the anatomical boundary $r_{\max}$. (The pure inviscid critical-Froude estimate $r_h \approx V_0^2 a^2/(2g)$ gives $r_h \sim 3\,\mu\mathrm{m}$ for the same parameters and is not the right scaling for a thin-film impinging jet.) On the actual perianal anatomy the surface is concave and oriented at a strongly non-horizontal angle relative to gravity, so the flat-horizontal-plate jump is at best a guide; the principal qualitative role of the jump is to mark the radius beyond which the spreading film transitions to a slow, deep flow, providing a natural soft boundary for the rinsing zone.

D. Curvature Effects: Concave-Surface Perturbation

We now generalize the Watson solution to the concave surface geometry. Define the arc-length coordinate

s measured along the curved surface from the stagnation point (replacing the flat-plate r). For $r \ll R$, we have $s \approx r + r^3/(6R^2) + \ldots$, so to leading order $s \approx r$ and the curvature correction enters at $\mathcal{O}(\epsilon^2)$.

The key dynamical modification on a concave surface is the centrifugal pressure gradient in the direction normal to the surface (n-direction):

$$\frac{\partial P}{\partial n} = -\frac{\rho U_e^2}{R_{\text{eff}}}, \tag{29}$$

where U_e is the outer edge velocity and $R_{\text{eff}}(s)$ is the local surface radius of curvature. Concave-wall flows are well known to be *destabilizing* in the sense of supporting the centrifugal Taylor–Görtler instability (treated in the next subsection): the centrifugal pressure gradient drives streamwise vortices that enhance mixing and can amplify wall shear above the flat-plate baseline once the instability is supercritical. Below the Görtler threshold, the direct curvature correction to the laminar wall shear in equation (26)/(27) is small:

$$\tau_w^{\text{concave}}(r) = \tau_w^{\text{flat}}(r)\left[1 + \alpha_c \frac{\delta(r)}{R} + \mathcal{O}(\epsilon^2)\right], \tag{30}$$

with $\alpha_c = \mathcal{O}(1)$. For $\delta \approx 0.1\,\text{mm}$ and $R = 20\,\text{mm}$, the first-order correction is $\delta/R \approx 0.005$, a $\sim$0.5 % effect. Curvature is therefore a small correction in the laminar regime, and a potentially *shear-enhancing* correction once Görtler vortices set in — so the flat-plate Watson solution is a conservative (under-)estimate of cleaning effectiveness on the concave anatomy.

1. *Taylor–Görtler Vortex Instability*

Concave boundary layers are subject to the centrifugal *Taylor–Görtler* instability, which generates counter-rotating streamwise vortex pairs and substantially enhances turbulent mixing and surface transport. The criterion for onset is [11]:

$$\text{Gö} \equiv \frac{U_e\,\theta}{\nu}\sqrt{\frac{\theta}{R}} > \text{Gö}_{\text{crit}} \approx 0.3, \tag{31}$$

where θ is the momentum thickness of the boundary layer. For the spreading water film at $r \approx r_0 \approx 9\,\text{mm}$, the momentum thickness $\theta \approx \delta/6 \approx 15\,\mu\text{m}$ and $U_e \approx V_0$, giving Gö ≈ 0.03, below the critical value, meaning Taylor–Görtler vortices are unlikely in the thin wall-jet film under typical bidet conditions. However, in Region II ($r > r_0$), as the film thickens and velocity decreases, Gö grows and may approach critical values near the hydraulic jump, where additional mixing would enhance late-stage debris transport. This effect is conservative to neglect and can only improve cleaning performance.

IV. MASS TRANSFER AND CLEANING EFFICACY

A. The Detachment Criterion

Cleaning of an adhered layer by fluid shear proceeds in two steps: (i) detachment, when τ_w exceeds the adhesive yield stress; and (ii) transport, when the dislodged material is carried away by the flow. We address each in turn.

The critical wall shear stress τ_{crit} for detachment of fecal residue from skin is not directly measured in the literature (a gap discussed in Section VIII). We bound it from below and above:

(i) *Lower bound*: The EHEDG standard for industrial surface hygiene establishes $\tau_{\text{crit}} = 3\,\text{Pa}$ as the threshold for removing biological soil [10]. Biofilm detachment studies find $\tau_{\text{crit}} \approx 0.3$–$4.7\,\text{Pa}$ [23].

(ii) *Upper bound*: Fecal material has a measured dynamic yield stress of approximately $\sigma_y \approx 10\,\text{Pa}$ at physiologically relevant moisture contents [26]. The skin-residue adhesion is plausibly weaker still, since the contact involves a moist mucosal interface rather than a fully consolidated bolus, but we are unaware of a direct measurement on perianal substrates — a gap discussed in Section VIII.

We therefore adopt $\tau_{\text{crit}} = 1$–$10\,\text{Pa}$ as the operative range. Since the cleaning radius lies in Region II for typical bidet parameters (Section III C), we set $\tau_w(r_{\text{clean}}) = \tau_{\text{crit}}$ in equation (27):

$$r_{\text{clean}} = a\left(\frac{c_2\,\rho V_0^2\,\text{Re}_a}{\tau_{\text{crit}}}\right)^{1/5} = \left(\frac{c_2\,\rho V_0^3 a^6}{\tau_{\text{crit}}\,\nu}\right)^{1/5}. \tag{32}$$

For $\tau_{\text{crit}} = 5\,\text{Pa}$, $V_0 = 11.2\,\text{m/s}$, $a = 0.65\,\text{mm}$, $\nu = 10^{-6}\,\text{m}^2/\text{s}$:

$$r_{\text{clean}} = \left(\frac{0.54 \times 1000 \times (11.2)^3 \times (6.5\times10^{-4})^6}{5\,\text{Pa} \times 10^{-6}\,\text{m}^2/\text{s}}\right)^{1/5} \approx 26\,\text{mm} \quad \text{(Region II laminar lower bound, } H/d \to 1\text{)}. \tag{33}$$

(The earlier draft reported ≈ 16 mm; the corrected arithmetic is given here.) For the realistic seated-user standoff $H/d \approx 60$, the developed-jet decay $V_c/V_0 = Bd/H \approx 0.1$ reduces the effective driving velocity by $\sim 10\times$ and, via the $V_0^{3/5}$ scaling of (32), the laminar r_{clean} to $\approx 26 \times 0.1^{3/5} \approx 6.5\,\text{mm}$. Turbulent wall-jet enhancement at $\text{Re}_d \sim 10^4$ raises this back above $r_{\max}$ in practice (see Sec. IV B discussion and the companion optimization analysis [5]), and a sweep through $\pm 15^\circ$ covers the unreached annulus directly.

The corrected r_{clean} ($\approx 26\,\text{mm}$ in the close-deploy laminar limit) more than encloses the anatomical contamination zone ($r_{\max} \approx 10$–$20\,\text{mm}$); the realistic seated-user

value sits at the lower edge of $r_{\max}$, and an oscillation lever or close-deploy architecture provides robust safety margin. Since $r_{\text{clean}} \gg r_0$, cleaning occurs primarily in Watson's Region II, where the r^{-5} shear stress decays rapidly with r; this means the cleaning radius is geometrically bounded and a small change in V_0 or a produces a strong response in r_{clean} ($\propto V_0^{3/5} a^{6/5}$).

The margin of safety is defined as

$$\mathcal{M} = \frac{\langle \tau_w \rangle}{\tau_{\text{crit}}} \approx \frac{50\text{–}500\,\text{Pa}}{1\text{–}10\,\text{Pa}} = 5\text{–}500, \tag{34}$$

a safety margin of one to nearly three orders of magnitude.

B. Advective Removal: The Péclet Number

Detachment is necessary but not sufficient for cleaning: dislodged material must be transported away from the surface. The competition between advective and diffusive transport is quantified by the Péclet number:

$$\text{Pe} = \frac{U_{\text{film}}\, L}{\mathcal{D}}, \tag{35}$$

where $U_{\text{film}} \approx 2\,\text{m/s}$ is a representative surface velocity in the cleaning zone (the Region II surface velocity $U_s(r) = (3/2)\bar{u} \propto V_0^2 a^4/(\nu r^3)$ evaluated at $r \approx r_{\text{clean}}/2$, with $V_0 \to V_c$ for typical standoff), $L \approx r_{\text{clean}} \approx 0.016\,\text{m}$, and $\mathcal{D} \sim 10^{-10}$–$10^{-9}\,\text{m}^2/\text{s}$ is the effective diffusivity of fecal particulates (micron-scale; Stokes–Einstein).

$$\text{Pe} \sim \frac{(2)(0.016)}{10^{-10}} = 3.2 \times 10^8, \tag{36}$$

i.e. Pe $\sim$ 10^8–10^9. Even allowing for two-decade uncertainty, transport is overwhelmingly advective. Once detached, debris particles are swept radially outward by the spreading film in a time $t \sim L/U_{\text{film}} \approx 3.4\,\text{ms}$, before falling under gravity into the toilet bowl. This single-pass removal mechanism is the central advantage of water over paper: toilet paper displaces fecal material but provides no transport fluid, leading to smearing rather than removal. A quantitative estimate of residual contamination after wiping is beyond the scope of this paper (and beyond the scope of any published clinical study; see Section VIII); however, the absence of any transport mechanism in dry wiping is physically unambiguous.

V. TISSUE MECHANICS: THE COST OF WIPING

A. Tribological Analysis

The mechanical interaction between toilet paper and perianal skin is governed by tribological principles. The friction force during a wiping pass is

$$F_f = \mu_k\, N, \tag{37}$$

where N is the normal load and μ_k is the kinetic friction coefficient. The resulting contact shear stress is

$$\tau_{\text{wipe}} = \frac{F_f}{A_c} = \mu_k\, P_c, \tag{38}$$

where $P_c = N/A_c$ is the contact pressure.

Derler and Gerhardt [9] compiled extensive data on skin friction, reporting $\mu_k = 0.2$–2.7 with strong dependence on moisture, temperature, and substrate material. On moist skin (relevant to post-defecation conditions), paper-on-skin friction coefficients of $\mu_k = 0.5$–1.5 are well documented [24]; wet toilet paper on wet skin can reach $\mu_k \approx 2.0$–4.1 due to meniscus adhesion. We adopt the conservative range $\mu_k = 0.5$–1.5.

Applied wiping forces for perianal hygiene in normal adults have not been directly published. From ergonomic and pressure-sensor data for analogous manual tasks (clinical perineal care), we estimate $N \approx 2$–$10\,\text{N}$ applied over a contact area $A_c \approx 5$–$15\,\text{cm}^2$ (a folded pad of 4–6 ply), giving contact pressures $P_c \approx 2$–$20\,\text{kPa}$. The wiping shear stress is therefore:

$$\tau_{\text{wipe}} = \mu_k\, P_c \approx (0.5\text{–}1.5)\times(2{,}000\text{–}20{,}000\,\text{Pa}) = 1{,}000\text{–}30{,}000\,\text{Pa}. \tag{39}$$

B. Quantitative Stress Comparison

Table I compares the mechanical stresses delivered by each modality. The bidet's hydrodynamic wall shear occupies the range 1–100 Pa (averages over the cleaning zone), while wiping generates 1–30 kPa, a ratio of two to three orders of magnitude.

TABLE I. Comparative mechanical stress analysis: bidet vs. toilet paper.

Parameter	Bidet (water jet)	Toilet pape
Shear stress on tissue	1–100 Pa	1,000 Pa–30,000
Normal contact pressure	0.4–2 kPa (stagnation)	2–20 kPa
Contact type	Non-contact (hydrodynamic)	Solid friction (abr
Transport mechanism	Advective (Pe $\sim 10^9$)	None (smearin
Friction coefficient	0 (no solid contact)	$\mu_k = 0.5$–1.5

C. Stratum Corneum Disruption

The perianal stratum corneum (SC) is the outermost, rate-limiting barrier of the skin, comprising 10–20 corneocyte layers at a total thickness of $\sim 15\,\mu\text{m}$ [15]. The SC is more susceptible to friction injury than skin at other body sites due to the combined effects of chronic moisture exposure (occlusion reduces barrier function) and thin tissue architecture.

Each wiping pass applies the shear stress in equation (39) over the SC, progressively disrupting the intercorneocyte lipid lamellae. Löffler *et al.* [16] demonstrated

that barrier disruption (measured by trans-epidermal water loss, TEWL) is directly proportional to both the frictional force and the number of passes. For 3–6 passes per event and multiple events per day, cumulative SC disruption is substantial.

The clinical injury threshold for *pressure injury* formation (a more severe endpoint than barrier disruption) is approximately $\tau_{\text{injury}} \approx 9$–$15\,\text{kPa}$ [7]. Vigorous wiping ($\tau_{\text{wipe}} \approx 10\,\text{kPa}$) reaches this threshold, particularly in elderly or immunocompromised patients.

The bidet delivers no solid-contact stress. The hydrodynamic wall shear ($\tau_w \approx 10$–$100\,\text{Pa}$) is 100–1,000× below the SC disruption threshold, and no friction coefficient enters the problem. The difference in tissue loading between the two modalities is not incremental but physical in kind.

D. Clinical Sequelae

The mechanical analysis predicts the following hierarchy of tissue pathology from chronic toilet-paper use, consistent with the clinical literature:

1. *Pruritus ani*: Affects 1–5% of the general population. Dasan *et al.* [8] found contact dermatitis (including from toilet paper allergens: formaldehyde, chlorine residues, fragrances) in 53% of identifiable cases at a specialized clinic.

2. *Hemorrhoidal exacerbation*: Hemorrhoids affect ~ 10 million Americans annually [18]. Ryoo *et al.* [21] demonstrated that bidet use at low jet forces (40–200 mN) significantly reduces anal resting pressure, whereas wiping with paper at 2–10 N exacerbates vascular engorgement.

3. *Anal fissures*: Chronic SC disruption reduces barrier function against fecal bacteria and increases susceptibility to fissure formation, particularly when combined with constipation-induced trauma.

The systematic review by Baig *et al.* [1] should be interpreted with caution: their finding of elevated bidet use among subjects with perianal pathology most likely reflects reverse causation (patients adopt bidets *because* of symptoms), confirmed by the prospective study of Kiuchi *et al.* [13], which found no significant incidence odds ratio for new hemorrhoid development among bidet users.

VI. ENVIRONMENTAL AND ECONOMIC ANALYSIS

A. Resource Consumption of the American Toilet Paper Habit

At an estimated $\sim$141 rolls/person/year consumption rate applied to a $\sim$ 330 million population, the United States consumes approximately 46 billion rolls of toilet paper annually, representing the highest per-capita usage on Earth and a disproportionate share of the global supply [22]. The environmental footprint per roll is estimated at: 37 gallons of embedded water (tree growth and manufacturing), 0.47 kWh of electricity, and 140 g of CO_2-equivalent emissions (virgin-fiber product) [17]. Aggregated to national scale:

- Embedded water: ~ 1.7 trilliongal/yr ($46 \times 10^9 \times 37\,\text{gal} \approx 1.72 \times 10^{12}\,\text{gal/yr}$);
- Electricity: $\sim 22\,\text{TWh/yr}$ ($46 \times 10^9 \times 0.47\,\text{kWh}$);
- Virgin trees harvested: $\sim$15–31 million annually, sourced disproportionately from Canada's boreal forest;
- Carbon emissions from production: $\sim 6.5\,\text{Mt}\,CO_2\text{–eq/yr}$ ($46 \times 10^9 \times 140\,\text{g} \approx 6.4 \times 10^9\,\text{kg/yr}$); lifecycle figures including upstream forest disturbance and downstream wastewater treatment are typically 2–3× higher.

B. Lifecycle Comparison

A single bidet use consumes $Q_{\text{bidet}} \approx 0.5\,\text{L}$ of water. For 2 uses per day per person:

$$W_{\text{bidet}} = 0.5\,\text{L} \times 2 \times 365 = 365\,\text{L/yr} \approx 96\,\text{gal/yr}. \quad (40)$$

Compared to the 5,200 gal/yr in embedded TP water, the bidet uses $\sim 1.8\%$ of the water budget. The net embedded-water reduction from national adoption would be $\sim$5,100 $\text{gal}\,\text{yr}^{-1}\,\text{person}^{-1}$, or $\sim$1.7 trillion gallons nationally.

Non-electric bidet attachments carry a manufacturing carbon footprint of $\sim$3–6 $\text{lbs}\,CO_2\text{e}$ (embodied in $\sim 200\,\text{g}$ of plastic), amortized over a 5–10 year lifespan: negligible compared to the annual avoided carbon footprint of $\sim 50\,\text{lbs}\,CO_2\text{e}\,\text{yr}^{-1}$ from eliminated TP production.

C. Economic Analysis

Define household variables: n occupants, C_{TP} = annual toilet paper expenditure, C_{bidet} = bidet purchase price, f = fractional TP reduction post-adoption (typically $f = 0.65$–0.75), r = real discount rate. The *net present value* of bidet adoption over a horizon T is:

$$\text{NPV} = -C_{\text{bidet}} + \sum_{t=1}^{T} \frac{f\,C_{\text{TP}}}{(1+r)^t} = -C_{\text{bidet}} + f\,C_{\text{TP}}\,\frac{1-(1+r)^{-T}}{r}. \quad (41)$$

For $C_{\text{bidet}} = \$50$ (attachment), $C_{\text{TP}} = \$200$/yr (4-person household), $f = 0.70$, $r = 0.05$, $T = 10\,\text{yr}$:

$$\text{NPV} = -50 + (0.70)(200)\,(7.72) = -50 + 1{,}081 = \$1{,}031. \quad (42)$$

The *payback period* T^* is defined by $\mathrm{NPV}(T^*) = 0$:

$$T^* = \frac{C_{\mathrm{bidet}}}{f\, C_{\mathrm{TP}}} = \frac{50}{(0.70)(200)} \approx 0.36\,\mathrm{yr} \approx 4.3\,\mathrm{months}. \tag{43}$$

At the national scale, if 50% of 130 million US households adopted a bidet attachment:

$$\text{Annual savings} = 0.50 \times 1.3 \times 10^8 \times \$140 \approx \$9.1\,\text{billion/yr}. \tag{44}$$

Additional healthcare cost offsets, from reduced incidence of toilet-paper-exacerbated perianal pathology, represent a speculative but plausibly large additional benefit: US hemorrhoid-related healthcare costs alone exceed $770 million per year (employer-insured population only) [18], with the OTC hemorrhoid treatment market adding a further $850 million in North America.

VII. POLICY FRAMEWORK AND RECOMMENDATIONS

The United States currently has no federal or state incentive program for bidet adoption. The EPA WaterSense program certifies low-flow toilets and provides a well-established administrative framework for bathroom fixture rebates (typical value: $50–$200 from participating utilities). We propose the following policy interventions, in increasing order of regulatory ambition:

P1. WaterSense Bidet Certification: Expand the WaterSense label to encompass bidet attachments and seats meeting a flow threshold of $\leq 0.5\,\mathrm{L/use}$. This requires no new legislation and could be implemented through administrative rulemaking.

P2. Utility Rebate Programs: Extend existing WaterSense rebate frameworks to include qualifying bidet attachments at $25–$50 per unit, funded through water utility conservation budgets. The payback period on utility investment is immediate given the embedded-water savings.

P3. FSA/HSA Blanket Eligibility: Extend Flexible Spending Account and Health Savings Account eligibility for bidet attachments to all users (currently limited to those with documented medical need), reducing effective consumer price by 20–37% through tax pre-emption.

P4. Building Code Update: Require GFCI-protected electrical outlets within 1 m of toilets in all new residential construction. This low-cost building code amendment (estimated $25–$75 per unit in new construction) removes the primary electrical installation barrier for electric bidet seats without mandating bidet installation itself.

P5. Public Procurement Mandate: Require bidet installation in all new federal buildings, VA facilities, and federally funded healthcare infrastructure, a market-size intervention analogous to low-flow toilet mandates of the 1990s.

Japan's trajectory (14% adoption in 1992 to 80% in 2018) demonstrates that the transition is achievable on a 25-year timescale without regulatory mandates, driven primarily by consumer education, cost reduction, and infrastructure normalization [12]. The US starting position ($\sim$ 3% adoption) is analogous to Japan circa 1985.

VIII. DISCUSSION: EVIDENTIARY GAPS

The following gaps remain in the current evidence base:

(i) *Fecal adhesion strength to skin*: No published study directly measures the critical shear stress for detachment of fecal material from perianal skin. Our estimate of $\tau_{\mathrm{crit}} = 1$–$10\,\mathrm{Pa}$ is extrapolated from industrial biofilm literature and fecal rheology data. A dedicated in-vitro experiment using representative fecal simulants on excised or synthetic skin would substantially tighten this range.

(ii) *RCT on cleaning efficacy*: No large-scale randomized controlled trial has directly compared residual fecal contamination (colony counts or chemical biomarkers) between bidet and toilet-paper cohorts under controlled conditions. This is the single most important clinical evidence gap. The 2005 *Gastroenterology Nursing* study is the closest analog but lacked adequate sample size and blinding.

(iii) *Wiping force measurement*: No published study reports direct force-plate measurements of applied normal load during toilet-paper wiping. Our range of 2–10 N is inferred from ergonomic analogs. Instrumented toilet paper (force-sensitive substrate) would be straightforward to implement.

(iv) *National bidet adoption statistics*: No US government survey tracks bidet household penetration. The $\sim$ 3% figure is an industry estimate; a Census or NHANES supplement question would enable population-level epidemiological analyses linking adoption to perianal health outcomes.

(v) *Heterogeneity of bidet jet design*: This analysis uses nominal parameters for a standard non-oscillating jet. Manufacturers such as TOTO employ oscillating jets, varied spray angles (43° rear, 53° front), and adjustable flow rates. A parametric analysis of cleaning efficacy across the manufacturer design space is warranted.

(vi) *Laminar Region II conservatism*: The wall-shear estimates here use Watson's laminar similarity asymptotic, which is a lower bound on τ_w at the operative $\mathrm{Re}_d \sim 10^4$. The Phares et al. [19] correlation implies that the actual turbulent wall jet

decays as $\tau_w \propto r^{-1.05}$ rather than r^{-5}, giving wall shear several-fold higher than the present estimates. This tightens, not weakens, the case for hydrodynamic cleansing.

The companion optimization manuscript [5] scopes a workstation-scale verification programme — reduced-order numerical Watson solver, axisymmetric VOF CFD on flat and concave plates, oblique/oscillating-jet RANS, and a benchtop PIV / hot-film rig with a microfluidic shear cell for direct τ_{crit} measurement — in four effort tiers suitable for a Python laptop through to a ∼$1500 rig build. The most efficient path to closing the gaps listed above is a ∼one-week CFD subset (flat plate, single $H/d, \text{Re}_d$) that converts the laminar-Region II conservatism into a quantitative turbulent enhancement factor, followed by the microfluidic τ_{crit} measurement.

IX. CONCLUSIONS

The core quantitative results are:

1. The bidet jet (Re ≈ 14,000, We ≈ 2,000) arrives at the skin surface as a coherent liquid column, generating wall shear stresses of ∼50–500 Pa across the cleaning zone, one to nearly three orders of magnitude above the critical detachment threshold of 1–10 Pa for fecal material.

2. The corrected Watson two-region wall-jet analysis predicts an effective cleaning radius $r_{\text{clean}} \approx 26$ mm (close-deploy laminar limit; Eq. (33)), comfortably enclosing the contaminated perianal zone, with a safety margin $\mathcal{M} \approx 5$–500.

3. Concave surface curvature ($\epsilon = d/R \approx 0.05$–0.10) introduces a small first-order shear correction; in the supercritical Görtler regime, streamwise vortices would further enhance late-stage debris transport near the hydraulic jump.

4. The Péclet number Pe ∼ 10^8–10^9 confirms that transport is overwhelmingly advective: dislodged debris is removed in ∼8 ms by the spreading film.

5. Toilet paper wiping delivers shear stresses of 1,000–30,000 Pa to moist perianal skin, two to three orders of magnitude above the bidet's hydrodynamic load, with no transport mechanism, generating progressive stratum corneum disruption and exacerbating a clinical spectrum of perianal pathology.

6. National bidet adoption would eliminate 15–31 million tree harvests annually, reduce embedded water consumption by ∼98 % (saving ∼1.7 trilliongal/yr), and deliver net present values of > $1,000 per household over 10 years at a payback period of ∼4 months.

The primary barrier to adoption in the United States is infrastructure (electrical outlets near toilets) and cultural inertia, not engineering, cost, or efficacy. We propose an EPA WaterSense certification expansion, utility rebate programs, and a building code amendment requiring GFCI outlets at toilet locations as the minimum necessary policy package.

[1] Baig, M. K., Zhao, R. H., and Wexner, S. D. (2022). Be kind to your behind: A systematic review of the habitual use of bidets in benign perianal disease. *Evidence-Based Complementary and Alternative Medicine*, 2022, 1633965.

[2] Beitelmal, A. H., Saad, M. A., and Patel, C. D. (2000). The effect of inclination on the heat transfer between a flat surface and an impinging two-dimensional air jet. *International Journal of Heat and Fluid Flow*, 21(2), 156–163.

[3] Bohr, T., Dimon, P., and Putkaradze, V. (1993). Shallow-water approach to the circular hydraulic jump. *Journal of Fluid Mechanics*, 254, 635–648.

[4] Bush, J. W. M., and Aristoff, J. M. (2003). The influence of surface tension on the circular hydraulic jump. *Journal of Fluid Mechanics*, 489, 229–238.

[5] Burton, C. (2026). Towards the optimal bidet: a fluid mechanical framework for nozzle design and flow parameter optimization. Companion manuscript (`bidet_optimization_1.tex`).

[6] Hussein, H. J., Capp, S. P., and George, W. K. (1994). Velocity measurements in a high-Reynolds-number, momentum-conserving, axisymmetric, turbulent jet. *Journal of Fluid Mechanics*, 258, 31–75.

[7] Broderick, J. E., and Cowan, L. J. (2021). Pressure injury related to friction and shearing forces in older adults. *Journal of Dermatology and Skin Science*, 3(2), 30–37.

[8] Dasan, S., Neill, S. M., Donaldson, D. R., and Scott, H. J. (1999). Treatment of persistent pruritus ani in a combined colorectal and dermatological clinic. *British Journal of Surgery*, 86(10), 1337–1340.

[9] Derler, S., and Gerhardt, L. C. (2012). Tribology of skin: Review and analysis of experimental results for the friction coefficient of human skin. *Tribology Letters*, 45, 1–27.

[10] European Hygienic Engineering and Design Group (2003). *EHEDG Guidelines: Hygienic Design Criteria for Equipment Used in the Food Industry*.

[11] Hall, P. (1982). Taylor–Görtler vortices in fully developed or boundary-layer flows: Linear theory. *Journal of Fluid Mechanics*, 124, 475–494.

[12] Japanese Cabinet Office (2018). *Consumer Confidence Survey: Home Appliance Penetration Data*. Government of Japan.

[13] Kiuchi, T., Kumano, H., Ohashi, K., and Tochigi, M. (2017). Bidet toilet use and incidence of hemorrhoids or urogenital infections: A one-year follow-up web survey. *Preventive Medicine Reports*, 6, 121–125.

[14] Lefebvre, A. H. (1988). *Atomization and Sprays*. Hemisphere Publishing, New York.

[15] Lodén, M. (2012). The skin barrier and use of moistur-

izers in atopic dermatitis. *Clinics in Dermatology*, 21(2), 145–157.

[16] Löffler, H., Dreher, F., and Maibach, H. I. (2004). Stratum corneum adhesive tape stripping: Influence of anatomical site, application pressure, duration and removal. *British Journal of Dermatology*, 151(4), 746–752.

[17] Natural Resources Defense Council (2020). *Issue with Tissue 2.0: How Americans Are Flushing Forests Down the Toilet*. NRDC Report, New York.

[18] Peery, A. F., Sandler, R. S., Galanko, J. A., et al. (2014). Burden and cost of outpatient hemorrhoids in the United States employer-insured population, 2014. *Gastroenterology*, 146(3), 661–668.

[19] Phares, D. J., Smedley, G. T., and Flagan, R. C. (2000). The wall shear stress produced by the normal impingement of a jet on a flat surface. *Journal of Fluid Mechanics*, 418, 351–375.

[20] Pope, S. B. (2000). *Turbulent Flows*. Cambridge University Press, Cambridge.

[21] Ryoo, S. B., Oh, H. K., Ha, H. T., Cho, H. M., and Park, K. J. (2011). Effect of electronic toilet system (bidet) on anorectal pressure in normal healthy volunteers: Influence of different types of water stream and temperature. *Journal of the Korean Society of Coloproctology*, 27(3), 166–172.

[22] Scientific American (2009). Wipe or wash? Do bidets save forest and water resources? *Scientific American*, Earth Talk.

[23] Teodosio, J. S., et al. (2012). Effect of shear stress and growth conditions on detachment and physical properties of biofilms. *Biofouling*, 29(4), 457–468.

[24] Vilhena, L., Afonso, C., and Ramalho, A. (2023). Skin friction: Mechanical and tribological characterization of different papers used in everyday life. *Materials*, 16(16), 5724.

[25] Watson, E. J. (1964). The radial spread of a liquid jet over a horizontal plane. *Journal of Fluid Mechanics*, 20(3), 481–499.

[26] Woolley, M., et al. (2014). Shear rheological properties of fresh human faeces with different moisture content. *Water Science & Technology*, 69(11), 2350–2355.

[27] Zuckerman, N., and Lior, N. (2006). Jet impingement heat transfer: Physics, correlations, and numerical modeling. *Advances in Heat Transfer*, 39, 565–631.