# Study Data Reviewer's Guide (SDRG)

DRAFT prepared by PHAXTON. It is not signed and not submitted; it requires review and sign-off by the responsible person before any use.

- Study: Estudio PROT-DG1
- Protocol: PROT-DG1
- Sponsor: Acme Pharma
- Compound: Compuesto
- Phase: Fase 1
- Indication: Not declared by the sponsor in this package
- Date generated: 2026-10-16

## 1. Introduction

This SDRG describes the structure, content and derivation rules of the 5 SDTM dataset(s) of study PROT-DG1, as delivered in this package. Every number in this document is inserted from the package results; Appendix A lists each one with its origin.

## 2. SDTM datasets overview

| Dataset | Label | Structure | Records | Subjects | Keys |
|---|---|---|---|---|---|
| DM | Demographics | One record per subject | 3 | 3 | STUDYID, USUBJID |
| EX | Exposure | One record per constant dosing interval per subject | 3 | 3 | STUDYID, USUBJID, EXSEQ |
| PC | Concentrations | One record per sample characteristic or time-point concentration per subject | 6 | 3 | STUDYID, USUBJID, PCSEQ |
| PP | PK Parameters | One record per PK parameter per time-concentration profile per subject | 30 | 3 | STUDYID, USUBJID, PPSEQ |
| TS | Trial Summary | One record per trial summary parameter value | 4 | n/a | STUDYID, TSPARMCD, TSSEQ |

## 3. Dataset details

### 3.1 DM - Demographics

DM has 3 records and 8 variables. Structure: One record per subject.

| Variable | Label | Type | Length | Role | Core | Origin | Observed values |
|---|---|---|---|---|---|---|---|
| STUDYID | Study Identifier | character | 20 | Identifier | Req | Collected | No |
| DOMAIN | Domain Abbreviation | character | 2 | Identifier | Req | Collected | No |
| USUBJID | Unique Subject Identifier | character | 40 | Identifier | Req | Collected | No |
| SUBJID | Subject Identifier for the Study | character | 20 | Topic | Req | Collected | Yes |
| AGE | Age | numeric | 8 | Record Qualifier | Exp | Collected | No |
| AGEU | Age Units | character | 10 | Variable Qualifier | Exp | Collected | No |
| SEX | Sex | character | 1 | Record Qualifier | Req | Collected | No |
| ARM | Description of Planned Arm | character | 40 | Synonym Qualifier | Req | Collected | No |

## 3.2 EX - Exposure

EX has 3 records and 9 variables. Structure: One record per constant dosing interval per subject.

| Variable | Label | Type | Length | Role | Core | Origin | Observed values |
|---|---|---|---|---|---|---|---|
| STUDYID | Study Identifier | character | 20 | Identifier | Req | Collected | No |
| DOMAIN | Domain Abbreviation | character | 2 | Identifier | Req | Collected | No |
| USUBJID | Unique Subject Identifier | character | 40 | Identifier | Req | Collected | No |
| EXSEQ | Sequence Number | numeric | 8 | Identifier | Req | Derived | No |
| EXTRT | Name of Treatment | character | 40 | Topic | Req | Collected | No |
| EXDOSE | Dose | numeric | 8 | Record Qualifier | Exp | Collected | No |
| EXDOSU | Dose Units | character | 10 | Variable Qualifier | Exp | Collected | No |
| EXROUTE | Route of Administration | character | 20 | Variable Qualifier | Perm | Collected | No |
| EXSTDTC | Start Date/Time of Treatment | character | 20 | Timing | Exp | Collected | No |

## 3.3 PC - Concentrations

PC has 6 records and 11 variables. Structure: One record per sample characteristic or time-point concentration per subject.

| Variable | Label | Type | Length | Role | Core | Origin | Observed values |
|---|---|---|---|---|---|---|---|
| STUDYID | Study Identifier | character | 20 | Identifier | Req | Collected | No |
| DOMAIN | Domain Abbreviation | character | 2 | Identifier | Req | Collected | No |
| USUBJID | Unique Subject Identifier | character | 40 | Identifier | Req | Collected | No |
| PCSEQ | Sequence Number | numeric | 8 | Identifier | Req | Derived | No |
| PCTESTCD | Pharmacokinetic Test Short Name | character | 8 | Topic | Req | Collected | No |
| PCTEST | Pharmacokinetic Test Name | character | 40 | Synonym Qualifier | Req | Collected | No |
| PCORRES | Result or Finding in Original Units | character | 40 | Result Qualifier | Exp | Collected | No |
| PCSTRESN | Numeric Result/Finding in Standard Units | numeric | 8 | Result Qualifier | Exp | Collected | No |
| PCSTRESU | Standard Units | character | 20 | Variable Qualifier | Exp | Collected | No |
| PCDTC | Date/Time of Specimen Collection | character | 20 | Timing | Exp | Collected | No |
| PCTPTNUM | Planned Time Point Number | numeric | 8 | Timing | Perm | Collected | No |

## 3.4 PP - PK Parameters

PP has 30 records and 9 variables. Structure: One record per PK parameter per time-concentration profile per subject.

| Variable | Label | Type | Length | Role | Core | Origin | Observed values |
|---|---|---|---|---|---|---|---|
| STUDYID | Study Identifier | character | 20 | Identifier | Req | Collected | No |
| DOMAIN | Domain Abbreviation | character | 2 | Identifier | Req | Collected | No |
| USUBJID | Unique Subject Identifier | character | 40 | Identifier | Req | Collected | No |
| PPSEQ | Sequence Number | numeric | 8 | Identifier | Req | Derived | No |
| PPTESTCD | Parameter Short Name | character | 8 | Topic | Req | Derived | Yes |
| PPTEST | Parameter Name | character | 40 | Synonym Qualifier | Req | Derived | Yes |
| PPORRES | Result or Finding in Original Units | character | 40 | Result Qualifier | Exp | Derived | Yes |
| PPSTRESN | Numeric Result/Finding in Standard Units | numeric | 8 | Result Qualifier | Exp | Derived | No |
| PPSTRESU | Standard Units | character | 20 | Variable Qualifier | Exp | Derived | Yes |

### 3.5 TS - Trial Summary

TS has 4 records and 11 variables. Structure: One record per trial summary parameter value.

| Variable | Label | Type | Length | Role | Core | Origin | Observed values |
|---|---|---|---|---|---|---|---|
| STUDYID | Study Identifier | character | 20 | Identifier | Req | Collected | No |
| DOMAIN | Domain Abbreviation | character | 2 | Identifier | Req | Collected | No |
| TSSEQ | Sequence Number | numeric | 8 | Identifier | Req | Derived | No |
| TSGRPID | Group ID | character | 20 | Identifier | Perm | Collected | No |
| TSPARMCD | Trial Summary Parameter Short Name | character | 8 | Topic | Req | Collected | Yes |
| TSPARM | Trial Summary Parameter | character | 40 | Synonym Qualifier | Req | Collected | Yes |
| TSVAL | Parameter Value | character | 200 | Result Qualifier | Exp | Collected | Yes |
| TSVALNF | Parameter Null Flavor | character | 8 | Result Qualifier | Perm | Collected | No |
| TSVALCD | Parameter Value Code | character | 40 | Result Qualifier | Exp | Collected | No |
| TSVCDREF | Name of the Reference Terminology | character | 20 | Result Qualifier | Exp | Collected | No |
| TSVCDVER | Version of the Reference Terminology | character | 20 | Result Qualifier | Exp | Collected | No |

## 4. CodeLists

Value lists observed in the delivered data (inferred from the data, not a CDISC CT release). Identifier variables are not listed.

### DM.SUBJID

| Code | Decode |
|---|---|
| 1 | 1 |
| 2 | 2 |
| 3 | 3 |

## PP.PPTESTCD

| Code | Decode |
|---|---|
| AUCIFO | AUCIFO |
| AUCLST | AUCLST |
| CLST | CLST |
| CMAX | CMAX |
| LAMZ | LAMZ |
| LAMZHL | LAMZHL |
| LAMZNPT | LAMZNPT |
| R2 | R2 |
| TLST | TLST |
| TMAX | TMAX |

## PP.PPTEST

| Code | Decode |
|---|---|
| AUC Infinity Obs | AUC Infinity Obs |
| AUC to Last Nonzero Conc | AUC to Last Nonzero Conc |
| Half-Life Lambda z | Half-Life Lambda z |
| Lambda z | Lambda z |
| Last Nonzero Conc | Last Nonzero Conc |
| Max Conc | Max Conc |
| Number of Points for Lambda z | Number of Points for Lambda z |
| R Squared | R Squared |
| Time of CMAX Observation | Time of CMAX Observation |
| Time of Last Nonzero Conc | Time of Last Nonzero Conc |

## PP.PPORRES

| Code | Decode |
|---|---|
| 0.115 | 0.115 |
| 0.12 | 0.12 |
| 0.98 | 0.98 |
| 1.5 | 1.5 |
| 10.2 | 10.2 |
| 24 | 24 |
| 40.5 | 40.5 |
| 43 | 43 |
| 5 | 5 |
| 6 | 6 |
| 8.2 | 8.2 |
| 9.2 | 9.2 |

## PP.PPSTRESU

| Code | Decode |
|---|---|
| | |
| /h | /h |
| h | h |
| h*ng/mL | h*ng/mL |
| ng/mL | ng/mL |

## TS.TSPARMCD

| Code | Decode |
|---|---|
| ACTSUB | ACTSUB |
| SPONSOR | SPONSOR |
| SSTDTC | SSTDTC |
| TITLE | TITLE |

### TS.TSPARM

| Code | Decode |
|---|---|
| Actual Number of Subjects | Actual Number of Subjects |
| Clinical Study Sponsor | Clinical Study Sponsor |
| Study Start Date | Study Start Date |
| Trial Title | Trial Title |

### TS.TSVAL

| Code | Decode |
|---|---|
| 2026-03-01 | 2026-03-01 |
| 3 | 3 |
| Acme Pharma | Acme Pharma |
| Estudio PROT-DG1 | Estudio PROT-DG1 |

## 5. Derivations

No derivation rule was declared for these datasets in this package.

## 6. Data conformance and deviations

• DM: 4 specification variable(s) absent in the source (written empty) (AGE, AGEU, SEX, ARM); 0 source column(s) outside the specification (not delivered); 0 sequence variable(s) generated.

• EX: 2 specification variable(s) absent in the source (written empty) (EXROUTE, EXSTDTC); 0 source column(s) outside the specification (not delivered); 0 sequence variable(s) generated.

• PC: 3 specification variable(s) absent in the source (written empty) (PCORRES, PCSTRESU, PCDTC); 0 source column(s) outside the specification (not delivered); 0 sequence variable(s) generated.

• PP: 0 specification variable(s) absent in the source (written empty); 0 source column(s) outside the specification (not delivered); 0 sequence variable(s) generated.

• TS: 0 specification variable(s) absent in the source (written empty); 0 source column(s) outside the specification (not delivered); 0 sequence variable(s) generated.

• PP: the list of NCA parameters excluded from the closed PK parameter list was not supplied to this guide; it is not known whether any were excluded.

• CDISC CORE no se ejecuto al generar este paquete: no hay evidencia de conformidad CDISC. There is no CDISC conformance evidence for these datasets.

• Protocol deviations: Not declared by the sponsor in this package.

## 7. Traceability of the delivered files

| File | SHA-256 (start) | Reader A | Reader B | XPT arbitration (A, B and metadata) |
|---|---|---|---|---|
| DM.xpt | ea6c83bb39a2f995... | foreign::read.xport | pandas.read_sas | passed |
| EX.xpt | 8062e9a1d434ab86... | foreign::read.xport | pandas.read_sas | passed |
| PC.xpt | f167381af2cba8aa... | foreign::read.xport | pandas.read_sas | passed |
| PP.xpt | 59d4c74b9c44d018... | foreign::read.xport | pandas.read_sas | passed |
| TS.xpt | 47560bd6c2db3500... | foreign::read.xport | pandas.read_sas | passed |

## 8. Conventions

• Datasets with a specification (DM, EX, PC, PP, TS) are SAS Transport v5 files written with xportr; variable names up to 8 characters, labels up to 40.

• Standards referenced by this package: SDTM Implementation Guide v3.2 (reference table: variables of DM, EX, PC and PP only; role and core are n/a elsewhere); CDISC Define-XML v2.0.

• Data listings of DM, EX, PC, PP, TS are delivered in docs/listados/ (one PDF per dataset, generated from the conformed data frame and checked against the rendered PDF, in cell order).

## Appendix A. Numbers in this document and their origin

| Key | Value | Origin |
|---|---|---|
| n_datasets | 5 | datasets SDTM del paquete |
| n_descartadas.DM | 0 | conformar(): columnas del origen fuera de la spec, DM |
| n_descartadas.EX | 0 | conformar(): columnas del origen fuera de la spec, EX |
| n_descartadas.PC | 0 | conformar(): columnas del origen fuera de la spec, PC |
| n_descartadas.PP | 0 | conformar(): columnas del origen fuera de la spec, PP |
| n_descartadas.TS | 0 | conformar(): columnas del origen fuera de la spec, TS |
| n_generadas.DM | 0 | conformar(): variables --SEQ derivadas, DM |
| n_generadas.EX | 0 | conformar(): variables --SEQ derivadas, EX |
| n_generadas.PC | 0 | conformar(): variables --SEQ derivadas, PC |
| n_generadas.PP | 0 | conformar(): variables --SEQ derivadas, PP |
| n_generadas.TS | 0 | conformar(): variables --SEQ derivadas, TS |
| n_reg.DM | 3 | filas del dataset DM entregado |
| n_reg.EX | 3 | filas del dataset EX entregado |
| n_reg.PC | 6 | filas del dataset PC entregado |
| n_reg.PP | 30 | filas del dataset PP entregado |
| n_reg.TS | 4 | filas del dataset TS entregado |
| n_suj.DM | 3 | USUBJID distintos en DM |
| n_suj.EX | 3 | USUBJID distintos en EX |
| n_suj.PC | 3 | USUBJID distintos en PC |
| n_suj.PP | 3 | USUBJID distintos en PP |
| n_vacias.DM | 4 | conformar(): variables de la spec ausentes en el origen, DM |
| n_vacias.EX | 2 | conformar(): variables de la spec ausentes en el origen, EX |
| n_vacias.PC | 3 | conformar(): variables de la spec ausentes en el origen, PC |
| n_vacias.PP | 0 | conformar(): variables de la spec ausentes en el origen, PP |
| n_vacias.TS | 0 | conformar(): variables de la spec ausentes en el origen, TS |
| n_var.DM | 8 | variables de DM (spec) |
| n_var.EX | 9 | variables de EX (spec) |
| n_var.PC | 11 | variables de PC (spec) |
| n_var.PP | 9 | variables de PP (spec) |
| n_var.TS | 11 | variables de TS (spec) |