

Riverside OS v0.60.0 Printable Deployment Guide

Riverside OS v0.60.0 Printable Deployment Guide

Use this guide for the live-store install of:

- **Backoffice / Server PC:** PostgreSQL, Riverside server, web/PWA files, migrations, firewall, startup task, and optional Back Office desktop app.
- **Register #1 Windows PC:** Riverside desktop app, station API base, receipt printer, cash drawer, scanners, and primary till close.
- **Register #2 iPad:** PWA satellite register lane.
- **Other devices:** Back office browser/PWA workstations, phones, and support devices.

Print this guide and check each box during deployment.

1. Release Assets To Use

Use only the official GitHub release:

```
https://github.com/cpg716/riverside-os/releases/tag/v0.60.0
```

Required assets:

- ☐ RiversideOS-v0.60.0-af23cef-Windows-Deployment.zip
- ☐ Riverside.POS_0.60.0_x64_en-US.msi
- ☐ Riverside.POS_0.60.0_x64_en-US.msi.sig
- ☐ latest.json
- ☐ riverside-updater-build-manifest.json

Expected release identity:

```
Version: 0.60.0
Release SHA: af23cefccac60f60050e009c527987571a012510
Deployment package: RiversideOS-v0.60.0-af23cef-Windows-Deployment.zip
```

Do not mix files from older releases.

2. Store Deployment Roles

Station	Device	Role
Backoffice / Server PC	Windows PC	Runs PostgreSQL, Riverside server, web/PWA files, migrations, backups, and optional Back Office desktop app. Keep this PC on.
Register #1	Windows PC	Primary cashier station. Owns the physical cash drawer, receipt printer, and Z-close for the till group.
Register #2	iPad PWA	Satellite register lane. Must attach to the open Register #1 till group.
Other Back Office PCs	Browser/PWA or desktop app	Use for back-office work against the same server. Do not install the server role here.
Phones / remote devices	PWA over trusted network or Tailscale	Use only trusted/private access. Do not expose staff apps on public plain HTTP.

Operational rule:

- Register #1 is the cash drawer lane.
- Register #2+ are satellite lanes.
- Z-close on Register #1 closes the till group.
- Physical cash lives in Register #1 even when a sale is entered from Register #2.

3. Before You Start

Required

- ☐ Download and unzip `RiversideOS-v0.60.0-af23cef-Windows-Deployment.zip`.
- ☐ Keep the unzipped package on a USB drive or local folder available to both Windows PCs.
- ☐ Confirm you have Windows Administrator access on the Backoffice / Server PC.
- ☐ Confirm you have Windows Administrator access on Register #1.
- ☐ Confirm the store network is working.
- ☐ Confirm the Backoffice / Server PC has a stable name or IP address.
- ☐ Confirm Register #1 and iPad can reach the same network.
- ☐ Confirm Epson receipt printer IP or Windows printer name.
- ☐ Confirm Zebra scanner(s) are ready in HID keyboard mode.
- ☐ Confirm payment terminal device codes and provider credentials are available if using Helcim.
- ☐ Keep the prior installer and a fresh database backup available for rollback.

Recommended

- ☐ Put the Backoffice / Server PC on UPS power.
 - ☐ Reserve static/DHCP IPs for the Backoffice / Server PC and Epson receipt printer.
 - ☐ Record every password, station role, device IP, and install result in the deployment log.
-

4. Backoffice / Server PC Install

Run this first.

4.1 Open Deployment Manager

1. On the Backoffice / Server PC, open the unzipped deployment package.
2. Right-click or double-click:

```
Start-RiversideDeployment.cmd
```

3. Choose:

```
Backoffice / Server
```

4. Click **Check**.
5. Resolve any failed readiness checks before installing.
6. Click **Install**.

The installer should:

- Install or use PostgreSQL.
- Create/update Riverside database credentials.
- Copy `riverside-server.exe`.
- Copy the web/PWA files.
- Apply migrations.
- Write `C:\RiversideOS\server\.env`.
- Add the firewall rule.
- Create startup scheduled task `Riverside OS Server`.
- Start the server.
- Check the local app URL.

4.2 PostgreSQL Password Prompts

- If PostgreSQL already exists, enter the existing `postgres` admin password.
- If the Deployment Manager installs PostgreSQL and password fields are blank, it can generate passwords.
- Do not commit or publicly share `riverside-deployment.config.json`.
- Keep the generated credentials with the store deployment records.

4.3 Server Acceptance Check

On the Backoffice / Server PC:

- ☐ Riverside opens locally.
- ☐ Staff sign-in screen loads.
- ☐ Settings -> Updates shows Riverside version `0.60.0`.
- ☐ Settings -> General -> About this build shows the expected server/API.
- ☐ Settings -> Data & Backups opens.
- ☐ Backup path is writable.
- ☐ Server restart works through the Deployment Manager or scheduled task.

From another device on the store network:

- ☐ Open the server URL, for example `http://SERVER-PC-NAME:3000`.
- ☐ Staff sign-in screen loads.
- ☐ No certificate/browser warning appears if using HTTPS.

4.4 Meilisearch / Help / ROSIE

After the server is installed:

- ☐ If Meilisearch is enabled, go to Settings -> Integrations -> Meilisearch.
- ☐ Run **Rebuild search index** after deploy, restore, Meilisearch wipe, or major import.
- ☐ Confirm product/customer/order search returns expected matches.
- ☐ Confirm Help Center opens.
- ☐ Confirm ROSIE is available only if the local model/runtime is installed and configured.

5. Register #1 Windows PC Install

Run this after the Backoffice / Server PC is working.

5.1 Open Deployment Manager

1. On Register #1, open the same unzipped deployment package.
2. Run:

```
Start-RiversideDeployment.cmd
```

3. Choose:

```
Register #1
```

4. Enter or confirm the API base for the Backoffice / Server PC.

Examples:

```
http://SERVER-PC-NAME:3000
http://192.168.1.25:3000
https://ros.yourstore.example
```

Do not use `127.0.0.1` on Register #1 unless the Riverside server is actually running on Register #1.

5. Click **Check**.
6. Resolve failed checks.
7. Click **Install**.

The installer should:

- Write `C:\ProgramData\RiversideOS\station-config.json`.
- Install the Riverside desktop app from the package.
- Save the API base and printer settings.
- Launch the app when possible.

5.2 Register #1 First Launch

- ☐ Open the Riverside desktop app.
- ☐ Confirm the app icon is the Riverside logo, not an old placeholder.
- ☐ Confirm Settings -> Updates shows `0.60.0`.
- ☐ Confirm Settings -> General -> About this build shows the Register #1 API base.
- ☐ Staff sign-in works.
- ☐ Open Register #1.
- ☐ Enter the opening float according to store procedure.
- ☐ Confirm Register #1 is the cash drawer lane.

5.3 Receipt Printer And Cash Drawer

Preferred receipt printer setup:

```
Mode: Network address
Printer: Epson TM-m30III
Port: 9100
IP: static or DHCP-reserved Epson IP
```

Use **Installed printer on this PC** only for USB/driver-managed fallback.

Checklist:

- ☐ Epson receipt printer has paper.
- ☐ Epson printer IP or Windows printer name is recorded.
- ☐ Printers & Scanners settings are saved.
- ☐ Test receipt prints.
- ☐ Cash drawer opens for CASH/CHECK tender.
- ☐ Cash drawer does not intentionally open for card-only tender or receipt reprint.
- ☐ Register #1 receipt reprint path works.

5.4 Scanner

- ☐ Scanner is in HID keyboard mode.
- ☐ Scanner sends Enter/Tab suffix if desired.
- ☐ POS product search receives scanned text.
- ☐ Inventory/search input receives scanned text.
- ☐ Charging/spare scanner plan is known.

5.5 Register #1 Smoke Test

Run one supervised safe flow:

- ☐ Sign in as staff.
 - ☐ Open Register #1.
 - ☐ Search or scan an item.
 - ☐ Add item to cart.
 - ☐ Open checkout drawer.
 - ☐ Cancel safely or complete a store-approved low-risk test sale.
 - ☐ Confirm receipt behavior.
 - ☐ Confirm drawer behavior.
 - ☐ Confirm Register #1 can Z-close the till group.
-

6. Register #2 iPad PWA Install

Register #2 is a PWA satellite lane. It should use the Backoffice / Server PC URL while inside the store.

6.1 Prepare iPad

- ☐ iPad is on the same store Wi-Fi/network as the Backoffice / Server PC.
- ☐ iPad date/time is correct.
- ☐ Safari is available.
- ☐ Bluetooth scanner, if used, is paired as keyboard/HID input.

6.2 Install PWA On iPad

1. Open Safari.
2. Visit the Riverside server URL.

Examples:

```
http://SERVER-PC-NAME:3000
http://192.168.1.25:3000
https://ros.yourstore.example
```

3. Confirm the Riverside sign-in screen loads.
4. Tap **Share**.
5. Tap **Add to Home Screen**.

6. Name it:

Riverside Register 2

7. Launch Riverside from the new Home Screen icon.

Do not run Register #2 from a regular Safari tab for production use.

6.3 Register #2 First Launch

- ☐ Launch from Home Screen icon.
- ☐ Staff sign-in works.
- ☐ Confirm Settings -> Updates shows version 0.60.0 .
- ☐ Confirm no **Update incomplete** warning.
- ☐ Open/attach Register #2 only after Register #1 is open.
- ☐ Confirm it behaves as a satellite lane.
- ☐ Confirm customer lookup works.
- ☐ Confirm item lookup/cart works.
- ☐ Confirm checkout drawer fits comfortably on the iPad.
- ☐ Confirm staff understand physical cash is handled at Register #1.

6.4 iPad Scanner

- ☐ Pair Zebra CS6080 or similar as Bluetooth keyboard/HID.
- ☐ Open a product/SKU search field.
- ☐ Scan a barcode.
- ☐ Confirm scanned text appears in the focused field.
- ☐ Confirm suffix behavior is acceptable.

6.5 iPad Receipts

Operational rule:

- Register #1 remains the primary receipt and cash-drawer station.
- iPad receipt printing is allowed only if the server can reach the Epson network printer.
- If iPad print fails, reprint from Register #1.

Checklist:

- ☐ If iPad receipt printing is expected, Epson printer has a network IP.
- ☐ Backoffice / Server PC can reach Epson printer IP on port 9100 .
- ☐ Server-side receipt print is tested from the iPad flow.
- ☐ Staff know the Register #1 reprint recovery path.

7. Other Back Office PCs / Browser PWA Devices

For Windows PCs that are not the server and not Register #1:

- ☐ Open the Riverside server URL in Edge/Chrome.

- ☐ Use browser install prompt if desired.
- ☐ Sign in with staff PIN.
- ☐ Confirm Customers loads.
- ☐ Confirm Orders loads.
- ☐ Confirm Inventory loads.
- ☐ Confirm Reports/Insights loads if the role has access.
- ☐ Confirm Settings -> Updates shows 0.60.0 .
- ☐ Do not install the Backoffice / Server role on these PCs.

Use the Riverside desktop app only when native printer/scanner reliability is required.

8. Updates After Install

After any update:

- ☐ Update Backoffice / Server PC first.
- ☐ Confirm server starts and Settings -> Updates shows 0.60.0 .
- ☐ Update Register #1 desktop app.
- ☐ Relaunch Register #1 and confirm Settings -> Updates shows 0.60.0 .
- ☐ On iPad, open Settings -> Updates -> iPad and browser app -> Check app files.
- ☐ If the PWA update prompt appears, tap **Reload now** only when no sale is in progress.
- ☐ Confirm no station shows **Update incomplete**.

Never run sales if server, Windows app, and PWA files show different Riverside versions.

9. Backup And Rollback Readiness

Before live use:

- ☐ Create a fresh database backup.
- ☐ Confirm the backup file exists and has non-trivial size.
- ☐ Keep a copy off the server PC if practical.
- ☐ Keep the previous installer/build accessible.
- ☐ Record backup timestamp and file name.
- ☐ Record who has rollback authority.

Rollback rule:

- Stop all registers.
 - Close active transactions.
 - Restore the database backup before running older binaries against migrated data.
 - Do not run an older server against a newer migrated database without restore approval.
-

10. Go-Live Station Checklist

Run this on each station before first customer use.

Backoffice / Server PC

- ☐ Server starts after reboot.
- ☐ Staff sign-in works.
- ☐ Backup path works.
- ☐ Meiliseach status is understood.
- ☐ Help Center opens.
- ☐ Settings -> Updates shows 0.60.0 .

Register #1

- ☐ Staff sign-in works.
- ☐ Register #1 opens.
- ☐ Scanner works.
- ☐ Receipt prints.
- ☐ Cash drawer opens for CASH/CHECK.
- ☐ Card/Helcim flow is validated if enabled.
- ☐ Z-close path is understood.

Register #2 iPad

- ☐ Launches from Home Screen icon.
- ☐ Staff sign-in works.
- ☐ Register #2 attaches after Register #1 is open.
- ☐ Scanner works if used.
- ☐ Receipt path is understood.
- ☐ No stale version warning.

Store Operations

- ☐ Staff know who to call for support.
 - ☐ Staff know not to close apps during active checkout.
 - ☐ Staff know Register #1 owns cash and Z-close.
 - ☐ Staff know iPad receipt fallback is Register #1 reprint.
 - ☐ Deployment log is filled out.
-

11. Quick Troubleshooting

PWA will not load

1. Confirm the device is on the correct network.
2. Open the API/server URL in the device browser.
3. Check DNS/server name.

4. Check firewall on Backoffice / Server PC.
5. If using HTTPS, check certificate/date/time.
6. Close and reopen the Home Screen icon.
7. If still stale, remove the icon, clear site data, and Add to Home Screen again.

Register app will not reach server

1. Check Settings -> General -> About this build for API base.
2. Confirm Register #1 is not pointed at 127.0.0.1 unless the server is local.
3. Ping/open the Backoffice / Server PC URL from Register #1.
4. Run Repair from Deployment Manager if station config is wrong.

Receipt will not print

1. Check Printers & Scanners.
2. For network mode, confirm Epson IP and port 9100 .
3. For installed-printer mode, confirm Windows test page works.
4. Restart the desktop app after printer/network changes.
5. For iPad, confirm the server can reach the network printer.

Update incomplete

1. Finish updating the Backoffice / Server PC.
 2. Finish updating Register #1 desktop app.
 3. On iPad/PWA, Check app files and reload.
 4. Do not continue production work until all surfaces show 0.60.0 .
-

12. Deployment Log

Item	Value
Deployment date	
Release version	0.60.0
Release SHA	af23cefccac60f60050e009c527987571a012510
Backoffice / Server PC name	
Backoffice / Server PC IP	
Register #1 PC name	
Register #1 API base	
iPad Register #2 URL	
Epson receipt printer IP/name	
Zebra scanner model(s)	
Backup file name	
Backup timestamp	
Installer owner	
Store manager signoff	
Rollback authority	