



Riverside OS v0.90.0 — 30-Minute Quick-Start Deployment Guide

Authoritative reference manual for store hardware configuration, software package updates, schema migrations, and backup verification.

TARGET VERSION	v0.90.0
DOCUMENT CLASSIFICATION	Operational Standard Work
AUTHORIZED STATIONS	Main Hub / Register #1 / Register #2 (iPad) / Counterpoint PC
GENERATED ON	June 7, 2026

CONFIDENTIAL • INTERNAL STORE OPERATIONS ONLY • DO NOT DISTRIBUTE

Table of Contents

- 30-Minute Timeline Overview
- Phase 1: Preparation (0-5 minutes)
- Phase 2: Main Hub Install (5-12 minutes)
- Phase 3: Critical Integrations (12-18 minutes)
- Phase 4: Register #1 Setup (18-22 minutes)
- Phase 5: Register #2 iPad PWA (22-25 minutes)
- Phase 6: Test Sale and Go Live (25-30 minutes)
- Integration Troubleshooting Quick Reference
- Common Issues and Fixes
- Updates and Hotfixes
- Backup and Rollback
- DevOps Center (In-App)
- Additional Resources
- v0.90.0 Current Release Changes to Verify
- External Go-Live Gates
- Deployment Log

Goal: Get fully up and running in 30 minutes (sync time not counted)

This guide takes you from zero to processing your first sale on Riverside OS. Print this guide and check off each step as you complete it.

30-Minute Timeline Overview

Phase	Time	What You'll Do
Preparation	0-5 min	Download files, gather info, prep network
Main Hub Install	5-12 min	Install Main Hub and verify
Integrations	12-18 min	Configure critical integrations (QBO, Helcim, etc.)
Register #1	18-22 min	Install main register with peripherals
Register #2	22-25 min	Set up iPad PWA satellite lane
Test Sale	25-30 min	Run smoke test and process first sale

Note: Initial data sync (Counterpoint, catalog, etc.) runs in background and doesn't count toward the 30 minutes.

v0.90.0 Deployment Notes

- v0.90.0 is the current **GO LIVE readiness** release and should be installed as a complete Main Hub + register package.
- The Main Hub must be updated before Windows register apps and PWA stations.
- ROSIE is optimized for the local Gemma E4B, SenseVoice, and Kokoro stack. The knowledge layer is local and provider-neutral, so a future approved cloud LLM/TTS/STT provider can use the same bounded Riverside context without changing deployment permissions.
- Help Library search can use Meilisearch. Ask ROSIE and ROSIE Chat use the local approved ROSIE knowledge index and should not depend on Help Library search availability.
- Full Windows deployment, real payment/shipping/accounting credentials, Counterpoint SQL reconciliation, and backup restore remain store-site go-live gates.

Phase 1: Preparation (0-5 minutes)

What You Need Before Starting

Download Required Files:

- ☐ Download from: <https://github.com/cpg716/riverside-os/releases/tag/v0.90.0>
- ☐ `RiversideOS-v0.90.0-<build-sha>-Windows-Deployment.zip` (published release asset; certification build example: `RiversideOS-v0.90.0-1e630a1-Windows-Deployment.zip`)
- ☐ `Riverside.POS_0.90.0_x64_en-US.msi`
- ☐ Matching `Riverside.POS_0.90.0_x64_en-US.msi.sig`
- ☐ Standalone Deployment Manager, Server Manager, and Counterpoint Bridge GUI installers when present in the release assets
- ☐ Unzip the deployment package
- ☐ Review `docs/releases/v0.90.0-release-notes.md` , `docs/releases/v0.90.0-certification.md` , and `docs/audits/v0.90.0_READY_TO_TEST_BLOCKER_AUDIT.md` before station rollout
- ☐ For Counterpoint cutover, prefer the packaged Counterpoint Bridge GUI installer so Node.js and `npm install` are not required on the Counterpoint machine

Gather This Information:

- ☐ Main Hub name and LAN IP (e.g., `10.64.70.196`)
- ☐ Epson receipt printer IP or Windows printer name
- ☐ Scanner is in HID keyboard mode
- ☐ Payment terminal device codes (if using Helcim)
- ☐ Windows Administrator access on Main Hub and Register #1

Network Setup:

- ☐ All devices (Main Hub, Register #1, iPad) on same store network
- ☐ Confirm devices can reach each other
- ☐ Reserve static/DHCP IPs for Main Hub and printer (recommended)

Store Roles (Quick Reference):

Station	Device	API Host
Main Hub	Windows PC	http://127.0.0.1:3000
Register #1	Windows PC	http://MAIN-HUB-IP:3000
Register #2	iPad PWA	http://MAIN-HUB-IP:3000

Critical Rule: Register #1 is the physical cash drawer lane. All other lanes attach to Register #1's till group.

Phase 2: Main Hub Install (5-12 minutes)

Install Main Hub

Step 1: Run Deployment Manager (2 minutes)

- ☐ On Main Hub, open unzipped deployment package
- ☐ Run `Start-RiversideDeployment.cmd`
- ☐ Choose "Main Hub"
- ☐ Click **Check** and resolve any failed checks
- ☐ Click **Install**

What the installer does:

- Installs/uses PostgreSQL
- Creates Riverside database and user
- Copies server files and web/PWA assets
- Applies database migrations
- Installs/updates the bundled Deployment Manager, Server Manager, and support tools where included
- Downloads or installs ROSIE runtime assets: llama.cpp host, Gemma GGUF, SenseVoice STT, Kokoro TTS, and required support files (may take extra time)
- Sets up firewall rule for port 3000
- Creates auto-start tasks for Riverside Server and ROSIE where applicable
- Starts Riverside Server and local ROSIE Host when ready

Step 2: Verify Server Health (3 minutes)

- ☐ Open <http://127.0.0.1:3000> on Main Hub

- ☐ Staff sign-in screen loads
- ☐ Settings → Updates shows 0.90.0
- ☐ Settings → General → About shows correct API host
- ☐ Settings → Data & Backups opens
- ☐ Backup path is writable

Step 3: Test Network Access (2 minutes)

- ☐ From another device, open http://MAIN-HUB-IP:3000
- ☐ Staff sign-in screen loads
- ☐ No version mismatch warning

Server Repair Tools (if needed):

Tool	When to Use
Deployment Manager → Repair	Server files, firewall, task need refresh
Deployment Manager → PostgreSQL Status	Check/restart PG service
ROS Server Manager	Local server start/stop/status when the main app is down
Repair-RiversideCredentialsKey.cmd	Settings says credentials key must be set
Set-CounterpointBridgeToken.cmd	Counterpoint bridge fails with 401

Phase 3: Critical Integrations (12-18 minutes)

Credential Key Setup (1 minute)

Required before saving any integration credentials:

- ☐ Sign in as administrator
- ☐ Navigate to Settings → any integration (e.g., Helcim)
- ☐ Try to save configuration
- ☐ If warning says RIVERSIDE_CREDENTIALS_KEY must be set :
 - ☐ Run Repair-RiversideCredentialsKey.cmd on Main Hub (as admin)

- ☐ Re-login and confirm integrations can be saved

QuickBooks Online (3 minutes)

For sales invoice and payment sync:

- ☐ Settings → Integrations → QuickBooks
- ☐ Enter Client ID and Client Secret
- ☐ Click "Connect to QuickBooks"
- ☐ Sign in with store QBO account, select Company file
- ☐ Authorize connection
- ☐ Configure account mappings:
 - ☐ Sales Income Account
 - ☐ Cash/Tender Deposit Bank Account
 - ☐ Sales Tax Liability Account
 - ☐ Accounts Receivable (AR) Account
 - ☐ Inventory Asset Account
 - ☐ COGS Account
- ☐ Verify QBO Sync Worker status is `Idle` or `Syncing`

Helcim Card Payments (3 minutes)

For physical card terminal integration:

- ☐ Settings → Integrations → Helcim
- ☐ Enter Merchant ID and API Access Token
- ☐ Set Environment to **Production** (unless testing)
- ☐ Configure terminal IP/device code for Register #1
- ☐ Trigger test ping, confirm "Terminal Connected"
- ☐ Copy webhook URL: `http://MAIN-HUB-IP:3000/api/webhooks/helcim`
- ☐ Configure in Helcim Developer Portal for events: `order.approved` , `transaction.captured`

Shippo Shipping (2 minutes)

For carrier rates and label printing:

- ☐ Settings → Integrations → Shippo
- ☐ Enter Shippo API Key (starts with `shippo_prod_` for live)
- ☐ Enter Default Store Origin Address
- ☐ Click Save

- ☐ Go to Fulfillment → Shipments Hub, verify carriers load

Meiliseach Search (2 minutes)

For fast product/customer/help-library search:

- ☐ Verify Meiliseach service running on port 7700
- ☐ Settings → Integrations → Meiliseach
- ☐ Confirm URL: `http://127.0.0.1:7700`
- ☐ Enter API Key
- ☐ Click "Test Connection" → status shows `Connected`
- ☐ Click "Full Reindex"
- ☐ Test search bar, confirm instant results
- ☐ Test Help Library search
- ☐ Confirm Ask ROSIE still answers even if Help Library search is not the direct source

Optional Integrations (Configure as needed)

Podium Texting:

- ☐ Settings → Integrations → Podium
- ☐ Enter API Token and Location ID
- ☐ Verify webhook receiver is Active
- ☐ Map Staff Tracking IDs to Podium User IDs

Counterpoint Bridge:

- ☐ Settings → Integrations → Counterpoint
- ☐ Copy generated Bridge sync token
- ☐ On Counterpoint PC, set `ROS_BASE_URL=http://MAIN-HUB-IP:3000`
- ☐ Set `COUNTERPOINT_SYNC_TOKEN` to match
- ☐ Verify `CP_AUTO_SCHEMA` variable in bridge env:
 - If `CP_AUTO_SCHEMA=0` (manual-SQL mode), verify startup schema validation passes with no empty query check errors.
- ☐ Restart Counterpoint Node Bridge service
- ☐ Verify dashboard shows `Connected`

Sweden-Style Cash Rounding:

- ☐ Settings → Register (Terminal Overrides)
- ☐ Configure the "Cash Rounding" toggle (Sweden-style \$0.05 rounding)

- ☐ Verify that unauthenticated registers query the setting on lane initialization

NuORDER Wholesale:

- ☐ Settings → Integrations → NuORDER
- ☐ Save OAuth credentials (Consumer Key/Secret, User Token/Secret)
- ☐ Trigger health check, confirm `Connected`
- ☐ Link Vendors to Brands in Vendor Hub
- ☐ Trigger manual sync, verify no errors

Metabase Analytics:

- ☐ Verify Metabase container running on port 3001
- ☐ Connect database in Metabase (user: `metabase_ro`)
- ☐ Run `scripts/metabase-refresh-reporting-metadata.mjs`
- ☐ Create collections: `Staff Approved`, `Admin Financial`
- ☐ Create user groups with appropriate permissions
- ☐ In Settings → Integrations → Metabase, save Admin and Staff credentials so encrypted saved credentials are used before env fallback
- ☐ Run the non-destructive Metabase verification/check mode from Settings or ROS Dev Center
- ☐ Test Insights iframe loads in Back Office

ROSIE AI Copilot:

- ☐ Confirm required binaries exist inside `C:\RiversideOS\rosie\bin\`: `llama-server.exe`, `sherpa-onnx-offline.exe`, `sherpa-onnx-offline-tts.exe`, and required DLLs
- ☐ Confirm SenseVoice model exists at `C:\RiversideOS\rosie\stt\sherpa-onnx-sense-voice-zh-en-ja-ko-yue-int8-2024-07-17\model.int8.onnx`
- ☐ Confirm Kokoro model exists at `C:\RiversideOS\rosie\tts\kokoro-multi-lang-v1_0\model.onnx`
- ☐ Confirm Kokoro espeak support data exists under the Kokoro TTS folder
- ☐ Confirm Gemma model downloaded and verified: `C:\RiversideOS\rosie\models\gemma-4-e4b\google_gemma-4-E4B-it-Q4_K_M.gguf`
- ☐ Verify `rosie_ready` flag file is created at `C:\RiversideOS\rosie\rosie_ready`
- ☐ Verify `.env` contains:
 - ☐ `RIVERSIDE_LLAMA_MODEL_PATH` pointing to the Gemma GGUF model
 - ☐ `RIVERSIDE_LLAMA_UPSTREAM=http://127.0.0.1:8080`
 - ☐ `RIVERSIDE_LLAMA_EXTRA_ARGS=--reasoning off`
 - ☐ `ROSIE_PROVIDER_MODE=local-gemma`

☐ `ROSIE_FORCE_LOCAL_FOR_SENSITIVE=true`

- ☐ Verify scheduled tasks exist: `Riverside OS LLM Host` and `Riverside OS ROSIE Watchdog`
- ☐ Test `http://127.0.0.1:8080/health` on the Main Hub
- ☐ In Help Center, test **Help Library**, **Ask ROSIE**, and **ROSIE Chat**
- ☐ In ROSIE Chat, test Speech Off/On behavior and verify TTS does not read markdown symbols aloud
- ☐ If future approved cloud LLM/TTS/STT provider credentials are configured, confirm sensitive workflows still force local mode per store policy

Auxiliary APIs:

- ☐ Settings → Integrations → Fal.ai (visual AI)
- ☐ Settings → Integrations → Geoapify (delivery/mapping)
- ☐ Settings → Integrations → Weather (Visual Crossing)
- ☐ Settings → Integrations → Email (SMTP/IMAP)
- ☐ Settings → Integrations → Cloud Backups (S3)
- ☐ Settings → Online Store (JWT secret)

Constant Contact:

- ☐ Settings → Integrations → Constant Contact
- ☐ Save OAuth Client ID and Secret
- ☐ Click "Authorize Account", complete OAuth flow
- ☐ Configure target mailing lists
- ☐ Trigger manual sync, verify success logs
- ☐ Configure webhook URL in Constant Contact portal

Phase 4: Register #1 Setup (18-22 minutes)

Install Register #1 Windows PC

Step 1: Run Deployment Manager (2 minutes)

- ☐ On Register #1, open unzipped deployment package
- ☐ Run `Start-RiversideDeployment.cmd`
- ☐ Choose "Register #1"
- ☐ Enter Main Hub API base: `http://MAIN-HUB-IP:3000` (NOT `127.0.0.1`)
- ☐ Enter Register #1 station label

- ☐ Choose receipt printer mode (Network address recommended)
- ☐ Choose cash drawer setting
- ☐ Click **Check**, resolve any failed checks
- ☐ Click **Install**

What the installer does:

- Writes station config to `C:\ProgramData\RiversideOS\station-config.json`
- Installs Riverside desktop app
- Saves API base, printer, and cash drawer settings
- Launches the app

Step 2: First Launch Verification (2 minutes)

- ☐ Open Riverside desktop app
- ☐ Confirm app icon is Riverside logo
- ☐ Settings → Updates shows `0.90.0`
- ☐ Settings → General → About shows `http://MAIN-HUB-IP:3000`
- ☐ Staff sign-in works
- ☐ Open Register #1
- ☐ Enter opening float per store procedure
- ☐ Confirm Register #1 is cash drawer lane

Peripherals Setup (2 minutes)

Receipt Printer:

- ☐ Epson TM-m30III has paper
- ☐ Printer IP recorded (network mode) or Windows printer name (installed mode)
- ☐ Settings → Printers & Scanners saved
- ☐ Test receipt prints successfully
- ☐ PWA receipt test prints from Epson IP/port
- ☐ Receipt reprint path works

Cash Drawer & Rounding:

- ☐ Cash drawer connected to receipt printer
- ☐ Opens for CASH/CHECK tender
- ☐ Does NOT open for card-only tender
- ☐ Verify cash sales apply Sweden-style rounding to nearest \$0.05 when enabled
- ☐ Verify card, check, and gift card tenders use exact-cent precision

- ☐ Staff understand cash belongs to Register #1

Scanner:

- ☐ Scanner in HID keyboard mode
- ☐ Scanner sends Enter/Tab suffix (if desired)
- ☐ POS product search receives scanned text
- ☐ Inventory/search input receives scanned text

Reports and Tags:

- ☐ Reports printer configured in Settings → Printers & Scanners
 - ☐ Report-style printing routes directly to the configured Reports printer in the desktop app
 - ☐ Browser/Windows print is used only when the workflow is intentionally browser/PWA based
 - ☐ Clothing tags use Zebra 2844 station
 - ☐ Zebra network checks fail clearly if unreachable
-

Phase 5: Register #2 iPad PWA (22-25 minutes)

Prepare iPad (1 minute)

- ☐ iPad on same store Wi-Fi as Main Hub
- ☐ iPad date/time correct
- ☐ Safari available
- ☐ Bluetooth scanner paired as keyboard/HID (if used)

Install PWA (2 minutes)

- ☐ Open Safari on iPad
- ☐ Visit: `http://MAIN-HUB-IP:3000`
- ☐ Confirm Riverside sign-in screen loads
- ☐ Tap **Share** → **Add to Home Screen**
- ☐ Name it: "Riverside Register 2"
- ☐ Launch from Home Screen icon (not Safari tab)

First Launch Verification (1 minute)

- ☐ Launch from Home Screen icon
- ☐ Staff sign-in works

- ☐ Settings → Updates shows 0.90.0
- ☐ No "Update incomplete" warning
- ☐ Open Register #2 only after Register #1 is open
- ☐ Behaves as satellite lane
- ☐ Customer lookup works
- ☐ Item lookup/cart works
- ☐ Checkout drawer fits on iPad

iPad Scanner and Receipt (1 minute)

- ☐ Bluetooth scanner paired and working
- ☐ Scan barcode, text appears in focused field
- ☐ Main Hub can reach network printer (if iPad printing expected)
- ☐ Receipt reprint from Register #1 if iPad print fails

Phase 6: Test Sale and Go Live (25-30 minutes)

Production Smoke Test (3 minutes)

Main Hub:

- ☐ Reboot/restart Main Hub
- ☐ "Riverside OS Server" starts automatically
- ☐ Sign-in works on Main Hub
- ☐ Another device opens http://MAIN-HUB-IP:3000
- ☐ Backup path writable
- ☐ Deployment Manager PostgreSQL Status: running, OK

Register #1:

- ☐ Staff sign-in works
- ☐ Register #1 opens
- ☐ Scanner works
- ☐ Receipt prints
- ☐ Cash drawer opens for CASH/CHECK
- ☐ Card/Helcim flow validated (if enabled)
- ☐ Sale Complete screen shows real transaction ID, sale total, tender, and receipt actions
- ☐ Return/exchange path opens the guided exchange/return wizard

- ☐ Z-close path understood

Register #2 iPad:

- ☐ Launches from Home Screen icon
- ☐ Staff sign-in works
- ☐ Register #2 attaches after Register #1 open
- ☐ Scanner works (if used)
- ☐ Receipt fallback path understood
- ☐ No stale version warning

Process First Sale (2 minutes)

Run supervised test sale:

- ☐ Sign in as staff
- ☐ Open Register #1
- ☐ Search or scan an item
- ☐ Add item to cart
- ☐ Open checkout drawer
- ☐ Complete store-approved test sale
- ☐ Confirm receipt prints correctly
- ☐ Confirm cash drawer opens (if cash tender)
- ☐ Confirm transaction appears in history
- ☐ Confirm Daily Sales and Register Day Summary reports show the transaction
- ☐ If weather reporting is enabled, confirm Daily Sales Weather report loads

Backup Before Go Live (1 minute)

- ☐ Create fresh database backup
- ☐ Confirm backup file exists with non-trivial size
- ☐ Keep backup off Main Hub if practical
- ☐ Record backup timestamp and filename
- ☐ Record who has rollback authority

You're Live! 🎉

Riverside OS v0.90.0 is now ready for production use.

Integration Troubleshooting Quick Reference

Integration	Issue	Solution
QBO	Shows Disconnected	Re-auth via "Connect to QuickBooks"
Helcim	Terminal times out	Verify terminal IP, confirm same subnet
Shippo	Carrier quote error 401	Replace invalid/revoked API key
Podium	Texts fail to deliver	Check Location ID, verify account credits
Meilisearch	Search returns zero	Confirm service running, click "Full Reindex"
Counterpoint	health 401 or 503	Run Set-CounterpointBridgeToken.cmd
NuORDER	Sync 401 unauthorized	Verify OAuth credentials match brand
Metabase	Insights iframe fails	Run Settings/ROS Dev Center verification; check port 3001, saved credentials, metabase_ro, and shared auth
ROSIE	Ask/Chat unavailable	Check rosie_component_status.json, rosie_ready, Riverside OS LLM Host, and <code>http://127.0.0.1:8080/health</code>
ROSIE Voice	Speech input/output unavailable	Check SenseVoice/Kokoro model folders, sherpa binaries, and Kokoro espeak data
Constant Contact	Sync failed/oauth error	Verify Client ID/Secret, check redirect URI

Common Issues and Fixes

PWA will not load

1. Confirm device on correct network
2. Open `http://MAIN-HUB-IP:3000` in browser

3. Check DNS/server name
4. Check firewall on Main Hub
5. Close/reopen Home Screen icon
6. If stale, remove icon, clear site data, re-add

Register app won't reach Main Hub

1. Check Settings → General → About for API base
2. Confirm Register #1 NOT pointed at `127.0.0.1`
3. Open Main Hub URL from Register #1
4. Run Repair from Deployment Manager

PostgreSQL down/unreachable

1. Open Deployment Manager
2. Check PostgreSQL Status panel
3. If stopped, click **Start PG**
4. If connection failed, verify PG installed and running
5. Use **Restart PG** if service running but connections failing

Receipt won't print

1. Check Printers & Scanners settings
2. For network mode, confirm Epson IP and port 9100
3. For installed mode, confirm Windows test page works
4. Restart desktop app after printer changes
5. For iPad, confirm Main Hub can reach network printer

Reports won't print

1. Confirm Reports printer is saved in Settings → Printers & Scanners
2. Confirm the report is running in the desktop app when direct Reports printer routing is expected
3. Print a Windows test page to the configured Reports printer
4. Reopen the report after changing printer settings
5. Use browser print only for browser/PWA contexts

ROSIE is slow or unavailable

1. Open ROSIE settings and confirm Host Runtime Status is healthy
2. Check `C:\RiversideOS\rosie\rosie_component_status.json`

3. Start or restart the `Riverside OS LLM Host` scheduled task
4. Run `Start-RiversideLlama.cmd` or `start-riverside-llama.ps1` from the deployment package
5. Confirm `RIVERSIDE_LLAMA_UPSTREAM=http://127.0.0.1:8080`
6. For speech, confirm SenseVoice/Kokoro assets and sherpa binaries are present
7. Re-run `Install-RosieAiStack.ps1` after network connectivity is restored

Update incomplete

1. Update Main Hub first
2. Update Register #1 desktop app
3. On iPad, Check app files and reload
4. Do not continue until all surfaces show `0.90.0`

Updates and Hotfixes

After any update:

- ☐ Update Main Hub first
- ☐ Confirm Main Hub server starts, Settings shows `0.90.0`
- ☐ Update Register #1 desktop app
- ☐ Relaunch Register #1, confirm Settings shows `0.90.0`
- ☐ On iPad, Settings → Updates → Check app files
- ☐ If PWA update prompt appears, tap **Reload now** (when no sale in progress)
- ☐ Confirm no station shows **Update incomplete**

Never run sales if Main Hub server, Windows app, and PWA show different versions.

Backup and Rollback

Before live use:

- ☐ Create fresh database backup
- ☐ Confirm backup file exists with non-trivial size
- ☐ Keep copy off Main Hub if practical
- ☐ Keep previous installer/build accessible

- ☐ Record backup timestamp and filename
- ☐ Record who has rollback authority

Rollback procedure:

1. Stop all registers
 2. Stop active checkouts
 3. Record reason for rollback
 4. Restore database backup before running older binaries
 5. Do not run older server against newer migrated data without approval
-

DevOps Center (In-App)

For staff with `ops.dev_center.view` permission.

Access:

1. Open Riverside on any device
2. Sign in as staff with DevOps permissions
3. Open Settings → ROS Dev Center

What it shows:

- Operational status (DB health, integrations, stations)
- Runtime diagnostics (memory, disk, service status)
- E2E health (latest CI test lane status)
- Alerts (open system alerts, ack/resolve actions)
- Stations (register heartbeat status and versions)
- Bug reports (pending bugs with server log snapshots)
- GitHub (recent workflow runs, releases, one-click builds)

Trigger release build (requires `ops.dev_center.actions` permission and `RIVERSIDE_GITHUB_TOKEN`):

1. In ROS Dev Center, scroll to GitHub DevOps
 2. Select release version and click "Build Release"
-

Additional Resources

- **Full Deployment Guide:** See `docs/DEPLOYMENT_GUIDE.md` for detailed technical reference
 - **Production Hardening:** See `docs/PRODUCTION_HARDENING_GUIDE.md` for enterprise features
 - **Redis Integration:** See `docs/REDIS_INTEGRATION_GUIDE.md` for distributed caching
 - **Job Queue:** See `docs/JOB_QUEUE_GUIDE.md` for background job processing
 - **Metrics System:** See `docs/METRICS_SYSTEM_GUIDE.md` for business and technical KPIs
-

v0.90.0 Current Release Changes to Verify

These checks are specific to the current v0.90.0 same-version rebuild.

ROSIE and Help Center

- ☐ ROSIE local knowledge retrieval is active for Ask ROSIE and ROSIE Chat.
- ☐ Help Library search works through Meilisearch, but Ask ROSIE/ROSIE Chat still use the local approved knowledge index.
- ☐ Ask ROSIE answers direct procedure questions instead of telling staff to read/search manuals.
- ☐ ROSIE Chat speech can be turned off at the station.
- ☐ Speech output strips markdown symbols and does not read `asterisks` or source formatting aloud.
- ☐ Full Help Guide print opens the system print dialog after building the guide.

Reports and Insights

- ☐ Insights launches with saved encrypted Metabase Admin/Staff credentials before env fallback.
- ☐ Settings and ROS Dev Center readiness checks agree on Metabase status.
- ☐ Metabase non-destructive verification passes for reporting schema, sample database, and shared-auth checks.
- ☐ Daily Sales Weather report loads.
- ☐ Register Day Summary and Daily Sales display captured weather when available.
- ☐ Reports printing routes to the configured Reports printer in the desktop app.

POS, Commissions, and Inventory

- ☐ Employee discounts apply correctly in POS checkout.
- ☐ Sale Complete screen shows a real transaction ID, sale total, tender, and receipt actions.

- ☐ SPIFF setup targets scanner-friendly products/SKUs.
- ☐ Combo commission setup uses product-based requirements, not SKU-only logic.
- ☐ Commission reporting includes fulfilled/pickup/takeaway/completed transaction attribution.
- ☐ Inventory Reports are discoverable from the Inventory sidebar.
- ☐ Physical Inventory wording, lockout, and validation behavior match current staff workflow.
- ☐ Promotions can target full inventory or selected SKU sets as configured.

Orders, Weddings, and QBO

- ☐ Wedding group-pay member attribution is correct.
- ☐ Wedding financial context loads after group payments.
- ☐ Alteration-ready propagation no longer writes invalid `transaction_lines.updated_at`.
- ☐ QBO export mappings are explicit; no generic fallback account is used for exportable activity.
- ☐ QBO staging can still post/void/re-stage in the configured sandbox or production process.

Bug Reports and Support

- ☐ Bug report screenshot capture works in browser and Tauri contexts.
- ☐ Bug reports include recent server log snapshots.
- ☐ Unsupported CSS color functions do not break screenshot capture.
- ☐ ROS Dev Center shows current runtime, release, stations, bug, and GitHub workflow status.

External Go-Live Gates

These require the real store environment and are not complete just because source validation passed.

- ☐ Full Windows Main Hub install/update/uninstall rehearsal completed.
- ☐ ROSIE install/update verified on the target Windows hardware.
- ☐ Counterpoint SQL live sync reconciliation completed.
- ☐ QBO sandbox post/void/re-stage proof completed.
- ☐ Helcim terminal payment and webhook flow tested with real credentials.
- ☐ Podium text workflow tested with live account.
- ☐ Shippo live or sandbox label/rate flow tested.
- ☐ Backup restore rehearsal completed on the Windows Main Hub against a non-production drill database.

☐ Store manager signs off that Register #1, iPad PWA, printers, scanners, reports, and ROSIE are ready.

Deployment Complete! 🎉

You now have Riverside OS v0.90.0 fully deployed and ready for production use. The system will handle initial data sync (Counterpoint, catalog, etc.) in the background.

Deployment Log

Item	Value
Deployment date	
Release version	0.90.0
Release asset ZIP	
Release build SHA	
POS MSI/signature verified	
Main Hub name	
Main Hub IP	
Server API host on Main Hub	http://127.0.0.1:3000
Register #1 PC name	
Register #1 API base	
iPad Register #2 URL	
Counterpoint PC name	
Counterpoint ROS_BASE_URL	
Epson receipt printer IP/name	
Reports printer name	
Zebra scanner model(s)	
Helcim terminal/device codes verified	
QBO company connected	
Metabase verification passed	
ROSIE rosie_ready verified	
ROSIE Host health URL	http://127.0.0.1:8080/health

Item	Value
Backup file name	
Backup timestamp	
Restore rehearsal timestamp	
Installer owner	
Store manager signoff	
Rollback authority	