# **O**

# Worksheet 18

# To accompany Chapter 7.1 The Discrete Fourier Transform

We will step through this worksheet in class.

You are expected to have at least watched the video presentation of <u>Chapter 7.1</u> of the <u>notes</u> before coming to class.

If you haven't watch it afterwards!

#### List of Abbreviations

- CT Continuous Time
- DT Discrete Time
- DF Discrete frequency
- DFT Discrete (Time) Fourier Transform
- FFT Fast Fourier Transform

#### **Notation**

In the following we shall denote a DT signal as x[n] and its discrete frequency function as X[m].

### **Z-Transform**

Recall that

$$F(z) = \mathcal{Z}f[n] = \sum_{n=0}^{\infty} f[n]z^{-n}.$$

The value of this function on the unit circle in the Z-plane will be

$$F(\exp(j\omega T)) = \sum_{n=0}^{\infty} f[n] \exp(-jn\omega T).$$

This is an infinite sum. So to compute it, we need to truncate it.

# The Discrete-time Fourier Transform

Let's assume that instead of an infinite number of points, we have N points, equally distributed around the unit circle, then the truncated version will be:

$$X[m] = \sum_{n=0}^{N-1} x[n] \exp\left(-j2\pi \frac{mn}{N}\right)$$

where

$$\omega = \left(\frac{2\pi}{N}\right) nm$$

and m = 0, 1, 2, ..., N - 1 and n = 0, 1, 2, ..., N - 1.

We refer to the equation

$$X[m] = \sum_{n=0}^{N-1} x[n] \exp\left(-j2\pi \frac{mn}{N}\right)$$

#### To accompany Chapter 7.1 The

**Discrete Fourier Transform** 

**List of Abbreviations** 

<u>Notation</u>

**Z-Transform** 

#### The Discrete-time Fourier Transform

In Class Example 1

Solution 1

<u>In Class Example 2</u>

Solution 2

Simulink model of the DFT

MATLAB model of the DFT

A useful compact notation

In Class Example 3

Solution 3

MATLAB implementation of DFT

Notes

<u>In Class Example 4</u>

#### A summary of the important features

of sampling and the DFT

Example 4 (continued)

<u>In Class Example 5</u>

Solution

The inverse DFT is defined as

$$x[n] = \frac{1}{N} \sum_{m=0}^{N-1} X[m] \exp\left(j2\pi \frac{mn}{N}\right)$$

for  $n = 0, 1, 2, \dots, N - 1$ .

Note the symmetry of the DFT and the Inverse DFT!

In general, the DFT is complex, and thus it can be expressed as

$$X[m] = \Re \{X[m]\} + \Im \{X[m]\}$$

for m = 0, 1, 2, ..., N - 1.

Since

$$\exp\left(-j2\pi\frac{mn}{N}\right) = \cos\left(2\pi\frac{mn}{N}\right) - j\sin\left(2\pi\frac{mn}{N}\right)$$

the DFT can be expresssed as

$$X[m] = \sum_{n=0}^{N-1} x[n] \exp\left(-j2\pi \frac{mn}{N}\right) = \sum_{n=0}^{N-1} x[n] \cos\left(2\pi \frac{mn}{N}\right) - j \sum_{n=0}^{N-1} x[n] \sin\left(2\pi \frac{mn}{N}\right).$$

For n = 0 this reduces to

$$X[m] = x[0].$$

Then the real part of X[m] is

$$\Re\{X[m]\} = x[0] + \sum_{n=1}^{N-1} x[n] \cos\left(2\pi \frac{mn}{N}\right) \quad \text{for} \quad m = 0, 1, 2, \dots, N-1$$

and the imaginary part is

$$\Im \{X[m]\} = -\sum_{n=1}^{N-1} x[n] \sin \left(2\pi \frac{mn}{N}\right) \quad \text{for} \quad m = 0, 1, 2, \dots, N-1.$$

Note that the summations are from 1 to N-1 because n=0 is covered in the real term, and as x[0] is real, it is zero in the corresponding imaginary term.

# In Class Example 1

A discrete time signal is defined by the sequence

$$x[0] = 1$$
,  $x[1] = 2$ ,  $x[2] = 2$ ,  $x[3] = 1$ , and  $x[n] = 0$  for all other values of  $n$ .

Compute the frequency components X[m].


#### Solution 1

• Compute the N point DFT for  $\Re \{X[m]\}$ .




• Compute the four point DFT for $\Im \{X[m]\}$ .
ullet Add these together to find $X[m]$ .
In Class Example 2
Use the inverse DFT to compute the discrete-time sequence $x[n]$ from $X[m]$ .
Solution 2
ullet Write down the expression $x[n]$ in terms of $X[m]$ .

< •







Try inputting your student number.

#### MATLAB model of the DFT

Karris Example 10.1. To successfully run this script you will need to download the functions <u>dft.m</u> and <u>idft.m</u> and make them available on your MATLABPATH.

# A useful compact notation

The term

$$\exp\left(\frac{-j2\pi}{N}\right)$$

is a rotating vector where the range  $0 <= \theta <= 2\pi$  is divided into 360/N equal segments.

It is convenient to represent this as  $\mathit{W}_{\mathit{N}}$  , that is

$$W_N = \exp\left(\frac{-j2\pi}{N}\right)$$

and consequently,

$$W_N^{-1} = \exp\left(\frac{j2\pi}{N}\right).$$

# In Class Example 3


Compute the complex numbers represented by the rotating vector  $W_8$ 

### Solution 3





Visualize on unit circle



• Complete this table

n	$\theta$	Real	Imaginary	$W_8^n$
0	0	1	0	1

$$X[m] = \sum_{n=0}^{N-1} x[n] W_N^{nm}$$

and 
$$x[n] = \frac{1}{N} \sum_{n=0}^{N-1} X[m] W_N^{-nm}$$



### MATLAB implementation of DFT

Using the W notation, it is very easy to write a function to implement the DFT.

We will demonstrate this in class.

For example, consider dft.m:

Similarly for the inverse DFT idft.m:

#### **Notes**

In the remainder of these notes, the correspondence between x[n] and X[m] will be written

$$x[n] \Leftrightarrow X[m]$$

In Example 2, we found that, although the DT sequence x[n] was real, the discrete frequency (DF) sequence was complex. However, in most applications we are interested in the magnitude and phase of the DF, that is

|X[m]|

and

 $\angle X[m]$ .

# In Class Example 4

Use MATLAB to compute the magnitude of the frequency components of the following DT function:

x[n] 1.0 1.5 2.0 2.3 2.7 3.0 3.4 4.1 4.7 4.2 3.5 3.6 3.2 2.9 2.5 1.8

We will compute this in class and make some comments afterwards.

```
xn = [ 1, 2, 3, 2.5, 1.5, 0.5,...
-0.5, -1.5, -2.5, -0.5,...
0.25, 1.25, 2, 1.5, 1, 0.5];
```

```
stem([0:15],xn),xlabel('n'),ylabel('x[n]'),title('Discrete Time Sequence')
```

```
Xm = dft(xn,16);
```

```
stem([0:15],abs(Xm)),xlabel('m'),ylabel('|X[m]|'),title('Discrete Frequency Sequence')
```

Points to note:

- X[0] = 12 is the DC component of the DT sequence.
- After the |X[8]| = 1.4872 term, the magnitude of the frequency values for the range  $9 <= m \le 15$  are the mirror image of the values for the range 0 <= m <= 7.
- This is not a coincidence, in fact if x[n] is an N-point real discrete time function, only N/2 of the frequency components of |X[m]| are unique.

# A summary of the important features of sampling and the DFT

- ullet N is the number of samples in frequency.
- $f_s$  sampling frequency, samples per second.
- $T_t$  period of a periodic DT function.
- $t_s$  interval between the N samples in time period  $T_t$ .
- $f_f$  period of a periodic DF function.
- $F_s$  interval between the N samples in frequency period  $T_f$ .

The relationships between these quantities are:

$$t_t = \frac{T_t}{N}$$

$$f_s = \frac{1}{t_t}$$

$$t_f = \frac{T_f}{N}$$


$$t_t = \frac{1}{T_f}$$

$$f_f = \frac{1}{T_t}$$

We will add these quantities to the results of Example 4 in class.

## Example 4 (continued)





To reproduce this plot use repeat.m.

# In Class Example 5

The period of a periodic DT function is 0.125 ms and it is sampled at 1024 equally spaced points. It is assumed that with this number of samples, the sampling theorem is satisfied and thus there will be no aliasing.

- 1. Compute the interval  $t_t$  between samples for the periodic signal
- 2. Compute the period  $T_f$  of the frequency spectrum in  $\ensuremath{\mathrm{kHz}}$
- 3. Compute the interval  $t_f$  between frequency components in kHz
- 4. Compute the sampling frequency  $f_s$ .
- 5. Compute the Nyquist frequency  $f_n$ .


## Solution

To be done in class.

• (	Compute :	the	interval	$t_t$	between	samples	for	the	periodic	signal	
-----	-----------	-----	----------	-------	---------	---------	-----	-----	----------	--------	--



- Compute the period of the frequency spectrum  $T_f$  in kHz



Print to PD

$ullet$ Compute the interval $t_f$ between frequency components in kHz	•
	(
	G
$ullet$ Compute the sampling frequency $f_s$ .	
$ullet$ Compute the Nyquist frequency $f_n$ .	

By Dr Chris P. Jobling

© Copyright Swansea University (2019-2022).

This page was created by <u>Dr Chris P. Jobling</u> for <u>Swansea University</u>.