

Blank bottom check: tape-measure sheet

Shaper Assistant · one blank per sheet · gaps to the nearest 1/16"

Maker _____ Blank name, as printed on it _____ Length, tip to tip _____ Date _____

How to measure

1. **Pick one straight reference and keep it for the whole blank.** Bottom up on stands with a tight string or a straightedge along the stringer, or bottom down on a flat floor or bench, wedged so it cannot rock.
2. **Hook the tape on the tail tip** and mark the stringer every 6" all the way to the nose.
3. **At each mark, measure the gap** between the reference and the foam of the bottom, square to the reference. Write it beside that mark.
4. **The nose tip gets its own row:** its distance from the tail tip and its gap.
5. **Optional:** the blank's thickness at each mark, with calipers.

Reference used: ☐ string or straightedge, bottom up ☐ flat floor or bench, bottom down

Tape laid: ☐ along the foam ☐ held straight

From the tail tip	Gap to the bottom	Thickness optional	From the tail tip	Gap to the bottom	Thickness optional
0" (tail tip)			72"		
6"			78"		
12"			84"		
18"			90"		
24"			96"		
30"			102"		
36"			108"		
42"			114"		
48"			120"		
54"			126"		
60"			132"		
66"			Nose tip, at _____		

It does not matter if the blank sits a little tilted, or which of the two references you use: the check allows for that. What matters is one reference for the whole blank and a gap at every mark. Stop at the last mark your blank reaches.

Phase 14, decision D-08. Send a photo of the filled-in sheet, or the numbers, to the Shaper session; they are checked against the app's curve for that blank between its printed stations.