

ELEC2100: Signals and Systems

Lecture 5

Impulse Response (Deduction)

(Ref: Chapter 2 O&W)




- I) Impulse Response for DT LTI System
- II) The Convolution Sum and Example DT Impulse Responses
- III) Impulse Response and the Convolution Integral for CT LTI System
- IV) Example CT Impulse Responses

I. Impulse Response for DT LTI System

- In this lecture, we will introduce the concept of impulse response and show how it fully characterizes any LTI system
- Let's start with the Discrete-Time (DT) case. Given an input $x[n]$, how can we determine the output $y[n]$?

Given an input

$x[n]$




What is the output???

$y[n]???$

DT Impulse Response


- Let $h[n]$ be the output of a DT LTI system when the input is the unit impulse $\delta[n]$. We call $h[n]$ the impulse response.



- If we know $h[n]$, we can determine the output of this LTI system for any input.
- Remember, we have shown that *any DT input signal can be viewed as a **superposition** of **shifted** unit impulse signals.*

For example, we can describe the signals to the right as:



$$x_1[n] = 1.5\delta[n+2] + \delta[n-1] - 0.5\delta[n-3]$$




DT Signal as Weighted Sum of Shifted Impulses

Mathematically, we can express any $x[n]$ as


$$x[n] = \sum_{k=-\infty}^{\infty} \underbrace{x[k]}_{\text{weight/magnitude of impulse}} \underbrace{\delta[n-k]}_{\text{impulse at } n=k} \quad \text{Eq. (2.2)}$$



Weighted impulse
at $n = -1$



Weighted impulse
at $n = 0$



Weighted impulse
at $n = 1$

and so on

Output of an LTI System

- If system is **linear**, output must be the same weighted sum of the responses to the individual shifted impulses. Let $h_k[n]$ be the system's response to a $\delta[n - k]$. Then

$$x[n] = \sum_{k=-\infty}^{\infty} x[k] \delta[n - k] \rightarrow \text{Linear System} \rightarrow y[n] = \sum_{k=-\infty}^{\infty} x[k] h_k[n] \quad \text{Eq. (2.3)}$$

Input is a weighted sum of $\delta[n - k]$ Output is a weighted sum of responses to $\delta[n - k]$

- If system is **time-invariant**, $h_k[n]$ must be $h[n - k]$. Hence:

$$x[n] = \sum_{k=-\infty}^{\infty} x[k] \delta[n - k] \rightarrow \text{Linear Time-Invariant (LTI) System} \rightarrow y[n] = \sum_{k=-\infty}^{\infty} x[k] h[n - k] \quad \text{Eq. (2.6)}$$

$h_k[n] = h[n - k]$
↓

- Eq. (2.6) is called the **convolution sum**.
- It **means** that $y[n]$, the output of an LTI system at any time n , can be founded by summing up the responses arising from the inputs at all different times k and the response at time n arising from the input at time k is $x[k]h[n - k]$.

Example – Investment in Couponed Bond

Example: When the government or a company wants to borrow money from the public, it issues bonds. A couponed bond is one that offers intermediate payouts before maturation.

- Assume there is a couponed US government bond that provides the following payout schedule:

10% rebate immediately

8% after one year

8% after two years

100% at the end of the third year

Thus, you invest \$1, you get \$1.26
back in total over 3 years.

We can think of this bond as an LTI
system with the impulse response of:

$$\Rightarrow h[0]=0.1$$


$$\Rightarrow h[1]=0.08$$

$$\Rightarrow h[2]=0.08$$

$$\Rightarrow h[3]=1$$

$$h[n] = 0.1\delta[n] + 0.08\delta[n-1] + 0.08\delta[n-2] + \delta[n-3]$$

Corresponding
Impulse Response



- To help pay for your HKUST education, your parents buy for you \$10 of this bond in 2015, \$20 of this bond in 2016, \$40 of this bond in 2017. How much of a payout will you receive in 2019?

$y[2019]=?$

$$y[2019] = x[2015] \times h[4] \quad \leftarrow 2019-2015=4; h[4]=0$$

$$+ x[2016] \times h[3] \quad \leftarrow 2019-2016=3; h[3]=1$$

$$+ x[2017] \times h[2] \quad \leftarrow 2019-2017=2; h[2]=0.08$$

$$+ x[2018] \times h[1] \quad \leftarrow 2019-2018=1; h[1]=0.08$$

$$+ x[2019] \times h[0] \quad \leftarrow 2019-2019=0; h[0]=0.1$$

$$= \$10 \times 0 + \$20 \times 100\% + \$40 \times 8\% + \$0 \times 8\% + \$0 \times 10\% = \$\mathbf{23.2}$$

The output in year 2019 is simply the sum of the outputs arising from inputs in all different years!

This is what the convolution sum mean!

$$y[n] = \sum_{k=-\infty}^{\infty} x[k] h[n - k]$$

ELEC2100: Signals and Systems

Lecture 5

Chapter 2 – Impulse Response

- I) Impulse Response for DT LTI System
- II) The Convolution Sum and Example DT Impulse Responses
- III) Impulse Response and the Convolution Integral for CT LTI System
- IV) Example CT Impulse Responses


II. The Convolution Sum and Example Impulse Responses

- We say that the output of an LTI system is the **convolution** of the input with the system's impulse response.
- We use the “*” symbol to denote convolution:

$$y[n] = x[n] * h[n] = \sum_{k=-\infty}^{\infty} x[k] h[n - k]$$

convolution

Convolution sum

The equation is enclosed in a red rectangular box. A blue arrow points from the word 'convolution' to the asterisk symbol in the first part of the equation. A blue horizontal line is drawn under the summation term, with a blue arrow pointing from the text 'Convolution sum' to it.

Convolution = LTI

- **Conversely**, if the output of a system is given by convolving the input with any function $h[n]$, then the system is LTI! It is because the convolution operation is LTI:

Convolution is Linear:

Convolving a weighted sum with h :

$$\begin{aligned}
 & \underline{(ax_1[n] + bx_2[n]) * h[n]} = \sum_{k=-\infty}^{\infty} \underline{(ax_1[k] + bx_2[k])} h[n-k] \\
 & \qquad \qquad \qquad \qquad \qquad \qquad \qquad \qquad \qquad \qquad \qquad \qquad \qquad \text{put weighted sum into convolution sum} \\
 & = a \sum_{k=-\infty}^{\infty} x_1[k] h[n-k] + b \sum_{k=-\infty}^{\infty} x_2[k] h[n-k] = ax_1[n] * h[n] + bx_2[n] * h[n] \\
 & \qquad \qquad \qquad \text{break into two weighted sums} \qquad \qquad \qquad \text{= weighted sum of the individual convolutions}
 \end{aligned}$$

Convolution is TI:

Convolving shifted x with h

$$\begin{aligned}
 x[n-m] * h[n] &= \sum_{k=-\infty}^{\infty} x[k-m] h[n-k] \quad \text{Replace } x[k] \text{ by } x[k-m] \\
 \text{let } g[n] &= x[n-m] \quad \text{then } g[k] = x[k-m] \quad \text{Let } k' = k-m \\
 &= \sum_{k'=-\infty}^{\infty} x[k'] h[(n-m)-k'] = y[n-m] \\
 & \qquad \qquad \qquad \text{Summing over } k \text{ from } -\infty \text{ to } \infty \text{ means summing over } k' \text{ from } -\infty \text{ to } \infty \text{ as well, and } k' \text{ is just a dummy variable for summation.} \\
 & \qquad \qquad \qquad \text{This means we are evaluating the output at time } n-m
 \end{aligned}$$

- So system being LTI means convolution and convolution means LTI!

Example Impulse Response 1: $h[n] = \delta[n]$ the Identity System

- Consider convolving a DT signal $x[n]$ with $h[n] = \delta[n]$:

$$x[n] * h[n] = x[n] * \delta[n] = \sum_{k=-\infty}^{\infty} x[k] \delta[n-k] = x[n]$$

Only one non-zero term in the sum because:

$$\delta[n-k] = \begin{cases} 0 & k \neq n \\ 1 & k = n \end{cases}$$

This means that $\delta[n]$ is the *identity* function under convolution. Convolving any signal $x[n]$ with $\delta[n]$ results in $x[n]$ unchanged.

- So an LTI system with $h[n] = \delta[n]$ is a *do-nothing* system, or *identity system*.
- $h[n] = A\delta[n]$ is an *amplifier* that multiplies the input by A

Example Impulse Response 2: $h[n] = \delta[n - m]$ is a Delay System

- What about an LTI system with $h[n] = \delta[n - m]$, a shifted impulse?

$$x[n] * h[n] = x[n] * \delta[n - m] = \sum_{k=-\infty}^{\infty} x[k] \underbrace{\delta[(n - m) - k]}_{\substack{\text{Non-zero and equals 1 only when} \\ \text{argument is 0, i.e., } k = n - m}} = x[n - m]$$

$h[n - k] = \delta[(n - m) - k]$ since $h[n] = \delta[n - m]$


- Convolving any $x[n]$ with $\delta[n - m]$ produces $x[n - m]$.

$h[n] = \delta[n - m]$ represents a delay system that delays the input by m .

Other Example Impulse Responses

For each system below, express output $y[n]$ in terms of input $x[n]$ and explain what the system does.


3. $h[n] = \delta[n] + 0.3\delta[n - 4]$



$$y[n] = x[n] + 0.3x[n - 4]$$

An echo system


4. $h[n] = u[n]$



$$y[n] = \sum_{k=-\infty}^n x[k]$$

An first sum system


5. $h[n] = \frac{1}{3}(u[n] - u[n - 3])$



$$y[n] = \frac{1}{3}x[n] + \frac{1}{3}x[n - 1] + \frac{1}{3}x[n - 2]$$

A window averager/smoothen

6. $h[n] = \delta[n] - \delta[n - 1]$



$$y[n] = x[n] - x[n - 1]$$

A first difference system


Ripple is convolution

Pretty Lena

A Pretty Picture of Lena



Lena after a smoother



You will learn in the future that we need to smooth a picture first before we down-sample it – i.e., when creating a thumbnail

Lena after a first difference system (differentiator)



Allows us to detect boundaries/outlines of objects in an image

ELEC2100: Signals and Systems


Lecture 5

Chapter 2 – Impulse Response

- I) Impulse Response for DT LTI System
- II) The Convolution Sum and Example DT Impulse Responses
- III) Impulse Response and the Convolution Integral for CT LTI System
- IV) Example CT Impulse Responses

III. Impulse response and Convolution Integral for CT System

- Now, for a CT system, let $h(t)$ be the output when the input is the CT impulse $\delta(t)$
- $h(t)$ is the impulse response



- Next, we will show that any signal $x(t)$ can be viewed as a superposition of shifted impulse signals in the form of an integral.
- We do so by first showing that any CT signal can be *approximated* by a weighted sum of shifted narrow pulses. In the limit these pulses become infinitesimally narrow, the approximation becomes exact and the weighted sum becomes an integral.


Representation of CT Signal as a sum of narrow pulses

- In Chapter 1, we argued that $\delta(t)$ can be approximated by $\delta_\Delta(t)$, a narrow pulse with width Δ and height $1/\Delta$
- The signal $\delta_\Delta(t)\Delta$ would be a narrow pulse with width Δ and height 1.
- We can approximate a CT signal $x(t)$ using shifted $\delta_\Delta(t)\Delta$ signals by what is called a staircase approximation:


Staircase approximation: Weighted sum of shifted narrow pulses:

Each term in the sum is a narrow pulse at $k\Delta$ with height given by $x(k\Delta)$


Approximate impulse
Introduced in Chapter 1



Multiply by Δ gives a
narrow pulse with height 1




$$x(t) \approx \hat{x}(t) = \sum_{k=-\infty}^{\infty} x(k\Delta) \delta_\Delta(t - k\Delta) \Delta$$







Representation of CT Signal as a sum of narrow pulses

- $\delta_{\Delta}(t - k\Delta)\Delta$ is a narrow pulse shifted to $k\Delta$.
- We scale the height of each narrow pulse by the value of $x(k\Delta)$ and add all the weighted narrow pulses together to form the staircase approximation.



A shifted narrow pulses with unit height

$$\delta_{\Delta}(t - k\Delta)\Delta$$



Next, we take limit of Δ going to zero. Then the approximation becomes exact and the summation becomes an integral:

$$\begin{aligned}
 x(t) &= \lim_{\Delta \rightarrow 0} \hat{x}(t) = \lim_{\Delta \rightarrow 0} \sum_{k=-\infty}^{\infty} x(k\Delta) \delta_{\Delta}(t - k\Delta) \Delta \\
 &= \int_{-\infty}^{\infty} x(\tau) \delta(t - \tau) d\tau
 \end{aligned}
 \tag{Eq. (2.27)}$$

$$\lim_{\Delta \rightarrow 0} \sum_{k=K_1}^{K_2} g(k\Delta) \Delta = \int_{L_1}^{L_2} g(\tau) d\tau$$

- Observe that Eq. (2.27) looks very similar to Eq. (2.2), $x[n] = \sum_{k=-\infty}^{\infty} x[k] \delta[n - k]$. Here, it means that:

Any signal $x(t)$ can be viewed as weighted sum (by integrating) of infinitely many shifted impulses $\delta(t - \tau)$ with infinitesimally small weights of $x(\tau) d\tau$

- As in the DT case, we can also interpret Eq. (2.27) as a convolution of $x(t)$ with $\delta(t)$, with $\delta(t)$ being the identity function under convolution. Any $x(t)$ convolving with $\delta(t)$ produces $x(t)$ unchanged.

Response of CT LTI System

$$\lim_{\Delta \rightarrow 0} \delta_{\Delta}(t) = \delta(t)$$

- Let $h_{\Delta}(t)$ be the response of a CT system to the input $\delta_{\Delta}(t)$. In limit, $\lim_{\Delta \rightarrow 0} h_{\Delta}(t) = h(t)$
- For a CT LTI system, if the input is a superposition of shifted $\delta_{\Delta}(t)$, the output is the same superposition of shifted $h_{\Delta}(t)$:

$$\hat{x}(t) = \sum_{k=-\infty}^{\infty} x(k\Delta) \delta_{\Delta}(t - k\Delta) \Delta \quad \longrightarrow \quad \text{CT LTI system} \quad \longrightarrow \quad \hat{y}(t) = \sum_{k=-\infty}^{\infty} x(k\Delta) h_{\Delta}(t - k\Delta) \Delta$$

- Now, we take limit $\Delta \rightarrow 0$, the input becomes $x(t)$ and the output becomes:

$$x(t) = \lim_{\Delta \rightarrow 0} \sum_{k=-\infty}^{\infty} x(k\Delta) \delta_{\Delta}(t - k\Delta) \Delta \quad \longrightarrow \quad \text{CT LTI system} \quad \longrightarrow \quad \boxed{\begin{aligned} y(t) &= \lim_{\Delta \rightarrow 0} \sum_{k=-\infty}^{\infty} x(k\Delta) h_{\Delta}(t - k\Delta) \Delta \\ &= \int_{-\infty}^{\infty} x(\tau) h(t - \tau) d\tau \end{aligned}} \quad \text{Eq. 2.33}$$

Convolution of input with impulse response

The Convolution Integral

- In summary, for a CT LTI system, we can determine the output from the input and the impulse response by:

$$y(t) = \int_{-\infty}^{\infty} x(\tau)h(t - \tau)d\tau$$

- This is called the *convolution integral* and we also use the “*” symbol to denote it:

$$y(t) = x(t) * h(t)$$

- Just like the DT case, for an LTI system, the output is the convolution of the input and the system’s impulse response!

ELEC2100: Signals and Systems

Lecture 5

Chapter 2 – Impulse Response

- I) Impulse Response for DT LTI System
- II) The Convolution Sum and Example DT Impulse Responses
- III) Impulse Response and the Convolution Integral for CT LTI System
- IV) Example CT Impulse Responses

IV. Example CT Impulse Responses

Example 1. What is a CT LTI system with $h(t) = \delta(t)$?

Let $x(t)$ be the input, then the output is:

$$y(t) = x(t) * h(t) = x(t) * \delta(t) = \int_{\tau=-\infty}^{\infty} x(\tau) \delta(t - \tau) d\tau = x(t)$$

from Eq. (2.27), $x(t)$ as limit of staircase approximation


Again, convolving any signal $x(t)$ with $\delta(t)$ yields $x(t)$ unchanged

- LTI system with impulse response $h(t) = \delta(t)$ is a do-nothing system, or an identity system.

Example 2: $h(t) = \delta(t - t_0)$

- What about an LTI system with $h(t) = \delta(t - t_0)$?

As function of τ ,
 $x(\tau)\delta((t - t_0) - \tau) = x(t - t_0)\delta((t - t_0) - \tau)$



$$y(t) = x(t) * \delta(t - t_0) = \int_{\tau=-\infty}^{\infty} x(\tau) \delta((t - t_0) - \tau) d\tau$$

$h(t - \tau) = \delta((t - t_0) - \tau)$

Sampling property of impulse!

$$= \int_{\tau=-\infty}^{\infty} x(t - t_0) \delta((t - t_0) - \tau) d\tau = x(t - t_0)$$

Also directly from the
sifting property of impulse,
Lecture 03-3, Property 6


Convolution with a shifted impulse yields a shifted version of the input.

- $h(t) = \delta(t - t_0)$ represents a time-delay system. The time shift is $-t_0$. delay is t_0

Other Example CT Impulse Responses


3. Echo/Multipath System: $h(t) = \delta(t) + 0.3\delta(t - 4)$ Impulse plus a delayed and attenuated impulse

$$h(t) = \delta(t) + 0.3\delta(t - 4)$$



$$y(t) = x(t) + 0.3x(t - 4)$$

4. Integrator: $h(t) = u(t)$




Since $u(t - \tau) = 0$ when $\tau > t$

$$y(t) = \int_{\tau=-\infty}^{\infty} x(\tau) \overset{h(t-\tau)=u(t-\tau)}{u(t-\tau)} d\tau = \int_{-\infty}^t x(\tau) d\tau = \int x(t)$$

5. Windowed Integrator/Smoother


5a. $h(t) = (u(t) - u(t - 3))$



$$h(t - \tau) = \begin{cases} 1 & 0 < t - \tau < 3 \Rightarrow t - 3 < \tau < t \\ 0 & \text{otherwise} \end{cases}$$

$$y(t) = \int_{\tau=-\infty}^{\infty} x(\tau)h(t - \tau)d\tau = \int_{t-3}^t x(\tau)d\tau$$

5b. $h(t) = (u(t + 3) - u(t - 1))1/4$



$$h(t - \tau) = \begin{cases} 1/4 & -3 < t - \tau < 1 \Rightarrow t - 1 < \tau < t + 3 \\ 0 & \text{otherwise} \end{cases}$$

$$y(t) = \frac{1}{4} \int_{t-1}^{t+3} x(\tau)d\tau$$

Non-causal because response is non-zero before $t = 0$

This is a non-causal system since integrating to $t + 3$

CT Differentiator

- Recall that differentiation is LTI. What is the $h(t)$ for a differentiator?
- If the input is $\delta(t)$, the output of a differentiator must be its derivative, $\frac{d\delta(t)}{dt}$.
- The derivative of $\delta(t)$ is called the *unit doublet*.
- The unit doublet is discussed in Section 2.5.3 of the text. We will not study its mathematical properties. The key is to recognize that differentiation is LTI.

Self-Test – Lecture 5

1. From memory and based on understanding, write down the convolution sum and convolution integral
2. If $y(t) = \int_{t-2}^{t+1} x(\tau) d\tau$, where $y(t)$ is the output to any input $x(t)$.
Is the system LTI, and what is the impulse response?