In [1]:

```
import pandas as pd
import numpy as np
from numpy.linalg import inv
import math as m
from math import sqrt
import sympy as sp
from sympy import collect, simplify, expand, fraction, latex
from IPython.display import display, Markdown, Math
import control as co
import seaborn as sns
import matplotlib.pyplot as plt
from matplotlib import colors as mcolors
sp.init_printing(use_latex='mathjax')
plt.rcParams['figure.figsize'] = [20, 10]
```

In [2]:

```
class numden_coeff:
    def __init__(self, expr, symb):
        self.num, self.denum = fraction(expr)
        self.symb = symb
        self.common_factor = None
        self.lst_denum_coeff = self.build_lst(self.denum)
        self.lst_num_coeff = self.build_lst(self.num)

    def build_lst(self, poly):
        order = sp.Poly(poly, self.symb).degree()
        lst = [expand(poly).coeff(self.symb**i) for i in range(order, 0, -1)]
        lst.append(poly.subs(self.symb, 0))
        if self.common_factor == None:
            self.common_factor = lst[0]

        lst = [simplify(lst[i]/self.common_factor) for i in range(order + 1)]
        return lst

    def disp(self):
        display(Markdown("Numerator coefficients (\\beta)"), self.lst_num_coeff)
        display(Markdown("Denominator coefficients (\\alpha)"), self.lst_denum_coeff)
```

In [3]:

```
def theta_hat_ploter(df, theta0, title, line_width=1.2):
    lst_color = ['b', 'y', 'g', 'r']
    lst_labels = df.columns
    graph = sns.lineplot(data=df, dashes=False)

    for i in range(len(theta0)):
        graph.axhline(y=theta0[i], color=lst_color[i], linestyle='--', linewidth=line_width, label=lst_labels[i])

    plt.title(title, fontsize=20)
    plt.ylabel("Magnitude of "theta_hat"", fontsize=18)
    plt.xlabel("Time Steps "t"", fontsize=18)
    plt.legend(bbox_to_anchor=(1.01, 1),
               loc=2,
               borderaxespad=0,
               labels=lst_labels,
               fontsize='xx-large')
    plt.show()
```

Problem 1

Part 1

In [38]:

```
c, d= sp.symbols('c d')
s, zeta, omega = sp.symbols('s zeta omega')
r1, s0, s1, a0, t0 = sp.symbols('r_1 s_0 s_1 a_0 t_0')

a = 1
b = 1
G1 = b/(s + a)
G2 = c/(s+d)
G = collect(expand(G1*G2), s)
B, A = fraction(G)
B_minus = B
```

$$G_1(s)G_2(s) = G(s) = \frac{c}{d + s^2 + s(d+1)}$$

Therefore

$B = c$

$A = d + s^2 + s(d+1)$

Since $Deg(B)$ is clearly 0, $B^+ = 1$ and $B^- = c$

In [39]:

```
Am = s**2 + 2*s + 1
Bm = 1
Gm = Bm/Am
Bm_prime = Bm/B_minus
```

A_m is given to be $s^2 + 2s + 1$. Letting the desired model take the form of

$$G_m = \frac{\omega^2}{s^2 + 2\zeta\omega s + \omega^2}$$

ω and ζ are equivalent to 1. Since $\omega = 1$, B_m must be equal to 1 which yeilds

$$G_m = \frac{1}{s^2 + 2s + 1}$$

Additionally, $B_m' = \frac{B_m}{B^-} = \frac{1}{c}$

In order for minimum phase to be achived, the following conditions on the degrees of the polynomials making up the system must be met and will ultimatley guide the desing.

$$Deg(A_0) = Deg(A) - Deg(B^+) - 1 = 2 - 0 - 1 = 1$$

$$Deg(A_c) = 2(Deg(A)) - 1 = 2 * 2 - 1 = 3$$

$$Deg(R) = Deg(S) = Deg(A_c) - Deg(A) = 3 - 2 = 1$$

In [40]:

```
A0 = s + a0
R_prime = s + r1
R = R_prime
S = s0*s + s1
T_ = A0*Bm_prime
```

Since $Deg(B^+) = 0$ then $Deg(R') = 1$ and therfore

$R = B^+R' = R' = r_1 + s$

Additionally, considering the polynomial degrees derived above, we know that

$A_0 = a_0 + s$

$S = ss_0 + s_1$

Lastly,

$T = A_0 B_m' = \frac{a_0 + s}{c}$

In [41]:

```
# derivation of Diophantine equation
LHS = collect(expand(A*R_prime + B_minus*S), s)
RHS = collect(expand(A0*Am), s)
equ = sp.Eq(LHS,RHS)

# Derivation of control parameters
r_1 = sp.solve(sp.Eq(LHS.coeff(s**2),RHS.coeff(s**2)), r1)[0]
s_0 = sp.solve(sp.Eq(LHS.coeff(s**1),RHS.coeff(s**1)), s0)[0]
s_1 = sp.solve(sp.Eq(LHS.subs(s,0),RHS.subs(s,0)), s1)[0]
```

The Diophantine equation in terms of control parameters is given by

$AR' + B^-S = A_0 A_m$

$\Rightarrow cs_1 + dr_1 + s^3 + s^2(d + r_1 + 1) + s(cs_0 + dr_1 + d + r_1) = a_0 + s^3 + s^2(a_0 + 2) + s(2a_0 + 1)$

Grouping the coefficients of the same ordered s terms and solving for the control parameters yeilds

$r_1 = a_0 - d + 1$

$s_0 = \frac{2a_0 - dr_1 - d - r_1 + 1}{c}$

$s_1 = \frac{a_0 - dr_1}{c}$

Part 2

ODE of Plant

In [42]:

```
y_t, u_t, p = sp.symbols('y(t) u(t) p')

ode_RHS = ((-A.coeff(s**1)*p - A.subs(s,0))*y_t) + (B.coeff(s**2)*p**2 + B.coeff(s**1)*p**1 + B.subs(s,0))*u_t
ode_RHS
```

Out[42]: $cu(t) + y(t)(-d + p(-d-1))$

The ODE of 2^{nd} order describing the process is given by

$p^2 y(t) = -(d+1)py(t) - dy(t) + cu(t)$

where p is the time shifting operator. The reliance of the RHS of the equation on derivatives can be changed to integrals by filtering the input $u(t)$ and output $y(t)$ of the plant by a filter whose denominator polynomial is of a greater order than the highest derivative term. The above equation becomes

$p^2 y_f(t) = -(d+1)py_f(t) - dy_f(t) + cu_f(t)$

$\Rightarrow p^2 H_f(p)y(t) = -(d+1)pH_f(p)y(t) - dH_f(p)y(t) + cH_f(p)u(t)$

$\Rightarrow \frac{p^2}{\tau_m}y(t) = -(d+1)\frac{p}{\tau_m}y(t) - d\frac{1}{\tau_m}y(t) + c\frac{1}{\tau_m}u(t)$

For simplicity, let $(d+1) = x$. The ODE then becomes

$\Rightarrow \frac{p^2}{\tau_m}y(t) = -x\frac{p}{\tau_m}y(t) - d\frac{1}{\tau_m}y(t) + c\frac{1}{\tau_m}u(t)$

This equation can be further simplified as

$\Rightarrow y_{f2}(t) = -xy_{f1}(t) - dy_{f0}(t) + cu_{f0}(t)$

This equation will be used for the measurment model i.e.

$$y_{f2}(t) = \phi^T\theta = [-y_{f1}(t) \;\; -y_{f0}(t) \;\; u_{f0}(t)][x \;\; d \;\; c]^T$$

Bilinear Transformation of Filtered ODE

In [43]:

```
# Filter
H_f = (1/Am)
H_f_p = (H_f).subs(s,p)
```

The filter $H_f(p)$ is given to be

$$H_f(p) = \frac{1}{\tau_m} = \frac{1}{p^2 + 2p + 1}$$

This filter, and the ODE above are however, in terms of p and are therfore, in continuous time domain. To convert the filter to discrete time (q), a bilinear transformation will be performed. i.e.

$$p \rightarrow \frac{2(1 - \frac{1}{q})}{T(1 + \frac{1}{q})}$$

The ODE can now be represented in the discret time domain by

$$y_f(kT) = H_f(q^{-1})y(kT) = \frac{p^2}{\tau_m(p)}\bigg|_{p=\frac{2(1-q^{-1})}{T(1+q^{-1})}} y(kT), \quad u_f(kT) = \frac{p^2}{\tau_m(p)}\bigg|_{p=\frac{2(1-q^{-1})}{T(1+q^{-1})}} u(kT)$$

In [44]:

```
T, q = sp.symbols('T q')

bilinear_T = (2/T)*((1 - q**(-1))/(1 + q**(-1))) # what will be substituted for s (kept actual equations in te[illegible]

H_fy2 = collect(simplify(expand((s**2)*H_f).subs(s,bilinear_T))), q)
H_fy1 = collect(simplify(expand((s*H_f).subs(s,bilinear_T))), q)
H_fy0 = collect(simplify(expand(H_f.subs(s,bilinear_T))), q)
H_fu0 = collect(simplify(expand(H_f.subs(s,bilinear_T))), q)

# Creation of numerator and denominator coefficient extractor objects (numden_coeff() class defined at the top[illegible]
obj_H_fy2 = numden_coeff(H_fy2, q)
obj_H_fy1 = numden_coeff(H_fy1, q)
obj_H_fy0 = numden_coeff(H_fy0, q)
obj_H_fu0 = numden_coeff(H_fu0, q)

a0_fy2 = obj_H_fy2.lst_denum_coeff
b0_fy2 = obj_H_fy2.lst_num_coeff

a0_fy1 = obj_H_fy1.lst_denum_coeff
b0_fy1 = obj_H_fy1.lst_num_coeff

a0_fy0 = obj_H_fy0.lst_denum_coeff
b0_fy0 = obj_H_fy0.lst_num_coeff

a0_fu0 = obj_H_fu0.lst_denum_coeff
b0_fu0 = obj_H_fu0.lst_num_coeff
```

For $y_{f1} = H_f p y(kT)$, the coefficients of the denominator α_{fy1} are

$$\alpha_{fy1} = \left[1, \; \frac{2(T-2)}{T+2}, \; \frac{T^2 - 4T + 4}{T^2 + 4T + 4}\right]$$

(ordered by powers of q going from q^0 to q^{-2}) and the coefficients of the numerator β_{fy1} are

$$\beta_{fy1} = \left[\frac{2T}{T^2 + 4T + 4}, \; 0, \; -\frac{2T}{T^2 + 4T + 4}\right]$$

which are also ordered by powers of q going from q^0 to q^{-2}. Similarly, the coefficients for the denominator (α) and numerator (β) of y_{f0} and u_{f0} are

$$\alpha_{fy0} = \left[1, \; \frac{2(T-2)}{T+2}, \; \frac{T^2 - 4T + 4}{T^2 + 4T + 4}\right]$$

$$\beta_{fy0} = \left[\frac{T^2}{T^2 + 4T + 4}, \; \frac{2T^2}{T^2 + 4T + 4}, \; \frac{T^2}{T^2 + 4T + 4}\right]$$

$$\alpha_{fu0} = \left[1, \; \frac{2(T-2)}{T+2}, \; \frac{T^2 - 4T + 4}{T^2 + 4T + 4}\right]$$

$$\beta_{fu0} = \left[\frac{T^2}{T^2 + 4T + 4}, \; \frac{2T^2}{T^2 + 4T + 4}, \; \frac{T^2}{T^2 + 4T + 4}\right]$$

Note that $\alpha_{fy0} = \alpha_{fu0}$ and $\beta_{fy0} = \beta_{fu0}$

$$\alpha_{fy2} = \left[1, \; \frac{2(T-2)}{T+2}, \; \frac{T^2 - 4T + 4}{T^2 + 4T + 4}\right]$$

$$\beta_{fy2} = \left[\frac{4}{T^2 + 4T + 4}, \; -\frac{8}{T^2 + 4T + 4}, \; \frac{4}{T^2 + 4T + 4}\right]$$

In [45]:

```
y_k, y_k_1, y_k_2 = sp.symbols('y(k) y(k-1) y(k-2)')
u_k, u_k_1, u_k_2 = sp.symbols('u(k) u(k-1) u(k-2)')
y1_k, y1_k_1, y1_k_2 = sp.symbols('y_{1}(k) y_{1}(k-1) y_{1}(k-2)')
y0_k, y0_k_1, y0_k_2 = sp.symbols('y_{0}(k) y_{0}(k-1) y_{0}(k-2)')
u0_k, u0_k_1, u0_k_2 = sp.symbols('u_{0}(k) u_{0}(k-1) u_{0}(k-2)')

# Derivation of filtered signal equations
[illegible]
```

The equations for the filtered output and input y_{f1}, y_{f0} and u_{f0} equations are

$$y_{f1}(kT) = \frac{2Ty(k)}{T^2 + 4T + 4} - \frac{2Ty(k-2)}{T^2 + 4T + 4} - \frac{2y_1(k-1)(T-2)}{T+2} - \frac{y_1(k-2)(T^2 - 4T + 4)}{T^2 + 4T + 4}$$

$$y_{f0}(kT) = \frac{T^2 y(k)}{T^2 + 4T + 4} + \frac{2T^2 y(k-1)}{T^2 + 4T + 4} + \frac{T^2 y(k-2)}{T^2 + 4T + 4} - \frac{2y_0(k-1)(T-2)}{T+2} - \frac{y_0(k-2)(T^2 - 4T + 4)}{T^2 + 4T + 4}$$

$$u_{f0}(kT) = \frac{T^2 u(k)}{T^2 + 4T + 4} + \frac{2T^2 u(k-1)}{T^2 + 4T + 4} + \frac{T^2 u(k-2)}{T^2 + 4T + 4} - \frac{2u_0(k-1)(T-2)}{T+2} - \frac{u_0(k-2)(T^2 - 4T + 4)}{T^2 + 4T + 4}$$

In [46]:

```
y2_k, y2_k_1, y2_k_2 = sp.symbols('y_{2}(k) y_{2}(k-1) y_{2}(k-2)')

[illegible]

equ = sp.Eq(y2_k, y2_eq)
y = sp.solve(equ, y_k)[0]
```

An equation for $y(kT)$ can be obtained by isolating the $y(kT)$ term in the $y_{f2}(kT)$ equation. The $y_{f2}(kT)$ equation is

$$y_{f2}(kT) = \frac{4y(k)}{T^2 + 4T + 4} - \frac{8y(k-1)}{T^2 + 4T + 4} + \frac{4y(k-2)}{T^2 + 4T + 4} - \frac{2y_2(k-1)(T-2)}{T+2} - \frac{y_2(k-2)(T^2 - 4T + 4)}{T^2 + 4T + 4}$$

Isolating $y(kT)$ gives

$$y(kT) = \frac{T^2 y_{f2}(k)}{4} + \frac{T^2 y_{f2}(k-1)}{2} + \frac{T^2 y_{f2}(k-2)}{4} + Ty_{f2}(k) - Ty_{f2}(k-2) + 2y(k-1) - y(k-2) + y_{f2}(k) - 2y_{f2}(k-1) + y_{f2}(k-2)$$

The above equation depends only on present and past values of $y_{f2}(kT)$, in which the present value can be obtained via the measurment model $(\phi^T\theta)$ and past values of $y(kT)$

Bilinear Transformation of Control Signal u(t)

In [47]:

```
T_R = simplify(T_/R)
S_R = simplify(S/R)

T_subd = T_
R_subd = R.subs(r1, r_1)
S_subd = collect(simplify(S.subs([(s0, s_0), (s1, s_1), (r1, r_1)])), s)

T_R_subd = T_subd/R_subd
S_R_subd = simplify(S_subd/R_subd)

[illegible]
```

The control signal of the system is given by

$u(t) = \frac{T}{R}u_c(t) - \frac{S}{R}y(t)$

$u(t) = \frac{a_0 + s}{c(r_1 + s)}u_c(t) - \frac{ss_0 + s_1}{r_1 + s}y(t)$

$u(t) = \frac{a_0 + s}{c(a_0 - d + s + 1)}u_c(t) - \frac{[illegible]}{c(a_0 - d + s + 1)}y(t)$

This however, must also be converted to the discrete time domain with a bilinear transformation as well. This will be done by directly performing the transformation on $\frac{T}{R}$ and $\frac{S}{R}$ (no filtering) and using the α and β coefficients to derive difference equations for $u_T(t)$ and $u_S(t)$ respectively.

The bilinear transformations of $\frac{T}{R}$ and $\frac{S}{R}$ are

$$\frac{T}{R}\bigg|_{p=\frac{2(1-q^{-1})}{T(1+q^{-1})}} = [illegible]$$

$$\frac{S}{R}\bigg|_{p=\frac{2(1-q^{-1})}{T(1+q^{-1})}} = [illegible]$$

In [48]:

```
obj_TR = numden_coeff(TR, q)
obj_SR = numden_coeff(SR, q)

aTR = obj_TR.lst_denum_coeff
bTR = obj_TR.lst_num_coeff

aSR = obj_SR.lst_denum_coeff
bSR = obj_SR.lst_num_coeff
```

For $\frac{T}{R}$, the coefficients of the numerator and denominator are

$$\alpha_R^T = \left[1, \; \frac{Tr_1 - 2}{Tr_1 + 2}\right]$$

and

$$\beta_R^T = \left[\frac{Ta_0 + 2}{c(Tr_1 + 2)}, \; \frac{Ta_0 - 2}{c(Tr_1 + 2)}\right]$$

while the coefficients of the numerator and denominator for $\frac{S}{R}$ are

$$\alpha_R^S = \left[1, \; \frac{Tr_1 - 2}{Tr_1 + 2}\right]$$

and

$$\beta_R^S = \left[\frac{Ts_1 + 2s_0}{Tr_1 + 2}, \; \frac{Ts_1 - 2s_0}{Tr_1 + 2}\right]$$

In [49]:

```
uc_k, uc_k_1 = sp.symbols('u_{c}(k) u_{c}(k-1)')

[illegible]
```

The difference equation representing the control signal becomes

$$u(k) = [illegible]$$

part 3

In [50]:

```
[illegible]
```

The for the implementation of the design, a sampling period of 0.1 $(T = 0.1)$ and an observer polynomial parameter of 5 $(a_0 = 5)$ will be used. The difference equations for $y_{f1}, y_{f0}, u_{f0}, y(kT)$ and $u(kT)$ become

[illegible]

In [51]:

```
[illegible]
```







Problem 2

part 1

In [52]:

```
[illegible]
```

Out[52]: $\frac{1}{s^2 + 1.5s + 0.5}$

In [53]:

```
[illegible]
```

The pulse transfer function can be obtained be taking performing a zero order hold on the plant. The zero order hold equation is

$$H(q) = (1 - q^{-1})Z\left\{\mathcal{L}^{-1}\left\{\frac{G(s)}{s}\right\}\right\}$$

If $T = 2s$, then the pulse function is

$$[illegible] \quad dt = 2$$

Which matches exactly the pulse transfer function given in the homework.

part 2

The roots of the numerator of $H(q)$ are

In [54]:

```
[illegible]
```

Out[54]: [illegible]

Since [illegible] is sufficiently far from the unit circle edge, it can be cancelled without risk.

In [55]:

```
[illegible]
```

$B = B^+ B^- = b_0\left(q + \frac{b_1}{b_0}\right)$

Therefore,

$$Deg(B^-) = 0$$

and

$$Deg(B^+) = Deg(B) - Deg(B^-) = 1$$

Additionally

[illegible]

In [56]:

```
[illegible]
```

The control polynomials become

[illegible]

Additionally, to achieve unity gain, the final value theorem can be implemented on A_m to obtain the value of B_m. This is achieved by the equation $B_m = A_m(1)q^n$. This way, when k goes to infinity $(q \rightarrow 1)$, $G_m = 1$ and $Deg(B_m) = Deg(B)$. Therefore,

$B_m = A_m(1)q$

From this result, T can be calculated

[illegible]

In [57]:

```
[illegible]
```

We can see that

[illegible]

Solving the diophantine equation

$AR' + B^- S = A_0 A_m$ [illegible]

yields the following control parameters

[illegible]

In [58]:

```
[illegible]
```

The control polynomials in terms of control parameters are

[illegible]

Part 3

[illegible]

Control signal u(t)

[illegible]

For $\frac{T}{R}$, the coefficients of the numerator and denominator are

$$\alpha\frac{T}{R} = \left[1, \frac{b_1}{b_0}\right]$$

and

$$\beta\frac{T}{R} = \left[\frac{a_{m1} + a_{m2} + 1}{b_0}, 0\right]$$

while the coefficients of the numerator and denominator for $\frac{S}{R}$ are

$$\alpha\frac{S}{R} = \left[1, \frac{b_1}{b_0}\right]$$

and

$$\beta\frac{S}{R} = \left[\frac{-a_1 + a_{m1}}{b_0}, \frac{-a_2 + a_{m2}}{b_0}\right]$$

In [26]:
```
u_k, u_k_1, uc_k, y_k, y_k_1, y_k_2 = sp.symbols('u(k) u(k-1) u_{c}(k) y(k) y(k-1) y(k-2)')

uk = -u_k_1*aTR[1] + uc_k*bTR[0] - y_k*bSR[0] - y_k_1*bSR[1]
```

The control equation in terms of the plant and model parameters is

$$u(t) = -\frac{b_1 u(k-1)}{b_0} + \frac{u_c(k)\left(a_{m1} + a_{m2} + 1\right)}{b_0} - \frac{y(k)\left(-a_1 + a_{m1}\right)}{b_0} - \frac{y(k-1)\left(-a_2 + a_{m2}\right)}{b_0}$$

In [27]:
```
co.sample_system(co.tf([1], [1, 2, 1]), Ts=2, method='zoh') # pulse transfer function of model
```

Out[27]:

$$\frac{0.594z + 0.1537}{z^2 - 0.2707z + 0.01832} \quad dt = 2$$

We can see from the pulse transfer function of model above that $a_{m1} = -0.2707$ and $a_{m2} = 0.01832$

part 4

In [28]:
```
# Tunable components vvvvvvvvvvvvvvvvvvvvvvvvvvvvvvvvv
sample_depth = 100
starting_samples = 2

# starting estimate for plant parameters
est = 0.5

lam = 1 # forgeting factor lambda

# true plant parameters
a_1 = -0.503215
a_2 = 0.0497871
b_0 = 1.59831
b_1 = 0.587984
theta0 = np.array([a_1, a_2, b_0, b_1]).reshape(-1,1)

# Tunable components ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^

theta_hat = [np.array([est]*len(theta0)).reshape(-1,1) for _ in range(starting_samples)]

# model parameters
a_m1 = -0.2707
a_m2 = 0.01832

# Convert control equation derived above symbolically into numeric function
uk_subd = uk.subs([(am1, a_m1), (am2, a_m2)]) # subing in true values for am1 and am2 into control input funct
uk_func = sp.lambdify([u_k_1, uc_k, y_k, y_k_1, a1, a2, b0, b1], uk_subd)

# System input
sample_range = range(sample_depth)
t = [i for i in sample_range]
u_c = np.ones(sample_depth)
u_c[np.where([m.sin(t[i]*m.pi/20)<=0 for i in sample_range])] = 0

y = [0]*starting_samples
u = [0]*starting_samples

I = np.identity(len(theta0))
p = 1000*I

for k in range(starting_samples ,sample_depth):
    phi = np.array([-y[-1], -y[-2], u[-1], u[-2]]).reshape(-1,1)

    y.append(np.reshape(phi.T@theta0, ()))
    K = p@phi@inv(lam + phi.T@p@phi)
    p = (I - K@phi.T)@p/lam
    theta_hat.append(theta_hat[-1] + K*(y[k] - phi.T@theta_hat[-1]))

    u.append(np.reshape(uk_func(u[k-1], u_c[k], y[k], y[k-1],
                              theta_hat[-1][0], theta_hat[-1][1],
                              theta_hat[-1][2], theta_hat[-1][3]), ()))

# ploting of estimated parameters
df_theta = pd.DataFrame(np.asarray(theta_hat).reshape(-1,4), columns=['a1', 'a2', 'b0', 'b1'])
theta_hat_ploter(df_theta, theta0, 'Theta_hat Estimates')

# ploting of control sig
plt.step(t,u)
plt.title('Control Input', fontsize=20)
plt.ylabel('u(t)', fontsize=18)
plt.xlabel('Time Stamps "t"', fontsize=18)
plt.grid()
plt.show()

# ploting of input vs output
plt.plot(t,u_c)
plt.plot(t,y)
plt.title('u_c(t) Vs y(t)', fontsize=20)
plt.ylabel('Magnitude', fontsize=18)
plt.xlabel('Time Stamps "t"', fontsize=18)
plt.show()
```







Step 5

In [29]:
```
x0, y0, r01, s00, s01 = sp.symbols('x_0 y_0 r_{01} s_{00} s_{01}')

Ad = q - 1 # Disturbance filter

# original Control Polynomials
R0 = q + r01
S0 = s00*q + s01
T = q*t0

X = q + x0
Y = y0

X_ = q
Y_ = (-X_*R0/B).subs(q,1)

R = collect(expand(X_*R0 + Y*B),q)
S = collect(expand(X_*S0 - Y*A),q)

r_01 = r_1
s_00 = s_0
s_01 = s_1

b_0 = sp.solve(sp.Eq(Y_, y0), b0)[0]
R_prime = simplify((R/Ad).subs(b0, b_0))
```

x_0 will be chosen to be equal to 0. This introduces a pole at the origin. Since the new R is given by

$A_d R = R_0 Y + YR \Rightarrow (q-1)R = (q + r_{01})(q + x_0) + Y(b_0 q + b_1)$ Y must be a scalar value to maintain the order of R. This is done by finding the steady state of the above equation and solving for y_0. This gives

$$Y = y_0 = -\frac{r_{01} + 1}{b_0 + b_1}$$

Pluging this result back into the equation for R gives

$$R = \{q(q + r_{01}) + (-\frac{r_{01} + 1}{b_0 + b_1})(b_0 q + b_1) = b_1 y_0 + q^2 + q\left(b_0 y_0 + r_{01}\right)$$

Similarly,

$$S = XS_0 - YA = -a_2 y_0 + q^2\left(s_{00} - y_0\right) + q\left(-a_1 y_0 + s_{01}\right)$$

Derivations of Equations of Filtered System

Filtered Output Equation y_f(t)

$$A_f(q)A(q)y(t) = A_f(q)B(q)(u(t) + v(t))$$

$$\Rightarrow q(1 - q^{-1})A(q)y(t) = q(1 - q^{-1})B(q)(u(t) + v(t))$$

$$\Rightarrow (1 - q^{-1})A(q)y(t) = (1 - q^{-1})B(q)(u(t) + v(t))$$

$$\Rightarrow A(q)y_f(t) = B(q)u_f(t) + e(t)$$

$$\Rightarrow (a_1 q + a_2 + q^2)y_f(t) = (b_0 q + b_1)u_f(t) + e(t)$$

Therefore

$$y_f(t+2) = -a_1 y_f(t+1) - a_2 y_f(t) + b_0 u_f(t+1) + b_1 u_f(t)$$

$$\Rightarrow y_f(t) = -a_1 y_f(t-1) - a_2 y_f(t-2) + b_0 u_f(t-1) + b_1 u_f(t-2)$$

This means that the measurment model is

$$y_f(t) = \phi^T\theta = [-y_f(t-1)\ \ -y_f(t-2)\ \ u_f(t-1)\ \ u_f(t-2)]\,[a_1\ a_2\ b_0\ b_1]^T$$

Output Equation y(t)

We know that

$$y_f(t) = A_f(q^{-1})y(t)$$

$$\Rightarrow y_f(t) = (1 - q^{-1})y(t)$$

$$\Rightarrow y_f(t) = y(t) - y(t-1)$$

$$\Rightarrow y(t) = y_f(t) + y(t-1)$$

Filtered Control Input Equation u_f(t)

Similarly

$$u_f(t) = A_f(q^{-1})u(t)$$

$$\Rightarrow u_f(t) = u(t) - u(t-1)$$

Control Equation u(t)

In [30]:
```
TR = simplify(T/R)
SR = simplify(S/R)

obj_TR = numden_coeff(TR, q)
obj_SR = numden_coeff(SR, q)

aTR = obj_TR.lst_denum_coeff
bTR = obj_TR.lst_num_coeff

aSR = obj_SR.lst_denum_coeff
bSR = obj_SR.lst_num_coeff
```

For $\frac{T}{R}$, the coefficients of the numerator and denominator are

$$\alpha\frac{T}{R} = \left[1, b_0 y_0 + r_{01}, b_1 y_0\right]$$

and

$$\beta\frac{T}{R} = \left[t_0, 0\right]$$

while the coefficients of the numerator and denominator for $\frac{S}{R}$ are

$$\alpha\frac{S}{R} = \left[1, b_0 y_0 + r_{01}, b_1 y_0\right]$$

and

$$\beta\frac{S}{R} = \left[s_{00} - y_0, -a_1 y_0 + s_{01}, -a_2 y_0\right]$$

In [31]:
```
u_k_1, u_k_2, uc_k_1, y_k, y_k_1, y_k_2 = sp.symbols('u(k-1) u(k-2) u_{c}(k-1) y(k) y(k-1) y(k-2)')

uk_ = -u_k_1*aTR[1] -u_k_2*aTR[2] + uc_k_1*bTR[0] - y_k*bSR[0] - y_k_1*bSR[1] - y_k_2*bSR[2]
uk = simplify(uk_.subs([(t0, t_0), (y0, Y_), (r01, r_01), (s00, s_00), (s01, s_01)]))
```

The control equation becomes

$$u(t) = a_2 y(k-2)y_0 - b_1 u(k-2)y_0 + t_0 u_c(k-1) - u(k-1)\left(b_0 y_0 + r_{01}\right) - y(k)\left(s_{00} - y_0\right) - y(k-1)\left(-a_1 y_0 + s_{01}\right)$$

$$\Rightarrow u(t) = \frac{-a_2 y(k-2) + b_1 u(k-2) + u(k-1)\left(b_0 - b_1\right) + u_c(k-1)\left(a_{m1} + a_{m2} + 1\right) - y(k)\left(-a_1 + a_{m1} + 1\right) - y(k-1)\left(a_1 - a_2 + a_{m2}\right)}{b_0}$$

In [32]:
```
# Tunable components vvvvvvvvvvvvvvvvvvvvvvvvvvvvvvvvv
sample_depth = 100
starting_samples = 3

# starting estimate for plant parameters
est = 0.5

lam = 1 # forgeting factor lambda

# true plant parameters
a_1 = -0.503215
a_2 = 0.0497871
b_0 = 1.59831
b_1 = 0.587984
theta0 = np.array([a_1, a_2, b_0, b_1]).reshape(-1,1)

# Tunable components ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^

theta_hat = [np.array([est]*len(theta0)).reshape(-1,1)]

# model parameters
a_m1 = -0.2707
a_m2 = 0.01832

# Convert control equation derived above symbolically into numeric function
uk_subd = uk.subs([(am1, a_m1), (am2, a_m2)])
uk_func = sp.lambdify([u_k_1, u_k_2, uc_k_1, y_k, y_k_1, y_k_2,
                       a1, a2, b0, b1], uk_subd)

sample_range = range(sample_depth)

# system input
t = [i for i in sample_range]
u_c = np.ones(sample_depth)
u_c[np.where([m.sin(t[i]*m.pi/20)<=0 for i in sample_range])] = 0

# system disturbance starting at t=40
dist = np.zeros(sample_depth)
dist[np.where([t[i]>= 40 for i in sample_range])] = 1

y = [0]*starting_samples
u = [0]*starting_samples

yf = [0]*starting_samples
uf = [0]*starting_samples

I = np.identity(len(theta0))
p = 1000*I

for k in range(starting_samples ,sample_depth):
    phi = np.array([-yf[-1], -yf[-2], uf[-1], uf[-2]]).reshape(-1,1)
    yf.append(np.reshape(phi.T@theta0 + dist[k] - dist[k-1], ()))

    K = p@phi@inv(lam + phi.T@p@phi)
    p = (I - K@phi.T)@p/lam

    theta_hat.append(theta_hat[-1] + K*(yf[k] - phi.T@theta_hat[-1]))

    y.append(yf[k] + y[k-1])

    u.append(np.reshape(uk_func(u[k-1], u[k-2], u_c[k-1], y[k], y[k-1], y[k-2],
                              theta_hat[-1][0], theta_hat[-1][1],
                              theta_hat[-1][2], theta_hat[-1][3]), ()))

    uf.append(u[k] - u[k-1])

# ploting of estimated parameters
df_theta = pd.DataFrame(np.asarray(theta_hat).reshape(-1,4), columns=['a1', 'a2', 'b0', 'b1'])
theta_hat_ploter(df_theta, theta0, 'Theta_hat Estimates')

# ploting of control sig
plt.step(t,u)
plt.title('Control Input', fontsize=20)
plt.ylabel('u(t)', fontsize=18)
plt.xlabel('Time Stamps "t"', fontsize=18)
plt.grid()
plt.show()

# ploting of input vs output
plt.plot(t,u_c)
plt.plot(t,y)
plt.title('u_c(t) Vs y(t)', fontsize=20)
plt.ylabel('Magnitude', fontsize=18)
plt.xlabel('Time Stamps "t"', fontsize=18)
plt.show()
```







Problem 3

In [33]:
```
r1, t0 = sp.symbols('r_1 t_0')

A = q**2 + a1*q + a2
B = b0*q + b1
B_minus = b0
B_plus = simplify(B/B_minus)
H = B/A
A0 = 1

S = s0*q + s1
R = q + r1 # define b1/b0 as r1
R_prime = 1
T = q*t0 # t0 = (am1 + am2 + 1)/b0
```

Part 1

$$H = \frac{b_0 q + b_1}{a_1 q + a_2 + q^2}$$

$$B = B^+B^- = (b_0)(q + \frac{b_1}{b_0})$$

Therfore,

$$Deg(B^-) = 0$$

and

$$Deg(B^+) = Deg(B) = Deg(B_m) = 1$$

Additionally

$$Deg(A) = Deg(A_m) = 2$$

$$Deg(S) = Deg(R) = Deg(A) - 1 = 2 - 1 = 1$$

$$Deg(R') = Deg(R) - Deg(B^+) = 1 - 1 = 0$$

$$Deg(A_0) = Deg(A) + Deg(R) - Deg(A_m) = 2 + 0 - 2 = 0$$

The control polynomials become

$$A_0 = 1$$

$$S = qs_0 + s_1$$

$$R = q + r_1$$

$$R' = 1$$

$$A_m = a_{m1}q + a_{m2} + q^2$$

Additionally, to achive unity gain, the final value theorem can implemented on A_m to obtain the value of B_m. This is achived by the equation $B_m = A_m(1)q^m$. This way, when k goes to infinity $(q \to 1)$, $G_m = 1$ and $Deg(B_m) = Deg(B)$. Therfore,


Theta_hat Estimates
s0 = 0.145
s1 = -0.020
Magnitude of "Theta_hat"
Time Stamps "t"


Control Input
u(t)
Time Stamps "t"


u_c(t) Vs y(t)
Magnitude
Time Stamps "t"