

# CS 193G

## Lecture 2: GPU History & CUDA Programming Basics

# Outline of CUDA Basics


- **Basic Kernels and Execution on GPU**
- **Basic Memory Management**
- **Coordinating CPU and GPU Execution**
- **See the Programming Guide for the full API**

# **BASIC KERNELS AND EXECUTION ON GPU**

# CUDA Programming Model

- **Parallel code (kernel) is launched and executed on a device by many threads**
- **Launches are hierarchical**
  - Threads are grouped into blocks
  - Blocks are grouped into grids
- **Familiar serial code is written for a thread**
  - Each thread is free to execute a unique code path

# High Level View




# Blocks of threads run on an SM


Streaming Processor




Thread




Streaming Multiprocessor



Threadblock



# Whole grid runs on GPU




# Thread Hierarchy


- **Threads launched for a parallel section are partitioned into thread blocks**
  - **Grid = all blocks for a given launch**
- **Thread block is a group of threads that can:**
  - **Synchronize their execution**
  - **Communicate via shared memory**



# Memory Model



# Memory Model



# Example: Vector Addition Kernel

## Device Code

```
// Compute vector sum C = A+B
// Each thread performs one pair-wise addition
__global__ void vecAdd(float* A, float* B, float* C)
{
    int i = threadIdx.x + blockDim.x * blockIdx.x;
    C[i] = A[i] + B[i];
}
```

```
int main()
{
    // Run grid of N/256 blocks of 256 threads each
    vecAdd<<< N/256, 256>>>>(d_A, d_B, d_C);
}
```

# Example: Vector Addition Kernel

```
// Compute vector sum C = A+B
// Each thread performs one pair-wise addition
__global__ void vecAdd(float* A, float* B, float* C)
{
    int i = threadIdx.x + blockDim.x * blockIdx.x;
    C[i] = A[i] + B[i];
}
```

Host Code

```
int main()
{
    // Run grid of N/256 blocks of 256 threads each
    vecAdd<<< N/256, 256>>>(d_A, d_B, d_C);
}
```

# Example: Host code for `vecAdd`

```
// allocate and initialize host (CPU) memory
float *h_A = ..., *h_B = ...; *h_C = ... (empty)

// allocate device (GPU) memory
float *d_A, *d_B, *d_C;
cudaMalloc( (void**) &d_A, N * sizeof(float));
cudaMalloc( (void**) &d_B, N * sizeof(float));
cudaMalloc( (void**) &d_C, N * sizeof(float));

// copy host memory to device
cudaMemcpy( d_A, h_A, N * sizeof(float),
            cudaMemcpyHostToDevice );
cudaMemcpy( d_B, h_B, N * sizeof(float),
            cudaMemcpyHostToDevice );

// execute grid of N/256 blocks of 256 threads each
vecAdd<<<N/256, 256>>>(d_A, d_B, d_C);
```

## Example: Host code for `vecAdd` (2)

```
// execute grid of N/256 blocks of 256 threads each  
vecAdd<<<N/256, 256>>>(d_A, d_B, d_C);
```

```
// copy result back to host memory
```

```
cudaMemcpy( h_C, d_C, N * sizeof(float),  
            cudaMemcpyDeviceToHost) );
```

```
// do something with the result...
```

```
// free device (GPU) memory
```

```
cudaFree(d_A);  
cudaFree(d_B);  
cudaFree(d_C);
```

## Kernel Variations and Output

```
__global__ void kernel( int *a )
{
    int idx = blockIdx.x*blockDim.x + threadIdx.x;
    a[idx] = 7;
}
```

Output: 7777777777777777

```
__global__ void kernel( int *a )
{
    int idx = blockIdx.x*blockDim.x + threadIdx.x;
    a[idx] = blockIdx.x;
}
```

Output: 0 0 0 0 1 1 1 1 2 2 2 2 3 3 3 3

```
__global__ void kernel( int *a )
{
    int idx = blockIdx.x*blockDim.x + threadIdx.x;
    a[idx] = threadIdx.x;
}
```

Output: 0 1 2 3 0 1 2 3 0 1 2 3 0 1 2 3

# Code executed on GPU

- **C/C++ with some restrictions:**
  - Can only access GPU memory
  - No variable number of arguments
  - No static variables
  - No recursion
  - No dynamic polymorphism
- **Must be declared with a qualifier:**
  - **\_\_global\_\_** : launched by CPU,  
cannot be called from GPU must return void
  - **\_\_device\_\_** : called from other GPU functions,  
cannot be called by the CPU



# Memory Spaces

- **CPU and GPU have separate memory spaces**
  - Data is moved across PCIe bus
  - Use functions to allocate/set/copy memory on GPU
    - Very similar to corresponding C functions
- **Pointers are just addresses**
  - Can't tell from the pointer value whether the address is on CPU or GPU

# GPU Memory Allocation / Release

- Host (CPU) manages device (GPU) memory:
  - `cudaMalloc (void ** pointer, size_t nbytes)`
  - `cudaMemset (void * pointer, int value, size_t count)`
  - `cudaFree (void* pointer)`

```
int n = 1024;  
int nbytes = 1024*sizeof(int);  
int * d_a = 0;  
cudaMalloc( (void**)&d_a, nbytes );
```

# Data Copies

- **cudaMemcpy( void \*dst, void \*src, size\_t nbytes, enum cudaMemcpyKind direction);**
  - returns after the copy is complete
  - blocks CPU thread until all bytes have been copied
  - doesn't start copying until previous CUDA calls complete
- **enum cudaMemcpyKind**
  - cudaMemcpyHostToDevice
  - cudaMemcpyDeviceToHost
  - cudaMemcpyDeviceToDevice
- **Non-blocking copies are also available**

# Code Walkthrough 1

```
// walkthrough1.cu
#include <stdio.h>

int main()
{
    int dimx = 16;
    int num_bytes = dimx*sizeof(int);

    int *d_a=0, *h_a=0; // device and host pointers
```

# Code Walkthrough 1

```
// walkthrough1.cu
#include <stdio.h>

int main()
{
    int dimx = 16;
    int num_bytes = dimx*sizeof(int);

    int *d_a=0, *h_a=0; // device and host pointers

    h_a = (int*)malloc(num_bytes);
    cudaMalloc( (void**)&d_a, num_bytes );

    if( 0==h_a || 0==d_a )
    {
        printf("couldn't allocate memory\n");
        return 1;
    }
}
```

# Code Walkthrough 1

```
// walkthrough1.cu
#include <stdio.h>

int main()
{
    int dimx = 16;
    int num_bytes = dimx*sizeof(int);

    int *d_a=0, *h_a=0; // device and host pointers

    h_a = (int*)malloc(num_bytes);
    cudaMalloc( (void**)&d_a, num_bytes );

    if( 0==h_a || 0==d_a )
    {
        printf("couldn't allocate memory\n");
        return 1;
    }

    cudaMemset( d_a, 0, num_bytes );
    cudaMemcpy( h_a, d_a, num_bytes,
cudaMemcpyDeviceToHost );
```

# Code Walkthrough 1

```
// walkthrough1.cu
#include <stdio.h>

int main()
{
    int dimx = 16;
    int num_bytes = dimx*sizeof(int);

    int *d_a=0, *h_a=0; // device and host pointers

    h_a = (int*)malloc(num_bytes);
    cudaMalloc( (void**)&d_a, num_bytes );

    if( 0==h_a || 0==d_a )
    {
        printf("couldn't allocate memory\n");
        return 1;
    }

    cudaMemset( d_a, 0, num_bytes );
    cudaMemcpy( h_a, d_a, num_bytes, cudaMemcpyDeviceToHost );

    for(int i=0; i<dimx; i++)
        printf("%d ", h_a[i] );
    printf("\n");

    free( h_a );
    cudaFree( d_a );

    return 0;
}
```

# Example: Shuffling Data

```
// Reorder values based on keys
// Each thread moves one element
__global__ void shuffle(int* prev_array, int*
    new_array, int* indices)
{
    int i = threadIdx.x + blockDim.x * blockIdx.x;
    new_array[i] = prev_array[indices[i]];
}
```

Host Code

```
int main()
{
    // Run grid of N/256 blocks of 256 threads each
    shuffle<<< N/256, 256>>>(d_old, d_new, d_ind);
}
```



# IDs and Dimensions

- **Threads:**

- 3D IDs, unique within a block


- **Blocks:**

- 2D IDs, unique within a grid

- **Dimensions set at launch**

- Can be unique for each grid

- **Built-in variables:**



# Kernel with 2D Indexing

```
__global__ void kernel( int *a, int dimx, int dimy )
{
    int ix  = blockIdx.x*blockDim.x + threadIdx.x;
    int iy  = blockIdx.y*blockDim.y + threadIdx.y;
    int idx = iy*dimx + ix;

    a[idx] = a[idx]+1;
}
```

```

__global__ void kernel( int *a, int dimx, int dimy )
{
    int ix  = blockIdx.x*blockDim.x + threadIdx.x;
    int iy  = blockIdx.y*blockDim.y + threadIdx.y;
    int idx = iy*dimx + ix;

    a[idx] = a[idx]+1;
}

```

```

int main()
{
    int dimx = 16;
    int dimy = 16;
    int num_bytes = dimx*dimy*sizeof(int);

    int *d_a=0, *h_a=0; // device and host pointers

    h_a = (int*)malloc(num_bytes);
    cudaMalloc( (void**)&d_a, num_bytes );

    if( 0==h_a || 0==d_a )
    {
        printf("couldn't allocate memory\n");
        return 1;
    }

    cudaMemset( d_a, 0, num_bytes );

    dim3 grid, block;
    block.x = 4;
    block.y = 4;
    grid.x = dimx / block.x;
    grid.y = dimy / block.y;

    kernel<<<grid, block>>>( d_a, dimx, dimy );

    cudaMemcpy( h_a, d_a, num_bytes, cudaMemcpyDeviceToHost );

    for(int row=0; row<dimy; row++)
    {
        for(int col=0; col<dimx; col++)
            printf("%d ", h_a[row*dimx+col] );
        printf("\n");
    }

    free( h_a );
    cudaFree( d_a );

    return 0;
}

```

# Blocks must be independent

- Any possible interleaving of blocks should be valid
  - presumed to run to completion without pre-emption
  - can run in any order
  - can run concurrently OR sequentially
- Blocks may coordinate but not synchronize
  - shared queue pointer: OK

**Questions?**