

# Django Notes

---

# Python lists

Python list syntax looks like array.

```
> fruit = [ "apple", 'banana', "orange" ]
> len(fruit)                # not OO syntax
3
> fruit[1]
'banana'
> fruit[1] = "mango"        # change an element
> fruit.pop()
"orange"
> fruit
['apple', 'mango']
> fruit.append('fig')
```

# Python dictionary

A **key-value** collection, like Map in Java.

```
> langs = {"python": "easy", "java": "cool",  
           "ruby": "weird"}
```

```
> langs.keys()      # order is not preserved  
dict.keys(['ruby', 'java', 'python'])
```

```
> langs['java']  
'cool'
```

```
> langs['ruby'] = "too much like Perl"
```

```
> for lang in langs:  # iterate over all keys  
    print("{0} is {1}".format(lang, langs[lang]))
```

```
ruby is too much like Perl
```

```
java is cool
```

```
python is easy
```

# More fluent Python

---

Instead of:

```
for lang in langs: # iterate over all keys
    print(lang, "is", langs[lang]))
```

Python programmers would write:

```
for (key,value) in langs.items(): # get pairs
    print(key, "is", value)
```

Syntax is similar to *multiple assignment*:

```
(name,id,email) = "Nok,1234,nok@gmail".split(',')
```

# Django Page Templates

---

In a Django `template`, you put values inside `{{ var }}`  
`templates/polls/details.html`:

```
<p>
```

```
Q{{question.id}} is {{question.question_text}}
```

```
</p>
```

To insert values into a template:

```
from django.template import loader
```

```
template =
```

```
    loader.get_template('polls/details.html')
```

```
# insert variables using a dictionary
```

```
template.render( {'question': question}, request )
```

# Page Templates & Context

---

The data used in a `template` is called a `context`.

```
template =  
    loader.get_template('polls/details.html')  
  
# context: key-values to use in template  
context = {'question': question, 'user': user, ...}  
  
return HttpResponse(  
    template.render( context, request ) )
```

# In a "view" what is **request**?

What is **request**? What is **HttpResponse**?

A Django "view" function looks like this:

```
from django.http import HttpResponse
from django.template import loader

def detail(request, question_id):
    questions = Question.objects.all()[0:10]
    context = {'question_list': questions}
    template = loader.get_template('some_file')

    return HttpResponse(
        template.render(context, request) )
```

# Shortcut for render and return

Inject a `context` and `render` a `template` is very common. Django has a "render" shortcut for previous slide:

```
from django.shortcuts import render
from django.template import loader

def detail(request, question_id):
    questions = Question.objects.all()[0:10]
    context = {'question_list': questions,
               'username': user.name }

    return render(request, 'some_file', context)
```



# URL Dispatching

Each "app" can have a `urls.py` to match request URLs and [dispatch](#) them to a "view".

```
from django.urls import path

# app_name is used to define a namespace
# (used for "reverse mapping")
app_name = 'polls'

url_patterns = [
    path('', views.index, name='index'),
    path('<int:question_id>/',
         views.detail, name='detail'),
    path('<int:question_id>/vote',
         views.vote, name='vote'),
    path('<int:question_id>/results',
         views.results, name='results'),
]
```

# Dispatch these URLs

Which view would handle each of these requests:

- 1) `http://localhost:8000/polls/`
- 2) `http://localhost:8000/polls//4/`
- 3) `http://localhost:8000/polls/8/vote?username=nok`
- 4) `http://localhost:8000/polls/8/vote/summary`

```
url_patterns = [  
    path('', views.index, name='index'),  
    path('<int:question_id>/',  
        views.detail, name='detail'),  
    path('<int:question_id>/vote/',  
        views.vote, name='vote'),  
]
```

# Mapping from View to URL

Inside html template, we want to insert a URL of a view.


Example: add a link to the polls index page.

How to "build" this URL inside a template?

```
<!-- question details template -->
<p>Question Id: {{ question.id }} </p>
<p>Text: {{ question.question_text }} </p>

<a href="{% url 'polls:index' %}">
    Back to Polls index
</a>

>> Notice that {%...%} is processed even inside "..."
```



The diagram shows two red arrows pointing from the text 'polls:index' in the code to the labels 'app\_name' and 'view name' below it. The arrow from 'polls' points to 'app\_name', and the arrow from 'index' points to 'view name'.

*Why is this (creating URL for a view) important?*

# Reverse Dispatch

Sometimes a view controller wants to redirect the user to a different URL.

```
from django.http import HttpResponseRedirect

def vote(request, question_id):
    question = Question.objects.get(id=question_id)
    // TODO save the vote for this question
    ...
    // Show all votes for this question
    _____Redirect to polls/{id}/results_____
```



How to redirect the browser to this page?

# Reverse Dispatch: reverse()

Sometimes a view (controller) wants to redirect the user to a different URL.

```
from django.http import HttpResponseRedirect

def vote(request, question_id):
    question = Question.objects.get(id=question_id)
    ## TODO get user's choice and add +1 to votes
    ...
    # Redirect browser to page of vote results
    HttpResponseRedirect(
        reverse('polls:results', args=(q.id)) )
```



Get the URL that matches the named route

# Thorough Testing is Needed!

---

Python code is *interpreted*.

There is no pre-compilation to catch errors (as in Java).  
So, you need to **test every path of execution**.

```
NameError at /polls/1/vote/  
name 'reverse' is not defined
```

Programmer forgot (in views.py):

```
from django.urls import reverse
```

but error is not detected until `reverse()` is encountered  
at **run-time**.

# All Frameworks must do this

---

Most web apps need a way to:

1. Include links to other app urls in HTML page
  - Amazon products page has links to each product
2. Redirect user to another page in our app
  - After add item to cart, redirect to view\_cart page.

Issue:

How to *inject* the correct URLs, without hardcoding them?

# Django's Solution

---

Most web apps need a way to:

1. Include links to other app urls in HTML page

```
{% url 'app_name:view_name' args %}
```

2. Redirect user to another page in our app

```
HttpResponseRedirect(  
    reverse('app_name:view_name',  
args=(...)) )
```

Rationale:

Make "apps" reusable by providing app-level naming of URL mappings.



# Exploring Models

Use Django to start an interactive Python shell.  
This is described in Tutorial part 2.

```
python manage.py shell  [ -i python ]

>>> from polls.models import Question, Choice
>>> q = Question.objects.get(id=1)
>>> q.question_text
"What is your favorite programming language?"
>>> choices = q.choice_set.all( )
>>> for c in choices:
...     print("%-10s %d" % (c.choice_text, c.votes))
Basic          0
C              1
Java           4
Python         2
```

# Try out Persistence

Try persistence operations: save(), get(), delete()

```
>>> c = Choice()
>>> c.choice_text = "Lisp"    # or "Racket" ("Scheme")
>>> c.votes = 2
## Foreign Key.  You have to find this separately.
>>> c.question_id = 1
>>> c.save()
>>> for choice in q.choice_set.all():
...     print(choice)
## Now the output includes "Lisp"
>>>
```

# Persistence Operations: CRUD

---

All Persistence Frameworks provide a way to...

- **save** (create) an entity to database
- **retrieve** an object, by id or by field value (query)
- **retrieve** all objects
- **update** object data in database
- **delete** a persisted object from database

How does Django do these?