



Exercise Using Selenium

"Scrape" URLs from a page of search results

Revised 11 Nov 2022 for selenium 4.6.0

Selenium

Browser automation.

Not just testing.

`https://selenium.dev/`

We will use Selenium WebDriver

- programmatically control a web browser

Selenium Example

Goal:

Use duckduckgo.com to find links to Kasertsart U.

Print the top 10 links.

Software Needed

- Python 3.x
- Selenium WebDriver: `pip install selenium`
- Driver for the Web browser you use:

Firefox driver, called "geckodriver"

<https://github.com/mozilla/geckodriver/releases>

Chrome & Chromium driver (*brittle*):

<https://sites.google.com/chromium.org/driver/>

Safari driver: already in `/usr/bin/safaridriver`

Try it! Get a web page

```
from selenium import webdriver


# get the duckduckgo search page
url = "https://duckduckgo.com"

# browser: a WebDriver object
browser = webdriver.Firefox()

# or: browser = webdriver.Chrome()

browser.get( url )
```

Get the id of the search input box



We will use this "id" to locate the input field

Firefox: right-click in search box -> "Inspect Element".

```
<input id='search_form_input_homepage' name="q" type="text" ...>
```

Find the input field & send data

```
from selenium.webdriver.common.by import By
from selenium.webdriver.common.keys import Keys
# Find an "element" for the search box
element_id = 'search_form_input_homepage'
element = browser.find_element(By.ID,
                                element_id)
# Enter the search text & press ENTER
element.send_keys("Kasetsart Univer")
element.send_keys(Keys.ENTER)
# Run It! (if you are using a script)
# the browser should display results
```

Inspect the Page & Identify Links

We need a way for Selenium to "find" the hyperlinks on the results page.

```
browser.find_element( by=_____, "value to find" )
```

```
By.CLASS_NAME      By.NAME
```

```
By.ID              By.TAG_NAME
```

```
By.LINK_TEXT       By.PARTIAL_LINK_TEXT
```

```
By.CSS_SELECTOR
```

You can omit the parameter name ("**by**")

Inspect one search result

Select a search result. Right Click -> Inspect.

The source looks like:

```
<div class="ikg2IXiCD14iVX7AdZo1">
<h2 class="LnpumSThxEWMIsDdAT17 CXMyPcQ6nDv47DKFeywM">
<a href="https://www.ku.ac.th/en/community-home"
rel="noopener" target="_self"
class="eVNpHGjtxRBq_gLOfGDr LQNqh2U1kzYxREs65IJu" data-
testid="result-title-a" data-handled-by-react="true">
<span class="EKtkFWMYpwzMKOYr0GYm
LQVY1Jpkk8nyJ6HBWKAk">News and Activities - Kasetsart
University</span>
</a></h2>
</div>
```

The class names are random. Nothing we can reliably search.

Find all the "a" tags

```
# Find all "a" elements on page
```

```
links = browser.find_elements(  
    By.TAG_NAME, "a")
```

```
len(links)
```

```
107
```

```
# Too many! Find links with text "Kaset.."
```

```
match = browser.find_elements(  
    By.PARTIAL_LINK_TEXT, "Kasetsart")
```

```
len(match)
```

```
17
```

Getting Data from a WebElement

`browser.find_element` and `browser.find_elements` returns **WebElements** that are parts of the page DOM.

You can:

- get "**attributes**" or **text** from each WebElement
- search its child WebElements - the DOM is a **tree**

Print value of the "href=" attribute of the first matches.

```
>>> match[0].get_attribute('href')
'https://duckduckgo.com/?q=Kasetsart
%20University&t=h_'      (not what we want)
>>> match[2].get_attribute('href')
'https://en.wikipedia.org/wiki/
Kasetsart_University'    (yes!)
```

"Click" on elements

When you locate a "clickable" web element like a button or hyperlink, you can click to activate it.

```
>>> match[2].click()
```

The browser should open the link you clicked.

Exercise: print first 10 URLs

Print the URLs of the first 10 hyperlinks on the DuckDuckGo search results page.

- omit hyperlinks that refer to duckduckgo.com
- some "a" tags may not have an "href" attribute.


Use try - except to catch this.

Composite Design Pattern

WebElement is the primary object for interacting with a web page using Selenium.

WebElement may contain other WebElements.

WebDriver contains many of the same methods as WebElement



Headless Browsing

You can use a browser without opening the U.I. window.

This is called *headless mode*.

Headless mode is needed when running tests on a C.I. server, like Github Actions.

Headless mode is *faster*, too.

https://developer.mozilla.org/en-US/docs/Mozilla/Firefox/Headless_mode

References

Good Selenium Tutorial in Python

Uses the previous version of selenium, so some methods may no longer work.

<https://blog.testproject.io/2019/07/16/web-ui-testing-python-pytest-selenium-webdriver>

The same author has other good testing tutorials:

<https://blog.testproject.io/2019/07/16/>

Exercise

Write a unit test for this:

When I search DuckDuckGo for Kasetsart University,
then at least 1 of the top-10 search results contains a
link to `https://www.ku.ac.th/` (*anything*)

1. Use `setUp` to create the browser instance.
2. Write a unit test method to perform the test above.

Wrong: testing for exact match of `"https://www.ku.ac.th/"`,
because KU's home page could change.

3. Once your test works, add headless mode to `setUp` and rerun. My intro to Selenium shows how to.