



# Introduction to Objects

---

James Brucker

# Software Design and OOP

---

Object-oriented design and programming is the dominant paradigm in software development.

To understand why you first need to understand objects and classes.

# What is an Object?

---

An object is a program element that *encapsulates both data and behavior*.

An object contains both data and the methods that operate on the data.

An object can control what information it exposes to the outside, and what it hides.

# Example

---

a **String**: `s = new String("i am an object")`

- **data**: the characters in the String
- **methods**: `toLowerCase`, `substring`, `indexOf`, ...

a **Scanner**: `console = new Scanner(System.in)`

- **data**: in *input source* the scanner is reading, the current position in the input, the separator
- **methods**: `hasNext`, `next`, `hasNextInt`, `nextInt`, ...

# Conceptual meaning of Objects

---

Objects represent "**things**" in the problem domain.

## Examples:

Banking app:    **money**  
                  **bank account**  
                  **customer**

Board game:    **board**  
(chess)        **game piece**  
                  **player**

# Objects - give examples

---

What are some *kinds of things* that you would find in a **Restaurant Application**?

---

---

---

---

---

---

# Objects and Classes

---

A **class** defines a **kind of object**.

The class defines:

1. **attributes** - to hold the data an object knows
2. **methods** - object's behavior (what it can do)
3. **constructors** - how to initialize a "new" object

# String Class and Object

Consider a String object: `String s = "Hello";`  
String class defines

**attributes** - what the String *knows* (also called *fields*)

**methods** - what the String can *do* (its *behavior*)

String object (s) defines the **values of attributes (data)**

**s: String**

length = 5

value= ['H' , 'e' , 'l' , 'l' , 'o' ]

length( )

charAt( int )

substring( start, end)

toLowerCase( )

} **attributes** are information an object remembers or stores  
Also called: *fields*

} **methods** are what the object can do.  
Also called *behavior*



# **new** - Creates object from a class

---

"new" creates a new object.

"new" invokes a *constructor* to initialize the object's attributes.

Example: create some Date objects

```
// constructor with no parameters - current date
Date now = new Date( );

// constructor with 3 parameters - specify a date
Date ny = new Date(105,Calendar.JANUARY,1);

System.out.println( now ); // 24 Oct 2017, 14:05:32
System.out.println( ny );  // 01 Jan 2005, 00:00:00
```

# Each object has its own attributes

---

Each object has its own copy of the attributes.

Changes to one object do not modify attributes of other objects.

```
Date now = new Date( ); // today is 24 Oct 2017
Date now2 = new Date( );
now2.setMonth( Calendar.DECEMBER );
now2.setDate( 1 );
now.setHour( 12 );
System.out.println( now2 ); // 01 Dec 2017, 12:32
System.out.println( now ); // 24 Oct 2017, 14:32
```

# Class can have many Constructors

---

**Scanner class** has many constructors. [See the Javadoc.](#)

```
// Scanner for reading InputStream
Scanner s1 = new Scanner( System.in );

// Scanner for parsing a String
Scanner s2 = new Scanner("Parse me, man.");

// Scanner opens and reads a File object
File file = new File("/etc/passwd");
Scanner s3 = new Scanner( file );
```

# Default Constructor

---

A constructor that has no parameters.

Also called "no argument constructor".

Not all classes have a default constructor!

```
// An empty ArrayList object (default constructor)
ArrayList list1 = new ArrayList();

// ArrayList object with data copied from array
String[] arr = "To data or not to data?".split(" ");
ArrayList<String> list2 = new ArrayList<>( arr );

// Error: Scanner does not have default constructor
Scanner scanner = new Scanner( ); // ERROR
```

# State

---

An object has "**state**", which is usually defined by its attributes.

**State** may also be defined by things an object is connected to, such as a file or InputStream.

Examples:

**LightBulb object** - state is "off" or "on"

**FileInputStream object** - open or closed, data in a file

**Scanner object** - "state" is delimiter pattern and its position in the input source.

# 3 Characteristics of Objects

---

Objects have:

**Behavior** - what an object can do. Defined by methods.

**State or Knowledge or Data** - what an object knows.  
Defined by attributes

**Identity** - objects are unique, even if they have the same type and attribute values.

**Memorize These**

# Invoking Behavior (Methods)

---

To invoke a method of an object, write:

`variable.method( )`

A variable that  
refers to the object

A method that  
belongs to the object

```
> String s = "Hello Dog";  
> s.length()  
9  
> s.toUpperCase()  
"HELLO DOG"  
> s.substring(0,5)  
"Hello"
```

# Class defines a kind of object

---

Memorize this.

Definition:

"A **class** is a **blueprint** or **definition** for a *kind* of object."

**Sale** class defines:

- **attributes** of a sale.
- **behavior** (methods) of a sale.
- how to **create and initialize** a sale.



# Objects are distinct, even if same value

---

## Identity: Objects are distinct

Each time you call "new" it creates a new object.

```
String s1 = new String("OOP");  
String s2 = new String("OOP"); //same data  
// same object?  
System.out.println(s1 == s2);  
                        FALSE
```

# Review

---

1. What is the definition of a **class** in OOP?
2. What are the **3 characteristics of objects**?
3. How do you create a Date object for the date Feb 15, 2000?
4. Is this true or false? Why?

```
Double x = new Double(1.0);  
Double y = new Double(1.0);  
(x == y)
```

# Next

---

1. **Exercise:** create Scanner objects that read the same file.

**Purpose:** to see that each object has its own state

2. How to define your own classes.

3. Other ways to create objects - "new" is for newbies