



Chris Trimmer

CS-300-T1159 DSA: Analysis and Design

Milestone 5-3: Tree Data Structure Pseudocode

22EW1 – 09/29/2022



The purpose of this document is to provide a pseudocode and algorithm analysis of code for a course planner that we are going to design for ABC University (ABCU). The pseudocode will consist of functions that pertain to file parsing, creating objects and storing them in a binary search tree data structure, searching the data structure, and printing the data. Where applicable, a runtime analysis will be documented for a function.

The main object used in the assignment is a Course class. Each course will contain a string value for its id, a string value for its title, and a list will store prerequisite courses for the given Course object. I use a vector to store prerequisites because a course can have more than one prerequisite and a vector is suitable for dynamic insertion. The binary search tree will represent the schedule of class objects. At a high-level representation, a schedule will contain multiple courses, and each course in the schedule can have zero or more prerequisite courses.

File Parsing

```
Void LoadCourses(string filepath, BinarySearchTree* bst) {
```

```
    Create vector to store the master course list
    Call to create the master course list using filepath
```

```
    Create infile ifstream object
    Use infile object to open the filepath
```

```
    If the infile object returns null
        return to caller immediately
```

```
    Create string object, line, to hold a line read from the file
    Create a char object, delim, which is a “,” (comma), to use as delimiter when reading each line
    Create a string object, word, to hold each word in the line
    Create a vector of strings, courseLine, that will hold each word
```

```
    Loop through infile object, and store each line in the line object
        Pass each line as an object to stringstream object, fullLine and parse using delim
```

```
    Loop through fullLine, and push back each word in the line to courseLine vector
```

```
    // check file format
    If the courseLine vector contains less than two objects, then this is an incomplete record
        Print output to user regarding invalid file format
        Return to caller
```

```
    // verify if prerequisite classes are valid
    For each word in courseLine vector
```

Remove whitespace from each word

If the word is not a valid course
Then skip the word

// now that we have a valid courseLine and valid prerequisites, perform object creation
Call AddCourse

(... outer loop continues after completion of creating the course object, and inserting into the hash table)

Clear the courseLine vector before starting the next loop

} // end LoadSchedule

| Code | Line Cost | Execution Times | Total Cost |
|---|-----------|-----------------|------------|
| Create master course vector | 1 | n | n |
| Create ifstream object | 1 | 1 | 1 |
| Open filepath | 1 | 1 | 1 |
| if infile is null, return | 2 | 1 | 2 |
| Create 4 local variables | 4 | 1 | 4 |
| while file has lines to read | 1 | n | n |
| create sstream object | 1 | 1 | 1 |
| while there are words in the stream object | 1 | n | n |
| trim whitespace from each word for each sstream object | 4 | n | 4n |
| push each word to vector | 1 | n | n |
| if courseLine less than 2 | 2 | 1 | 2 |
| return to caller | 1 | 1 | 1 |
| Create course object | 1 | 1 | 1 |
| if size of courseLine > 2 | 2 | 1 | 2 |
| for each prereq | 1 | n | n |
| compare prereq to master course list | 1 | n | n |
| if the prereq is found | 2 | 1 | 2 |
| insert prereq to course | 1 | 1 | 1 |
| Search tree to verify if course has already been added | 1 | logN+1 | logN+1 |
| if the course doesn't exist | 2 | 1 | 2 |

| | | | |
|-----------------------------|---|---------------|----------------------|
| then call Add Course | 1 | $2\log N + 9$ | $2\log N + 9$ |
| clear the courseLine vector | 1 | 1 | 1 |
| close the file | 1 | 1 | 1 |
| Total Cost: | | | $3\log N + 10n + 32$ |
| Runtime | | | $O(N\log N)$ |

Creating and Storing Objects

```
Void AddCourse(String courseLine) {
```

```
    Instantiate Course object
```

```
    For each word in line
```

```
        Set course id to line[0]
```

```
        Set course title to line[1]
```

```
    For each additional word in line
```

```
        Push back word into the prereq list stored in the Course object
```

```
    // the course now has all its data
```

```
    Call insert function of binary search tree class passing the Course object
```

```
}
```

| Code | Line Cost | Execution Times | Total Cost |
|--|-----------|-----------------|---------------------|
| Instantiate blank course object | 1 | 1 | 1 |
| for each word in lines | 1 | n | n |
| set course id to line[0] | 1 | 1 | 1 |
| set course title to line[1] | 1 | 1 | 1 |
| for each additional word in lines | 1 | n | n |
| push back word to prereq vector | 1 | 1 | 1 |
| call insert function to pass course object | 1 | 1 | $2\log N + 10$ |
| Total Cost: | | | $2\log N + 2n + 14$ |
| Runtime | | | $O(N\log N)$ |

Inserting the Courses in the tree (Recursive)

```
Void InsertRecursive(Node* node, Course course) {
    If course.id is less than the node.id
        If node->left is null
            Create new node with course object
            Assign new node to node->left
        Else
            Recursively call InsertRecursive with node->left and the course
    Else
        If node->right is null
            Create new node with course object
            Assign new node to node->right
        Else
            Recursively call InsertRecursive with node->right and the course
}
```

| Code | Line Cost | Execution Times | Total Cost |
|---------------------------------------|-----------|-----------------|------------|
| if id is less than node Id | 2 | 1 | 2 |
| if node->left is null | 2 | 1 | 2 |
| create new node with object | 1 | 1 | 1 |
| assign new node to node->left | 1 | 1 | 1 |
| else, recursively call insert w/left | 1 | logN+1 | logN+1 |
| else if node->right is null | 1 | 1 | 1 |
| create new node with object | 1 | 1 | 1 |
| assign new node to node->right | 1 | 1 | 1 |
| else, recursively call insert w/right | 1 | logN+1 | logN+1 |
| Total Cost: | | | 2logN + 9 |
| Runtime: | | | O(NlogN) |

Get number of prerequisites

```
Int GetNumberOfPrereqs(string key) {
```

```
    For each letter in key
        Transform letter to uppercase
```

```
    Initialize sum variable to 0
```

```

For each course
  If the key matches the course->id
    For each prereq
      Increment sum

Return sum

```

```

}

```

| Code | Line Cost | Execution Times | Total Cost |
|-------------------------------|-----------|-----------------|------------|
| For each letter in key | 1 | n | 1 |
| transform letter to uppercase | 1 | 1 | 1 |
| Initialize sum variable to 0 | 1 | 1 | 1 |
| for each course | 1 | n | n |
| if key matches courseid | 1 | 1 | 1 |
| for each prereq | 1 | n | n |
| increment sum | 1 | 1 | 1 |
| return sum | 1 | 1 | 1 |
| Total Cost: | | | 2n + 6 |
| Runtime | | | O(n) |

Search for a Course (Recursive)

```

Course SearchRecursive(Node* node, string key) {
  If node is not null
    If key is equal to node->id
      Return the node->course
    Else if the key is less than the node->id
      Recursively call SearchRecursive with node->left and key
    Else
      Recursively call SearchRecursive with node->right and key
}

```

| Code | Line Cost | Execution Times | Total Cost |
|---------------------------|-----------|-----------------|------------|
| for each letter in key | 1 | n | n |
| transform letter to upper | 1 | 1 | 1 |
| if node not equal null | 1 | 1 | 1 |
| if key equal to node->id | 1 | 1 | 1 |

| | | | |
|-----------------------------------|---|--------|---------------|
| return node | 1 | 1 | 1 |
| else if key less than node->id | 1 | 1 | 1 |
| recursively call node->left | 1 | logN+1 | logN+1 |
| else recursively call node->right | 1 | logN+1 | logN+1 |
| Total Cost: | | | 2logN + N + 5 |
| Runtime | | | O(NlogN) |

Print Courses – InOrder Traversal

```
Void inOrder(Node* node) {
    if node is not null
        recursively call inOrder with left side
        print the node info
        recursively call inOrder with right side
}
```

| Code | Line Cost | Execution Times | Total Cost |
|------------------------------|-----------|-----------------|------------|
| if Node* not equal null | 1 | 1 | 1 |
| recursively call node->left | 1 | logN+1 | logN+1 |
| PrintCourseInfo | 1 | 1 | 1 |
| recursively call node->right | 1 | logN+1 | logN+1 |
| Total Cost: | | | 2logN + 4 |
| Runtime | | | O(NlogN) |