

# Image/video matting

--cvpr 2022

# Defination

Image. -> background + foreground (alpha matte)

$$I_i = \alpha_i F_i + (1 - \alpha_i) B_i, \quad \alpha_i \in [0, 1],$$




Reference:

Trimap (bg/fg/unknown) (DIM, GCA...)

background. (bg matting, bg matting v2)

Mask (mg matting)

Semantic (semantic image matting)





# MatteFormer

1. Transformer-based model / reducing computational cost -> Swin transformer (backbone)
2. Prior-token (represents global feature of fg/bg/unknown)
3. Design PAST block (prior-attentive swin transformer)
  - PA-WSA (self attention with spatial-tokens and prior-tokens)
  - Prior memory at each block

# Swin Transformer



1. high-resolution computation -> non-overlap small-size patches
2. Shift windows




# MatteFormer

## 1. prior-tokens

$$\mathbf{p}^q = \frac{1}{N_q} \sum_{i=1}^N r_i^q \cdot \mathbf{z}_i, \quad q \in \{\text{fg}, \text{bg}, \text{uk}\},$$



## 2. Network



# MatteFormer

## 1. Encoder: swin transformer


Decoder: Progressive Refinement Module

$$\alpha_l = \alpha'_l \odot g_l + \alpha_{l-1} \odot (1 - g_l),$$

$$g_l(x, y) = \begin{cases} 1, & \text{if } 0 < \alpha_{l-1}(x, y) < 1 \\ 0, & \text{otherwise} \end{cases},$$

## 2. Loss

$$L_{total} = L_{l1} + L_{comp} + L_{lap}$$



# MatteFormer

## Results. Based composition-1k

Method	SAD	MSE ( $10^{-3}$ )	Grad	Conn
Learning Based Matting [59]	113.9	48	91.6	122.2
Closed-Form Matting [20]	168.1	91	126.9	167.9
KNN Matting [6]	175.4	103	124.1	176.4
Deep Image Matting [51]	50.4	14	31.0	50.8
AlphaGan [33]	52.4	30	38.0	-
IndexNet [31]	45.8	13	25.9	43.7
HAttMatting [34]	44.0	7.0	29.3	46.4
AdaMatting [2]	41.7	10.0	16.8	-
SampleNet [40]	40.4	9.9	-	-
Fine-Grained Matting [27]	37.6	9.0	18.3	35.4
Context-Aware Matting [18]	35.8	8.2	17.3	33.2
GCA Matting [22]	35.3	9.1	16.9	32.5
HDMatt [53]	33.5	7.3	14.5	29.9
MG Matting [54]	31.5	6.8	13.5	27.3
MG Matting-trimap*	28.9	5.7	11.4	24.9
MG Matting-trimap,res50*	28.4	5.4	11.1	24.3
TIMINet [29]	29.1	6.0	11.5	25.4
SIM [39]	28.0	5.8	10.8	24.8
<b>Ours (MatteFormer)</b>	<b>23.8</b>	<b>4.0</b>	<b>8.7</b>	<b>18.9</b>


Method	SAD	MSE ( $10^{-3}$ )	Grad	Conn
Baseline (no prior-token)	26.43	5.20	9.57	21.89
Baseline + GAP prior-token	25.30	4.72	9.63	20.61
Baseline + uk prior-token	24.70	4.46	9.10	19.73
+ uk/fg/bg prior-token	24.19	4.05	8.72	19.19
+ prior-memory (MatteFormer)	23.80	4.03	8.68	18.90

Methods	w ASPP		w/o ASPP	
	SAD	MSE ( $10^{-3}$ )	SAD	MSE ( $10^{-3}$ )
Baseline (no prior-token)	26.97	5.35	26.43	5.20
+ u.k prior-token	25.60	4.68	24.71	4.46
+ u.k/f.g/b.g prior-token	25.52	4.38	24.19	4.05
+ prior-memory (MatteFormer)	25.15	4.30	23.80	4.03



# MatteFormer

visualization





# Paper link

Matteformer:

<https://arxiv.org/pdf/2203.15662.pdf>

Rmat:

<https://arxiv.org/pdf/2201.06889.pdf>