## IEEE JOURNAL OF

## SOLID-STATE CIRCUITS

A PUBLICATION OF THE IEEE SOLID-STATE CIRCUITS SOCIETY



JANUARY 2017 VOLUME 52 NUMBER 1 IJSCBC (ISSN 0018-9200)

## SPECIAL ISSUE ON THE 2016 IEEE INTERNATIONAL SOLID-STATE CIRCUITS CONFERENCE

STECKE ISSUE ON THE 2010 IEEE INTERNATIONAL SOCIED STATE CINCOLLS CONTERENCE	
Introduction to the January Special Issue on the 2016 IEEE International Solid-State Circuits Conference	3
DIGITAL CIRCUIT TECHNIQUES	
A 0.0021 mm <sup>2</sup> 1.82 mW 2.2 GHz PLL Using Time-Based Integral Control in 65 nm CMOS	8
A 0.5–9.5-GHz, 1.2-μs Lock-Time Fractional-N DPLL With ±1.25%UI Period Jitter in 16-nm CMOS for Dynamic Frequency and Core-Count Scaling	
	21
Asynchronous 3D Links	33
Postsilicon Voltage Guard-Band Reduction in a 22 nm Graphics Execution Core Using Adaptive Voltage Scaling and Dynamic Power Gating	50
A 200-mA Digital Low Drop-Out Regulator With Coarse-Fine Dual Loop in Mobile Application Processor	64
DIGITAL ARCHITECTURES AND SYSTEMS	
A 16 nm FinFET Heterogeneous Nona-Core SoC Supporting ISO26262 ASIL B Standard	77
A. Grenat, S. Naffziger, T. Burd, S. Kosonocky, S. Liepe, R. Rachala, M. Rodriguez, M. Austin, and S. Sambamurthy An Extended Shared Logarithmic Unit for Nonlinear Function Kernel Acceleration in a 65-nm CMOS Multicore	89
Cluster	98
D. Zhou, S. Wang, H. Sun, J. Zhou, J. Zhu, Y. Zhao, J. Zhou, S. Zhang, S. Kimura, T. Yoshimura, and S. Goto Eyeriss: An Energy-Efficient Reconfigurable Accelerator for Deep Convolutional Neural Networks	113
	127



A 502-GOPS and 0.984-mW Dual-Mode Intelligent ADAS SoC With Real-Time Semiglobal Matching and Intention	
Prediction for Smart Automotive Black Box System	139
IMAGERS, MEMS, MEDICAL AND DISPLAYS A 64×64-Pixels Digital Silicon Photomultiplier Direct TOF Sensor With 100-MPhotons/s/pixel Background Rejection	
and Imaging/Altimeter Mode With 0.14% Precision Up To 6 km for Spacecraft Navigation and Landing	151
Electronic-Photonic Integrated Circuit for 3D Microimaging	161
M. Jiang, V. Hokhikyan, H. Chandrakumar, V. Karkare, and D. Marković  A MEMS-Assisted Temperature Sensor With 20-μK Resolution, Conversion Rate of 200 S/s, and FOM of 0.04 pJK <sup>2</sup>	173
A. Singh, S. Pamarti, N. J. Miller, J. C. Doll, C. Arft, S. Tabatabaei, C. Sechen, A. Partridge, and V. Menon Multipath Wide-Bandwidth CMOS Magnetic Sensors J. Jiang and K. A. A. Makinwa	185 198
MEMORY	
256 Gb 3 b/Cell V-NAND Flash Memory With 48 Stacked WL Layers	
IM. Kim, P. Kwak, BK. Jung, DS. Lee, H. Kim, JD. Ihm, DS. Byeon, JY. Lee, KT. Park, and KH. Kyung  A Resistance Drift Compensation Scheme to Reduce MLC PCM Raw BER by Over 100× for Storage Class Memory  Applications	210
MH. Lee, TH. Su, KH. Yang, TF. Chen, TY. Wang, HP. Li, M. Brightsky, S. Kim, HL. Lung, and C. Lam 5.6 Mb/mm <sup>2</sup> 1R1W 8T SRAM Arrays Operating Down to 560 mV Utilizing Small-Signal Sensing With Charge Shared Bitline and Asymmetric Sense Amplifier in 14 nm FinFET CMOS Technology	218
J. P. Kulkarni, J. Keane, KH. Koo, S. Nalam, Z. Guo, E. Karl, and K. Zhang A 10 nm FinFET 128 Mb SRAM With Assist Adjustment System for Power, Performance, and Area Optimization	229
W. Rim, S. Park, Y. Kim, G. Yang, H. Kim, S. Baek, J. Jung, B. Kwon, S. Cho, H. Jung, Y. Choo, and J. Choi A 1.2 V 20 nm 307 GB/s HBM DRAM With At-Speed Wafer-Level IO Test Scheme and Adaptive Refresh Considering Temperature Distribution K. Sohn, WJ. Yun, R. Oh, CS. Oh, SY. Seo, MS. Park, DH. Shin, WC. Jung,	240
SH. Shin, JM. Ryu, HS. Yu, JH. Jung, H. Lee, SY. Kang, YS. Sohn, JH. Choi, YC. Bae, SJ. Jang, and G. Jin	250
TECHNOLOGY DIRECTIONS  Analysis and Design of a Passive Switched-Capacitor Matrix Multiplier for Approximate Computing  E. H. Lee and S. S. Wong	261
A Nonvolatile Flip-Flop-Enabled Cryptographic Wireless Authentication Tag With Per-Query Key Update and Power-Glitch Attack Countermeasures	272
A Handheld High-Sensitivity Micro-NMR CMOS Platform With B-Field Stabilization for Multi-Type Biological/Chemical Assays KM. Lei, H. Heidari, PI. Mak, MK. Law, F. Maloberti, and R. P. Martins	284
A 0.6-V, 0.015-mm <sup>2</sup> , Time-Based ECG Readout for Ambulatory Applications in 40-nm CMOS	298
Based on Flexible, Thin-Film Electronics	309