

IEEE JOURNAL OF SOLID-STATE CIRCUITS

A PUBLICATION OF THE IEEE SOLID-STATE CIRCUITS SOCIETY



JUNE 2017

VOLUME 52

NUMBER 6

IJSCBC

(ISSN 0018-9200)

REGULAR PAPERS

- A Compact Broadband Mixed-Signal Power Amplifier in Bulk CMOS With Hybrid Class-G and Dynamic Load Trajectory Manipulation *S. Hu, S. Kousai, and H. Wang* 1463
- A 0.42-mW 1-Mb/s 3- to 4-GHz Transceiver in 0.18- μ m CMOS With Flexible Efficiency, Bandwidth, and Distance Control for IoT Applications *D. Liu, X. Ni, R. Zhou, W. Rhee, and Z. Wang* 1479
- A 2.4-GHz ZigBee Transmitter Using a Function-Reuse Class-F DCO-PA and an ADPLL Achieving 22.6% (14.5%) System Efficiency at 6-dBm (0-dBm) P_{out} *X. Peng, J. Yin, P.-I. Mak, W.-H. Yu, and R. P. Martins* 1495
- A 1.9-mm-Precision 20-GHz Direct-Sampling Receiver Using Time-Extension Method for Indoor Localization *H. G. Han, B. G. Yu, and T. W. Kim* 1509
- Design and Self-Calibration Techniques for Inductor-Less Millimeter-Wave Frequency Dividers *A. I. Hussein and J. Paramesh* 1521
- A Dynamic Zoom ADC With 109-dB DR for Audio Applications *B. Gönen, F. Sebastiano, R. Quan, R. van Veldhoven, and K. A. A. Makinwa* 1542
- A 1.2-GS/s 8-bit Two-Step SAR ADC in 65-nm CMOS With Passive Residue Transfer *H. Huang, L. Du, and Y. Chiu* 1551
- A 5.8-Gb/s Adaptive Integrating Duobinary DFE Receiver for Multi-Drop Memory Interface *H.-W. Lim, S.-W. Choi, J.-K. Ahn, W.-K. Min, S.-K. Lee, C.-H. Baek, J.-Y. Lee, G.-C. Hwang, Y.-H. Jun, and B.-S. Kong* 1563
- In Vitro* Multi-Functional Microelectrode Array Featuring 59760 Electrodes, 2048 Electrophysiology Channels, Stimulation, Impedance Measurement, and Neurotransmitter Detection Channels *J. Dragas, V. Viswam, A. Shadmani, Y. Chen, R. Bounik, A. Stettler, M. Radivojevic, S. Geissler, M. E. J. Obien, J. Müller, and A. Hierlemann* 1576
- A Low-Power Digitizer for Back-Illuminated 3-D-Stacked CMOS Image Sensor Readout With Passing Window and Double Auto-Zeroing Techniques *Q. Liu, A. Edward, M. Kinyua, E. G. Soenen, and J. Silva-Martinez* 1591
- A Wide Linear Dynamic Range Image Sensor Based on Asynchronous Self-Reset and Tagging of Saturation Events *J. A. Leñero-Bardallo, R. Carmona-Galán, and Á. Rodríguez-Vázquez* 1605
- Hybrid CMOS/GaN 40-MHz Maximum 20-V Input DC-DC Multiphase Buck Converter *E. Aklimi, D. Piedra, K. Tien, T. Palacios, and K. L. Shepard* 1618
- A 23-mW Face Recognition Processor with Mostly-Read 5T Memory in 40-nm CMOS *D. Jeon, Q. Dong, Y. Kim, X. Wang, S. Chen, H. Yu, D. Blaauw, and D. Sylvester* 1628
- Power Integrity Analysis of a 28 nm Dual-Core ARM Cortex-A57 Cluster Using an All-Digital Power Delivery Monitor *P. N. Whatmough, S. Das, Z. Hadjilambrou, and D. M. Bull* 1643
-

Characterizing the Impact of RTN on Logic and SRAM Operation Using a Dual Ring Oscillator Array Circuit	<i>Q. Tang and C. H. Kim</i>	1655
A 3T1R Nonvolatile TCAM Using MLC ReRAM for Frequent-Off Instant-On Filters in IoT and Big-Data Processing	<i>M.-F. Chang, C.-C. Lin, A. Lee, Y.-N. Chiang, C.-C. Kuo, G.-H. Yang, H.-J. Tsai, T.-F. Chen, and S.-S. Sheu</i>	1664
SHORT REGULAR PAPERS		
A 28-GHz SiGe BiCMOS PA With 32% Efficiency and 23-dBm Output Power	<i>A. Sarkar, F. Aryanfar, and B. A. Floyd</i>	1680
PATENT ABSTRACTS		1687