IEEE JOURNAL OF

SOLID-STATE CIRCUITS

A PUBLICATION OF THE IEEE SOLID-STATE CIRCUITS SOCIETY



SEPTEMBER 2017 VOLUME 52 NUMBER 9	IJSCBC	(ISSN 0018-9200)
-----------------------------------	--------	------------------

New Associate Editor	2223
SPECIAL SECTION ON THE 2016 IEEE BCTM AND IEEE CSICS	
SPECIAL SECTION PAPERS	
Introduction to the Special Section on the 2016 IEEE BCTM and IEEE CSICS B. Sadhu and S. P. Voinigescu	2224
A 76- to 81-GHz Multi-Channel Radar Transceiver	2226
	2242
A Total-Power Radiometer Front End in a 0.25-μm BiCMOS Technology With Low 1/f-Corner	2256
An Ultra-Low-Power Dual-Polarization Transceiver Front-End for 94-GHz Phased Arrays in 130-nm InP HBT	2230
SK. Kim, R. Maurer, A. Simsek, M. Urteaga, and M. J. W. Rodwell W-Band Direct-Modulation >20-Gb/s Transmit and Receive Building Blocks in 32-nm SOI CMOS	2267
	2277
REGULAR PAPERS	
A SAW-Less 2.4-GHz Receiver Front-End With 2.4-mA Battery Current for SoC Coexistence	2292
A 5 GHz Digital Fractional-N PLL Using a 1-bit Delta–Sigma Frequency-to-Digital Converter in 65 nm CMOS M. Talegaonkar,	
T. Anand, A. Elkholy, A. Elshazly, R. K. Nandwana, S. Saxena, B. Young, WS. Choi, and P. K. Hanumolu A High-Speed Efficient 220-GHz Spatial-Orthogonal ASK Transmitter in 130-nm SiGe BiCMOS	2306
	2321
A Flash-Based Non-Uniform Sampling ADC With Hybrid Quantization Enabling Digital Anti-Aliasing Filter	
Analysis and Design of Continuous-Time Delta–Sigma Converters Incorporating Chopping	2335
Analysis and Design of Continuous-Time Detta–Signia Converters incorporating Chopping	2350
A 950 nW Analog-Based Data Reduction Chip for Wearable EEG Systems in Epilepsy	2550
	2362



A Fully Integrated Battery-Powered System-on-Chip in 40-nm CMOS for Closed-Loop Control of Insect-Scale Pico-Aerial Vehicle	
M. Lok, T. Tong, S. K. Lee, B. Reagen, S. Chaput, PE. J. Duhamel, R. J. Wood, D. Brooks, and GY. Wei	2374
Fully Integrated Fluorescence Biosensors On-Chip Employing Multi-Functional Nanoplasmonic Optical Structures in	
CMOS L. Hong, H. Li, H. Yang, and K. Sengupta	2388
A 40-Gb/s 14-mW CMOS Wireline Receiver	2407
A 50 Gb/s 190 mW Asymmetric 3-Tap FFE VCSEL Driver G. Belfiore, M. Khafaji, R. Henker, and F. Ellinger	2422
A Reconfigurable 16/32 Gb/s Dual-Mode NRZ/PAM4 SerDes in 65-nm CMOS	
	2430
A 2.6 μW-1.2 mW Autonomous Electromagnetic Vibration Energy Harvester Interface IC with Conduction-Angle-	
Controlled MPPT and up to 95% Efficiency	2448
A Nanosecond-Transient Fine-Grained Digital LDO With Multi-Step Switching Scheme and Asynchronous Adaptive	
Pipeline Control F. Yang and P. K. T. Mok	2463
Near- and Sub- V_t Pipelines Based on Wide-Pulsed-Latch Design Techniques	
W. Jin, S. Kim, W. He, Z. Mao, and M. Seok	2475
A Dual-Imaging Speed-Enhanced CMOS Image Sensor for Real-Time Edge Image Extraction	
	2488
A Compact-Area Low-VDDmin 6T SRAM With Improvement in Cell Stability, Read Speed, and Write Margin Using	
a Dual-Split-Control-Assist Scheme	
MF. Chang, CF. Chen, TH. Chang, CC. Shuai, YY. Wang, YJ. Chen, and H. Yamauchi	2498
Corrections to "A 10/20/30/40 MHz Feed-Forward FIR DAC Continuous-Time $\Delta\Sigma$ ADC With Robust Blocker	
Performance for Radio Receivers"	2515