

IEEE JOURNAL OF SOLID-STATE CIRCUITS

A PUBLICATION OF THE IEEE SOLID-STATE CIRCUITS SOCIETY



FEBRUARY 2017

VOLUME 52

NUMBER 2

IJSCBC

(ISSN 0018-9200)

REGULAR PAPERS

Injection-Locked Wideband FM Demodulation at IF	<i>A. Visweswaran and J. R. Long</i>	327
Two mm-Wave Vector Modulator Active Phase Shifters With Novel IQ Generator in 28 nm FDSOI CMOS	<i>D. Pepe and D. Zito</i>	344
A High-Gain mm-Wave Amplifier Design: An Analytical Approach to Power Gain Boosting	<i>H. Bameri and O. Momeni</i>	357
Watt-Level mm-Wave Power Amplification With Dynamic Load Modulation in a SiGe HBT Digital Power Amplifier	<i>K. Datta and H. Hashemi</i>	371
Dynamic Waveform Shaping With Picosecond Time Widths	<i>X. Wu and K. Sengupta</i>	389
A 0.92-THz SiGe Power Radiator Based on a Nonlinear Theory for Harmonic Generation	<i>H. Aghasi, A. Cathelin, and E. Afshari</i>	406
A 46 μ W 13 b 6.4 MS/s SAR ADC With Background Mismatch and Offset Calibration	<i>M. Ding, P. Harpe, Y.-H. Liu, B. Busze, K. Philips, and H. de Groot</i>	423
A 12-b ENOB 2.5-MHz BW VCO-Based 0-1 MASH ADC With Direct Digital Background Calibration	<i>K. Ragab and N. Sun</i>	433
A 43-mW MASH 2-2 CT $\Sigma\Delta$ Modulator Attaining 74.4/75.8/76.8 dB of SNDR/SNR/DR and 50 MHz of BW in 40-nm CMOS	<i>A. Edward, Q. Liu, C. Briseno-Vidrios, M. Kinyua, E. G. Soenen, A. I. Karcsilayan, and J. Silva-Martinez</i>	448
A 40-Gb/s SiGe-BiCMOS MZM Driver With 6 V_{p-p} Output and On-Chip Digital Calibration	<i>L. Vera and J. R. Long</i>	460
A 0.4 μ g Bias Instability and 1.2 μ g/ $\sqrt{\text{Hz}}$ Noise Floor MEMS Silicon Oscillating Accelerometer With CMOS Readout Circuit	<i>X. Wang, J. Zhao, Y. Zhao, G. M. Xia, A. P. Qiu, Y. Su, and Y. P. Xu</i>	472
Low-Power CMOS Vision Sensor for Gaussian Pyramid Extraction	<i>M. Suárez, V. M. Brea, J. Fernández-Berni, R. Carmona-Galán, D. Cabello, and Á. Rodríguez-Vázquez</i>	483
Offset-Canceling Current-Sampling Sense Amplifier for Resistive Nonvolatile Memory in 65 nm CMOS	<i>T. Na, B. Song, J. P. Kim, S. H. Kang, and S.-O. Jung</i>	496
A Performance-Aware Low-Quiescent Headphone Amplifier in 65-nm CMOS	<i>F. Xiao and P. K. Chan</i>	505
Design-Oriented Analysis for Miller Compensation and Its Application to Multistage Amplifier Design	<i>W. Qu, S. Singh, Y. Lee, Y.-S. Son, and G.-H. Cho</i>	517
A 0.26-nJ/node, 400-kHz Tx Driving, Filtered Fully Differential Readout IC With Parasitic RC Time Delay Reduction Technique for 65-in 169 \times 97 Capacitive-Type Touch Screen Panel	<i>S.-H. Park, H.-S. Kim, J.-S. Bang, G.-H. Cho, and G.-H. Cho</i>	528

CMOS Microflow Cytometer for Magnetic Label Detection and Classification	<i>P. Murali, A. M. Niknejad, and B. E. Boser</i>	543
A 1000 frames/s Vision Chip Using Scalable Pixel-Neighborhood-Level Parallel Processing	<i>J. A. Schmitz, M. K. Gharzai, S. Balkir, M. W. Hoffman, D. J. White, and N. Schemm</i>	556
A 100 MHz Hybrid Supply Modulator With Ripple-Current-Based PWM Control	<i>M. Tan and W.-H. Ki</i>	569
A Multiphase Switched-Capacitor DC–DC Converter Ring With Fast Transient Response and Small Ripple	<i>Y. Lu, J. Jiang, and W.-H. Ki</i>	579
A 5.28-Gb/s LDPC Decoder With Time-Domain Signal Processing for IEEE 802.15.3c Applications	<i>M.-R. Li, C.-H. Yang, and Y.-L. Ueng</i>	592
3-Gb/s High-Speed True Random Number Generator Using Common-Mode Operating Comparator and Sampling Uncertainty of D Flip-Flop	<i>S.-G. Bae, Y. Kim, Y. Park, and C. Kim</i>	605
PATENT ABSTRACTS		611
