

# IEEE JOURNAL OF SOLID-STATE CIRCUITS

A PUBLICATION OF THE IEEE SOLID-STATE CIRCUITS SOCIETY



APRIL 2017

VOLUME 52

NUMBER 4

IJSCBC

(ISSN 0018-9200)

## SPECIAL ISSUE ON THE 2016 SYMPOSIUM ON VLSI CIRCUITS

New Associate Editor .....	<i>J. Craninckx</i>	887
Introduction to the Special Issue on the 2016 Symposium on VLSI Circuits .....	<i>B. Ginsburg and M. Ikeda</i>	888
SPECIAL ISSUE PAPERS		
KiloCore: A 32-nm 1000-Processor Computational Array .....		
..... <i>B. Bohnenstiehl, A. Stillmaker, J. J. Pimentel, T. Andreas, B. Liu, A. T. Tran, E. Adeagbo, and B. M. Baas</i>		891
An Energy-Efficient Precision-Scalable ConvNet Processor in 40-nm CMOS .....	<i>B. Moons and M. Verhelst</i>	903
In-Memory Computation of a Machine-Learning Classifier in a Standard 6T SRAM Array .....		
..... <i>J. Zhang, Z. Wang, and N. Verma</i>		915
Embedded Memory and ARM Cortex-M0 Core Using 60-nm C-Axis Aligned Crystalline Indium–Gallium–Zinc Oxide FET Integrated With 65-nm Si CMOS .....	<i>T. Onuki, W. Uesugi, A. Isobe, Y. Ando, S. Okamoto, K. Kato, T. R. Yew, J. Y. Wu, C. C. Shuai, S. H. Wu, J. Myers, K. Doppler, M. Fujita, and S. Yamazaki</i>	925
A 0.9 $\mu\text{m}^2$ 1T1R Bit Cell in 14 nm High-Density Metal Fuse Technology for High-Volume Manufacturing and In-Field Programming ....	<i>Z. Chen, S. H. Kulkarni, V. E. Dorgan, S. M. Rajarshi, L. Jiang, and U. Bhattacharya</i>	933
A 4-fJ/b Delay-Hardened Physically Unclonable Function Circuit With Selective Bit Destabilization in 14-nm Trigate CMOS .....	<i>S. Satpathy, S. K. Mathew, V. Suresh, M. A. Anders, H. Kaul, A. Agarwal, S. K. Hsu, G. Chen, R. K. Krishnamurthy, and V. K. De</i>	940
A Low-Power Microcontroller in a 40-nm CMOS Using Charge Recycling ....	<i>K. Blutman, A. Kapoor, A. Majumdar, J. G. Martinez, J. Echeverri, L. Sevat, A. P. van de Wel, H. Fatemi, K. A. A. Makinwa, and J. P. de Gyvez</i>	950
A Sub- $\text{cm}^3$ Energy-Harvesting Stacked Wireless Sensor Node Featuring a Near-Threshold Voltage IA-32 Microcontroller in 14-nm Tri-Gate CMOS for Always-ON Always-Sensing Applications .....		
..... <i>S. Paul, V. Honkote, R. G. Kim, T. Majumder, P. A. Aseron, V. Grossnickle, R. Sankman, D. Mallik, T. Wang, S. Vangal, J. W. Tschanz, and V. De</i>		961
A 20-pW Discontinuous Switched-Capacitor Energy Harvester for Smart Sensor Applications .....		
..... <i>X. Wu, Y. Shi, S. Jeloka, K. Yang, I. Lee, Y. Lee, D. Sylvester, and D. Blaauw</i>		972
8.3 M-Pixel 480-fps Global-Shutter CMOS Image Sensor with Gain-Adaptive Column ADCs and Chip-on-Chip Stacked Integration .....	<i>Y. Oike, K. Akiyama, L. D. Hung, W. Niitsuma, A. Kato, M. Sato, Y. Kato, W. Nakamura, H. Shiroshita, Y. Sakano, Y. Kitano, T. Nakamura, T. Toyama, H. Iwamoto, and T. Ezaki</i>	985
A Front-End ASIC With Receive Sub-array Beamforming Integrated With a 32 $\times$ 32 PZT Matrix Transducer for 3-D Transesophageal Echocardiography .....	<i>C. Chen, Z. Chen, D. Bera, S. B. Raghunathan, M. Shabanmotlagh, E. Niothout, Z.-Y. Chang, J. Ponte, C. Prins, H. J. Vos, J. G. Bosch, M. D. Verweij, N. de Jong, and M. A. P. Pertijs</i>	994

A 2.048 Mb/s Full-Duplex Free-Space Optical Transceiver IC for a Real-Time <i>In Vivo</i> Brain–Computer Interface Mouse Experiment Under Social Interaction .....	<i>G. Hwang, J.-K. Choi, J. Yang, S. Lim, J.-M. Kim, M.-G. Choi, K. Gwak, J. Jeon, I.-H. Choi, S. Park, D.-S. Kim, H. S. Shin, and H.-M. Bae</i>	1007
A Sub-60- $\mu$ A Multimodal Smart Biosensing SoC With >80-dB SNR, 35- $\mu$ A Photoplethysmography Signal Chain ...	<i>A. Sharma, A. Polley, S. B. Lee, S. Narayanan, W. Li, T. Sculley, and S. Ramaswamy</i>	1021
A $\pm$ 36-A Integrated Current-Sensing System With a 0.3% Gain Error and a 400- $\mu$ A Offset From $-55^\circ\text{C}$ to $+85^\circ\text{C}$ .....	<i>S. Heidary Shalmany, D. Draxelmayr, and K. A. A. Makinwa</i>	1034
A BJT-Based Temperature-to-Digital Converter With $\pm 60$ mK ( $3\sigma$ ) Inaccuracy From $-55^\circ\text{C}$ to $+125^\circ\text{C}$ in 0.16 $\mu\text{m}$ CMOS .....	<i>B. Yousefzadeh, S. Heidary Shalmany, and K. A. A. Makinwa</i>	1044
A 0.23- $\mu\text{g}$ Bias Instability and 1- $\mu\text{g}/\sqrt{\text{Hz}}$ Acceleration Noise Density Silicon Oscillating Accelerometer With Embedded Frequency-to-Digital Converter in PLL .....	<i>J. Zhao, X. Wang, Y. Zhao, G. M. Xia, A. P. Qiu, Y. Su, and Y. P. Xu</i>	1053
A 16 b Multi-Step Incremental Analog-to-Digital Converter With Single-Opamp Multi-Slope Extended Counting .....	<i>Y. Zhang, C.-H. Chen, T. He, and G. C. Temes</i>	1066
Edge-Pursuit Comparator: An Energy-Scalable Oscillator Collapse-Based Comparator With Application in a 74.1 dB SNDR and 20 kS/s 15 b SAR ADC .....	<i>M. Shim, S. Jeong, P. D. Myers, S. Bang, J. Shen, C. Kim, D. Sylvester, D. Blaauw, and W. Jung</i>	1077
A 23-mW 24-GS/s 6-bit Voltage-Time Hybrid Time-Interleaved ADC in 28-nm CMOS .....	<i>B. Xu, Y. Zhou, and Y. Chiu</i>	1091
A 56-Gb/s PAM4 Wireline Transceiver Using a 32-Way Time-Interleaved SAR ADC in 16-nm FinFET .....	<i>Y. Frans, J. Shin, L. Zhou, P. Upadhyaya, J. Im, V. Kireev, M. Elzeftawi, H. Hedayati, T. Pham, S. Asuncion, C. Borrelli, G. Zhang, H. Zhang, and K. Chang</i>	1101
A 16-Gb/s 14.7-mW Tri-Band Cognitive Serial Link Transmitter With Forwarded Clock to Enable PAM-16/256-QAM and Channel Response Detection .....	<i>Y. Du, W.-H. Cho, P.-T. Huang, Y. Li, C.-H. Wong, J. Du, Y. Kim, B. Hu, L. Du, C. Liu, S. J. Lee, and M.-C. F. Chang</i>	1111
A $-244$ -dB FOM High-Frequency Piezoelectric Resonator-Based Cascaded Fractional-N PLL With Sub-ppb-Order Channel-Adjusting Technique .....	<i>S. Ikeda, H. Ito, A. Kasamatsu, Y. Ishikawa, T. Obara, N. Noguchi, K. Kamisuki, Y. Jiyang, S. Hara, D. Ruibing, S. Dosho, N. Ishihara, and K. Masu</i>	1123
DPLL for Phase Noise Cancellation in Ring Oscillator-Based Quadrature Receivers .....	<i>Z.-Z. Chen, Y.-C. Kuan, Y. Li, B. Hu, C.-H. Wong, and M.-C. F. Chang</i>	1134
A Bluetooth Low-Energy Transceiver With 3.7-mW All-Digital Transmitter, 2.75-mW High-IF Discrete-Time Receiver, and TX/RX Switchable On-Chip Matching Network .....	<i>F.-W. Kuo, S. Binsfeld Ferreira, H.-N. R. Chen, L.-C. Cho, C.-P. Jou, F.-L. Hsueh, I. Madadi, M. Tohidian, M. Shahmohammadi, M. Babaie, and R. B. Staszewski</i>	1144
SleepTalker: A ULV 802.15.4a IR-UWB Transmitter SoC in 28-nm FDSOI Achieving 14 pJ/b at 27 Mb/s With Channel Selection Based on Adaptive FBB and Digitally Programmable Pulse Shaping .....	<i>G. de Streel, F. Stas, T. Gurné, F. Durant, C. Frenkel, A. Cathelin, and D. Bol</i>	1163