

IEEE JOURNAL OF SOLID-STATE CIRCUITS

A PUBLICATION OF THE IEEE SOLID-STATE CIRCUITS SOCIETY



MAY 2017

VOLUME 52

NUMBER 5

IJSCBC

(ISSN 0018-9200)

SPECIAL SECTION ON THE 2016 RADIO FREQUENCY INTEGRATED CIRCUITS (RFIC) SYMPOSIUM

Introduction to the Special Section on the 2016 Radio Frequency Integrated Circuits (RFIC) Symposium	<i>D. Manstretta</i>	1183
SPECIAL SECTION PAPERS		
A 1–3 GHz Delta–Sigma-Based Closed-Loop Fully Digital Phase Modulator in 45-nm CMOS SOI	<i>H. Gheidi, T. Nakatani, V. W. Leung, and P. M. Asbeck</i>	1185
A Digital Polar Transmitter With DC–DC Converter Supporting 256-QAM WLAN and 40-MHz LTE-A Carrier Aggregation	<i>Q. Zhu, S. Yu, S. Wang, L. Huang, Z. Wang, X. Zhang, and Y. Xu</i>	1196
An 802.11a/b/g/n Digital Fractional- N PLL With Automatic TDC Linearity Calibration for Spur Cancellation	<i>D. Liao, H. Wang, F. F. Dai, Y. Xu, R. Berenguer, and S. M. Hermoso</i>	1210
An RF-Powered FDD Radio for Neural Microimplants	<i>Y. Rajavi, M. Taghivand, K. Aggarwal, A. Ma, and A. S. Y. Poon</i>	1221
A 28-GHz Phased-Array Receiver Front End With Dual-Vector Distributed Beamforming	<i>Y.-S. Yeh, B. Walker, E. Balboni, and B. Floyd</i>	1230
A 94-GHz 4TX–4RX Phased-Array FMCW Radar Transceiver With Antenna-in-Package	<i>A. Townley, P. Swirhun, D. Titz, A. Bisognin, F. Ganesello, R. Pilard, C. Luxey, and A. M. Niknejad</i>	1245
An All-Passive Negative Feedback Network for Broadband and Wide Field-of-View Self-Steering Beam-Forming With Zero DC Power Consumption	<i>M.-Y. Huang, T. Chi, F. Wang, and H. Wang</i>	1260
A Wideband Fully Integrated Software-Defined Transceiver for FDD and TDD Operation	<i>H. Yüksel, D. Yang, Z. Boynton, C. Lee, T. Tapen, A. Molnar, and A. Apsel</i>	1274
A Mixer Front End for a Four-Channel Modulated Wideband Converter With 62-dB Blocker Rejection	<i>D. Adams, Y. C. Eldar, and B. Murmann</i>	1286
Voltage Mode Doherty Power Amplifier	<i>V. Vorapipat, C. S. Levy, and P. M. Asbeck</i>	1295
High-Breakdown, High- f_{\max} Multiport Stacked-Transistor Topologies for the W -Band Power Amplifiers	<i>K. Datta and H. Hashemi</i>	1305
A Multiphase Switched Capacitor Power Amplifier	<i>W. Yuan and J. S. Walling</i>	1320

REGULAR PAPERS

A Wideband Noise-Canceling CMOS LNA With Enhanced Linearity by Using Complementary nMOS and pMOS Configurations	<i>B. Guo, J. Chen, L. Li, H. Jin, and G. Yang</i>	1331
Efficient Digital Quadrature Transmitter Based on IQ Cell Sharing	<i>H. Jin, D. Kim, and B. Kim</i>	1345
A CMOS Passive LPTV Nonmagnetic Circulator and Its Application in a Full-Duplex Receiver	<i>N. Reiskarimian, J. Zhou, and H. Krishnaswamy</i>	1358
A 60-GHz Dual-Vector Doherty Beamformer	<i>K. Greene, A. Sarkar, and B. Floyd</i>	1373
A 0.7-V 0.6- μ W 100-kS/s Low-Power SAR ADC With Statistical Estimation-Based Noise Reduction	<i>L. Chen, X. Tang, A. Sanyal, Y. Yoon, J. Cong, and N. Sun</i>	1388
A 2.8 mW/Gb/s, 14 Gb/s Serial Link Transceiver	<i>S. Saxena, G. Shu, R. K. Nandwana, M. Talegaonkar, A. Elkholy, T. Anand, W.-S. Choi, and P. K. Hanumolu</i>	1399
A 6.78-MHz Single-Stage Wireless Power Receiver Using a 3-Mode Reconfigurable Resonant Regulating Rectifier	<i>L. Cheng, W.-H. Ki, and C.-Y. Tsui</i>	1412
An AC Input Switching-Converter-Free LED Driver With Low-Frequency-Flicker Reduction	<i>Y. Gao, L. Li, and P. K. T. Mok</i>	1424
A 58-nm 2-Gb MLC “B4-Flash” Memory with Flexible Multisector Architecture	<i>T. Ogura, Y. Kasa, K. Kurosaki, M. Tomoeda, H. Otoi, S. Shimizu, M. Katsumata, N. Ajika, and K. Kobayashi</i>	1435

SHORT REGULAR PAPERS

A Subthreshold Voltage Reference With Scalable Output Voltage for Low-Power IoT Systems	<i>I. Lee, D. Sylvester, and D. Blaauw</i>	1443
A 1.5-GHz 6.144T Correlations/s 64×64 Cross-Correlator With 128 Integrated ADCs for Real-Time Synthetic Aperture Imaging	<i>J. Bell, P. Knag, S. Sun, Y. Lim, T. Chen, J. Fredenburg, C.-H. Chen, C. Zhai, A. Rocca, N. Collins, A. Tamez, J. A. Pernillo, J. M. Correll, A. B. Tanner, Z. Zhang, and M. P. Flynn</i>	1450
