

IEEE JOURNAL OF SOLID-STATE CIRCUITS

A PUBLICATION OF THE IEEE SOLID-STATE CIRCUITS SOCIETY



MARCH 2017

VOLUME 52

NUMBER 3

IJSCBC

(ISSN 0018-9200)

REGULAR PAPERS

A 5.6 ppm/°C Temperature Coefficient, 87-dB PSRR, Sub-1 V Voltage Reference in 65-nm CMOS Exploiting the Zero-Temperature-Coefficient Point	<i>J. Jiang, W. Shu, and J. S. Chang</i>	623
A Low Voltage SRAM Using Resonant Supply Boosting	<i>R. V. Joshi, M. M. Ziegler, and H. Wetter</i>	634
A High Dynamic-Range Neural Recording Chopper Amplifier for Simultaneous Neural Recording and Stimulation	<i>H. Chandrakumar and D. Marković</i>	645
A 75-MHz Continuous-Time Sigma-Delta Modulator Employing a Broadband Low-Power Highly Efficient Common-Gate Summing Stage	<i>C. Briseno-Vidrios, A. Edward, A. Shafik, S. Palermo, and J. Silva-Martinez</i>	657
A Pipeline Replica Bitline Technique for Suppressing Timing Variation of SRAM Sense Amplifiers in a 28-nm CMOS Process	<i>Z. Lin, X. Wu, Z. Li, L. Guan, C. Peng, C. Liu, and J. Chen</i>	669
A Self-Powered 50-Mb/s OOK Transmitter for Optoisolator LED Emulation	<i>S. S. Mallia, N. S. Sreeram, S. Adinarayana, and S. Aniruddhan</i>	678
A 103.125-Gb/s Reverse Gearbox IC in 40-nm CMOS for Supporting Legacy 10- and 40-GbE Links	<i>T. Yoon, J.-Y. Lee, J. Lee, K. Han, J.-S. Lee, S. Lee, T. Kim, J. Han, H. Won, J. Park, and H.-M. Bae</i>	688
A Fully Integrated Reconfigurable Self-Startup RF Energy-Harvesting System With Storage Capability	<i>M. A. Abouzied, K. Ravichandran, and E. Sánchez-Sinencio</i>	704
An Energy-Efficient Miniaturized Intracranial Pressure Monitoring System	<i>M. M. Ghanbari, J. M. Tsai, A. Nirmalathas, R. Muller, and S. Gambini</i>	720
Beamformer With Constant-Gm Vector Modulators and Its Spatial Intermodulation Distortion	<i>M. C. M. Soer, E. A. M. Klumperink, D.-J. van den Broek, B. Nauta, and F. E. van Vliet</i>	735
A 25 Gb/s 1.13 pJ/b –10.8 dBm Input Sensitivity Optical Receiver in 40 nm CMOS	<i>S.-H. Huang and W.-Z. Chen</i>	747
A Pseudo OFDM With Miniaturized FSK Demodulation Body-Coupled Communication Transceiver for Binaural Hearing Aids in 65 nm CMOS	<i>W. Saadeh, M. A. B. Altaf, H. Alsuradi, and J. Yoo</i>	757
Pole-Converging Intrastage Bandwidth Extension Technique for Wideband Amplifiers	<i>G. Feng, C. C. Boon, F. Meng, X. Yi, K. Yang, C. Li, and H. C. Luong</i>	769
A 36-V 49% Efficient Hybrid Charge Pump in Nanometer-Scale Bulk CMOS Technology	<i>Y. Ismail, H. Lee, S. Pamarti, and C.-K. K. Yang</i>	781
A 0.2–1.45-GHz Subsampling Fractional- <i>N</i> Digital MDLL With Zero-Offset Aperture PD-Based Spur Cancellation and <i>In Situ</i> Static Phase Offset Detection	<i>S. Kundu, B. Kim, and C. H. Kim</i>	799

(Contents Continued on Back Cover)

Implicit Common-Mode Resonance in <i>LC</i> Oscillators	<i>D. Murphy, H. Darabi, and H. Wu</i>	812
An Ultralow Power System on Chip for Automatic Sleep Staging <i>S. A. Imtiaz, Z. Jiang, and E. Rodriguez-Villegas</i>	822
Compact Thermal-Diffusivity-Based Temperature Sensors in 40-nm CMOS for SoC Thermal Monitoring <i>U. Sönmez, F. Sebastiano, and K. A. A. Makinwa</i>	834
A 58.6 mW 30 Frames/s Real-Time Programmable Multiobject Detection Accelerator With Deformable Parts Models on Full HD 1920×1080 Videos <i>A. Suleiman, Z. Zhang, and V. Sze</i>	844
A DC-to-12.5 Gb/s 9.76 mW/Gb/s All-Rate CDR With a Single <i>LC</i> VCO in 90 nm CMOS <i>J.-H. Yoon, S.-W. Kwon, and H.-M. Bae</i>	856
A 370-pJ/b Multichannel BFSK/QPSK Transmitter Using Injection-Locked Fractional-N Synthesizer for Wireless Biotelemetry Devices <i>K.-H. Teng and C.-H. Heng</i>	867
