

IEEE JOURNAL OF SOLID-STATE CIRCUITS

A PUBLICATION OF THE IEEE SOLID-STATE CIRCUITS SOCIETY



JULY 2018

VOLUME 53

NUMBER 7

IJSCBC

(ISSN 0018-9200)

SPECIAL ISSUE ON THE 47TH EUROPEAN SOLID-STATE CIRCUITS CONFERENCE (ESSCIRC)

New Associate Editor	<i>J. Craninckx</i>	1875
Special Issue on the 47th European Solid-State Circuits Conference (ESSCIRC)	<i>A. Bevilacqua, S. Das, and P. Harpe</i>	1876

SPECIAL ISSUE PAPERS

Analog and Data Converters

A 13-mW 64-dB SNDR 280-MS/s Pipelined ADC Using Linearized Integrating Amplifiers	<i>R. Sehgal, F. van der Goes, and K. Bult</i>	1878
A 1.25-GS/s 7-b SAR ADC With 36.4-dB SNDR at 5 GHz Using Switch-Bootstrapping, USPC DAC and Triple-Tail Comparator in 28-nm CMOS	<i>A. T. Ramkaj, M. Strackx, M. S. J. Steyaert, and F. Tavernier</i>	1889
A 1.2-V Dynamic Bias Latch-Type Comparator in 65-nm CMOS With 0.4-mV Input Noise	<i>H. S. Bindra, C. E. Lokin, D. Schinkel, A.-J. Annema, and B. Nauta</i>	1902
A 0.1% THD, 1-M Ω to 1-G Ω Tunable, Temperature-Compensated Transimpedance Amplifier Using a Multi-Element Pseudo-Resistor	<i>D. Djekic, G. Fantner, K. Lips, M. Ortmanns, and J. Anders</i>	1913
A 93.3% Peak-Efficiency Self-Resonant Hybrid-Switched-Capacitor LED Driver in 0.18- μ m CMOS Technology	<i>J. C. Castellanos, M. Turhan, and E. Cantatore</i>	1924
A 48-V Wide- V_{in} 9–25-MHz Resonant DC–DC Converter	<i>J. Wittmann, T. Funk, T. Rosahl, and B. Wicht</i>	1936

RF Circuits

An FDD Wireless Diversity Receiver With Transmitter Leakage Cancellation in Transmit and Receive Bands	<i>D. Montanari, G. Castellano, E. Kargaran, G. Pini, S. Tijani, D. De Caro, A. G. M. Strollo, D. Manstretta, and R. Castello</i>	1945
A 65-nm CMOS 2 \times 2 MIMO Multi-Band LTE RF Transceiver for Small Cell Base Stations	<i>K. Lim, S. Lee, Y. Lee, B. Moon, H. Shin, K. Kang, S. Kim, J. Lee, H. Lee, H. Shim, C. Sung, K. Park, G. Lee, M. Kim, S. Park, H. Jung, Y. Lim, C. Song, J. Seong, H. Cho, J. Choi, J. Lee, and S. Han</i>	1960
A Low-Flicker-Noise 30-GHz Class-F ₂₃ Oscillator in 28-nm CMOS Using Implicit Resonance and Explicit Common-Mode Return Path	<i>Y. Hu, T. Siriburanon, and R. B. Staszewski</i>	1977
A 28-nm FD-SOI 115-fs Jitter PLL-Based LO System for 24–30-GHz Sliding-IF 5G Transceivers	<i>S. Ek, T. Prahlsso, C. Elgaard, A. Carlsson, A. Axhult, A.-K. Stenman, L. Sundström, and H. Sjöland</i>	1988
A 60-GHz 8-Way Phased-Array Front-End With T/R Switching and Calibration-Free Beamsteering in 28-nm CMOS	<i>K. Khalaf, K. Vaesen, S. Brebels, G. Mangraviti, M. Libois, C. Soens, W. Van Thillo, and P. Wambacq</i>	2001

(Contents Continued on Back Cover)

A D-Band Digital Transmitter with 64-QAM and OFDM Free-Space Constellation Formation	2012
..... S. Shopov, O. D. Gurbuz, G. M. Rebeiz, and S. P. Voinigescu	
Bidirectional Communication Circuits for a 120-GHz PMF Data Link in 40-nm CMOS	2023
..... N. Van Thienen, Y. Zhang, and P. Reynaert	
<i>Sensor Systems</i>	
Isolator-Less Near-Field RFID Reader for Sub-Cranial Powering/Data Link of Millimeter-Sized Implants	2032
..... C. Sutardja and J. M. Rabaey	
A Battery-Powered Wireless Ion Sensing System Consuming 5.5 nW of Average Power	2043
..... H. Wang, X. Wang, A. Barfidokht, J. Park, J. Wang, and P. P. Mercier	
High-Density Redox Amplified Coulostatic Discharge-Based Biosensor Array	2054
..... A. C. Sun, E. Alvarez-Fontecilla, A. G. Venkatesh, E. Aronoff-Spencer, and D. A. Hall	
A Reconfigurable Ultrasound Transceiver ASIC With 24×40 Elements for 3-D Carotid Artery Imaging	2065
..... E. Kang, Q. Ding, M. Shabanimotlagh, P. Kruizinga, Z.-Y. Chang, E. Noothout, H. J. Vos, J. G. Bosch, M. D. Verweij, N. de Jong, and M. A. P. Pertijs	
A Multi-Sensor and Parallel Processing SoC for Miniaturized Medical Instrumentation	2076
..... P. Schönle, F. Glaser, T. Burger, G. Rovere, L. Benini, and Q. Huang	
<i>Digital Computing Systems</i>	
A 2.7 pJ/cycle 16 MHz, 0.7 μ W Deep Sleep Power ARM Cortex-M0+ Core SoC in 28 nm FD-SOI	2088
..... G. Lallement, F. Abouzeid, M. Cochet, J.-M. Daveau, P. Roche, and J.-L. Autran	
Margin Elimination Through Timing Error Detection in a Near-Threshold Enabled 32-bit Microcontroller in 40-nm CMOS	2101
..... H. Reyserhove and W. Dehaene	
A 32-KB ePCM for Real-Time Data Processing in Automotive and Smart Power Applications	2114
..... M. Pasotti, R. Zurla, M. Carissimi, C. Auricchio, D. Brambilla, E. Calvetti, L. Capecchi, L. Croce, D. Gallinari, C. Mazzaglia, V. Rana, A. Cabrini, and G. Torelli	
A 19.4-nJ/Decision, 364-K Decisions/s, In-Memory Random Forest Multi-Class Inference Accelerator	2126
..... M. Kang, S. K. Gonugondla, S. Lim, and N. R. Shanbhag	
An 800-MHz Mixed- V_T 4T IFGC Embedded DRAM in 28-nm CMOS Bulk Process for Approximate Storage Applications	2136
..... R. Gitterman, A. Fish, N. Geuli, E. Mentovich, A. Burg, and A. Teman	
