IEEE JOURNAL OF

SOLID-STATE CIRCUITS

A PUBLICATION OF THE IEEE SOLID-STATE CIRCUITS SOCIETY



SEPTEMBER 2018 VOLUME 53 NUMBER 9 IJSCBC (ISSN 0018-9200)

SPECIAL SECTION ON THE 2017 IEEE BCTM AND IEEE CSICS CONFERENCES

EDITORIAL Introduction to the Special Section on the 2017 IEEE BCTM and IEEE CSICS Conferences	
SPECIAL SECTION PAPERS	
A 61-GHz SiGe Transceiver Frontend for Energy and Data Transmission of Passive RFID Single-Chip Tags With Integrated Antennas C. Bredendiek, D. A. Funke, J. Schöpfel, V. Kloubert, B. Welp, K. Aufinger, and N. Pohl A Multi-Phase Coupled Oscillator Using Inductive Resonant Coupling and Modified Dual-Tank Techniques	2441
	2454
D-Band Frequency Quadruplers in BiCMOS Technology	
	2465
	2479
A Fully Decoupled LC Tank VCO Topology for Amplitude Boosted Low Phase Noise Operation	2488
A Capacitively Coupled, Pseudoreturn-to-Zero Input, Latched-Bias Data Receiver	2.00
Fully Integrated 94-GHz Dual-Polarized TX and RX Phased Array Chipset in SiGe BiCMOS Operating up to 105 °C	2500
C. Ozdag, Y. Aydogan, M. Yeck, A. Cabuk, A. Kepkep, S. K. Reynolds, E. Apaydin, and A. Valdes-Garcia	2512
REGULAR PAPERS Wideband 240-GHz Transmitter and Receiver in BiCMOS Technology With 25-Gbit/s Data Rate	
	2532
	2543
E-Band Multi-Phase LC Oscillators With Rotated-Phase-Tuning Using Implicit Phase Shifters L. Wu and Q. Xue A 0.5-V 1.6-mW 2.4-GHz Fractional-N All-Digital PLL for Bluetooth LE With PVT-Insensitive TDC Using Switched-Capacitor Doubler in 28-nm CMOS	2560
	2572



A Time-Interleaved 12-b 270-MS/s SAR ADC With Virtual-Timing-Reference Timing-Skew Calibration Scheme HW. Kang, HK. Hong, W. Kim, and ST. Ryu	2584
A 0.44-fJ/Conversion-Step 11-Bit 600-kS/s SAR ADC With Semi-Resting DAC SE. Hsieh and CC. Hsieh	2595
A 0.006 mm 2 1.2 μ W Analog-to-Time Converter for Asynchronous Bio-Sensors	
L. B. Leene and T. G. Constandinou	2604
Super Class-AB Recycling Folded Cascode OTA	2614
A Regulation-Free Sub-0.5-V 16-/24-MHz Crystal Oscillator With 14.2-nJ Startup Energy and 31.8-μW Steady-State Power	2624
A Sub-0.1°/h Bias-Instability Split-Mode MEMS Gyroscope With CMOS Readout Circuit	2636
Single Photon-Counting Pixel Readout Chip Operating up to 1.2 Gcps/mm ² for Digital X-Ray Imaging Systems	
A Fully Integrated Buck Regulator With 2-GHz Resonant Switching for Low-Power Applications	2651
An External Capacitorless Low-Dropout Regulator With High PSR at All Frequencies From 10 kHz to 1 GHz Using	2663
an Adaptive Supply-Ripple Cancellation Technique	2675
A 4×45 Gb/s Two-Tap FFE VCSEL Driver in 14-nm FinFET CMOS Suitable for Burst Mode Operation	2686
Loop Gain Adaptation for Optimum Jitter Tolerance in Digital CDRs	2696
CMOS Optical PUFs Using Noise-Immune Process-Sensitive Photonic Crystals Incorporating Passive Variations for	2090
Robustness X. Lu, L. Hong, and K. Sengupta	2709
DNN Engine: A 28-nm Timing-Error Tolerant Sparse Deep Neural Network Processor for IoT Applications	2722
COMMENTS AND CORRECTIONS	
Corrections to "Split-Array, C-2C Switched-Capacitor Power Amplifiers"	
	2732
Using an LPTV Resistor"	2733