

ASSIGNMENT – 1

DDL COMMANDS (Create, Alter, Drop,)

1) Create Command - CREATE command is to **define the structure of an object before storing data in it.**

```
CREATE TABLE Restuarant(  
    Order_ID INT,  
    Customer_Name VARCHAR(50),  
    Customer_Phone_Number VARCHAR(100),  
    Cuisine_Name VARCHAR(100)  
);
```

```
INSERT INTO Restuarant VALUES  
(092456,'Sachith',1234567890,'NorthIndian'),  
(123456,'Nitish',4455667890,'SouthIndian'),  
(033256,'Shreyas',7745362846,'Chats'),  
(093214,'Raghu',9905468462,'Chinese'),  
(198432,'Shrihan',6635284642,'Japanese'),  
(882542,'Swayam',7130184627,'Continental');
```

```
SELECT * FROM Restuarant;
```

The screenshot shows the OneCompiler interface with a MySQL query editor. The query is as follows:

```

1 CREATE TABLE Restuarant(
2     Order_ID INT,
3     Customer_Name VARCHAR (50),
4     Customer_Phone_Number VARCHAR (100),
5     Cuisine_Name VARCHAR (100)
6 );
7 SHOW TABLES;
8
9 INSERT INTO Restuarant VALUES
10 (892456,'Sachith','1234567890','NorthIndian'),
11 (123456,'Nitish','4455667890','SouthIndian'),
12 (833256,'Shreyas','7745362846','Chats'),
13 (893214,'Raghu','9905468462','Chinese'),
14 (198432,'Shrihan','6635284642','Japanese'),
15 (882542,'Swayam','7130184627','Continental');
16
17 SELECT * FROM Restuarant;
18

```

The output shows the table structure and the inserted data:

```

Output:
+-----+
| Tables_in_sandbox_db |
+-----+
| restaurant            |
+-----+
+-----+
| Order_ID | Customer_Name | Customer_Phone_Number | Cuisine_Name |
+-----+
| 92456    | Sachith       | 1234567890            | NorthIndian  |
| 123456   | Nitish        | 4455667890            | SouthIndian  |
| 33256    | Shreyas       | 7745362846            | Chats        |
| 93214    | Raghu         | 9905468462            | Chinese      |
| 198432   | Shrihan       | 6635284642            | Japanese     |
| 882542   | Swayam        | 7130184627            | Continental  |
+-----+

```

2) Alter Command - Used to modify the structure of an existing table without deleting it.

ALTER TABLE Restuarant

ADD Order_Price INT;

SELECT * FROM Restuarant;

The screenshot shows the OneCompiler interface with a MySQL query editor. The query is as follows:

```

1 CREATE TABLE Restuarant(
2     Order_ID INT,
3     Customer_Name VARCHAR(50),
4     Customer_Phone_Number VARCHAR(100),
5     Cuisine_Name VARCHAR(100)
6 );
7
8 INSERT INTO Restuarant VALUES
9 (892456,'Sachith','1234567890','NorthIndian'),
10 (123456,'Nitish','4455667890','SouthIndian'),
11 (833256,'Shreyas','7745362846','Chats'),
12 (893214,'Raghu','9905468462','Chinese'),
13 (198432,'Shrihan','6635284642','Japanese'),
14 (882542,'Swayam','7130184627','Continental');
15
16 SELECT * FROM Restuarant;
17
18 ALTER TABLE Restuarant
19 ADD Order_Price INT;
20
21 SELECT * FROM Restuarant;
22

```

The output shows the table structure and the inserted data, including the new column:

```

Output:
+-----+
| Order_ID | Customer_Name | Customer_Phone_Number | Cuisine_Name | Order_Price |
+-----+
| 92456    | Sachith       | 1234567890            | NorthIndian  | NULL        |
| 123456   | Nitish        | 4455667890            | SouthIndian  | NULL        |
| 33256    | Shreyas       | 7745362846            | Chats        | NULL        |
| 93214    | Raghu         | 9905468462            | Chinese      | NULL        |
| 198432   | Shrihan       | 6635284642            | Japanese     | NULL        |
| 882542   | Swayam        | 7130184627            | Continental  | NULL        |
+-----+

```

3) Drop Command - Command used to permanently delete a database object such as a table, database, or column.

The screenshot displays the OneCompiler web interface. The top navigation bar includes the OneCompiler logo, a "Upgrade" button, and icons for AI assistance, MySQL version selection, running the program, and user account management.

The main editor area shows a file named "queries.sql" containing the following SQL script:

```
1 CREATE TABLE Restaurant(  
2     Order_ID INT,  
3     Customer_Name VARCHAR(50),  
4     Customer_Phonenumber VARCHAR(100),  
5     Cuisine_Name VARCHAR(100)  
6 );  
7  
8 INSERT INTO Restaurant VALUES  
9 (092456,'Sachith','1234567890','NorthIndian'),  
10 (123456,'Nitiish','4455667890','SouthIndian'),  
11 (033256,'Shreyas','7745362846','Chats'),  
12 (093214,'Raghu','9905468462','Chinese'),  
13 (198432,'Shrihan','6635284642','Japanese'),  
14 (882542,'Swayan','7138184627','Continental');  
15  
16 SELECT * FROM Restaurant;  
17  
18 ALTER TABLE Restaurant  
19 ADD Order_Price INT;  
20  
21 SELECT * FROM Restaurant;  
22  
23 ALTER TABLE Restaurant  
24 DROP COLUMN Order_Price;  
25  
26 SELECT * FROM Restaurant;
```

The output section shows the results of the queries. It starts with a message "Input for the program (optional)" and then displays two tables. The first table is the result of the initial SELECT query, showing 5 rows of restaurant data. The second table is the result of the SELECT query after adding the Order_Price column, showing 5 rows with NULL values for the new column. The third table is the result of the SELECT query after dropping the Order_Price column, showing 5 rows without the new column.

Github Link - <https://github.com/cr-sparsh/dbms-3-sem>