








Ensure you mark as  
*Protected / Secret*  
sensitive variables in  
your C.I. system

Type		Key	Value	State
Variable	⬆	KUBE_URL	https://1.2.3.4	Protected <input type="checkbox"/>
File	⬆	KUBE_CA_PEM	-----BEGIN CERTIFICATE--- -- MIICyDCCAbCg	Protected <input type="checkbox"/>





Then ENV Leak!! (2/2)





Secrets

Actions

[Dependabot](#)

## Repository secrets



PYPI\_PASSWORD

Updated on 28 Aug

Update

Remove





# The ENV Leak! (2/2)


Ensure you mark as  
*Protected / Secret*  
sensitive variables in  
your C.I. system

Type	Key	Value	State
Variable	KUBE_URL	https://1.2.3.4	Protected <input checked="" type="checkbox"/>
File	KUBE_CA_PEM	-----BEGIN CERTIFICATE--- == MIICyDCCAbCg	Protected <input checked="" type="checkbox"/>

Secrets

Actions  
Dependabot

Repository secrets

 PYPI\_PASSWORD Updated on 28 Aug Update Remove





# A reverse **Shell** in the Pipeline

- What if an user can execute anything in a Pipeline?
- What if the C.I. has not limited the output traffic?