

Class 12: RNA-Seq Analysis Mini-Project

Chantal Rabay

2/28/2022

Section 1. Differential Expression Analysis

```
library(DESeq2)
```

```
## Loading required package: S4Vectors
```

```
## Loading required package: stats4
```

```
## Loading required package: BiocGenerics
```

```
##
```

```
## Attaching package: 'BiocGenerics'
```

```
## The following objects are masked from 'package:stats':
```

```
##
```

```
##      IQR, mad, sd, var, xtabs
```

```
## The following objects are masked from 'package:base':
```

```
##
```

```
##      anyDuplicated, append, as.data.frame, basename, cbind, colnames,  
##      dirname, do.call, duplicated, eval, evalq, Filter, Find, get, grep,  
##      grepl, intersect, is.unsorted, lapply, Map, mapply, match, mget,  
##      order, paste, pmax, pmax.int, pmin, pmin.int, Position, rank,  
##      rbind, Reduce, rownames, sapply, setdiff, sort, table, tapply,  
##      union, unique, unsplit, which.max, which.min
```

```
##
```

```
## Attaching package: 'S4Vectors'
```

```
## The following objects are masked from 'package:base':
```

```
##
```

```
##      expand.grid, I, unname
```

```
## Loading required package: IRanges
```

```
## Loading required package: GenomicRanges
```

```

## Loading required package: GenomeInfoDb

## Loading required package: SummarizedExperiment

## Loading required package: MatrixGenerics

## Loading required package: matrixStats

##
## Attaching package: 'MatrixGenerics'

## The following objects are masked from 'package:matrixStats':
##
##   colAlls, colAnyNAs, colAnys, colAvgPerRowSet, colCollapse,
##   colCounts, colCummaxs, colCummins, colCumprods, colCumsums,
##   colDiffs, colIQRDiffs, colIQRs, colLogSumExps, colMadDiffs,
##   colMads, colMaxs, colMeans2, colMedians, colMins, colOrderStats,
##   colProds, colQuantiles, colRanges, colRanks, colSdDiffs, colSds,
##   colSums2, colTabulates, colVarDiffs, colVars, colWeightedMads,
##   colWeightedMeans, colWeightedMedians, colWeightedSds,
##   colWeightedVars, rowAlls, rowAnyNAs, rowAnys, rowAvgPerColSet,
##   rowCollapse, rowCounts, rowCummaxs, rowCummins, rowCumprods,
##   rowCumsums, rowDiffs, rowIQRDiffs, rowIQRs, rowLogSumExps,
##   rowMadDiffs, rowMads, rowMaxs, rowMeans2, rowMedians, rowMins,
##   rowOrderStats, rowProds, rowQuantiles, rowRanges, rowRanks,
##   rowSdDiffs, rowSds, rowSums2, rowTabulates, rowVarDiffs, rowVars,
##   rowWeightedMads, rowWeightedMeans, rowWeightedMedians,
##   rowWeightedSds, rowWeightedVars

## Loading required package: Biobase

## Welcome to Bioconductor
##
##   Vignettes contain introductory material; view with
##   'browseVignettes()'. To cite Bioconductor, see
##   'citation("Biobase")', and for packages 'citation("pkgname)".

##
## Attaching package: 'Biobase'

## The following object is masked from 'package:MatrixGenerics':
##
##   rowMedians

## The following objects are masked from 'package:matrixStats':
##
##   anyMissing, rowMedians

Load our data files.

```

```
metaFile <- "GSE37704_metadata.csv"
countFile <- "GSE37704_featurecounts.csv"

# Import metadata and take a peak
colData = read.csv(metaFile, row.names=1)
head(colData)
```

```
##           condition
## SRR493366 control_sirna
## SRR493367 control_sirna
## SRR493368 control_sirna
## SRR493369      hoxa1_kd
## SRR493370      hoxa1_kd
## SRR493371      hoxa1_kd
```

```
# Import countdata
countData = read.csv(countFile, row.names=1)
head(countData)
```

```
##           length SRR493366 SRR493367 SRR493368 SRR493369 SRR493370
## ENSG00000186092      918         0         0         0         0         0
## ENSG00000279928      718         0         0         0         0         0
## ENSG00000279457     1982        23        28        29        29        28
## ENSG00000278566      939         0         0         0         0         0
## ENSG00000273547      939         0         0         0         0         0
## ENSG00000187634     3214        124        123        205        207        212
##           SRR493371
## ENSG00000186092         0
## ENSG00000279928         0
## ENSG00000279457        46
## ENSG00000278566         0
## ENSG00000273547         0
## ENSG00000187634       258
```

Q. Complete the code below to remove the troublesome first column from countData.

```
# Note we need to remove the odd first $length col
countData <- as.matrix(countData[,-1])
head(countData)
```

```
##           SRR493366 SRR493367 SRR493368 SRR493369 SRR493370 SRR493371
## ENSG00000186092         0         0         0         0         0         0
## ENSG00000279928         0         0         0         0         0         0
## ENSG00000279457        23        28        29        29        28        46
## ENSG00000278566         0         0         0         0         0         0
## ENSG00000273547         0         0         0         0         0         0
## ENSG00000187634       124        123        205        207        212        258
```

Q. Complete the code below to filter countData to exclude genes (i.e. rows) where we have 0 read count across all samples (i.e. columns).

```
sumrow <- as.data.frame(rowSums(countData))
zerosum <- which(sumrow[,1] == 0, arr.ind=TRUE)

# Filter count data where you have 0 read count across all samples.
countData = countData[-zerosum, ]
head(countData)
```

```
##           SRR493366 SRR493367 SRR493368 SRR493369 SRR493370 SRR493371
## ENSG00000279457      23       28       29       29       28       46
## ENSG00000187634     124      123      205      207      212      258
## ENSG00000188976    1637     1831     2383     1226     1326     1504
## ENSG00000187961     120      153      180      236      255      357
## ENSG00000187583      24       48       65       44       48       64
## ENSG00000187642       4        9       16       14       16       16
```

Running DESeq2

```
dds = DESeqDataSetFromMatrix(countData=countData,
                              colData=colData,
                              design=~condition)
```

```
## Warning in DESeqDataSet(se, design = design, ignoreRank): some variables in
## design formula are characters, converting to factors
```

```
dds = DESeq(dds)
```

```
## estimating size factors
```

```
## estimating dispersions
```

```
## gene-wise dispersion estimates
```

```
## mean-dispersion relationship
```

```
## final dispersion estimates
```

```
## fitting model and testing
```

```
dds
```

```
## class: DESeqDataSet
## dim: 15975 6
## metadata(1): version
## assays(4): counts mu H cooks
```

```
## rownames(15975): ENSG00000279457 ENSG00000187634 ... ENSG00000276345
## ENSG00000271254
## rowData names(22): baseMean baseVar ... deviance maxCooks
## colnames(6): SRR493366 SRR493367 ... SRR493370 SRR493371
## colData names(2): condition sizeFactor
```

```
res = results(dds)
```


Q. Call the `summary()` function on your results to get a sense of how many genes are up or down-regulated at the default 0.1 p-value cutoff.

```
summary(res)
```

```
##
## out of 15975 with nonzero total read count
## adjusted p-value < 0.1
## LFC > 0 (up)      : 4349, 27%
## LFC < 0 (down)    : 4396, 28%
## outliers [1]      : 0, 0%
## low counts [2]    : 1237, 7.7%
## (mean count < 0)
## [1] see 'cooksCutoff' argument of ?results
## [2] see 'independentFiltering' argument of ?results
```

Volcano Plot

```
plot( res$log2FoldChange, -log(res$padj) )
```




Q. Improve this plot by completing the below code, which adds color and axis labels

```
# Make a color vector for all genes
mycols <- rep("gray", nrow(res) )

# Color red the genes with absolute fold change above 2
mycols[ abs(res$log2FoldChange) > 2 ] <- "red"

# Color blue those with adjusted p-value less than 0.01
# and absolute fold change more than 2
inds <- (res$padj < 0.1) & (abs(res$log2FoldChange) > 2 )
mycols[ inds ] <- "blue"

plot( res$log2FoldChange, -log(res$padj), col=mycols, xlab="Log2(FoldChange)", ylab="-Log(P-value)" )
```



Adding Gene Annotation

Q. Use the `mapIDs()` function multiple times to add `SYMBOL`, `ENTREZID` and `GENENAME` annotation to our results by completing the code below.

```
library("AnnotationDbi")
library("org.Hs.eg.db")
```

```
##
```

```
columns(org.Hs.eg.db)
```

```
## [1] "ACCNUM"      "ALIAS"       "ENSEMBL"     "ENSEMBLPROT" "ENSEMBLTRANS"
## [6] "ENTREZID"    "ENZYME"      "EVIDENCE"    "EVIDENCEALL"  "GENENAME"
## [11] "GENETYPE"    "GO"          "GOALL"       "IPI"          "MAP"
## [16] "OMIM"        "ONTOLOGY"    "ONTOLOGYALL" "PATH"         "PFAM"
## [21] "PMID"        "PROSITE"     "REFSEQ"      "SYMBOL"       "UCSCKG"
## [26] "UNIPROT"
```

Adding Symbol annotation

```
res$symbol = mapIds(org.Hs.eg.db,
                    keys=row.names(res),
                    keytype="ENSEMBL",
                    column="SYMBOL",
                    multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

Adding EntrezID annotation

```
res$entrez = mapIds(org.Hs.eg.db,
                    keys=row.names(res),
                    keytype="ENSEMBL",
                    column="ENTREZID",
                    multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

Adding Gene name annotation

```
res$name = mapIds(org.Hs.eg.db,
                  keys=row.names(res),
                  keytype="ENSEMBL",
                  column="GENENAME",
                  multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
head(res, 10)
```

```
## log2 fold change (MLE): condition hoxa1 kd vs control sirna
## Wald test p-value: condition hoxa1 kd vs control sirna
## DataFrame with 10 rows and 9 columns
##           baseMean log2FoldChange      lfcSE      stat      pvalue
##           <numeric>      <numeric> <numeric> <numeric>      <numeric>
## ENSG00000279457   29.913579      0.1792571 0.3248216   0.551863 5.81042e-01
## ENSG00000187634  183.229650      0.4264571 0.1402658   3.040350 2.36304e-03
## ENSG00000188976 1651.188076     -0.6927205 0.0548465  -12.630158 1.43990e-36
## ENSG00000187961  209.637938      0.7297556 0.1318599   5.534326 3.12428e-08
## ENSG00000187583   47.255123      0.0405765 0.2718928   0.149237 8.81366e-01
## ENSG00000187642   11.979750      0.5428105 0.5215598   1.040744 2.97994e-01
## ENSG00000188290  108.922128      2.0570638 0.1969053  10.446970 1.51282e-25
## ENSG00000187608  350.716868      0.2573837 0.1027266   2.505522 1.22271e-02
## ENSG00000188157  9128.439422      0.3899088 0.0467163   8.346304 7.04321e-17
## ENSG00000237330    0.158192      0.7859552 4.0804729   0.192614 8.47261e-01
##           padj      symbol      entrez      name
##           <numeric> <character> <character>      <character>
## ENSG00000279457 6.86555e-01   WASH9P   102723897 WAS protein family h..
## ENSG00000187634 5.15718e-03   SAMD11   148398 sterile alpha motif ..
## ENSG00000188976 1.76549e-35   NOC2L    26155 NOC2 like nucleolar ..
## ENSG00000187961 1.13413e-07   KLHL17   339451 kelch like family me..
```



```
## ENSG00000187583 9.19031e-01 PLEKHN1 84069 pleckstrin homology ..
## ENSG00000187642 4.03379e-01 PERM1 84808 PPARGC1 and ESRR ind..
## ENSG00000188290 1.30538e-24 HES4 57801 hes family bHLH tran..
## ENSG00000187608 2.37452e-02 ISG15 9636 ISG15 ubiquitin like..
## ENSG00000188157 4.21963e-16 AGRN 375790 agrin
## ENSG00000237330 NA RNF223 401934 ring finger protein ..
```

Q.Finally for this section let's reorder these results by adjusted p-value and save them to a CSV file in your current project directory.

```
res = res[order(res$pvalue),]
write.csv(res, file = "deseq_results.csv")
```

Section 2. Pathway Analysis

KEGG pathways

```
library(pathview)
```

```
## #####
## Pathview is an open source software package distributed under GNU General
## Public License version 3 (GPLv3). Details of GPLv3 is available at
## http://www.gnu.org/licenses/gpl-3.0.html. Particullary, users are required to
## formally cite the original Pathview paper (not just mention it) in publications
## or products. For details, do citation("pathview") within R.
##
## The pathview downloads and uses KEGG data. Non-academic uses may require a KEGG
## license agreement (details at http://www.kegg.jp/kegg/legal.html).
## #####
```

Loading packages and setting up the KEGG data sets we need.

```
library(gage)
```

```
##
```

```
library(gageData)

data(kegg.sets.hs)
data(sigmet.idx.hs)

# Focus on signaling and metabolic pathways only
kegg.sets.hs = kegg.sets.hs[sigmet.idx.hs]

# Examine the first 3 pathways
head(kegg.sets.hs, 3)
```

```
## $'hsa00232 Caffeine metabolism'
## [1] "10" "1544" "1548" "1549" "1553" "7498" "9"
##
## $'hsa00983 Drug metabolism - other enzymes'
## [1] "10" "1066" "10720" "10941" "151531" "1548" "1549" "1551"
## [9] "1553" "1576" "1577" "1806" "1807" "1890" "221223" "2990"
## [17] "3251" "3614" "3615" "3704" "51733" "54490" "54575" "54576"
## [25] "54577" "54578" "54579" "54600" "54657" "54658" "54659" "54963"
## [33] "574537" "64816" "7083" "7084" "7172" "7363" "7364" "7365"
## [41] "7366" "7367" "7371" "7372" "7378" "7498" "79799" "83549"
## [49] "8824" "8833" "9" "978"
##
## $'hsa00230 Purine metabolism'
## [1] "100" "10201" "10606" "10621" "10622" "10623" "107" "10714"
## [9] "108" "10846" "109" "111" "11128" "11164" "112" "113"
## [17] "114" "115" "122481" "122622" "124583" "132" "158" "159"
## [25] "1633" "171568" "1716" "196883" "203" "204" "205" "221823"
## [33] "2272" "22978" "23649" "246721" "25885" "2618" "26289" "270"
## [41] "271" "27115" "272" "2766" "2977" "2982" "2983" "2984"
## [49] "2986" "2987" "29922" "3000" "30833" "30834" "318" "3251"
## [57] "353" "3614" "3615" "3704" "377841" "471" "4830" "4831"
## [65] "4832" "4833" "4860" "4881" "4882" "4907" "50484" "50940"
## [73] "51082" "51251" "51292" "5136" "5137" "5138" "5139" "5140"
## [81] "5141" "5142" "5143" "5144" "5145" "5146" "5147" "5148"
## [89] "5149" "5150" "5151" "5152" "5153" "5158" "5167" "5169"
## [97] "51728" "5198" "5236" "5313" "5315" "53343" "54107" "5422"
## [105] "5424" "5425" "5426" "5427" "5430" "5431" "5432" "5433"
## [113] "5434" "5435" "5436" "5437" "5438" "5439" "5440" "5441"
## [121] "5471" "548644" "55276" "5557" "5558" "55703" "55811" "55821"
## [129] "5631" "5634" "56655" "56953" "56985" "57804" "58497" "6240"
## [137] "6241" "64425" "646625" "654364" "661" "7498" "8382" "84172"
## [145] "84265" "84284" "84618" "8622" "8654" "87178" "8833" "9060"
## [153] "9061" "93034" "953" "9533" "954" "955" "956" "957"
## [161] "9583" "9615"
```

Fold change results from the DESeq2 analysis are stored in `res$log2FoldChange`

```
foldchanges = res$log2FoldChange
names(foldchanges) = res$entrez
head(foldchanges)
```

```
##      1266      54855      1465      51232      2034      2317
## -2.422719  3.201955 -2.313738 -2.059631 -1.888019 -1.649792
```

Running the gage pathways analysis

```
# Get the results
keggres = gage(foldchanges, gsets=kegg.sets.hs)
attributes(keggres)
```

```
## $names
## [1] "greater" "less" "stats"
```

Look at the first few down(less) pathway results:

```
# Look at the first few down (less) pathways
head(keggres$less)
```

```
##                                p.geomean stat.mean          p.val
## hsa04110 Cell cycle            8.995727e-06 -4.378644 8.995727e-06
## hsa03030 DNA replication       9.424076e-05 -3.951803 9.424076e-05
## hsa03013 RNA transport        1.375901e-03 -3.028500 1.375901e-03
## hsa03440 Homologous recombination 3.066756e-03 -2.852899 3.066756e-03
## hsa04114 Oocyte meiosis       3.784520e-03 -2.698128 3.784520e-03
## hsa00010 Glycolysis / Gluconeogenesis 8.961413e-03 -2.405398 8.961413e-03
##                                q.val set.size          exp1
## hsa04110 Cell cycle            0.001448312      121 8.995727e-06
## hsa03030 DNA replication       0.007586381       36 9.424076e-05
## hsa03013 RNA transport        0.073840037     144 1.375901e-03
## hsa03440 Homologous recombination 0.121861535      28 3.066756e-03
## hsa04114 Oocyte meiosis       0.121861535     102 3.784520e-03
## hsa00010 Glycolysis / Gluconeogenesis 0.212222694     53 8.961413e-03
```

Use pathway to make a pathway plot with our RNA Seq expression results

```
pathview(gene.data=foldchanges, pathway.id="hsa04110")
```

```
## 'select()' returned 1:1 mapping between keys and columns
```

```
## Info: Working in directory /Users/chantalrabay/Desktop/BGGN 213/Class12
```

```
## Info: Writing image file hsa04110.pathview.png
```

```
# A different PDF based output of the same data
```

```
pathview(gene.data=foldchanges, pathway.id="hsa04110", kegg.native=FALSE)
```

```
## 'select()' returned 1:1 mapping between keys and columns
```

```
## Info: Working in directory /Users/chantalrabay/Desktop/BGGN 213/Class12
```

```
## Info: Writing image file hsa04110.pathview.pdf
```

```
## Focus on top 5 upregulated pathways here for demo purposes only
```

```
keggrespathways <- rownames(keggres$greater)[1:5]
```

```
# Extract the 8 character long IDs part of each string
```

```
keggresids = substr(keggrespathways, start=1, stop=8)
```

```
keggresids
```

```
## [1] "hsa04640" "hsa04630" "hsa00140" "hsa04142" "hsa04330"
```

```

pathview(gene.data=foldchanges, pathway.id=keggresids, species="hsa")

## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory /Users/chantalrabay/Desktop/BGGN 213/Class12

## Info: Writing image file hsa04640.pathview.png

## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory /Users/chantalrabay/Desktop/BGGN 213/Class12

## Info: Writing image file hsa04630.pathview.png

## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory /Users/chantalrabay/Desktop/BGGN 213/Class12

## Info: Writing image file hsa00140.pathview.png

## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory /Users/chantalrabay/Desktop/BGGN 213/Class12

## Info: Writing image file hsa04142.pathview.png

## Info: some node width is different from others, and hence adjusted!

## 'select()' returned 1:1 mapping between keys and columns

## Info: Working in directory /Users/chantalrabay/Desktop/BGGN 213/Class12

## Info: Writing image file hsa04330.pathview.png

```

Section 3. Gene Ontology (GO)

Similar process with Gene Ontology

```

data(go.sets.hs)
data(go.subs.hs)

# Focus on Biological Process subset of GO
gobpsets = go.sets.hs[go.subs.hs$BP]

gobpres = gage(foldchanges, gsets=gobpsets, same.dir=TRUE)

lapply(gobpres, head)

```

```
## $greater
##
##          p.geomean stat.mean      p.val
## G0:0007156 homophilic cell adhesion      8.519724e-05  3.824205 8.519724e-05
## G0:0002009 morphogenesis of an epithelium 1.396681e-04  3.653886 1.396681e-04
## G0:0048729 tissue morphogenesis          1.432451e-04  3.643242 1.432451e-04
## G0:0007610 behavior                      2.195494e-04  3.530241 2.195494e-04
## G0:0060562 epithelial tube morphogenesis 5.932837e-04  3.261376 5.932837e-04
## G0:0035295 tube development              5.953254e-04  3.253665 5.953254e-04
##
##          q.val set.size      exp1
## G0:0007156 homophilic cell adhesion      0.1951953    113 8.519724e-05
## G0:0002009 morphogenesis of an epithelium 0.1951953    339 1.396681e-04
## G0:0048729 tissue morphogenesis          0.1951953    424 1.432451e-04
## G0:0007610 behavior                      0.2243795    427 2.195494e-04
## G0:0060562 epithelial tube morphogenesis 0.3711390    257 5.932837e-04
## G0:0035295 tube development              0.3711390    391 5.953254e-04
##
## $less
##
##          p.geomean stat.mean      p.val
## G0:0048285 organelle fission              1.536227e-15 -8.063910 1.536227e-15
## G0:0000280 nuclear division               4.286961e-15 -7.939217 4.286961e-15
## G0:0007067 mitosis                       4.286961e-15 -7.939217 4.286961e-15
## G0:0000087 M phase of mitotic cell cycle 1.169934e-14 -7.797496 1.169934e-14
## G0:0007059 chromosome segregation         2.028624e-11 -6.878340 2.028624e-11
## G0:0000236 mitotic prometaphase          1.729553e-10 -6.695966 1.729553e-10
##
##          q.val set.size      exp1
## G0:0048285 organelle fission              5.841698e-12    376 1.536227e-15
## G0:0000280 nuclear division               5.841698e-12    352 4.286961e-15
## G0:0007067 mitosis                       5.841698e-12    352 4.286961e-15
## G0:0000087 M phase of mitotic cell cycle 1.195672e-11    362 1.169934e-14
## G0:0007059 chromosome segregation         1.658603e-08    142 2.028624e-11
## G0:0000236 mitotic prometaphase          1.178402e-07     84 1.729553e-10
##
## $stats
##
##          stat.mean      exp1
## G0:0007156 homophilic cell adhesion      3.824205 3.824205
## G0:0002009 morphogenesis of an epithelium 3.653886 3.653886
## G0:0048729 tissue morphogenesis          3.643242 3.643242
## G0:0007610 behavior                      3.530241 3.530241
## G0:0060562 epithelial tube morphogenesis 3.261376 3.261376
## G0:0035295 tube development              3.253665 3.253665
```

Section 4. Reactome Analysis

Over-representation enrichment analysis and pathway-topology analysis with Reactome

```
sig_genes <- res[res$padj <= 0.05 & !is.na(res$padj), "symbol"]
print(paste("Total number of significant genes:", length(sig_genes)))
```

```
## [1] "Total number of significant genes: 8147"
```

```
write.table(sig_genes, file="significant_genes.txt", row.names=FALSE, col.names=FALSE, quote=FALSE)
```

Q. What pathway has the most significant “Entities p-value”? Do the most significant pathways listed match your previous KEGG results? What factors could cause differences between the two methods?

The pathway with the most significant p-value is the endosomal/vacuolar pathway. The results are not the same. This may just be due to differences in the databases and the data and methods that they use. The second most significant pathway in reactome was cell cycle, which was the most significant pathways listed from KEGG.