



# DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

## Experiment 8

**Student Name:** Akshit Gautam

**UID:** 23BAI71449

**Singh Branch:** CSE-AIML

**Section:** 23-AIT\_KRG\_G1

**Semester:** 5<sup>th</sup>

**Date of Performance:** 29-10-2025

**Subject Name:** ADBMS

**Subject Code:** 23CSP-333

### **1. AIM:**

Design a robust PostgreSQL transaction system for the students table where multiple student records are inserted in a single transaction.

If any insert fails due to invalid data, only that insert should be rolled back while preserving the previous successful inserts using savepoints.

The system should provide clear messages for both successful and failed insertions, ensuring data integrity and controlled error handling.

### **2. Tools Used:** Postgres

#### **Solutions:**

**HARD**

```
select * from student;
begin transaction;
DO $$ 
begin
    insert into student values('Aadi', 444, 'WEBD'),
                           ('Mahesh', 545, 'CYBE'),
                           ('Rohan', 090, 'CYBE');

    raise notice 'Insertion successful';

exception
    when others then
        raise notice 'Unhandled Exception : SQLSTATE % --- %', SQLSTATE,
SQLERRM;

        raise;
end;
$$
```

```

select * from student;

commit;

begin transaction;
DO $$ 
begin
    insert into student values('Sambhav', 404, 'WEBD'),
                           ('Mahesh', 545, 'CYBE'), --Wrong
insertion
                           ('Mahendra', 190, 'CYBE');

    raise notice 'Insertion successful';

exception
    when others then
        raise notice 'Unhandled Exception : SQLSTATE % --- %', SQLSTATE,
SQLERRM;

        raise;
end;
$$

rollback;

select * from student;

commit;

```

### 3. Output:

```

NOTICE: Insertion successful
DO

Query returned successfully in 65 msec.

```

```

NOTICE: Unhandled Exception : SQLSTATE 23505 --- duplicate key value violates unique constraint "student_pkey"

ERROR: duplicate key value violates unique constraint "student_pkey"
Key (uid)=(545) already exists.

SQL state: 23505
Detail: Key (uid)=(545) already exists.
Context: SQL statement "insert into student values('Sambhav', 404, 'WEBD'),
                           ('Mahesh', 545, 'CYBE'), --Wrong insertion
                           ('Mahendra', 190, 'CYBE')"

PL/pgSQL function inline_code_block line 3 at SQL statement

```

### **3. Learning Outcomes:**

- ❑ Understand the concept of PostgreSQL transactions and how to start, commit, and rollback.
- ❑ Learn how to use **SAVEPOINT** to handle partial rollbacks within a transaction.
- ❑ Practice controlled error handling for individual insert failures without affecting other successful operations.
- ❑ Gain experience in maintaining **data integrity** while performing multiple inserts.
- ❑ Learn to generate informative **NOTICES** to monitor transaction progress and errors.