

LARGE-SCALE CONTENT-BASED MATCHING OF MIDI AND AUDIO FILES

First author

Affiliation1

author1@ismir.edu

Second author

Retain these fake authors in

submission to preserve the formatting

Third author

Affiliation3

author3@ismir.edu

ABSTRACT

MIDI files, when paired with corresponding audio recordings, can be used as ground truth for many music information retrieval tasks. We present a system which can efficiently match and align MIDI files to entries in a large corpus of audio content without using any metadata. The core of our approach is a neural network-based cross-modality hashing scheme which transforms feature matrices into sequences of vectors in a common Hamming space. Once represented in this way, we can efficiently perform large-scale dynamic time warping searches to match MIDI data to audio recordings. We evaluate our approach on the task of matching a huge corpus of MIDI files to the Million Song Dataset.

1. TRAINING DATA FOR MIR

Central to the task of content-based Music Information Retrieval is the curation of ground-truth data for tasks of interest (e.g. timestamped chord labels for automatic chord estimation, beat positions for beat tracking, prominent melody time series for melody extraction, etc.). The quantity and quality of this ground-truth is often instrumental in the success of MIR systems which utilize it as training data. Unfortunately, creating appropriate labels for a recording of a given song by hand typically requires person-hours on the order of the length of the song. This often arguably makes the available training data a bottleneck to success for a given content-based MIR task.

It has previously been observed that MIDI files, when time-aligned to corresponding audio recordings, can be used to infer ground-truth information about a given song [6, 14]. This is due to the fact that a MIDI file can be viewed simplistically as a timed sequence of note annotations or a piano roll. It is much more straightforward to estimate, e.g., beat locations, chord labels, and the predominant melody from these representations than one which was derived from an audio signal. Unsurprisingly, a handful of tools have been developed for inferring this information from MIDI files [4, 5, 9, 10].

In [7], it is argued that some of the biggest successes in machine learning are thanks to the fact that “...a large training set of the input-output behavior that we seek to automate is available to us in the wild.” The main motivation behind this project is that this crucial availability of data holds true for MIDI files - through a large-scale web scrape, we obtained 140,910 unique MIDI files, which is orders of magnitude larger than the datasets typically used for MIR research. We believe this proliferation of data is largely caused to two factors: First, that karaoke files are typically distributed as MIDI data and that karaoke is wildly popular, and second, that transcribing popular music as MIDI files is a common pastime for hobbyist musicians.

1.1 Wrangling MIDI Files

The mere existence of a large collection of MIDI data is not enough, however. As noted above, in order to use MIDI files as ground truth, they need to be both matched (paired with a corresponding audio recording of the same song) and aligned (adjusted so that the timing of the events transcribed in the file match the audio recording). The latter problem has seen a great deal of research effort [6, 14], and will not be a main focus of this work.

Given large corpora of audio and MIDI files, the task of matching entries from each may seem to be a trivial problem involving fuzzy text matching of the files’ metadata. However, MIDI files have no formal mechanism for storing metadata (apart from text meta events, which are rarely used), and as a result the best-case scenario is that the artist and song title are included in the filename or subdirectory. While we found some examples of this in our collection of scraped MIDI files, the vast majority of the files had effectively no metadata information. Figure 1 shows a random sampling of subdirectory and filenames from our collection.

Fortunately, the goal of matching MIDI and audio files is to find pairs which have *content* in common (i.e., the MIDI file is a transcription of the audio file), an information source which is available regardless of metadata quality. However, comparing content has the potential to require much more computation than a fuzzy text comparison, and NM comparisons must be made to match a MIDI dataset of size N to an audio file dataset of size M . Motivated by this, we propose a system which can *efficiently* match MIDI files to audio based solely on their content. Our system learns to hash MIDI and audio content



© First author, Second author, Third author.

Licensed under a Creative Commons Attribution 4.0 International License (CC BY 4.0). **Attribution:** First author, Second author, Third author. “Large-Scale Content-Based Matching of MIDI and Audio Files”, 16th International Society for Music Information Retrieval Conference, 2015.

```

J/Jerseygi.mid
V/VARIA180.MID
Carpenters/WeveOnly.mid
2009 MIDI/handy_man1-D105.mid
G/Garotos Modernos - Bailanta De Fronteira.mid
Various Artists/REWINDNAS.MID
GoldenEarring/Twilight_Zone.mid
Sure.Polyphone.Midi/Poly 2268.mid
d/danza3.mid
100%sure.polyphone.midi/Fresh.mid
rogers_kenny/medley.mid
2009 MIDI/looking_out_my_backdoor3-Bb192.mid

```

Figure 1. Random sampling of 12 MIDI filenames and their parent directories from our corpus of 455,333 MIDI files scraped from the Internet.

to a common Hamming space where sequences of vectors can be compared efficiently using dynamic time warping (DTW).

The idea of using DTW distance to match MIDI files to audio recordings is not new. For example, in [8], MIDI-audio matching is done by finding the minimal DTW distance between all pairs of chromagrams of (synthesized) MIDI and audio files. Our approach differs in a few key ways: First, instead of using chromagrams (a hand-designed representation), we learn a common representation for MIDI and audio data. Second, our datasets are many orders of magnitude larger (hundreds of thousands vs. hundreds of files), which necessitates a much more efficient approach. Specifically, by mapping to a Hamming space we greatly speed up distance matrix calculation and we receive quadratic speed gains by implicitly downsampling the audio and MIDI feature sequences as part of our learned feature mapping.

In the following section, we detail the dataset of MIDI files we scraped from the Internet and describe how we prepared a subset for training our hasher. Our cross-modality hashing model is then described in Section 3. In Section 4, we cover our fast hash sequence DTW method and its accompanying pruning techniques. Finally, we evaluate our system’s performance on the task of matching files from our MIDI dataset to entries in the Million Song Dataset [2].

2. PREPARING DATA

Our project began with a large-scale scrape of MIDI files from the Internet. We obtained 455,333 files, of which 140,910 were found to have unique MD5 checksums. Most of these files were transcriptions of pieces of music of varying duration and quality. As mentioned previously, the majority of these files had very little useful metadata information. The goal of the present work is to develop an efficient way to match this corpus against the Million Song Dataset (MSD), or more specifically, to the short preview audio recordings provided by 7digital [11].

In order to evaluate our system, we need a collection of MIDI-audio pairs which we know are correctly matched. The accuracy of our approach can then be judged based on how accurately it is able to recover these pairings using the content of the audio and MIDI files alone. Fortunately,

we identified a subset of files where the subdirectory of the file indicated the artist and the filename indicated the song title. By cleaning up this subset and using the resulting metadata to match its entries against the Million Song Dataset, we can obtain the requisite ground-truth set of MIDI-audio pairings. We will refer to this collection of files as the “clean MIDI subset”.

A further data requirement for our system is a collection of feature vectors derived from audio and MIDI data which should be mapped to similar hashes. This dataset will be used to train our model for hashing MIDI and audio features to a common Hamming space (described in Section 3). In our application, we will be matching sequences of hashes using dynamic time warping, so we need to obtain pairs of sequences of feature vectors where the n th vector in one sequence should be mapped to the n th vector in the other. This necessitates a collection of MIDI files and audio recordings which we are confident are well-aligned in time. From this collection, we can extract features for each modality and be sure that there is a direct correspondence between the resulting hash sequences and the original feature vector sequences.

2.1 Metadata matching

We first extracted the song title and artist from each entry in the clean MIDI subset based on each MIDI file’s filename and subdirectory. The resulting metadata was still somewhat messy (for example, “The Beatles” appeared as an artist along with “Beatles, The”, “Beatles”, and “The Beatles John Paul Ringo George”). To normalize these issues, we applied some manual text processing and resolved the artists and song titles against the Freebase [3] and Echo Nest¹ databases. This resulted in 17,243 MIDI files for 10,060 unique songs.

As noted above, we will leverage the clean MIDI subset in two ways: First, to obtain ground-truth pairings of MSD/MIDI matches, and second, to create training data for our hashing scheme. Note that for the latter purpose, we do not need to restrict ourselves to audio data from the MSD, and we can reasonably expect that by using more training data we may be able to learn a better representation. As a result, we combined the MSD with three benchmark audio collections: CAL500 [15], CAL10k [12], and uspop2002 [1]. To match these datasets to the clean MIDI subset, we used the Python search engine library Whoosh to perform a fuzzy matching of their metadata. This resulted in 26,311 audio/MIDI file pairs corresponding to 5,243 unique songs.

¹ <http://developer.echonest.com/docs/v4>

2.2 Audio-to-audio alignment

3. CROSS-MODALITY HASHING OF MIDI AND AUDIO DATA

4. FAST DTW MATCHING OF HASH SEQUENCES

5. MATCHING MIDI FILES TO THE MSD

6. REFERENCES

- [1] Adam Berenzweig, Beth Logan, Daniel P. W. Ellis, and Brian Whitman. A large-scale evaluation of acoustic and subjective music-similarity measures. *Computer Music Journal*, 28(2):63–76, 2004.
- [2] Thierry Bertin-Mahieux, Daniel P. W. Ellis, Brian Whitman, and Paul Lamere. The million song dataset. In *ISMIR 2011: Proceedings of the 12th International Society for Music Information Retrieval Conference, October 24-28, 2011, Miami, Florida*, pages 591–596. University of Miami, 2011.
- [3] Kurt Bollacker, Colin Evans, Praveen Paritosh, Tim Sturge, and Jamie Taylor. Freebase: a collaboratively created graph database for structuring human knowledge. In *Proceedings of the 2008 ACM SIGMOD international conference on Management of data*, pages 1247–1250. ACM, 2008.
- [4] Michael Scott Cuthbert and Christopher Ariza. music21: A toolkit for computer-aided musicology and symbolic music data. In *Proceedings of the 11th International Conference on Music Information Retrieval*, pages 637–642, 2010.
- [5] Tuomas Eerola and Petri Toivainen. MIR in Matlab: The MIDI toolbox. In *Proceedings of the 5th International Conference on Music Information Retrieval*, pages 22–27, 2004.
- [6] Sebastian Ewert, Meinard Müller, Verena Konz, Daniel Müllensiefen, and Geraint A. Wiggins. Towards cross-version harmonic analysis of music. *IEEE Transactions on Multimedia*, 14(3):770–782, 2012.
- [7] Alon Halevy, Peter Norvig, and Fernando Pereira. The unreasonable effectiveness of data. *IEEE Intelligent Systems*, 24(2):8–12, 2009.
- [8] Ning Hu, Roger B. Dannenberg, and George Tzanetakis. Polyphonic audio matching and alignment for music retrieval. In *Applications of Signal Processing to Audio and Acoustics, 2003 IEEE Workshop on.*, pages 185–188. IEEE, 2003.
- [9] Cory McKay and Ichiro Fujinaga. jSymbolic: A feature extractor for MIDI files. In *Proceedings of the International Computer Music Conference*, pages 302–305, 2006.
- [10] Colin Raffel and Daniel P. W. Ellis. Intuitive analysis, creation and manipulation of MIDI data with pretty_midi. In *Proceedings of the 15th International Conference on Music Information Retrieval Late Breaking and Demo Papers*, 2014.
- [11] Alexander Schindler, Rudolf Mayer, and Andreas Rauber. Facilitating comprehensive benchmarking experiments on the million song dataset. In *Proceedings of the 13th International Conference on Music Information Retrieval*, pages 469–474, 2012.
- [12] Derek Tingle, Youngmoo E. Kim, and Douglas Turnbull. Exploring automatic music annotation with “acoustically-objective” tags. In *Proceedings of the international conference on Multimedia information retrieval*, pages 55–62. ACM, 2010.
- [13] Omitted to maintain anonymity.
- [14] Robert J. Turetsky and Daniel P. W. Ellis. Ground-truth transcriptions of real music from force-aligned MIDI syntheses. *Proceedings of the 4th International Conference on Music Information Retrieval*, pages 135–141, 2003.
- [15] Douglas Turnbull, Luke Barrington, David Torres, and Gert Lanckriet. Towards musical query-by-semantic-description using the CAL500 data set. In *Proceedings of the 30th annual international ACM SIGIR conference on Research and development in information retrieval*, pages 439–446. ACM, 2007.