Concepts of Route 53 Key Functions of Route 53



You can use Route 53 to perform three key functions in any combination as you see in the picture above:

- · Domain Registration,
- · DNS Routing,
- · Health Checking.

Domain Registration



• Domain Registration:

Your website uses a name, such as clarusway.com. Route 53 one of the domainname-provider lets you register a name for your website or web application, known as a domain name. After purchasing or leasing, the domain name will be dedicated only to you globally.

You can purchase or lease a domain name for the different timeframe via Route 53.

You can also transfer the registration for existing domains from other registrars to Route 53 or transfer the registration for domains that you register with Route 53 to another registrar.

DNS Routing



DNS Routing:

Route 53 route the internet traffic to the resources for your domain. When a user opens a web browser and enters your domain name (clarusway.com) or subdomain name (help.clarusway.com) into an address bar, Route 53 provides a connection between the browser and your website or web application.

After you register your domain name, Route 53 routes the web traffic of your domain with the help of the **DNS Record Sets** and **DNS Policies**.

Each DNS Record Set includes information about how you want to route traffic for your domain.

As for DNS Policies, they offer many scenario alternatives such as geographic, failover or weighted, etc.

We'll see more details about DNS Record Sets and DNS Policies in the following pages.

DNS Health Checking



Health Checking:

Health Checking, as the name suggests, is a function that checks whether our servers running with Route 53 are working properly. Then it allows mapping the traffic according to the information taken from this health check.

While Health Checking working, Route 53 sends automated requests over the internet to a resource, such as a web server, to verify that it's reachable, available, and functional.

You also can choose to receive notifications when a resource becomes unavailable and choose to route internet traffic away from unhealthy resources.

You can create three types of Amazon Route 53 Health Checks and you can use them while creating records:

Endpoint Health Checks:

It is a health checking method that monitors an endpoint that you specify either by IP address or by the domain name.


· Calculated Health Checks:

In this option you can create a health check that considers the other health checks that may be healthy or unhealthy. Hence, health control criteria can be more personalized and produce composite results.

CloudWatch Health Checks:

In this type of Health Check, you first create CloudWatch alarms that monitor and then create a health check that monitors the same data stream that CloudWatch monitors for the alarm.

Hosted Zones




A hosted zone is a container for records, and records contain information about how you want to route traffic for a specific domain.

For example, if your domain is **clarusway.com**, you can reach also the same website corresponding to your domain with the help of the records inside these hosted zones when you enter its subdomains such as **info.clarusway.com**, or **mobile.clarusway.com** on the browser.

A domain and its hosted zone have the same name.

There are two types of hosted zones: Public Hosted Zones and Private Hosted Zones

Public Hosted Zones



Public Hosted Zones:


A public hosted zone is a container that holds information (DNS Records) about how you want to route traffic on the internet for a specific domain. So, we can manage queries from the public internet through the DNS record sets and Policies that we create in the Public Hosted Zone.

Public Hosted Zones are accessible from the Public Internet.

If you want to create Public Hosted Zones, first of all, you need to have a domain name. You can purchase from AWS or you may migrate from another DNS registrar.

When you registered a domain name via Route 53, your Public Hosted Zone will be automatically created with the same name of your domain name.

Private Hosted Zones



Private Hosted Zones

Private Hosted Zones:


Private hosted zones contain records that specify how you want to route traffic in an Amazon VPC.

Private hosted Zone can only be accessed by our resources in VPC.

Unlike Public Hosted Zones, Private Hosted Zones are not created automatically when the domain name is registered with Route 53. So we can create it manually.

No domain name registration is required to create a Private Hosted Zone. Any name can be selected for the hosted zone. For example **team-clarusway.local**

DNS Record Sets



A DNS record sets are an information record used to map the domain names to an IP address in AWS Route 53. They provide you to manage user queries to an alternative web site.


Thanks to the DNS record we can associate our web site to one IP, multiple IP or any name. For example:

- wwww.clarusway.com is the hostname of your web site You can provide users to
 access this web site both from public.clarusway.com and wwww.clarusway.com
 via CNAME record.
- And also you can set your web site to be reachable from the IPs of 1.2.3.4.56 and IP: 7.8.9.10. thanks to the A or AAA records.

Amazon Route 53 currently supports 13 DNS record types (most used in bold) seen below:

- NS (Name Server Record)
- . SOA (Start of Authority Record)
- A (Address Record)
- CNAME (Canonical Name Record)
- PTR (Pointer Record)
- TXT (Text Record)
- ALIAS(Alias Record)
- CAA (Certification Authority Authorization)
- MX (Mail Exchange Record)
- NAPTR (Name Authority Pointer Record)
- AAAA (IPv6 Address Record)
- SPF (Sender Policy Framework)
- SRV (Service Locator)

SOA and NS Records



SOA and NS Records

When we register a domain name or create a hosted zone in AWS Route 53, 2 records are created by default. These records are SOA (Start Of Authority) and NS (Name Server)

• SOA (Start Of Authority):

SOA (Start Of Authority) contains administrative basic information about the associated domain. It is the first record in all zones. It is the record that determines that a DNS Server is responsible for that zone. In other words, it is the ID card of domain name

It is used to define the parameters of the primary DNS server for a particular zone. Zone version, zone management, data in the zone and name server information are kept in SOA records.

It includes fields such as serial number, refreshes rate, retries timeout, expiration time, and negative cache time. In addition, how often information is shared among multiple DNS servers hosting the same zone, SOA record determines.


NS (Name Server):

NS, as the name suggests, is a record that contains a list of servers authorized to host Name Server.

NS-records determine the DNS servers responsible (authoritative) for a zone.

Amazon Route 53 automatically creates a name server (NS) record that has the same name as your hosted zone. By default, it holds the **four** name servers that are the authoritative name servers for your hosted zone. You are not recommended to add, change, or delete name servers in these records.

A Records



A Record:

It is the most basic DNS record. It is an important record type that we can match with the domain or subdomain to IPs. For example, we can point the sub-domain of www.clarusway.com to IP addresses such as 1.2.3.4

A record can only take an IP address as a Value.


You can assign multiple IPs to the same domain/subdomain.

You can also assign different sub-domains to the same IP via A records.

You'll see the sample of A Record listings of different types in the picture above.

- In the section marked as 1, help.local.clarusway.com and www.local.clarusway.com are assigned to the same IP of 1.2.3.45. So, thanks to the these A records you'll reach the same web server when you search both www.local.clarusway.com and help.local.clarusway.com in the web browser.
- In the section marked as 2, IP of 14.15.16.17 and 10.11.12.13 are assigned to local.clarusway.com as a value. When you enter local.clarusway.com in a web browser, Route 53 route the guery to these IPs randomly.

CNAME Records



CNAME Records

• CNAME(Canonical Name) Records:

CNAME records are used to point a domain or subdomain to another hostname. It's a kind of alias for any hostname. If you want to provide a variety of associated services and subdomains (mail.clarusway.com, mobile.clarusway.com, etc.) on a single domain(clarusway.com) and, it is possible to define these subdomains record of each service to be directed to a single server with CNAME definitions.

Thus, when it is necessary to update the IP address record, instead of updating all the addresses one by one, we can only solve the problem with a change in the A Record.


As you see in the picture above, we have A record which points www.local.clarusway.com to the IP of 1.2.3.45 And we want to route also info.local.clarusway.com and help.local.clarusway.com to the same server. We have two options here:

- We can create two more A Records for info.local.clarusway.com and help.local.clarusway.com that point the IP of 1.2.3.45. But, in case of changing the IP address of the server, you need to change all IP values of these 3 A records, or
- In addition to www.local.clarusway.com A Record, we can create two CNAME records for info.local.clarusway.com and help.local.clarusway.com which point the A Record. So, in case of changing the IP address of the server, you'll just need to change the IP of A records and this automatically causes to change the CNAME record also.

▲ Avoid!:

· You can't create CNAME for the root/naked domain such as clarusway.com.

Alias Records



This is a DNS feature of Route 53 only. It is basically the same as the CNAME record, but instead of the IP address, we do DNS name mapping to the AWS resources like AWS Elastic Load Balancers, Amazon Cloud Front, AWS Elastic Beanstalk, or Amazon S3 Buckets.


Assume that you want to map your naked/root domain **clarusway.com** to your Amazon Elastic Load Balancers. As you remember from the previous lessons, Amazon Elastic Load Balancers only offers a DNS name, not IP addresses. Thus;

- If you create A record, it allows only IP addresses so it's not possible to create A record for the Amazon Elastic Load Balancers.
- As for CNAME records, although they offer name option, they cannot be used for a root or naked domain.

So you can only map your naked/root domain such as **clarusway.com**, to your Amazon Elastic Load Balancers by Alias record. Because Alias both can be used with naked/root domain and DNS belonging to AWS services

Alias records are embedded in the other Route 53 records. So you can create
an Alias record inside the other records.

Alias vs CNAME




Other DNS Records

- MX Record (Mail Exchange Record): Specifies the IP addresses of the servers that provide mail services related to the domain name.
- TXT Record(Text Record): As the name of the TXT record indicates, it allows you to keep the Text values records.
- PTR Records (Pointer Record): These are records defined in reverse zone files for reverse DNS records. It is used to analyze the hostname against IP address. For example, to find the name of the server with the IP address 10.61.2.116, the DNS server responds by looking at the PTR records.
- SRV Registration Record (Service Locator Record): It is the type of registration we use when we want to send port information besides IP addresses.
- . SPF Record (Sender Policy Framework Record): It is a record about sending spam and spoofing related to sending mail.
- AAAA (IPv6 address record): It is the IPv6 version of A Record designed for IPv4
- CAA Record (Certification Authority Authorization): A CAA record specifies which certificate authorities (CAs) are allowed to issue certificates for a domain or subdomain

If there is no CAA record, any CA is allowed to issue a certificate for the domain. If a CAA record is present, only the CAs existing in the record (s) are allowed to issue certificates for that hostname.

• NAPTR Record (A Name Authority Pointer Record): NAPTR Record Type is a type of record that is used by Dynamic Delegation Discovery System (DDDS) applications to convert one value to another or to replace one value with another. For example, one common use is to convert phone numbers into SIP URIs.

TTL(Time to Live)



TTL(Time to Live)

TTL(Time to Live) is a parameter that determines how long IPS (Internet Service Provider) will cache (store) the values for a record before submitting another request to Route 53 to get the current values for that record.


If the DNS resolver receives another request for the same domain before the TTL expires, the resolver returns the cached value.

Suppose there is a popular web site like www.google.com, so millions of devices are trying to enter this page and it will extremely increase the load of DNS servers. Instead, If we enter the TTL value as 1000 then IPS (Internet Service Provider) going to the DNS server again 1000 minutes after the first address is reached. Thus, the load of the DNS server will decrease.

TTL is set in seconds from the right-hand menu from the TTL section. You can manually enter a value as second or select 1 minute, 5 minutes, 1 hour and 1-day options on the menu.

A longer TTL reduces your Route 53 charges, which are based in part on the number of DNS queries that Route 53 responds to. So this provides great convenience in a static environment where IP addresses do not change.

Routing Policies



Routing Policy is a parameter that provides you to configure your traffic for different types of scenarios. When you create a record, you choose a routing policy, which determines how Amazon Route 53 responds to queries.

How the traffic is directed depends on which subject the policy based on. For example, While Latency Routing Policy takes action the distance/time, Geolocation Routing Policy considers the location of user and web-server.

Currently, Route 53 offers 7 types of policy seen below:

· Simple Routing Policy:

Used for a single resource that performs a given function for your domain, for example, a web server that serves content for the example.com website.

· Failover Routing Policy:

Use when you want to configure active-passive failover.

· Weighted Routing Policy:

Used for routing traffic to multiple resources in proportions that you specify(e.g proportions of 8/2, 10/90 or 1/5).

· Latency Routing Policy:

Use when you have resources in multiple AWS Regions and you want to route traffic to the region that provides the best latency.

Geolocation Routing Policy:

Use when you want to route traffic based on the location of your users.

Geoproximity Routing Policy

Use when you want to route traffic based on the location of your resources and, optionally, shift traffic from resources in one location to resources in another.

· Multivalue Answer Routing Policy:

Use when you want Route 53 to respond to DNS queries with up to eight healthy records selected at random

