RProtoBuf : Unit testing results

Romain François   Dirk Eddelbuettel   Murray Stokely

RProtoBuf version 0.4.10 as of August 13, 2017

Test Execution

```
Executing test function test.ascii  ...  done successfully.
```

```
Executing test function test.fileDescriptor  ...  done successfully.
```

```
Executing test function test.personOne  ...  done successfully.
```

```
Executing test function test.size  ...  done successfully.
```

```
Executing test function test.bool  ...  done successfully.
```

```
Executing test function test.all  ...  done successfully.
```

```
Executing test function test.descriptor  ...  done successfully.
```

```
Executing test function test.enums  ...  done successfully.
```

```
Executing test function test.extension  ...  done successfully.
```

```
Executing test function test.uint32  ...  done successfully.
```

```
Executing test function test.FieldDescriptor.class  ...  done successfully.
```

```
Executing test function test.has  ...  done successfully.


Executing test function test.import  ...  done successfully.


Executing test function test.invalidAssignments  ...  done successfully.


Executing test function test.readProtoFile  ...  done successfully.


Executing test function test.repeated.bools  ...  done successfully.


Executing test function test.repeatedFields  ...  done successfully.


Executing test function test.assign.in.global  ...  done successfully.


Executing test function test.import  ... /tmp/Rinst57a839ad51a/RProtoBuf/DESCRIPTION:1:1:Expected top-le
/tmp/Rinst57a839ad51a/RProtoBuf/DESCRIPTION:2:13:Already saw decimal point or exponent; can't have anoth
/tmp/Rinst57a839ad51a/RProtoBuf/DESCRIPTION:3:13:Numbers starting with leading zero must be in octal.
/tmp/Rinst57a839ad51a/RProtoBuf/DESCRIPTION:13:19:Already saw decimal point or exponent; can't have anot
/tmp/Rinst57a839ad51a/RProtoBuf/DESCRIPTION:18:64:Already saw decimal point or exponent; can't have anot
/tmp/Rinst57a839ad51a/RProtoBuf/DESCRIPTION:19:16:Expected top-level statement (e.g. "message").
/tmp/Rinst57a839ad51a/RProtoBuf/DESCRIPTION:19:27:Already saw decimal point or exponent; can't have anot
/tmp/Rinst57a839ad51a/RProtoBuf/DESCRIPTION:26:13:Already saw decimal point or exponent; can't have anot
/tmp/Rinst57a839ad51a/RProtoBuf/DESCRIPTION:26:17:Expected top-level statement (e.g. "message").
/tmp/Rinst57a839ad51a/RProtoBuf/DESCRIPTION:26:38:Expected top-level statement (e.g. "message").
/tmp/Rinst57a839ad51a/RProtoBuf/DESCRIPTION:26:44:Numbers starting with leading zero must be in octal.
/tmp/Rinst57a839ad51a/RProtoBuf/DESCRIPTION:26:63:Expected top-level statement (e.g. "message").
 done successfully.


Executing test function test.int32  ...  done successfully.


Executing test function test.int64  ...  done successfully.


Executing test function test.message  ...  done successfully.
```

```
Executing test function test.nested  ...  done successfully.


Executing test function test.proto3  ...  done successfully.


Executing test function test.serialize_pb  ...  done successfully.


Executing test function test.serialize_pb.alldatasets  ...  done successfully.


Executing test function test.arrayinputstream  ...  done successfully.


Executing test function test.encoding  ...  done successfully.


Executing test function test.serialize  ...  done successfully.
```

Test Results

```
RUNIT TEST PROTOCOL -- Sun Aug 13 09:56:11 2017
*************************************************
Number of test functions: 29
Number of errors: 0
Number of failures: 0


1 Test Suite :
RProtoBuf unit testing - 29 test functions, 0 errors, 0 failures



Details
**************************
Test Suite: RProtoBuf unit testing
Test function regexp: ^test.+
Test file regexp: ^runit.+\.[rR]$
Involved directory:
/tmp/Rinst57a839ad51a/RProtoBuf/unitTests
---------------------------
Test file: /tmp/Rinst57a839ad51a/RProtoBuf/unitTests/runit.addressbook.R
test.ascii: (8 checks) ... OK (0.01 seconds)
test.fileDescriptor: (1 checks) ... OK (0 seconds)
```

```
test.personOne: (11 checks) ... OK (0 seconds)
test.size: (3 checks) ... OK (0 seconds)
---------------------------
Test file: /tmp/Rinst57a839ad51a/RProtoBuf/unitTests/runit.bool.R
test.bool: (7 checks) ... OK (0.01 seconds)
---------------------------
Test file: /tmp/Rinst57a839ad51a/RProtoBuf/unitTests/runit.bytes.R
test.all: (10 checks) ... OK (0 seconds)
---------------------------
Test file: /tmp/Rinst57a839ad51a/RProtoBuf/unitTests/runit.descriptors.R
test.descriptor: (6 checks) ... OK (0 seconds)
---------------------------
Test file: /tmp/Rinst57a839ad51a/RProtoBuf/unitTests/runit.enums.R
test.enums: (15 checks) ... OK (0 seconds)
---------------------------
Test file: /tmp/Rinst57a839ad51a/RProtoBuf/unitTests/runit.extensions.R
test.extension: (13 checks) ... OK (0 seconds)
---------------------------
Test file: /tmp/Rinst57a839ad51a/RProtoBuf/unitTests/runit.extremevalues.R
test.uint32: (5 checks) ... OK (0 seconds)
---------------------------
Test file: /tmp/Rinst57a839ad51a/RProtoBuf/unitTests/runit.FieldDescriptor.R
test.FieldDescriptor.class: (23 checks) ... OK (0 seconds)
---------------------------
Test file: /tmp/Rinst57a839ad51a/RProtoBuf/unitTests/runit.golden.message.R
test.has: (4 checks) ... OK (0 seconds)
test.import: (5 checks) ... OK (0 seconds)
test.invalidAssignments: (1 checks) ... OK (0 seconds)
test.readProtoFile: (61 checks) ... OK (0 seconds)
test.repeated.bools: (3 checks) ... OK (0 seconds)
test.repeatedFields: (5 checks) ... OK (0 seconds)
---------------------------
Test file: /tmp/Rinst57a839ad51a/RProtoBuf/unitTests/runit.import.R
test.assign.in.global: (1 checks) ... OK (0 seconds)
test.import: (1 checks) ... OK (0 seconds)
---------------------------
Test file: /tmp/Rinst57a839ad51a/RProtoBuf/unitTests/runit.int32.R
test.int32: (8 checks) ... OK (0.01 seconds)
---------------------------
Test file: /tmp/Rinst57a839ad51a/RProtoBuf/unitTests/runit.int64.R
test.int64: (8 checks) ... OK (0.01 seconds)
---------------------------
Test file: /tmp/Rinst57a839ad51a/RProtoBuf/unitTests/runit.messages.R
test.message: (7 checks) ... OK (0.01 seconds)
---------------------------
Test file: /tmp/Rinst57a839ad51a/RProtoBuf/unitTests/runit.nested.R
test.nested: (1000 checks) ... OK (0.19 seconds)
---------------------------
Test file: /tmp/Rinst57a839ad51a/RProtoBuf/unitTests/runit.proto3.R
test.proto3: (3 checks) ... OK (0 seconds)
---------------------------
Test file: /tmp/Rinst57a839ad51a/RProtoBuf/unitTests/runit.serialize_pb.R
test.serialize_pb: (2 checks) ... OK (0.03 seconds)
test.serialize_pb.alldatasets: (1 checks) ... OK (0.52 seconds)
---------------------------
```

```
Test file: /tmp/Rinst57a839ad51a/RProtoBuf/unitTests/runit.serialize.R
test.arrayinputstream: (3 checks) ... OK (0.04 seconds)
test.encoding: (4 checks) ... OK (0 seconds)
test.serialize: (5 checks) ... OK (0 seconds)
```