Knee Injuries - Marginal Models

February 1, 2012

First the dataset knee is loaded:

- > library(catdata)
- > data(knee)
- > attach(knee)

To obtain a simple binary model the response variables are dichotomized. The groups are constructed by pain level up to level 2 und pain level higher than level 2.

```
> R2D <- rep(0, length(R2))
> R3D <- rep(0, length(R3))
> R4D <- rep(0, length(R3))
> R2D[R2>2] <- 1
> R3D[R3>2] <- 1
> R4D[R4>2] <- 1</pre>
```

Now the covariates have to be transformed so that they can be used for the functions "gee" from the "gee"–library and "geeglm" from the "geepack"–library, which will be employed for fitting the models.

```
> N <- rep(knee$N, each=3)
> Th <- rep(knee$Th, each=3)
> Age <- rep(knee$Age, each=3)
> Sex <- rep(knee$Sex, each=3)</pre>
```

Now the response vector is built and the quadratic age–effect "Age2" is computed.

```
> Response <- c(rbind(R2D,R3D,R4D))
> Age2 <- Age^2</pre>
```

The covariates therapy and sex are treated as factors:

```
> Th <- as.factor(Th)
> Sex <- as.factor(Sex)</pre>
```

First the GEEs are fitted with the funtion "gee" from library "gee".

> library(gee)

The first model is a GEE with independent correlation structure:

```
> gee1a <- gee(Response ~ Th + Sex + Age + Age2, id=N,
```

+ family=binomial(link=logit))

> summary(gee1a)

GEE: GENERALIZED LINEAR MODELS FOR DEPENDENT DATA gee S-function, version 4.13 modified 98/01/27 (1998)

Model:

Link: Logit
Variance to Mean Relation: Binomial
Correlation Structure: Independent

Call:

gee(formula = Response ~ Th + Sex + Age + Age2, id = N, family = binomial(link = logit))

Summary of Residuals:

Min 1Q Median 3Q Max -0.8093879 -0.4771034 0.2393885 0.3881349 0.7660757

Coefficients:

Estimate Naive S.E. Naive z Robust S.E. Robust z (Intercept) -4.749831307 1.279009755 -3.713679 1.821208734 -2.6080653 Th2 -0.673979165 0.223825316 -3.011184 0.334205312 -2.0166620 Sex1 0.265689239 0.241933592 1.098191 0.366733338 0.7244753 Age 0.381150842 0.087570504 4.352503 0.125833185 3.0290169 Age2 -0.006124345 0.001381627 -4.432705 0.001984839 -3.0855622

Estimated Scale Parameter: 1.019152

Number of Iterations: 1

Working Correlation

[,1] [,2] [,3] [1,] 1 0 0 [2,] 0 1 0 [3,] 0 0 1

The second model is a GEE with exchangeable correlation structure:

- > gee2a <- gee(Response ~ Th + Sex + Age + Age2, id=N,
 + family=binomial(link=logit), corstr="exchangeable")</pre>
- > summary(gee2a)

GEE: GENERALIZED LINEAR MODELS FOR DEPENDENT DATA gee S-function, version 4.13 modified 98/01/27 (1998)

Model:

Link: Logit
Variance to Mean Relation: Binomial

```
Correlation Structure:
                            Exchangeable
Call:
gee(formula = Response ~ Th + Sex + Age + Age2, id = N, family = binomial(link = logit),
    corstr = "exchangeable")
Summary of Residuals:
       Min
                  1Q
                          Median
-0.8093879 -0.4771034 0.2393885 0.3881349 0.7660757
Coefficients:
                Estimate Naive S.E.
                                        Naive z Robust S.E.
                                                              Robust z
(Intercept) -4.749831307 1.903793545 -2.4949298 1.821208734 -2.6080653
            -0.673979165 0.333161800 -2.0229785 0.334205312 -2.0166620
Sex1
            0.265689239 0.360115792 0.7377884 0.366733338 0.7244753
             0.381150842 0.130347841 2.9241055 0.125833185 3.0290169
Age
            -0.006124345 0.002056538 -2.9779873 0.001984839 -3.0855622
Age2
Estimated Scale Parameter: 1.019152
Number of Iterations: 1
Working Correlation
          [,1]
                    [,2]
                              [,3]
[1,] 1.0000000 0.6078016 0.6078016
[2,] 0.6078016 1.0000000 0.6078016
[3,] 0.6078016 0.6078016 1.0000000
  Finally a GEE with exponential correlation structure is fitted:
> gee3a <- gee(Response ~ Th + Sex + Age + Age2, id=N,
+ family=binomial(link=logit), corstr="AR-M", Mv=1)
> summary(gee3a)
 GEE: GENERALIZED LINEAR MODELS FOR DEPENDENT DATA
 gee S-function, version 4.13 modified 98/01/27 (1998)
Model:
Link:
                            Logit
Variance to Mean Relation: Binomial
 Correlation Structure:
                            AR-M , M = 1
Call:
gee(formula = Response ~ Th + Sex + Age + Age2, id = N, family = binomial(link = logit),
    corstr = "AR-M", Mv = 1)
Summary of Residuals:
```

3Q

Median

-0.8061636 -0.4668263 0.2354196 0.3833613 0.7933803

Min

1Q

Th2 -0.74849866 0.333910055 -2.2416176 0.328084283 -2.2814219 Sex1 0.19277195 0.361954995 0.5325854 0.362465544 0.5318352 Age 0.38489413 0.131285068 2.9317434 0.123289666 3.1218685

Age2 -0.00621548 0.002074949 -2.9954850 0.001945528 -3.1947525

Estimated Scale Parameter: 1.018095

Number of Iterations: 3

Working Correlation

[,1] [,2] [,3]

[1,] 1.0000000 0.7058422 0.4982131

[2,] 0.7058422 1.0000000 0.7058422

[3,] 0.4982131 0.7058422 1.0000000

In the following the corresponding marginal models are fitted with the function "geeglm" from the library "geepack".

> library(geepack)

Model with independent correlation structure:

```
> gee1b <- geeglm(Response ~ Th + Sex + Age + Age2, id=N,
+ family=binomial(link=logit))</pre>
```

> summary(gee1b)

Call:

```
geeglm(formula = Response ~ Th + Sex + Age + Age2, family = binomial(link = logit),
   id = N)
```

Coefficients:

```
Estimate Std.err Wald Pr(>|W|)
(Intercept) -4.749831 1.821209 6.802 0.00911 **
Th2 -0.673979 0.334205 4.067 0.04373 *
Sex1 0.265689 0.366733 0.525 0.46877
Age 0.381151 0.125833 9.175 0.00245 **
Age2 -0.006124 0.001985 9.521 0.00203 **
```

Signif. codes: 0 '***' 0.001 '**' 0.05 '.' 0.1 ' ' 1

Estimated Scale Parameters:

Estimate Std.err

(Intercept) 1.006 0.103

Correlation: Structure = independenceNumber of clusters: 127 Maximum cluster size: 3

Model with exchangeable correlation structure:

```
> gee2b <- geeglm(Response ~ Th + Sex + Age + Age2, id=N,
+ family=binomial(link=logit), corstr="exchangeable")
> summary(gee2b)
Call:
geeglm(formula = Response ~ Th + Sex + Age + Age2, family = binomial(link = logit),
   id = N, corstr = "exchangeable")
Coefficients:
           Estimate Std.err Wald Pr(>|W|)
(Intercept) -4.74983 1.82121 6.80 0.0091 **
           -0.67398 0.33421 4.07
                                    0.0437 *
Sex1
           0.26569 0.36673 0.52
                                   0.4688
            0.38115 0.12583 9.17
                                    0.0025 **
Age
           -0.00612 0.00198 9.52
                                   0.0020 **
Age2
Signif. codes: 0 '***' 0.001 '**' 0.05 '.' 0.1 ' ' 1
Estimated Scale Parameters:
           Estimate Std.err
(Intercept)
               1.01
                      0.103
Correlation: Structure = exchangeable Link = identity
Estimated Correlation Parameters:
     Estimate Std.err
alpha
        0.608 0.0883
Number of clusters: 127
                           Maximum cluster size: 3
  Model with exponential correlation structure:
> gee3b <- geeglm(Response ~ Th + Sex + Age + Age2, id=N,
+ family=binomial(link=logit), corstr="ar1")
> summary(gee3b)
Call:
geeglm(formula = Response ~ Th + Sex + Age + Age2, family = binomial(link = logit),
   id = N, corstr = "ar1")
Coefficients:
           Estimate Std.err Wald Pr(>|W|)
(Intercept) -4.72712 1.78605 7.00
                                    0.0081 **
Th2
           -0.74443 0.32828 5.14
                                     0.0233 *
Sex1
            0.19674 0.36257 0.29
                                     0.5874
Age
            0.38467 0.12338 9.72
                                    0.0018 **
           -0.00621 0.00195 10.17
                                     0.0014 **
Age2
```

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```
Estimated Scale Parameters:
```

Estimate Std.err

(Intercept) 1 0.102

Correlation: Structure = ar1 Link = identity

Estimated Correlation Parameters:

Estimate Std.err

alpha 0.676 0.0766

Number of clusters: 127 Maximum cluster size: 3

For comparison a simple GLM with logit–link is fitted with the same covariates as in the marginal models above:

```
> glm1 <- glm(Response ~ Th + Sex + Age + Age2,
```

- + family=binomial(link=logit))
- > summary(glm1)

Call

glm(formula = Response ~ Th + Sex + Age + Age2, family = binomial(link = logit))

Deviance Residuals:

Min 1Q Median 3Q Max -1.821 -1.139 0.740 0.991 1.705

Coefficients:

```
Estimate Std. Error z value Pr(>|z|)
(Intercept) -4.74983 1.26693 -3.75 0.00018 ***
                   0.22171 -3.04 0.00237 **
Th2
          -0.67398
Sex1
           0.26569
                      0.23965
                               1.11 0.26758
           0.38115
                      0.08674
                                4.39 1.1e-05 ***
Age
                               -4.47 7.6e-06 ***
           -0.00612
                      0.00137
Age2
```

Signif. codes: 0 '***' 0.001 '**' 0.05 '.' 0.1 ' ' 1

(Dispersion parameter for binomial family taken to be 1)

Null deviance: 513.32 on 380 degrees of freedom Residual deviance: 478.61 on 376 degrees of freedom

AIC: 488.6

Number of Fisher Scoring iterations: 4

It is often advatageous to center the variables like age around a value in the middle of its range. So now the marginal models from above are replicated with age centered around 30 years.

```
> Age <- Age-30
> Age2 <- Age^2</pre>
```

Again we use the function "gee" from the "gee"–library for fitting those models.

Model with independent correlation structure and centered age:

- > gee1c <- gee(Response ~ Th + Sex + Age + Age2, id=N,
- + family=binomial(link=logit))
- > summary(gee1c)

GEE: GENERALIZED LINEAR MODELS FOR DEPENDENT DATA gee S-function, version 4.13 modified 98/01/27 (1998)

Model:

Link: Logit
Variance to Mean Relation: Binomial
Correlation Structure: Independent

Call

gee(formula = Response ~ Th + Sex + Age + Age2, id = N, family = binomial(link = logit))

Summary of Residuals:

Min 1Q Median 3Q Max -0.809 -0.477 0.239 0.388 0.766

Coefficients:

	Estimate	Naive S.E.	Naive z	Robust S.E.	Robust z
(Intercept)	1.17278	0.28476	4.12	0.44806	2.617
Th2	-0.67398	0.22383	-3.01	0.33421	-2.017
Sex1	0.26569	0.24193	1.10	0.36673	0.724
Age	0.01369	0.01204	1.14	0.01736	0.789
Age2	-0.00612	0.00138	-4.43	0.00198	-3.086

Estimated Scale Parameter: 1.02

Number of Iterations: 1

Working Correlation

[,1] [,2] [,3] [1,] 1 0 0 [2,] 0 1 0 [3,] 0 0 1

Model with exchangeable correlation structure and centered age:

- > gee2c <- gee(Response ~ Th + Sex + Age + Age2, id=N,
- + family=binomial(link=logit), corstr="exchangeable")
- > summary(gee2c)

GEE: GENERALIZED LINEAR MODELS FOR DEPENDENT DATA gee S-function, version 4.13 modified 98/01/27 (1998)

```
Summary of Residuals:
  Min
          1Q Median
                         3Q
-0.809 -0.477 0.239 0.388 0.766
Coefficients:
           Estimate Naive S.E. Naive z Robust S.E. Robust z
(Intercept) 1.17278
                       0.42386
                                2.767
                                          0.44806
                                                       2.617
Th2
           -0.67398
                       0.33316 -2.023
                                            0.33421
                                                      -2.017
Sex1
            0.26569
                       0.36012
                                0.738
                                            0.36673
                                                     0.724
                       0.01792
            0.01369
                                0.764
                                            0.01736
                                                     0.789
Age
                       0.00206 -2.978
Age2
            -0.00612
                                            0.00198
                                                    -3.086
Estimated Scale Parameter: 1.02
Number of Iterations: 1
Working Correlation
      [,1] [,2] [,3]
[1,] 1.000 0.608 0.608
[2,] 0.608 1.000 0.608
[3,] 0.608 0.608 1.000
  Model with exponential correlation structure and centered age:
> gee3c <- gee(Response ~ Th + Sex + Age + Age2, id=N,
+ family=binomial(link=logit), corstr="AR-M", Mv=1)
> summary(gee3c)
 GEE: GENERALIZED LINEAR MODELS FOR DEPENDENT DATA
 gee S-function, version 4.13 modified 98/01/27 (1998)
Model:
Link:
                            Logit
 Variance to Mean Relation: Binomial
 Correlation Structure:
                            AR-M , M = 1
Call:
gee(formula = Response ~ Th + Sex + Age + Age2, id = N, family = binomial(link = logit),
   corstr = "AR-M", Mv = 1)
```

gee(formula = Response ~ Th + Sex + Age + Age2, id = N, family = binomial(link = logit),

Logit

Exchangeable

Variance to Mean Relation: Binomial

corstr = "exchangeable")

Correlation Structure:

Model: Link:

Call:

Summary of Residuals:
Min 1Q Median 3Q Max
-0.806 -0.467 0.235 0.383 0.793

Coefficients:

	Estimate	Naive S.E.	Naive z	Robust S.E.	Robust z
(Intercept)	1.22675	0.42743	2.870	0.44356	2.766
Th2	-0.74850	0.33391	-2.242	0.32808	-2.281
Sex1	0.19277	0.36195	0.533	0.36247	0.532
Age	0.01197	0.01797	0.666	0.01699	0.704
Age2	-0.00622	0.00207	-2.995	0.00195	-3.195

Estimated Scale Parameter: 1.02

Number of Iterations: 3

Working Correlation

[,1] [,2] [,3]

[1,] 1.000 0.706 0.498

[2,] 0.706 1.000 0.706

[3,] 0.498 0.706 1.000