# Examples for the datetimeutils package

#### Enrico Schumann

es@enricoschumann.net

### convert\_date

Convert dates in numeric external formats (e.g. from MATLAB or Excel) to Date.

```
> convert_date(40000, "excel")
```

```
[1] "2009-07-06"
```

> convert\_date(725935, "matlab")

```
[1] "1987-07-17"
```

#### convert\_tz

Convert a timestamp from one timezone to another.

```
> convert_tz("2016-05-10 12:00:00", "Europe/Berlin", "America/Chicago")
```

```
[1] "2016-05-10 05:00:00 CDT"
```

# **Business days**

See ?business\_days.

```
> is_weekend(as.Date("2017-1-5"))
```

```
[1] FALSE
```

```
> next_businessday(as.Date("2017-1-5")) ## there is also 'previous_businessday'
```

```
> next_businessday(as.Date("2017-1-5"), shift = 2) ## short-hand: 'next_bday'
```

```
[1] "2017-01-09"
```

[1] "2017-01-06"

# **Guess Timestamp Format**

> guess\_datetime(s)

```
[1] "1999-08-19 10:00:00 CEST" "1999-08-19 10:00:00 CEST" [3] "1999-08-19 10:00:00 CEST"
```

### Days of the week (or some other calendar period)

```
> last_weekday(5, as.Date("2017-1-1"))  ## last Friday of Jan 2017
```

```
[1] "2017-01-27"
```

```
> nth_weekday(1, as.Date("2017-1-1"), 2) ## second Monday of Jan 2017
```

```
[1] "2017-01-09"
```

```
> dates <- seq(as.Date("2012-1-1"), as.Date("2013-4-15"), by = "day")
> nth_day(dates, period = "quarter", n = "first")
```

```
[1] "2012-01-01" "2012-04-01" "2012-07-01" "2012-10-01" "2013-01-01"
```

[6] "2013-04-01"

> nth\_day(dates, period = c("Jan", "April"), n = "first")

```
[1] "2012-01-01" "2012-04-01" "2013-01-01" "2013-04-01"
```

> nth\_day(dates, period = c("Jan", "April"), n = "last")

```
[1] "2012-01-31" "2012-04-30" "2013-01-31" "2013-04-15"
```

> nth\_day(dates, period = c("Jan", "April"), n = c(2, 5))

```
[1] "2012-01-02" "2012-01-05" "2012-04-02" "2012-04-05" "2013-01-02" [6] "2013-01-05" "2013-04-02" "2013-04-05"
```

# > toLatex(sessionInfo())

- R version 4.3.3 (2024-02-29), x86\_64-pc-linux-gnu
- Locale: LC\_CTYPE=en\_US.UTF-8, LC\_NUMERIC=C, LC\_TIME=en\_GB.UTF-8, LC\_COLLATE=C, LC\_MONETARY=en\_GB.UTF-8, LC\_MESSAGES=en\_US.UTF-8, LC\_PAPER=en\_GB.UTF-8, LC\_NAME=C, LC\_ADDRESS=C, LC\_TELEPHONE=C, LC\_MEASUREMENT=en\_GB.UTF-8, LC\_IDENTIFICATION=C
- Time zone: Europe/Zurich
- TZcode source: system (glibc)
- Running under: Ubuntu 23.10
- Matrix products: default
- BLAS: /usr/lib/x86\_64-linux-gnu/openblas-openmp/libblas.so.3
- LAPACK: /usr/lib/x86\_64-linux-gnu/openblas-openmp/libopenblasp-r0.3.23.so; LAPACK version3.11.0
- Base packages: base, datasets, grDevices, graphics, methods, stats, utils
- Other packages: datetimeutils 0.6-4
- Loaded via a namespace (and not attached): compiler 4.3.3, tools 4.3.3