Examples for the datetimeutils package

Enrico Schumann es@enricoschumann.net

convert date

Convert dates in numeric external formats (e.g. from MATLAB or Excel) to Date.

```
> convert_date(40000, "excel")
```

```
[1] "2009-07-06"
```

> convert_date(725935, "matlab")

```
[1] "1987-07-17"
```

convert tz

Convert a timestamp from one timezone to another.

```
> convert_tz("2016-05-10 12:00:00", "Europe/Berlin", "America/Chicago")
[1] "2016-05-10 05:00:00 CDT"
```

Business days

See ?business_days.

```
> is_weekend(as.Date("2017-1-5"))
```

```
[1] FALSE
```

```
> next_businessday(as.Date("2017-1-5")) ## there is also 'previous_businessday'
[1] "2017-01-06"
```

```
> next_businessday(as.Date("2017-1-5"), shift = 2) ## short-hand: 'next_bday'
[1] "2017-01-09"
```

Guess Timestamp Format

Days of the week (or some other calendar period)

```
> last_weekday(5, as.Date("2017-1-1")) ## last Friday of Jan 2017

[1] "2017-01-27"

> nth_weekday(1, as.Date("2017-1-1"), 2) ## second Monday of Jan 2017

[1] "2017-01-09"
```

```
> dates <- seq(as.Date("2012-1-1"), as.Date("2013-4-15"), by = "day")
> nth_day(dates, period = "quarter", n = "first")
```

```
[1] "2012-01-01" "2012-04-01" "2012-07-01" "2012-10-01" "2013-01-01" [6] "2013-04-01"
```

> toLatex(sessionInfo())

- R version 3.4.3 (2017-11-30), x86_64-pc-linux-gnu
- Locale: LC_CTYPE=en_US.UTF-8, LC_NUMERIC=C, LC_TIME=en_GB.UTF-8, LC_COLLATE=C, LC_MONETARY=en_GB.UTF-8, LC_MESSAGES=en_US.UTF-8, LC_PAPER=en_GB.UTF-8, LC_NAME=C, LC_ADDRESS=C, LC_TELEPHONE=C, LC_MEASUREMENT=en_GB.UTF-8, LC_IDENTIFICATION=C
- Running under: Ubuntu 17.10
- · Matrix products: default
- BLAS:/usr/lib/x86_64-linux-gnu/openblas/libblas.so.3
- LAPACK: /usr/lib/x86_64-linux-gnu/libopenblasp-r0.2.20.so
- Base packages: base, datasets, grDevices, graphics, methods, stats, utils
- Other packages: datetimeutils 0.2-12
- Loaded via a namespace (and not attached): compiler 3.4.3, tools 3.4.3