# The Graph Partitioning Problem

#### Adam Rahman

September 4, 2017

The graph partitioning problem can be formulated as the following primal optimization problem

minimize 
$$tr(\mathbf{CX})$$
  
subject to 
$$tr(\mathbf{11}^{\mathsf{T}}\mathbf{X}) = \alpha$$

$$diag(\mathbf{X}) = \mathbf{1}$$

Here,  $\mathbf{C} = -(diag(\mathbf{B1}) - \mathbf{B})$ , for an adjacency matrix  $\mathbf{B}$ , and  $\alpha$  is any real number.

The function gpp, takes as input a weighted adjacency matrix B and a real number alpha and returns the input necessary to solve the problem using sqlp.

```
R> out <- gpp(B,alpha)
R> blk <- out$blk
R> At <- out$At
R> C <- out$C
R> b <- out$b</pre>
R> sqlp(blk,At,C,b)
```

## Numerical Example

To demonstrate the output provided by sqlp, we make use of the following adjacency matrix

```
R> data(Bgpp)
R> Bgpp
```

```
V1 V2 V3 V4 V5 V6 V7 V8 V9 V10
[1,]
                  0
                     0 1
               1
[2,]
[3,]
            0
               0
                  0 0 0
      0
         0
[4,]
               0
                  0
                     0
[5,]
        0
            0
              0 0 0
[6,]
            0
               0
[7,]
      1
               0
         1
                  1
                    0
[8,]
               1
                  1
[9,]
      0
         1
            0
               0
                  1
[10,]
         1
               1
                  1
```

Any value of  $\alpha$  in  $(0, n^2)$  can be chosen, so without loss of generality, we choose a value of n to solve the problem.

```
alpha <- nrow(Bgpp)

out <- gpp(Bgpp, alpha)
blk <- out$blk
At <- out$At
C <- out$C
b <- out$b

out <- sqlp(blk,At,C,b)</pre>
```

As with the max-cut problem, the output of interest here is the primal objective function, keeping in mind that we have swapped the sign of the objective function so that the primal problem is a minimization.

### out\$pobj

### [1] -57.20785

Also like the maxcut problem, the set of feasible solutions are correlation matrices

out\$X[[1]]		#Rounded to 3 decimal places								
	[,1]	[,2]	[,3]	[, 4]	[,5]	[,6]	[,7]	[,8]	[,9]	[,10]
V1	1.000	1.000	0.550	-0.604	0.702	0.895	-0.611	0.006	-0.920	0.741
٧2	1.000	1.000	0.572	-0.583	0.721	0.907	-0.590	-0.020	-0.930	0.723
VЗ	0.550	0.572	1.000	0.333	0.981	0.865	0.325	-0.832	-0.834	-0.153
٧4	-0.604	-0.583	0.333	1.000	0.143	-0.186	1.000	-0.800	0.243	-0.983
٧5	0.702	0.721	0.981	0.143	1.000	0.946	0.135	-0.708	-0.926	0.043
۷6	0.895	0.907	0.865	-0.186	0.946	1.000	-0.194	-0.440	-0.998	0.365
٧7	-0.611	-0.590	0.325	1.000	0.135	-0.194	1.000	-0.796	0.251	-0.984
V8	0.006	-0.020	-0.832	-0.800	-0.708	-0.440	-0.796	1.000	0.387	0.676
۷9	-0.920	-0.930	-0.834	0.243	-0.926	-0.998	0.251	0.387	1.000	-0.418
V10	0.741	0.723	-0.153	-0.983	0.043	0.365	-0.984	0.676	-0.418	1.000