

PAY RESULT API

Request Direction: IO Controller -> PMS

Endpoint: POST [/w4g/PayResult](#)

```
{
  "State": "0",
  "OrderId": "asd455fdgd99898fdgd989fd",
  "PayType": 0,
  "CardNo": "43243212",
  "Balance": 50000,
  "PayTime": 1702279204,
  "STAN": "12CD34",
  "APPR_CODE": "123456"
}
```

Field Name	Mandatory	Data Type	Description
State	Yes	string	Deduction results, 0- Success others- Failed
OrderId	Yes	string	The order number carried when requesting. (Maximum 32 characters)
PayType	Yes	int	0- TNG card 1- 1-VISA 2- 2-MASTER 3- 3-MCCS 4-TNG E-wallet
CardNo	Yes	string	Card manufacturing no.
Balance	Yes	int	Card balance after the transaction amount deduction.

Field Name	Mandatory	Data Type	Description
PayTime	Yes	long	Transaction date and time. UTC time (0 time zone)
STAN	Yes	string	Trace Number,3 bytes BCD, Example: “000001”=0x00 0x00 0x01
APPR_CODE	Yes	string	Approval Code, the authorization code from bank for a successful transaction, ascii code

PMS Response

```
{
  "State":0,
  "OrderId":"asd455fdgd99898fdgd989fd",
}
```

Field Name	Mandatory	Data Type	Description
State	Yes	int	Receive results, 0- Success others- Failed
OrderId	Yes	string	The order number carried when requesting. (Maximum 32 characters)

Instruction

Only when State is 0, the other fields behind are meaningful. PMS must **acknowledge receipt** to prevent retries.