

Principles of Programming


Module 8: Objects and Classes

Object Oriented Programming, Implementing a Simple Class

Today's Objectives

- Topics
 - 8.1 Object Oriented Programming
 - 8.2 Implementing a Simple Class

A Car Race!



Last Lecture *on a Page*

- Java programs can use command line arguments.

```
public static void main(String[] args) { ... }
```

```
>java CaesarCipher -d encrypt.txt output.txt
```

↑ ↑ ↑
args[0] args[1] args[2]

- "Dangerous" code should be in a try block:

```
try {
    String filename = "input.txt";
    Scanner in = new Scanner(new File(filename));
}
catch (FileNotFoundException f) {
    System.out.println("File not found");
}
```


Handled

Declared

- Or declare that you might throw the Exception:

```
public void readStuff(String filename) throws FileNotFoundException {
    ...
}
```

Java Exceptions



"Unchecked Exceptions" do not.

"Checked Exceptions" must be handled or declared.

Object-Oriented Programming

- You have learned structured programming:
 - Breaking tasks into subtasks.
 - Writing reusable methods to handle tasks.
- We will now study object-oriented programming:
 - Using Objects and Classes to build larger and more complex programs.
 - Also used to model objects we use in the world.



A **class** describes a set of objects with the same information and the same behavior.

- The *class* Car describes *all* passenger vehicles.
- The *class* String describes *all* character strings.

An **object** is a member of a class.

- I own a particular Car *object*.
- Suspect is a particular String.
`String suspect = "Prof. Plum";`

Objects and Programs

- Java programs are made of objects that interact with each other.
 - Each object is a member of a particular class.
 - That class defines the data for the objects and its behavior.
- Behavior: the methods to use with its objects
 - For example, the String class provides methods:
 - Examples: `length()` and `charAt()` methods

String
+length(): int +charAt(int): char +substring(int, int): String +substring(): String +compareTo(String): int +equals(String): boolean

class String


object suspect

```
String suspect = "Prof. Plum";  
int len = suspect.length();  
char c1 = suspect.charAt(0);
```

Calling a *method*,
defined by *class String*,
on *object suspect*

Diagram of a Class

- Private Data
 - Each object has its own private data that other objects cannot directly access.
- Public Interface
 - Each object has a set of methods available for other objects to use.
- This is called *Encapsulation*.



Notice the subtle introduction to UML notation for classes!

Math
+PI: double
+sqrt(double): double +pow(double, double): double +random(): double

Why we use Encapsulation

- Programmer using a class -
 - Only needs to know what the class does,
 - Not how it does it.
- Programmer writing a class -
 - Can protect the data needed to ensure correct behavior.
 - Can change the implementation later without effecting others.
- Manage Complexity!



Classes and Objects


- A class is a template definition of the methods and variables common for a particular set of objects.
- An object is a specific instance of a class; it contains real values instead of variables.
- A class is the cookie cutter, an object is the cookie.



Implementing a Simple Class


- Tally Counter: A class that models a mechanical device that is used to count people.
 - For example, to find out how many people attend a concert or board a bus.
- What does it need to keep track of?
 - The current count
- What should it do?
 - Increment the tally
 - Get the current total

Class diagram
in UML



Tally Counter Class

- Specify instance variables in the class declaration:



- Each object instantiated from the class has its own set of instance variables.
 - Each tally counter has its own current count (`value`).
- Access Specifiers:
 - Classes are **public**
 - Instance variables are almost always **private**
 - Most methods are **public**

Instantiating Objects


- Objects are created based on classes.
 - Use the **new** operator to construct objects.
 - Give each object a unique name (like variables).
- You have used the **new** operator before:

```
Scanner in = new Scanner(System.in);
```

- Creating two instances of Counter objects:

Class name Object name Class name

```
Counter concertCounter = new Counter();  
Counter boardingCounter = new Counter();
```




Counter

value =

Tally Counter Methods

- Design a method named `count` that adds 1 to the instance variable.
- Which instance variable?
 - Use the name of the object:
 - `concertCounter.count()`
 - `boardingCounter.count()`



```
public class Counter
{
    private int value = 0;

    public void count()
    {
        value = value + 1;
    }

    public int getValue()
    {
        return value;
    }
}
```

Another Class Example

- Define a Car class.
- What instance variables might it have?
- What methods will it have?

Car
-color: String -model: String -odometer: long
+setColor(c: String): void +setModel(m: String): void +addMiles(trip: int): void +getMiles(): long +print(): void


```
class Car {  
    private String color;  
    private String model;  
    private long odometer;  
  
    public void setColor(String c) {  
        ...  
    }  
    ...  
}
```

Typically private

'global'
Declared *inside* the class, but *outside* any method.

Objects

- A *running* Java program is made up of objects.
- Each object has values for its instance variables.



- Objects are created in Java with the *new* statement

```
Car ericsCar = new Car();  
ericsCar.setColor("silver");  
ericsCar.setModel("Prius");
```

```
Car joesCar = new Car();  
joesCar.setColor("red");  
joesCar.setModel("Rav 4");
```

Local vs. 'Global' (instance) Variables

The diagram illustrates the scope of variables in a Java class. It shows the following code structure with annotations:

```
public class HelloWorld {  
    public String name;  
    public static void main(String[] args) {  
        int i = 22;  
        System.out.println("Hello World! " + i);  
    }  
}
```

Annotations and their targets:

- Class**: A bracket on the left side of the code, spanning from the opening curly brace of the class to the closing curly brace, indicating the entire class structure.
- Instance Variable "global" variable**: An arrow points to the `public String name;` line, indicating it is an instance variable.
- Local Variable**: An arrow points to the `int i = 22;` line, indicating it is a local variable.
- Method**: A bracket on the right side of the code, spanning from the opening curly brace of the `main` method to the closing curly brace, indicating the method scope.

Using Instance Variables

- The code in the methods can use the instance attributes.
 - A method is called on a particular object.
 - The method will use the instance variables for that object.
- Example:

```
Class Car {  
    private String color;  
    private long odometer = 0;  
  
    public void setColor(String c) {  
        color = c;  
    }  
    public void addMiles(int tripMileage) {  
        odometer = odometer + tripMileage;  
    }  
}
```


Using Classes

- Example:

```
class CarTest {  
    public static void main(String[] args) {  
        Car c1 = new Car();  
        Car c2 = new Car();  
  
        c1.setColor("white");  
        c1.addMileage(1200);  
        c1.addMileage(100);  
  
        c2.setColor("blue");  
    }  
}
```

- Result:

- c1: white, 1300 miles
- c2: blue: 0 miles

Things to Remember

- Each class must be in its own file.
 - As always, the name of the class must match the name of the file.
- To use another class
 - It must be in the same package
 - Or, you must use the import

```
public class Car {  
    private String color;  
    private String model;  
    private long odometer = 0;  
  
    public void setColor(String c) {  
        color = c;  
    }  
  
    public void setModel(String m) {  
        model = m;  
    }  
  
    public void addMiles(int tripMileage) {  
        odometer = odometer + tripMileage;  
    }  
  
    public long getMiles() {  
        return odometer;  
    }  
  
    public void print() {  
        System.out.println("At " + odometer + ", the " + color + " " + model);  
    }  
}
```

Car
-color: String -model: String -odometer: long
+setColor(c: String): void +setModel(m: String): void +addMiles(trip: int): void +getMiles(): long +print(): void

CSE110 – Principles of Programming

Eric Eckert

eric.eckert@asu.edu

Disclaimer: These slides can only be used as study material for the class CSE110 at ASU. They cannot be distributed or used for another purpose.

This presentation is derived from the publisher's material. Copyright © 2013 by John Wiley & Sons. All rights reserved.