

PACE: Probabilistic Adaptive Contention Control for Non-Primary Channel Access in IEEE 802.11bn

Taewon Song

Division of Electronics and Electrical Engineering

Dongguk University

Seoul, Republic of Korea

twsong@dongguk.edu

Abstract—Modern Wi-Fi deployments increasingly suffer from spectrum underutilization as overlapping Basic Service Sets (OBSSs) compete for primary channel access. IEEE 802.11bn introduces Non-Primary Channel Access (NPCA) to exploit these underutilized intervals, yet the standard contention mechanism is fundamentally mismatched to NPCA’s constrained transmission windows: backoff counters routinely exceed the remaining opportunity duration, wasting slots that could otherwise carry data. We propose PACE, a probabilistic adaptive contention control scheme that enables stations to collectively converge toward a theoretically optimal transmission probability without central coordination. PACE combines a distributed multiplicative feedback rule—copying the successful sender’s probability on solo receptions—with a prospective self-exclusion mechanism that silences stations whose frame length exceeds the remaining window. We evaluate PACE through simulation spanning a wide range of station counts and window lengths, comparing against Binary Exponential Backoff and several competing adaptive schemes under both homogeneous and heterogeneous frame-length distributions. PACE consistently outperforms standard backoff in channel utilization and achieves Pareto-dominance in the throughput-fairness tradeoff. The advantage is most pronounced when the available window is scarce relative to the contending population, precisely the regime in which standard backoff wastes the largest share of transmission opportunities. These results identify the tight-window regime as the critical operating condition for NPCA and establish PACE as a practical design reference for adaptive contention policy in next-generation Wi-Fi networks.

Index Terms—Non-Primary Channel Access, IEEE 802.11bn, Probabilistic Access Control, OBSS, Adaptive Contention, Wi-Fi

I. INTRODUCTION

Spectrum efficiency in next-generation Wi-Fi networks depends critically on how effectively stations exploit available channel time. In dense deployments, overlapping Basic Service Sets (OBSSs) routinely occupy the primary channel while adjacent channels remain idle, creating a persistent underutilization problem. IEEE 802.11bn addresses this gap by introducing Non-Primary Channel Access (NPCA), which allows stations to transmit opportunistically on non-primary channels during ongoing OBSS intervals [1], [2].

NPCA, however, presents a contention challenge distinct from conventional channel access. Each NPCA opportunity has a finite duration bounded by the ongoing OBSS transmission, and competing stations must coordinate their access within this constrained window. The Binary Exponential

Backoff (BEB) mechanism was designed for open-ended contention: each collision doubles the backoff window, and the resulting delay frequently exceeds the remaining NPCA window duration. Affected stations are effectively silenced for the rest of the interval, leaving the channel idle even when other stations could have transmitted. In heterogeneous deployments where stations carry frames of varying lengths, the problem is further compounded: stations whose frame cannot fit in the remaining window continue to occupy contention slots despite having no viable transmission opportunity.

Consider a dense office environment where multiple stations detect an OBSS transmission and attempt to use the secondary channel concurrently. Early collisions trigger exponential backoff growth; within a few rounds, a large fraction of stations have accumulated backoff counts that exceed the remaining window duration. The channel spends the final slots idle, not because no station wanted to transmit, but because the contention mechanism pushed every backoff counter beyond the opportunity horizon.

Existing work on NPCA has focused on characterizing aggregate throughput and delay under the standard switching rule, taking Binary Exponential Backoff within the non-primary channel as given [2]–[4]. The contention dynamics within the finite NPCA window—and the mismatch between BEB’s infinite-horizon design and the window’s bounded duration—have not been addressed. Adaptive probabilistic schemes designed for infinite-horizon neighbor discovery, such as the ALOHA-like Neighbor Discovery (AND) algorithm [5], reduce overhead by avoiding explicit coordination, but their stationary-population assumption makes them ill-suited to a window that depletes over time. BEB’s infinite-horizon design and AND’s open-loop phase structure both fail to track the time-varying optimal access probability as the window shrinks and the set of viable stations changes (see Table I).

In this paper, we propose PACE, a Probabilistic Adaptive Contention control scheme for NPCA that enables stations to collectively converge toward the theoretically optimal transmission probability for each moment within the window, without central coordination or explicit inter-station signaling. PACE adapts the MIMD feedback rule of the Probabilistic Neighbor Discovery (PND) algorithm [6] to the finite-window NPCA context: stations copy the successful sender’s probability on solo receptions, reduce on collision, and in-

TABLE I: Comparison of Contention Control Schemes

Method	Mechanism	Objective	PPDU-aware	Signaling-free	NPCA target
AND [5]	Fixed-probability slotted ALOHA	Discover all neighbors in finite time without coordination	×	✓	×
PND [6]	Multiplicative feedback with solo-copy rule	Converge transmission probability to optimal without N	×	✓	×
Cali <i>et al.</i> [7]	p-persistent with contender estimation	Approach theoretical throughput limit in a distributed manner	×	✓	×
BLADE [8]	Hybrid increase / multiplicative decrease via access rate	Eliminate packet-delivery droughts for real-time Wi-Fi	×	✓	×
IYT [9]	Neighbor-ordered backoff interval assignment	Reduce collision probability and worst-case latency	×	✓	×
ACWB-DQN [10]	Deep Q-network contention window selection	Maximize throughput under varying network load	×	×	×
FC-MAPPO [11]	Fairness-constrained multi-agent policy optimization	Minimize collisions while ensuring inter-station fairness	×	×	×
PACE (proposed)	Multiplicative feedback with PPDU-aware self-exclusion	Maximize channel utilization in finite NPCA window	✓	✓	✓

crease on idle slots, causing distributed dynamics to track the throughput-optimal policy. PACE further adds a PPDU-aware self-exclusion rule that silences stations whose frame length exceeds the remaining window, eliminating a class of futile contention attempts that BEB would otherwise sustain.

The design of PACE is motivated by two requirements that are unique to NPCA's bounded-window structure: (i) the optimal transmission probability is time-varying and must track the depleting window rather than converge to a static equilibrium, and (ii) stations whose frame length exceeds the remaining window must proactively self-exclude to prevent futile contention that wastes viable slots. The main contributions of this paper are as follows:

- We derive the throughput-optimal transmission probability for finite-window NPCA, showing that it must continuously track the remaining window duration and the number of still-viable competing stations—a time-varying target that neither BEB nor existing infinite-horizon adaptive schemes can follow.
- We propose PACE, a fully distributed algorithm that addresses both requirements simultaneously: MIMD feedback drives the transmission probability toward the time-varying optimum (i), while PPDU-aware self-exclusion eliminates futile contention by silencing stations that cannot complete a frame within the remaining window (ii), all without inter-station signaling or knowledge of the total station count.
- Through extensive simulation under homogeneous and heterogeneous frame-length distributions, we demonstrate that PACE achieves significantly higher window utilization than BEB, is Pareto-dominant in the throughput-fairness tradeoff, and maintains proportional fairness between native and visiting stations.

The remainder of this paper is organized as follows. Section II reviews related work on NPCA and adaptive MAC protocols. Section III presents the system model. Section IV describes the PACE algorithm and its theoretical foundation. Section V presents simulation results, and Section VI concludes the paper.

II. RELATED WORK

Table I summarizes the key distinctions among existing contention control schemes and the proposed PACE.

A. Non-Primary Channel Access in IEEE 802.11bn

IEEE 802.11bn introduces NPCA as a core mechanism for exploiting idle secondary channels during OBSS transmissions [1], [12]. Wei *et al.* [2] extended Bianchi's DCF model to a multi-channel setting, establishing analytically that NPCA always outperforms the legacy baseline; a follow-up study [4] incorporated switching overhead and proposed a threshold policy to toggle between NPCA and legacy modes based on primary channel occupancy. Bellalta *et al.* [3] developed a Continuous-Time Markov Chain model for a multi-BSS topology, identifying a secondary-channel contention trade-off that can limit NPCA gains when the secondary channel is shared. Lee and Song [13] further showed that PPDU frame duration has a nonlinear effect on inter-BSS coexistence, and Song [14] applied deep reinforcement learning to the NPCA channel-activation decision.

Across these studies, however, the contention mechanism within the NPCA window is held fixed at Binary Exponential Backoff. How stations should adapt their access probability as the window depletes and viable stations drop out has not been studied.

B. Adaptive Contention Control in Wireless LANs

Bianchi [15] established that BEB operates below the theoretical throughput ceiling, and Cali *et al.* [7] showed that p-persistent access with dynamic contender estimation can approach this limit in a distributed manner. Subsequent work has diversified the adaptation mechanisms: BLADE [8] uses a HIMD policy driven by a universally observable channel signal; Wilhelmi *et al.* [9] impose structured transmission order via inter-BSS activity awareness; and learning-based approaches optimize the contention window through deep Q-networks [10] or fairness-constrained multi-agent policy optimization [11].

Despite this breadth, all existing schemes assume stations contend over an open-ended horizon and target steady-state




Fig. 1: The medium access process comparison between legacy and NPCA.

convergence. NPCA’s bounded window demands a fundamentally different approach: the optimal transmission probability must evolve as the window shrinks and the viable station population changes. The MIMD feedback rule of PND [6] is the closest mechanism in spirit, but was designed for infinite-horizon neighbor discovery and provides no accounting for bounded window duration or frame-length viability.

III. SYSTEM MODEL

A. Network and Channel Model

We consider a single Basic Service Set (BSS) comprising an Access Point (AP) and a set $\mathcal{N} = \{1, 2, \dots, N\}$ of associated non-AP stations that operate under IEEE 802.11bn. Following the NPCA capability requirement, the BSS occupies a wide operating channel of at least 80 MHz. The operating channel is partitioned into a *BSS primary channel* and a secondary portion of one or more 20 MHz subchannels. Within the secondary portion the AP designates one 20 MHz subchannel as the *NPCA primary channel*, which serves as an auxiliary contention channel during NPCA operation. Throughout, we use the qualifier “BSS” to distinguish the original primary channel from the NPCA primary channel, consistent with the terminology of P802.11bn Draft [1].

B. Legacy versus NPCA Medium Access

Fig. 1 contrasts the two medium-access processes. Under *legacy* access (top), a station contends only on the BSS primary channel.¹ It decrements its backoff counter while the channel is idle and transmits when the counter reaches zero. If the secondary channel is also sensed idle at this instant, the station may bond it with the BSS primary channel and transmit a wideband PPDU spanning the combined bandwidth (e.g., 40, 80, or 160 MHz). When an overlapping BSS (OBSS) transmission seizes the BSS primary channel, however, the station must defer and freeze its backoff for the entire OBSS busy period, even though the secondary channel is idle.

Under *NPCA* access (bottom), a station no longer wastes the OBSS busy period. When it detects an OBSS transmission on the BSS primary channel, it decodes the preamble of that transmission and learns its duration in advance; rather

than freezing its backoff for the whole period, it switches to the idle NPCA primary channel and continues to contend and transmit there. On each such switch the station saves its backoff state on the BSS primary channel and initializes a fresh contention window for the NPCA primary channel, so every NPCA visit begins at the minimum backoff stage regardless of prior history. The station already knows when the OBSS transmission will finish, so it sets a timer to that instant and switches back to the BSS primary channel when the timer expires, restoring the saved state without having to re-sense the channel. In this way the secondary spectrum that the legacy station leaves idle is put to use, and a station can complete one or more transmissions that it would otherwise have had to postpone.

Two constraints shape this access. First, a radio transition delay δ_{sw} is incurred on each switch. Second, the opportunity lasts only until the known end of the OBSS transmission, whose remaining duration D_{rem} is read from the preamble. Contention and transmission must therefore fit within a bounded window of

$$W_{eff} = \left\lfloor \frac{D_{rem} - \delta_{sw}}{\sigma} \right\rfloor \text{ slots}, \quad (1)$$

where σ is the slot time, typically 9 μs in IEEE 802.11-compliance systems. This deadline is the crux of NPCA: every backoff decision competes against it. A station that collides doubles its contention window as usual, and once the resulting backoff exceeds the slots left in W_{eff} , it can no longer transmit before the window closes so it wastes the rest of the opportunity despite having data to send.

Because the contention window is reset at every NPCA visit, this penalty recurs each time rather than amortizing across visits. This mismatch between open-ended backoff and the finite window is the inefficiency that PACE targets.

C. Slotted Contention Model

IEEE 802.11 stations access the medium through the DCF, a CSMA/CA mechanism in which each station maintains a backoff counter rather than transmitting at random in every slot. Directly analyzing DCF over a finite window is intractable, so we adopt the standard slotted abstraction introduced by Bianchi [15]: the backoff process of a saturated DCF station is represented by a single per-slot transmission probability τ , the steady-state probability that the station transmits in a randomly chosen slot. We stress that this is an analytical model, not a change to the access mechanism—802.11 remains backoff-based DCF, and Section IV maps the probabilities derived here back to a concrete, backoff-compatible rule.

Under this abstraction, we model time on the NPCA primary channel as a sequence of slots of duration σ and index them by $t \in \{0, 1, \dots, W_{eff}\}$. We denote by $W_{rem}(t) = W_{eff} - t$ the number of slots remaining at slot t , so that W_{rem} counts down toward the deadline as contention proceeds.

Let $\mathcal{V} \subseteq \mathcal{N}$ be the set of stations that switch to the NPCA primary channel, each holding a pending PPDU whose transmission occupies L_i slots. Because a transmission must

¹We use the term *BSS primary channel* to distinguish the original primary channel from the NPCA primary channel introduced in IEEE 802.11bn. Prior to 802.11bn, when NPCA was not yet defined, this channel was referred to simply as the *primary channel*.

sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

V. PERFORMANCE EVALUATION

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

VI. CONCLUSION

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

REFERENCES

- [1] IEEE, "IEEE Standard for Information Technology—Telecommunications and Information Exchange between Systems—Local and Metropolitan Area Networks—Specific Requirements—Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications—Amendment: Enhancements for Ultra High Reliability," 2023. [Online]. Available: <https://mentor.ieee.org/802.11/dcn/23/11-23-0480-03-0uhr-uhr-proposed-par.pdf>
- [2] D. Wei, L. Cao, L. Zhang, X. Gao, and H. Yin, "Non-Primary Channel Access in IEEE 802.11 UHR: Comprehensive Analysis and Evaluation," in *2024 IEEE 100th Vehicular Technology Conference (VTC2024-Fall)*. IEEE, 2024, pp. 1–6.
- [3] B. Bellalta, F. Wilhelmi, L. Galati-Giordano, and G. Geraci, "Performance Analysis of IEEE 802.11 bn Non-Primary Channel Access," *arXiv preprint arXiv:2504.15774*, 2025.
- [4] D. Wei, L. Cao, L. Zhang, X. Gao, and H. Yin, "Optimized Non-Primary Channel Access Design in IEEE 802.11 bn," in *GLOBECOM 2024-2024 IEEE Global Communications Conference*. IEEE, 2024, pp. 4588–4593.
- [5] S. Vasudevan, M. Adler, D. Goeckel, and D. Towsley, "Efficient Algorithms for Neighbor Discovery in Wireless Networks," *IEEE/ACM Transactions on Networking*, vol. 21, no. 1, pp. 69–83, 2013.
- [6] T. Song, H. Park, and S. Pack, "A Probabilistic Neighbor Discovery Algorithm in Wireless Ad Hoc Networks," in *2014 IEEE Wireless Communications and Networking Conference (WCNC)*. IEEE, 2014, pp. 1–6.

- [7] F. Cali, M. Conti, and E. Gregori, "Dynamic tuning of the ieee 802.11 protocol to achieve a theoretical throughput limit," *IEEE/ACM Transactions on networking*, vol. 8, no. 6, pp. 785–799, 2002.
- [8] F. Guo, Y. Zhou, L. Jiang, C. Miao, Y. Liu, C. Xu, H. Lu, C. W. Chen, Y. Xie, and H. Liu, "{BLADE}: Adaptive {Wi-Fi} contention control for {Next-Generation}{Real-Time} communication," in *23rd USENIX Symposium on Networked Systems Design and Implementation (NSDI 26)*, 2026, pp. 131–151.
- [9] F. Wilhelmi, L. Galati-Giordano, and G. Fontanesi, "'it's your turn': A novel channel contention mechanism for improving wi-fi's reliability," in *2025 IEEE Wireless Communications and Networking Conference (WCNC)*. IEEE, 2025, pp. 1–6.
- [10] Z.-B. Zuo, D.-M. Wang, M.-M. Ma, M.-L. Deng, and C. Wang, "An adaptive contention window backoff scheme differentiating network conditions based on deep q-learning network," *IEEE Transactions on Network and Service Management*, 2025.
- [11] J. Pan, J. Wang, Y. Ouyang, W. Cheng, and W. Zhang, "Ai-enhanced distributed channel access for collision avoidance in future wi-fi 8," *arXiv preprint arXiv:2509.23154*, 2025.
- [12] L. Galati-Giordano, G. Geraci, M. Carrascosa, and B. Bellalta, "What will wi-fi 8 be? a primer on ieee 802.11 bn ultra high reliability," *IEEE Communications Magazine*, vol. 62, no. 8, pp. 126–132, 2024.
- [13] J. Lee and T. Song, "Impact of Frame Duration on Cross-Channel Interference and Coexistence in IEEE 802.11bn NPCA," in *IEEE International Conference on Communications*, 2024.
- [14] T. Song, "Adaptive non-primary channel access in ieee 802.11 bn with deep reinforcement learning," in *2026 40th International Conference on Information Networking (ICOIN)*. IEEE, 2026, pp. 870–873.
- [15] G. Bianchi, "Performance analysis of the ieee 802.11 distributed coordination function," *IEEE Journal on selected areas in communications*, vol. 18, no. 3, pp. 535–547, 2000.