

检测报告  
Certificate of Analysis

编号 ( CoA No ) 1002246312

|                     |                                 |                      |           |
|---------------------|---------------------------------|----------------------|-----------|
| 顾客名称 ( Customer )   | 柳州兆丰汽车部件有限公司                    |                      |           |
| 材料牌号 ( Brand )      | AIP-2616 WLP7AK-G0068(P0709-LV) | 材料名称 ( Description ) | WL-PP-J01 |
| 发货日期(Delivery Date) | 2026/3/27                       | 材料批号 ( LOT No. )     | 12524413  |

| 检测项目Items                               | 单位Unit  | 执行标准Method/Standard  | 检测结果Results |
|-----------------------------------------|---------|----------------------|-------------|
| 拉伸强度(tensile strength)                  | MPa     | GBT1040              | 16.5        |
| 密度(density)                             | g/cm3   | GB/T 1033.1          | 1.054       |
| 弯曲模量(Flexural modulus)                  | MPa     | GBT9341              | 1633        |
| 熔体流动速率(MFR)                             | g/10min | GB/T 3682            | 21.63       |
| 弯曲强度(Flexural strength)                 | MPa     | GBT9341              | 24.9        |
| 悬臂梁缺口冲击强度(IZOD notched impact strength) | kJ/m2   | GBT1843              | 41.8        |
| 悬臂梁缺口冲击强度(IZOD notched impact strength) | kJ/m2   | GBT1843              | 5.4         |
| 断裂伸长率(Elongation at break)              | %       | GBT1040              | 44.5        |
| 热变形温度(HDT)                              | ℃       | GBT1634              | 101.6       |
| 色差(ChromaticAberration)                 | ——      | 对比法(Contrast method) | 合格(PASS)    |
| 外观(Appearance)                          | ——      | KFB202A.277.B-2021   | 合格(PASS)    |
| 灰分(Ash content)                         | %       | GB/T 9345.1-2008     | 21.48       |
| 结论 ( Conclusion ) : 合格 ( PASS )         |         |                      |             |



附件(Accessory):/

检测员 ( Inspector ) : 胡毅

审核 ( Checker ) : 郝莲