

检测报告

Certificate of Analysis

编号 (CoA No)

1002226329

顾客名称 (Customer)	柳州双英科技有限公司		
材料牌号 (Brand)	AIP-2616 WLP7AK-G0068(P0709-LV)	材料名称 (Description)	WL-PP-J01
发货日期(Delivery Date)	2026/3/14	材料批号 (LOT No.)	12511743

检测项目Items	单位Unit	执行标准Method/Standard	检测结果Results
拉伸强度(tensile strength)	MPa	GBT1040	16.5
密度(density)	g/cm3	GB/T 1033.1	1.054
弯曲模量(Flexural modulus)	MPa	GBT9341	1626
熔体流动速率(MFR)	g/10min	GB/T 3682	21.22
弯曲强度(Flexural strength)	MPa	GBT9341	24.2
悬臂梁缺口冲击强度(IZOD notched impact strength)	kJ/m2	GBT1843	41.8
悬臂梁缺口冲击强度(IZOD notched impact strength)	kJ/m2	GBT1843	5.3
断裂伸长率(Elongation at break)	%	GBT1040	44.5
热变形温度(HDT)	℃	GBT1634	101.5
色差(ChromaticAberration)	——	对比法(Contrast method)	合格(PASS)
外观(Appearance)	——	KFB202A.277.B-2021	合格(PASS)
灰分(Ash content)	%	GB/T 9345.1-2008	21.69
结论 (Conclusion) : 合格 (PASS)			

附件 (Accessory):/

检测员 (Inspector) : 胡毅

审核 (Checker) : 郝莲