



[Home](#)

[WinALDL](#)

WinALDL - Supported ECM types

I have tried to make a list of vehicles supported by WinALDL, and what selection to use in the configuration dialog.

This is not a complete list, and the ECM part numbers may not match all the vehicles listed for that ECM. In some cases many different ECM's use the same serial data, and one ECM can send different data in different applications.

If you have more information, please send me a mail and I will try to correct this list. I have very little information about the carbed applications, and what ECM's they use.

TBI data streams

READ DATA ON PIN "E" OF ALDL CONNECTOR

WinALDL selection (not shown in selection)	Application
1227747 1228062 (1227429)	A030 4.3L TBI CPC - (LB4) - (Z) - 86, 87 CARS
	A033 4.3L TBI - (LB4) - (Z) - 86,87,88 TRUCKS 5.0L TBI - (L03) - (H) - 87,88 TRUCKS 5.7L TBI - (L05) - (K) - 87,88 TRUCKS MW2 uses "Idle Flag" and "High Bat Voltage" MWAFF1 uses "Clear Flood Flag"
	A035 2.8L TBI CPC - (LL2) - (R) - 86,87 TRUCKS MW2 uses "Cool Flag" and "High Bat Voltage" MWAFF1 uses "Not Closed Loop"
	A040 2.8L TBI (LL2) (VIN=R) 88,89,90,91 TRUCKS 3.1L TBI (LG6) (VIN=D) 89 TRUCKS 2.8L TBI (LL2) (VIN=R) 92 S TRUCK 2.8L TBI (LL2) (VIN=R) 93 S TRUCK

	MW2 uses "Cool Flag" and "High Bat Voltage" MWAf1 uses "Not Closed Loop" A058 4.3L TBI (LB4) (VIN=Z) 89 TRUCKS 4.3L TBI (LB4) (VIN=Z) 90 91 S/T TRUCKS w/auto TRANS 4.3L TBI (LB4) (VIN=Z) 90 C/K/G/M/L/R/V TRUCKS 4.3L TBI (LU2) (VIN=B) 90 TRUCKS 5.0L TBI (L03) (VIN=H) 89, 90 TRUCKS 5.7L TBI (L05) (VIN=K) 89 TRUCKS 5.7L TBI (L05) (VIN=K) 90 TRUCKS LIGHT DUTY EMISSIONS 6.0L TBI (LS0) (VIN=P) 89 TRUCKS 7.4L TBI (L19) (VIN=N) 89 TRUCKS 7.4L TBI (L19) (VIN=N) 90 TRUCKS LIGHT DUTY E// NS 7.4L TBI (L19) (VIN=N) 91 TRUCKS LIGHT DUTY EMISSIONS MW2 uses "Idle Flag" and "1st Time Idle Flag" MWAf1 uses "Clear Flood Flag" A068 4.3L TBI - (LB4) - (Z) - 88 CARS MW2 uses "Cool Flag" and "High Bat Voltage" MWAf1 uses "Not Closed Loop" A084 4.3L TBI - (LB4) - (Z) - 89,90 CARS MW2 uses "Idle Flag" and "High Bat Voltage" MWAf1 uses "Not Closed Loop"
1228746	A041 A83 A090 1988 5.0 V8 TBI L03 1989-92 5.0 V8 TBI 'E' L03 ('F' body) 1989-90 5.0 V8 TBI 'E' L03 ('B' body) 1989-90 5.7 V8 TBI '7' L05 ('B' body)
1225550 1225570 1225610	A001 A062 1982 5.0 V8 CFI '7' LU5 1982 5.7 V8 CFI '8' L83 1982-86 1.8 L4 TBI 'O' LH8 1982-86 2.5 L4 TBI 'R' LR8 1982-86 2.5 L4 TBI 'U' L68 1982-86 2.5 L4 TBI '2' LQ9 1985-86 2.5 L4 TBI 'E' LN8 1983 5.0 V8 CFI 'S' LU5
1227808	VN & VP Holden Commodore

1226026	A063 1985 4.3 V6 TBI 'Z' LB4 1985 5.0 V8 CFI '5' LB9 1983-85 5.7 V8 CFI '8' L83
16144288	A104 16144288 4.3L TBI (LB4) (VIN=Z) 90 C/K TRUCK 4.3L TBI (LB4) (VIN=Z) 91 S/T TRUCK W/MANUAL TRANSMISSION 4.3L TBI (LB4) (VIN=Z) 91 C,K,G,M,L TRUCK W/MANUAL TRANSMIS 4.3L TBI (LB4) (VIN=Z) 90 M/L/G 4.3L TBI (LB4) (VIN=Z) 90 S/T TRUCK W/MANUAL TRANSMISSION 4.3L TBI (LB4) (VIN=Z) 92 C,K,S,T,M,L,G TRUCK 4.3L TBI (LB4) (VIN=Z) 93 C,K TRUCK MW2 uses "1st time Idle Flag" and "ESC 43B Ready for PE" MWAFF1 uses "Old High Gear Flag" and "4-3 Downshift for TCC unlock" MCU2IO uses "AIR Divert" and "AIR Switch" Sensor uses "FP Switch Voltage" (Fuel Pump) A136 3.1L TBI (LG6) (VIN=D) 91 U VAN 3.1L TBI (LG6) (VIN=D) 92 U VAN 3.1L TBI (LG6) (VIN=D) 93 U VAN 3.1L TBI (LG6) (VIN=D) 94 1,2,3U VAN 3.1L TBI (LG6) (VIN=D) 95 1,2,3U VAN MW2 uses "High Bat Voltage" and "ESC 43B Ready for PE" MWAFF1 uses "Old High Gear Flag" and "4-3 Downshift for TCC unlock" MCU2IO uses "Fan #1", "Fan #2" and "Heated Windshield" Sensor uses "FP Switch Voltage" (Fuel Pump) A137 6.0L TBI (LS0) (VIN=P) 91 7.0L TBI (LR0) (VIN=M) 91 6.0L TBI (LS0) (VIN=P) 92 GMT530 TRUCK 7.0L TBI (LR0) (VIN=M) 92 GMT530 TRUCK 6.0L TBI (LS0) (VIN=P) 93 GMT530 TRUCK 7.0L TBI (LR0) (VIN=M) 93 GMT530 TRUCK 6.0L TBI (LS0) (VIN=P) 94 GMT530 TRUCK 7.0L TBI (LR0) (VIN=M) 94 GMT530 TRUCK 6.0L TBI (LS0) (VIN=P) 95 GMT530 TRUCK 7.0L TBI (LR0) (VIN=M) 95 GMT530 TRUCK MW2 uses "1st time Idle Flag" and "OL Idle Flag" MWAFF1 uses "CL Idle" and "AF Cold Park" MCU2IO uses "Idle Kicker Switch" and "Idle Kicker Light" Sensor uses "PS Switch Voltage" (Power Steering) A179 A195 5.0L TBI L03 VIN=H 92 C,K,G 5.7L TBI L05 VIN=K 92 C,K,G,R,V 5.0L TBI L03 VIN=H 93 C,K 5.7L TBI L05 VIN=K 93 C,K,P

5.0L TBI L03 VIN=H 94 C,K
 5.7L TBI L05 VIN=K 94 C,K,P
 5.0L TBI L03 VIN=H 95 C,K
 5.7L TBI L05 VIN=K 95 C,K,P
 5.7L TBI L05 VIN=K 92 CNG COMPRESSED NATURAL GAS G VAN & C/K TRUCK

 MW2 uses "1st time Idle Flag" and "OL Idle Flag"
 MWAF1 uses "CL Idle" and "AF Cold Park"
 MCU2IO uses "AIR Divert" and "AIR Switch"
 Sensor uses "FP Switch Voltage" (Fuel Pump)

PFI data streams

READ DATA ON PIN "E" OF ALDL CONNECTOR

WinALDL selection	Application
1227170	1986-88 2.8 V6 MPFI '9' L44
1985 2.8 litre MPI	1985 2.8 litre MPI
1986 2.8 litre MPI	1986 2.8 litre MPI
1226870	1985 5.0 V8 PFI 'F' LB9 1985 5.7 V8 PFI '8' L98
1227165	A028 A059 1986-89 5.0 V8 PFI 'F' LB9 1986-89 5.7 V8 PFI '8' L98
1227148	A003 A008 1986-88 3.8 SFI '3' LG3 1986-91 3.8 SFI '7' LC2 1986-87 3.8 SFI 'B' LG2

CARB data streams

READ DATA ON PIN "D" OF ALDL CONNECTOR

WinALDL selection	Application
CLCC 1984 truck	A006 A007 5.0L V8 CLCC (LV2) - (Y) - 84 5.0L V8 CLCC (L69) - (G) - 84 5.0L V8 CLCC (LG4) - (H) - 84 5.0L V8 CLCC (LG8) - (9) - 84 5.0L V8 CLCC (LM1) - (6) - 84 5.0L V8 CLCC (LV2) - (Y) - 85, 86, 87 5.0L V8 CLCC (LG8) - (9) - 85 5.0L V8 CLCC (L69) - (G) - 85 5.0L V8 CLCC (LG4) - (H) - 85, 86, 87

	5.7L V8 CLCC (LM1) - (6) - 85, 86, 87, 88 4.3L V8 CLCC (LB1) - (N) - 85, 86 5.0L V8 CLCC (LF3) - (H) - 85, 86 5.7L V8 CLCC (LS9) - (L) - 85, 86
CLCC 1984 car, 1985, 1986	A005 A012 A018 A019 A066 3.0l CLCC (LK9) - (E) - 84 85 3.8l V6 CLCC (LD5) - (A) - 84, 85, 86, 87 4.1l V6 CLCC (LC4) - (4) - 84, 85 4.3L V6 CLCC (LS5) - (S) - 85, 86 3.8l CLCC V6 (LC3) - (9) - 84 2.8 CARB (LE2) - (X) - 84, 85 2.8 CARB (LC1) - (1) - 84 2.8 CARB (LH7) - (Z) - 84 2.8 CARB (LL1) - (L) - 84 2.8 CARB (LR2) - (B) - 84, 85 2.8l CARB CHEVY - (LE2) - (X) - 86 5.0l V8 CLCC (L69) - (G) - 86, 87, 88 5.0L V8 CLCC (LG4) - (H) - 88



e-mail winaldl@joby.se