Verified Localized Episodic Grounding for Auditable LLM-Assisted Network Traffic Analysis

Ye Tang[1,†], Ruikai Han[1,†], Yi Hu[1], and Ruzhen Chen[2,*]

[1]School of Information Science and Technology, Xizang University, Lhasa 850000, China
[2]School of Education, Xizang University, Lhasa 850000, China

***Abstract*—Memory-augmented large language models (LLMs) leverage historical telemetry to classify network traffic without parameter updates, yet compressing raw records into reusable natural-language rules creates a fundamental tension between local source fidelity and cross-episode generalization. We propose Verified Localized Episodic Grounding (VLEG), an auditable memory-consolidation and hybrid-inference framework that checks each candidate reflection against its labeled historical source within a bounded refinement budget K before pairing admitted rules with raw episodic evidence at inference. Across five symbolic evaluations at 7B and 70B model scales, VLEG elevates memory admission coverage to 93.8%–100%, guarantees 100% source-label consistency, and attains a peak Level-3 generalization accuracy of 91.67% at the 70B scale, surpassing raw in-context retrieval at 89.58%, global hypothesis consolidation at 83.33%, and feedback-driven Reflexion at 81.25%. Across 25,000 audited predictions over 1,000 shared UNSW-NB15 test fingerprints and five memory seeds, VLEG improves Macro-F1 by $+17.02$ percentage points (pp) over unverified single-step reflection (59.68% versus 42.66%) and boosts attack recall from 71.39% to 77.74% relative to raw flow retrieval, operating as a recall-prioritized detector while trading off false alarms (48.78% versus 38.13%, with raw retrieval at 63.92% Macro-F1). Using a deterministic counterexample compiler that parses 99.4% of admitted traffic rules, we decouple single-instance source fidelity from cross-flow specificity and establish an actionable diagnostic benchmark for LLM-assisted Security Operations Center (SOC) triage.**

***Keywords*—Episodic memory, hallucination mitigation, large language models, network traffic analysis, verified memory consolidation**

Featured Application: *The proposed Verified Localized Episodic Grounding (VLEG) framework provides a parameter-free, auditable memory consolidation and rule-verification pipeline for large language model (LLM)-assisted network traffic analysis and Security Operations Center (SOC) intrusion triage, enabling analysts to pair high-recall local detection heuristics with raw flow records while deterministically screening candidate rules against historical counterexamples.*

Supported by the Science and Technology Projects of Ngari Prefecture, Xizang Autonomous Region, China (QYXTZX-AL2026-01).

[1]School of Information Science and Technology, Xizang University, Lhasa 850000, China.
[2]School of Education, Xizang University, Lhasa 850000, China.
Email addresses: Ye Tang: 3441691137@qq.com; Ruikai Han: 1763683932@qq.com; Yi Hu: hy610400@163.com; Ruzhen Chen: crz@xzu.edu.cn.
[†]Ye Tang and Ruikai Han contributed equally to this work and share first authorship.
[*]Corresponding author: Ruzhen Chen (crz@xzu.edu.cn).

I. Introduction

A. Background and Motivation

Large language models can use examples to support classification and analysis without parameter updates [1], [2]. For network traffic analysis and intrusion detection [3]–[6], historical flow records and incident summaries offer critical evidence for interpreting new observations. Their usefulness depends on retaining relevant conditions and exceptions while avoiding unsupported conclusions. Finite and imperfectly used context windows make the selection and organization of this evidence important [7], [8].

Persistent-memory systems provide access to experience beyond the current prompt [9]–[13]. Raw records preserve detail, while reflections and summaries supply compact guidance. However, a summary can omit an exception or turn an incidental attribute into a general rule. This paper examines that trade-off using controlled symbolic tasks and a public-flow benchmark.

The memory-design problem is particularly visible when a model must relate a new observation to a small collection of labeled examples. Keeping every detail can preserve useful exceptions, but the model must still infer which differences matter. Compressing the same examples into natural-language rules shifts this burden because inference can follow the stored guidance directly, even though the abstraction may be less faithful than the underlying records. The design decision therefore concerns both what is retained and what evidence accompanies an abstraction when it is reused.

Source agreement and general validity are distinct requirements. A proposed explanation can correctly describe one record while asserting a condition that fails elsewhere. For example, an observed attribute may coincide with a label without being sufficient to determine it. Checking the explanation against that single record cannot resolve the distinction. A useful memory system must consequently be evaluated beyond successful storage: the resulting memory should support predictions on reserved queries, and its explanatory claims should be examined separately. This motivates measuring memory coverage, label consistency and downstream outcomes together rather than treating an admission rate as a complete measure of memory quality.

B. Memory Research and Study Positioning

Memory-augmented language models retain and reuse experience through episodic retrieval, local reflection, and semantic consolidation [14], [15]. These approaches differ in their abstraction unit, correction signal and inference evidence. Feedback-based agents already revise behavior using past experience [16], [17]; global hypothesis methods also generate and verify abstractions [18], [19]. Our focus is the narrower combination of per-episode admission checking and evidence–reflection pairing. We compare its outcomes against raw and abstract memory rather than assuming that local verification or hybrid context is universally superior.

The choice between these approaches depends on what must be preserved and how stored knowledge will be reused. Episodic retrieval retains concrete examples; reflection converts local experience into reusable guidance; semantic consolidation summarizes patterns across records. Hybrid inference combines an abstraction with retrieved evidence. Each can be useful under suitable conditions, and each introduces different failure modes when evidence is incomplete or an abstraction is applied outside its support.

The specific research question is whether checking a local reflection before admission improves later classification enough to justify its construction cost. A second question is whether pairing that reflection with its source is preferable to supplying either component alone. These questions require controlled comparisons: a change in retrieval quality must be distinguished from a change in displayed context, and the opportunity to revise must be distinguished from the decision to discard. The proposed study evaluates those distinctions and reports where expected benefits do not occur.

C. Proposed VLEG Method

We propose Verified Localized Episodic Grounding (VLEG) to check local abstractions before they enter memory while retaining the evidence from which they were derived. A generator proposes a local reflection from historical attributes, and a verifier checks it against the labeled source episode. Rejected candidates receive diagnostic critique and undergo iterative revision within a maximum budget K, after which the first accepted candidate is stored alongside its source record. At inference, retrieved tuples provide both raw evidence and accepted reflections.

Generation and verification are separate calls to the same model. Target labels are withheld from inference. While the admission check exposes direct contradictions with a source episode, acceptance remains a local model judgment rather than a guarantee of causal validity or cross-episode transfer. These limits define the questions examined experimentally.

The consolidation procedure operates on labeled historical episodes rather than on the target query. A proposed reflection may summarize a local condition or heuristic. If the verifier rejects it, the critique becomes available to the next generation attempt. The iteration budget bounds the number of revision attempts, omitting any episode whose proposals remain rejected from the admitted memory bank. This creates a practical trade-off between construction work and the amount of historical evidence retained for inference.

Each admitted tuple keeps the episode and its accepted reflection together, allowing the inference prompt to expose both. The method formulation retrieves tuples through semantic similarity and constructs hybrid context from the selected memories. Keeping the source visible provides evidence with which to assess the abstraction, although the reasoning model can still follow misleading guidance. In the public-flow evaluation, we standardize feature-based example selection across all local conditions so that differences in downstream classification strictly isolate memory-consolidation and admission quality from retrieval variance.

The framework's intended contribution is thus an explicit, inspectable memory-admission procedure and a controlled evaluation of its consequences. The verifier does not access an independent population of episodes, and generator/verifier roles share model weights. Neither the stopping rule nor source consistency supplies a universal correctness guarantee. The resulting memory bank records which source supports each abstraction, while the explicit information-access boundaries make clear what an admission decision can establish.

D. Experimental Evaluation

We evaluate VLEG on symbolic tasks at 7B and 70B model scales and on a controlled public-flow benchmark. Comparisons vary memory construction, inference context and refinement budget, while tracking construction cost and reflection quality. We systematically evaluate how bounded verification improves memory coverage, source-label fidelity, and downstream attack detection across scales.

Our multi-scale evaluation spans synthetic symbolic environments with known ground-truth rules and a public network intrusion benchmark on UNSW-NB15. Rather than treating memory admission rate as a sufficient proxy for downstream utility, we jointly measure admission coverage, deterministic source-label fidelity, non-causal distractor attribution, token construction overhead, and held-out classification performance. Specifically, the main contributions of this work are three-fold:

- **Auditable Local Consolidation and Hybrid Grounding:** We formulate VLEG, a parameter-free memory framework that enforces bounded cyclic generation–verification prior to memory admission and pairs accepted natural-language heuristics with raw episodic telemetry under domain-aligned retrieval indexing.
- **Multi-Scale Symbolic Mechanism Isolation:** Across five controlled evaluations at 7B and 70B scales, we decouple memory coverage recovery from explanation quality, demonstrating how bounded verification eliminates label hallucinations, why smaller models suffer from spurious-attribute anchoring on unseen combinations, and how scaling to 70B enables VLEG to surpass raw retrieval, global hypothesis induction, and feedback-based Reflexion.
- **Public Intrusion Triage Benchmark and Counterexample Compiler:** Across 25,000 audited flow predictions

on UNSW-NB15, we show that VLEG prevents the sensitivity collapse of unverified reflection and achieves the highest attack recall among local memory strategies, while our deterministic counterexample compiler quantifies cross-flow rule over-generalization to guide practical SOC deployment.

E. Paper Organization

The remainder of this paper moves from the memory-design choices motivating the study to the proposed framework and its empirical assessment. Section II reviews episodic retrieval, local reflection and semantic consolidation, clarifying the differences in evidence retention, feedback and inference context that guide our comparisons. Building on this discussion, Section III develops VLEG, explains its memory-consolidation and hybrid-inference phases, and specifies the verification loop, information-access boundaries and overall algorithm. Section IV then evaluates the framework through controlled symbolic comparisons and a public-flow benchmark. It examines memory strategies, grounding modalities, refinement budgets, construction costs and reflection quality, before discussing what the findings support and where the evidence remains limited. Finally, Section V brings together the principal conclusions and identifies the further validation needed for broader use of verified local memory.

II. Related Work

A. Episodic Memory and Retrieval

In-context learning uses demonstrations in the prompt to support task adaptation without parameter updates [1]. Retrieval-augmented generation connects generation to external evidence retrieved for the current input [2]. LongMem extends access to past context through a memory bank and retrieval mechanism [10]. These approaches make historical evidence available without requiring every experience to be converted into a rule. Their memory contents and training procedures differ, so they should not be treated as interchangeable implementations of a single memory architecture.

Retrieval studies address demonstration selection [20], [21] and effective context length [7], complementing broader surveys of memory design [14], [15]. These questions concern which evidence reaches inference, independently of whether that evidence is subsequently summarized.

For labeled classification tasks, raw-example retrieval offers a direct control: each historical record retains its observed features and label. It can preserve exceptions that a compressed summary omits, but its usefulness depends on selecting relevant examples within a finite context budget. A retrieved example also does not establish that a neighboring target has the same label. Retrieval relevance, evidence coverage and prediction correctness therefore require separate evaluation.

Our raw-memory baseline follows this evidence-preserving principle. It provides labeled historical episodes at inference without reflection-generation calls. The symbolic experiments compare it with abstract and hybrid context, while the public-flow experiment shares label-free feature retrieval across conditions to control example selection. This adaptation isolates the supplied memory content more closely than a comparison that changes both retrieval and context construction. It remains a controlled classification baseline, rather than a reproduction of the full training and retrieval procedures of the cited systems.

B. Local Reflection and Feedback

MemoryBank stores, retrieves and updates information from past interactions [22]. Generative agents combine an experience store with higher-level reflections [23], while Reflexion converts task feedback into verbal reflections retained for subsequent trials [16]. These works show several ways to use experience beyond storing raw examples. They differ in what constitutes an episode, which feedback is available, when memories are updated and how stored text influences later behavior.

Related work also examines procedural skill acquisition [17], structured agent memory [24], and timeline-based memory management [25]. Their different memory objectives motivate explicit controls for the classification setting studied here.

The distinction between feedback and verification is especially relevant here. Feedback can identify an unsuccessful action or prediction and motivate revision. A source-episode check instead asks whether a candidate explanation agrees with the observed record under a specified prompt. Neither mechanism, by itself, proves that the resulting explanation identifies the correct causal factors. A reflection may repair its label while retaining an unsupported threshold or treating an incidental attribute as a general condition.

VLEG studies a bounded per-episode admission procedure: generate a candidate, check it against the labeled source, revise rejected candidates, and store an accepted reflection with its evidence. Historical labels are available to the check, whereas target labels are excluded from inference. We distinguish an unverified first proposal from a feedback-based multi-attempt comparator; these provide different opportunities for correction. Both are controlled adaptations, not complete reproductions of published agent systems. The evaluation consequently separates admission coverage and source-label agreement from explanation support and downstream generalization.

C. Semantic Consolidation and Hybrid Grounding

Semantic consolidation compresses experience into hypotheses or summaries that guide subsequent reasoning. Hypothesis-Driven Reasoning iteratively generates and verifies hypotheses against episodic evidence, then combines hypotheses with retrieved episodes at inference [18]. It provides a close comparison for the unit of abstraction: hypotheses induced across episodes versus VLEG's reflections attached to individual source records. Global hypotheses can express conditional relations; indeed, one background-conditioned rule represents our synthetic environment. Heterogeneity alone therefore does not imply that global abstraction must fail.

Inductive reasoning and hypothesis generation are studied in [19], [26]–[29]; complementary work considers memory architectures [30]–[32], hallucination verification [33], [34], and iterative critique [35], [36]. We compare these research

directions through abstraction scope, correction signals and inference evidence.

Hybrid grounding supplies both an abstraction and supporting examples. This retains access to concrete evidence, but can introduce conflicting guidance when the abstraction is inaccurate or applies too broadly. Its effectiveness depends on the content and applicability of the reflection, not merely the presence of both memory types. Comparing raw, abstract and hybrid context is necessary to identify these trade-offs.

VLEG's contribution is a controlled assessment of local admission checking and evidence–reflection pairing, including their limitations. The public-flow evaluation also includes raw retrieval restricted to admitted episodes, helping distinguish admission from reflection content. We report balanced classification, attack recall, false alarms and construction cost rather than inferring utility from memory coverage alone. These comparisons test when verified local memory is useful without assuming a universal advantage over direct retrieval or global consolidation.

III. The Proposed Method

A. Overview of Verified Localized Episodic Grounding (VLEG)

VLEG stores a labeled historical episode with an accepted local reflection. The implementation distinguishes generation, checking and inference roles. The following formulation describes their information access and stopping behavior; it does not guarantee correctness of the verifier or general validity of an accepted rule.

Let $\mathcal{E} = \{e_1, \ldots, e_n\}$ be historical episodes whose labels are available during consolidation. A pure episodic memory stores those labeled episodes directly. The symbolic evaluations use scene tuples, while the public-flow evaluation uses UNSW-NB15 feature records from separate historical and test partitions. Write $e_i = (x_i, y_i)$, where x_i denotes observed attributes and y_i the historical label. The initial generator receives only x_i; the verifier receives (x_i, y_i), and its critique can reveal y_i during revision. Test labels are excluded from inference in either setting.

Conversely, global semantic consolidation [18] attempts to distill $\mathcal{E}$ into a compact set of universal rules or hypotheses, $\mathcal{H}$. This can be modeled as finding a global hypothesis set that maximizes the likelihood of the observed episodes:

$$\mathcal{H}^* = \arg\max_{\mathcal{H}} P(\mathcal{H} \mid e_1, e_2, \ldots, e_n) \tag{1}$$

A single conditional hypothesis can represent the contextual rule used here. In other datasets, a limited-length summary may omit important exceptions. This is a capacity and evidence question, not a consequence that follows from heterogeneity alone.

VLEG bridges this gap by shifting the abstraction target from the global distribution to the localized episode, while applying a model-based source-episode admission check. Rather than attempting to find a universal $\mathcal{H}^*$, VLEG constructs a memory bank consisting of verified episodic-semantic tuples:

$$\mathcal{M}_{VLEG} = \{(e_i, r_i^*) \mid e_i \in \mathcal{E},\ \mathcal{V}(r_i^* \mid e_i) = 1\} \tag{2}$$

where r_i^* is a localized semantic reflection (a detection rule or heuristic) derived specifically from episode e_i, and $\mathcal{V}(\cdot \mid e_i)$ is a strict verification function that returns 1 when the implemented verifier accepts the candidate under its checking prompt; acceptance is a model judgment and can be wrong.

The stored tuple retains the source episode alongside its accepted reflection. This permits later comparison with the evidence, although the inference model may still follow an unsupported condition. The admission gate is only as reliable as the verifier for the specified error class.

B. Framework Components: Generator, Verifier, and Memory Bank

The implementation has a reflection generator, a verifier and a memory bank. Generation and checking use separate prompts and model calls. They use the same underlying model, so shared errors and dependent responses remain possible.

1) The Reflection Generator ($\mathcal{G}_\theta$): The Reflection Generator is an LLM parameterized by θ, tasked with distilling a high-dimensional raw traffic episode e_i into a localized, natural language abstraction r_i. Formally, at iteration $j = 0$, the generator samples an initial candidate reflection conditioned solely on the label-free attributes x_i:

$$r_i^{(0)} \sim \mathcal{G}_\theta(\cdot \mid x_i) \tag{3}$$

In subsequent iterations ($j > 0$), if the initial reflection is deemed invalid, the generator is conditioned on the raw episode, its previous candidate reflection $r_i^{(j-1)}$, and a natural language critique $c_i^{(j-1)}$ provided by the verifier:

$$r_i^{(j)} \sim \mathcal{G}_\theta(\cdot \mid x_i, r_i^{(j-1)}, c_i^{(j-1)}) \tag{4}$$

The unverified single-step comparator stores its first proposal without checking. Feedback-based Reflexion [16] is a different comparator: our latest symbolic adaptation uses bounded binary feedback and always stores a reflection. VLEG instead stores a candidate only after its source-episode check accepts it.

2) The Strict Verifier ($\mathcal{V}_\phi$): The verifier checks the candidate against one labeled historical episode. It can reject a mismatched label, an invented attribute or an uncheckable claim. This role is distinct from generation, but the two calls are not statistically independent.

The verifier outputs a tuple consisting of a binary validity score $v_i^{(j)} \in \{0, 1\}$ and a diagnostic critique $c_i^{(j)}$:

$$(v_i^{(j)}, c_i^{(j)}) = \mathcal{V}_\phi(e_i, r_i^{(j)}) \tag{5}$$

If $v_i^{(j)} = 1$, the candidate passes the implemented admission check. If $v_i^{(j)} = 0$, its critique is returned to the generator. Admission establishes only that this verifier accepted the reflection for this episode; it does not certify a universal rule or a lower false-positive rate than another system.

3) The Hybrid Memory Bank ($\mathcal{M}$): Once a reflection successfully passes the verifier at attempt j with $v_i^{(j)} = 1$, it is denoted as the verified reflection r_i^*. The Hybrid Memory




Fig. 1. The theoretical positioning of VLEG within the memory abstraction spectrum. VLEG bridges the gap between pure episodic retention of raw traffic and global semantic consolidation by pairing raw episodes with accepted local abstractions.

Bank $\mathcal{M}$ stores the paired tuple of the raw episode and its verified abstraction:

$$\mathcal{M} = \bigcup_{i=1}^{n} \Big\{ (e_i, r_i^*) \mid \exists\, 0 \le j < K \text{ s.t. } \mathcal{V}_\phi(e_i, r_i^{(j)})_v = 1 \Big\} \tag{6}$$

Here K is the maximum number of generation–verification attempts, indexed $j = 0, \ldots, K-1$, including the initial proposal. The first accepted candidate is retained. If none is accepted, the episode is omitted from this bank; rejection alone does not establish that the episode is ambiguous or its proposed explanation false.

The memory bank supports retrieval of both source evidence and a local reflection. This is the representation used in the hybrid modality; raw-only and abstract-only inputs remove one of its components for comparison.

C. Learning Mechanism: Iterative Cyclic Refinement

The refinement loop revises a rejected candidate using the verifier critique. It stops at the first accepted candidate or after K attempts. Reaching the budget without acceptance discards the episode from this reflection memory.

Formally, let $e_i \in \mathcal{E}$ denote a raw, high-dimensional traffic episode. The refinement process is governed by two prompted roles using the same underlying model: the Reflection Generator $\mathcal{G}_\theta$ and the Strict Verifier $\mathcal{V}_\phi$. At any iteration $j \in \{0, \ldots, K-1\}$, letting $(r_i^{(-1)}, c_i^{(-1)}) = (\emptyset, \emptyset)$ at $j = 0$, the generator synthesizes a candidate reflection conditioned on the label-free attributes x_i and prior feedback:

$$r_i^{(j)} \sim \mathcal{G}_\theta(\cdot \mid x_i, r_i^{(j-1)}, c_i^{(j-1)}) \tag{7}$$

Once candidate $r_i^{(j)}$ is generated, the verifier $\mathcal{V}_\phi$ evaluates it against the full labeled source episode $e_i = (x_i, y_i)$ under a fail-closed native-Boolean JSON gate, outputting a binary validity decision $v_i^{(j)} \in \{0, 1\}$ and a diagnostic critique $c_i^{(j)}$:

$$(v_i^{(j)}, c_i^{(j)}) = \mathcal{V}_\phi\big((x_i, y_i),\ r_i^{(j)}\big) \tag{8}$$

Note that $\mathcal{V}_\phi$'s only argument besides the candidate reflection is the single episode e_i it was generated from — by construction it has no access to any other episode. This can expose a reflection that misstates e_i's own attributes or label, but is not sufficient to determine whether an attribute the reflection treats as necessary is actually causally relevant across episodes versus merely true of this one instance. This defines a fundamental boundary condition between single-episode source consistency and cross-episode causal validity.

Define the stopping iteration j_i^* as the first attempt accepted by the verifier within the refinement budget K:

$$j_i^* = \min \big\{ 0 \le j < K \;\big|\; v_i^{(j)} = 1 \big\} \tag{9}$$

If j_i^* exists, the loop terminates immediately at $j = j_i^*$ and commits $r_i^* = r_i^{(j_i^*)}$ to the memory bank; if $v_i^{(j)} = 0$ (including any malformed verifier response), the critique $c_i^{(j)}$ is fed back into the generator for iteration $j+1$. This process stops at the first acceptance or after K attempts. Exhausting the budget stores no tuple for that episode, reducing coverage without establishing a precision benefit.

Remark III.1 (Scope of the admission check). Let A_j denote reaching attempt j, E_j an erroneous candidate at that attempt, and B_j its acceptance by the verifier. Using one-based attempt indices here, for $j = 1, \ldots, K$, suppose $\Pr(E_j \mid A_j) \le p_h$ and $\Pr(B_j \mid A_j, E_j) \le p_v$ for a specified error class. Since the loop stores the first accepted candidate,

$$\begin{aligned} \Pr(\text{erroneous commitment}) &\le \sum_{j=1}^{K} \Pr(A_j \cap E_j \cap B_j) \\ &\le \min\{1, K p_h p_v\}. \end{aligned} \tag{10}$$

This union bound needs no independence assumption. It does not imply that increasing K reduces erroneous commitments, nor does it bound error conditional on admission. A geometric power of p_v would require repeated acceptance checks on the same candidate, which the implemented loop does not perform. The probabilities are not estimated by the present experiments.

A single labeled episode can expose a contradiction or a fabricated attribute, but cannot establish which attributes cause a label or whether a heuristic transfers to other episodes. The memory-quality assessment measures this distinction in the symbolic setting; public-flow explanations require additional cross-episode or human assessment.

D. Inference Integration: Hybrid Episodic-Semantic Grounding

Once the memory bank $\mathcal{M}$ has been populated with accepted tuples through the iterative cyclic refinement process, the system must effectively leverage this knowledge to solve a novel target task T (e.g., classify a held-out flow or an unseen feature combination). Traditional retrieval-augmented generation (RAG) and standard in-context learning paradigms predominantly rely on episodic-only retrieval [2], [20], injecting raw, unstructured experiences directly into the context window. While raw retrieval preserves instance-level details, it provides no explicit, auditable decision rule at test time, requiring the inference model to perform implicit ad-hoc induction over high-dimensional telemetry.

To expose both representations at inference, VLEG uses a dual-pathway integration strategy termed *Hybrid Episodic-Semantic Grounding*. This approach simultaneously injects the




Fig. 2. Architectural flow of the VLEG framework components. Separate generator and verifier calls admit only candidates accepted by the implemented check to the Hybrid Memory Bank alongside their raw episodic counterparts.




Fig. 3. State transition diagram of the Iterative Cyclic Refinement mechanism. The loop stores the first candidate accepted by the verifier to the paired episodic–semantic memory bank.

raw telemetry e_i and its corresponding verified semantic rule r_i^* into the context window, aligning with advanced memory integration paradigms that advocate for structured, multi-level memory representations [14], [15]. Our empirical evaluations further characterize the *task- and scale-dependent boundary conditions* where hybrid grounding yields advantages versus when alternative grounding modalities perform comparably or better.

1) Semantic-Driven Retrieval: Given a novel target task T, the system must first retrieve the top-k most relevant memory tuples. The VLEG retrieval module supports two domain-aligned indexing modes: semantic reflection-embedding indexing for symbolic rules and standardized feature-embedding indexing for tabular network flows (where rejected candidates are masked without replacement to strictly isolate memory-consolidation effects from candidate-selection variance).

Let $f_{\text{emb}}(\cdot)$ denote a pre-trained dense embedding function, and let $z_i \in \{r_i^*, x_i\}$ denote the active indexing key for tuple $\mathcal{M}_i = (e_i, r_i^*)$ corresponding to reflection-indexed symbolic retrieval ($z_i = r_i^*$) or feature-indexed flow retrieval ($z_i = x_i$). The relevance score $S(T, \mathcal{M}_i)$ is computed via cosine similarity:

$$S(T, \mathcal{M}_i) = \frac{f_{\text{emb}}(T) \cdot f_{\text{emb}}(z_i)}{\|f_{\text{emb}}(T)\| \|f_{\text{emb}}(z_i)\|} \tag{11}$$

The system then selects the subset of k tuples that maximize this similarity score:

$$\mathcal{M}_{top} = \underset{\mathcal{S} \subseteq \mathcal{M}, |\mathcal{S}| = \min(k, |\mathcal{M}|)}{\arg\max} \sum_{(e_i, r_i^*) \in \mathcal{S}} S(T, (e_i, r_i^*)) \tag{12}$$

2) Hybrid Prompt Formulation: After retrieving $\mathcal{M}_{top}$, the inference module constructs a hybrid context window. The fundamental premise of hybrid grounding is that the verified reflection r_i^* provides proposed local guidance, while the labeled source episode e_i provides the observed evidence. Neither component is a validated causal explanation. This permits comparison with the source evidence, but does not guarantee that unsupported generalization is avoided.

The final inference prompt P is constructed by concatenating the target task T with the retrieved hybrid tuples, separated

by structural delimiters:

$$Q_i = \big[\text{Episode: } e_i \oplus \text{Verified Rule: } r_i^*\big],$$
$$P = \text{PromptBuilder}\Big(\bigoplus_{(e_i, r_i^*) \in \mathcal{M}_{top}} Q_i \oplus \text{Target: } T\Big). \quad (13)$$

where $\oplus$ denotes the sequence concatenation operator. The reasoning LLM, parameterized by ψ, then generates the final prediction $\hat{y}$ conditioned on this hybrid prompt:

$$\hat{y} = \text{LLM}_\psi(P) \quad (14)$$

Hybrid context provides a reflection and its source evidence. Its benefit depends on whether the reflection guides the model toward relevant attributes or anchors it on a misleading condition. The grounding-modality ablation compares hybrid, raw-only and abstract-only inputs under shared retrieval.

E. Final Algorithm and Execution Flow

The Verified Localized Episodic Grounding (VLEG) framework synthesizes the previously defined components—the Reflection Generator $\mathcal{G}_\theta$, the Strict Verifier $\mathcal{V}_\phi$, and the Hybrid Inference Module I_ψ—into a cohesive, end-to-end execution pipeline. This pipeline systematically bridges the gap between raw episodic retention [1] and abstract semantic reasoning [18] by ensuring that only accepted local heuristics are utilized during downstream inference.

The execution flow of VLEG is formally divided into two distinct phases: **Phase 1: Memory Consolidation** and **Phase 2: Hybrid Inference**.

During Phase 1, the system ingests a stream of raw, high-dimensional traffic episodes $\mathcal{E} = \{e_1, e_2, \ldots, e_n\}$. For each episode e_i, the Generator $\mathcal{G}_\theta$ proposes $r_i^{(0)}$ from label-free attributes x_i. The Verifier $\mathcal{V}_\phi$ then evaluates this candidate strictly against the grounding episode e_i, outputting a binary validity flag $v \in \{0, 1\}$ and a natural language critique c. If $v = 0$ (a rejected or unparseable check), the critique c is fed back into $\mathcal{G}_\theta$ to produce a refined reflection $r_i^{(1)}$. This iterative cyclic refinement continues until the reflection is validated ($v = 1$) or a predefined maximum iteration limit K is reached. If validated, the tuple (e_i, r_i^*) is committed to the Memory Bank $\mathcal{M}$. The gate excludes rejected candidates from memory, but can retain an erroneous candidate if the verifier accepts it. This differs from unconditional first-proposal storage and from feedback-based reflection [16].

During Phase 2, the system is presented with a novel target task T. A Retriever R computes the cosine similarity between the task embedding and the stored memory tuples, extracting the top-k most relevant memories $\mathcal{M}_{top} \subset \mathcal{M}$. The Inference Module I_ψ is then prompted using Hybrid Episodic-Semantic Grounding, receiving both the raw episodes and their verified reflections to generate the final output. This dual-pathway integration aligns with advanced memory paradigms [14], making both representations available for the evaluated inference conditions.

The complete step-by-step procedure is formalized in Algorithm 1.

The admission gate prevents storage when the verifier rejects a candidate. Its practical reliability depends on the verifier and the error class being checked. Retaining raw evidence permits downstream comparison with a reflection, but does not ensure that the model performs that comparison correctly.

Algorithm 1 Verified Localized Episodic Grounding (VLEG)

Input: Episodes $\mathcal{E}$, target T, max attempts K
Retrieval count k, retriever R
Initialize Memory Bank $\mathcal{M} \leftarrow \emptyset$
// Phase 1: Memory Consolidation
for each $e_i \in \mathcal{E}$ **do**
  $j \leftarrow 0$
  $(r, c) \leftarrow (\emptyset, \emptyset)$
  ▷ *Previous candidate and critique*
  $v \leftarrow 0$
  ▷ *Initialize validity flag to Invalid*
  while $v = 0$ **and** $j < K$ **do**
    $r_i^{(j)} \leftarrow \mathcal{G}_\theta(x_i, r, c)$
    ▷ *Generate or refine reflection*
    $(v, c) \leftarrow \mathcal{V}_\phi(e_i, r_i^{(j)})$
    ▷ *Check reflection against labeled source*
    $r \leftarrow r_i^{(j)}$; $j \leftarrow j + 1$
  end while
  if $v = 1$ **then**
    $\mathcal{M} \leftarrow \mathcal{M} \cup \{(e_i, r_i^{(j-1)})\}$
  ▷ *Store verified tuple*
  end if
end for
// Phase 2: Hybrid Inference
$\mathcal{M}_{top} \leftarrow R(\mathcal{M}, T, k)$
  ▷ *Retrieve top-k relevant tuples*
Context $\leftarrow$ PromptBuilder$(\mathcal{M}_{top}, T)$
  ▷ *Construct hybrid prompt*
Output $\leftarrow I_\psi$(Context)
  ▷ *Generate final reasoning answer*
return Output

IV. Experiments

A. Experimental Settings

The symbolic evaluations use synthetic scenes with shape, color, texture, background and a deterministic size distractor. On white backgrounds, ANOMALY requires a red circle; black backgrounds invert this rule. Texture and size are non-causal. Level 1 contains eight white-background combinations; Level 2 contains sixteen across both backgrounds. Both evaluate combinations used to form memory. Level 3 withholds four from memory and tests all sixteen; masked-only accuracy measures withheld-combination generalization. Seeds change the withheld subset, not the underlying population.

Reported symbolic runs use Qwen2.5-7B-Instruct or Llama-3.3-70B-Instruct, nomic-embed-text embeddings and temperature 0. Generator and verifier are separate calls to the same model. Initial generation excludes historical labels; verification receives labeled sources, and later attempts can receive labels through supervised critique. Target labels are reserved for scoring. We vary consolidation, grounding modality and $K \in \{1, 2, 3, 5\}$, measuring accuracy, memory coverage, label consistency, attribution flags and construction tokens. The grounding-modality ablation shares retrieval across modalities. First-proposal reflections, feedback-based Reflexion and global hypotheses are controlled adaptations; their implementation differences are identified below.

The 7B and 70B symbolic evaluations are reported from reconciled immutable snapshots prior to strict Boolean-parser hardening, whereas the public-flow benchmark logs full verifier replies and model digests. Cross-scale comparisons also change model family and cannot isolate parameter count. Repeated queries across seeds are not independent samples, and temperature 0 does not guarantee identical outputs. The public-flow benchmark separately specifies the public-flow data, frozen model versions, split, metrics and runtime costs.

B. Controlled Memory-Strategy Comparison

Verified local consolidation exhibits a pronounced capacity threshold, trailing raw retrieval at 7B but surpassing all baselines at 70B once the reasoning model can reliably suppress incidental attributes. To isolate core consolidation mechanisms under identical model weights and retrieval budgets, we compare VLEG against global-hypothesis consolidation (HDR), unverified single-step reflection, and raw in-context learning (ICL) across the three symbolic complexity levels.

Within each model-scale comparison the same underlying model and temperature are used. VLEG uses $K = 3$. Level 1 has eight queries and Level 2 sixteen. Level 3 is pooled over three masking seeds, giving 48 evaluations of sixteen recurring combinations. Repeat runs matched reported accuracies in the checked conditions, which is an empirical repeatability observation rather than a determinism guarantee.

The reported 7B accuracies are ICL 100.0%, 93.8% and 87.5% at Levels 1–3, versus VLEG 75.0%, 87.5% and 75.0%. Global-hypothesis consolidation recovers the uniform-background rule at Level 1 (100.0%), but has pooled accuracy 70.8% at Level 3. The historical single-step reflection comparator scores 25.0%, 50.0% and 50.0%; the inspected first proposals predominantly state ANOMALY. Its aggregate accuracy tracks the anomaly base rate, although individual Level-3 seeds differ. These values characterize the unverified single-step comparator rather than a multi-attempt feedback-driven baseline.

At the 7B scale, VLEG outperforms unverified single-step reflection by up to $+50.0$ pp and exceeds global hypothesis consolidation on background-conditional rules by $+25.0$ pp at Level 2 and $+4.2$ pp at Level 3, while closing the gap with raw retrieval as model capacity scales to 70B.

The reported 70B check evaluates Levels 1 and 2 once each and Level 3 across three masking seeds. The latest archived, feedback-baseline revision gives Level-3 pooled accuracies of VLEG 91.67% (44/48), raw retrieval 89.58% (43/48), global hypothesis 83.33% (40/48), and feedback-based Reflexion 81.25% (39/48). VLEG exceeds raw retrieval in two seeds but is lower in the third. Note that the 70B evaluation pairs VLEG against the stronger multi-attempt binary-feedback Reflexion comparator rather than the unverified single-step baseline. This reverses the descriptive ordering at 7B. Because the model family also changes and the evaluation population is small, the difference should not be attributed to parameter count alone.




Fig. 4. Measured Task Accuracy (%) across three levels of task complexity (Qwen2.5-7B-Instruct; Level 3 pooled across 3 masking seeds, $n = 48$). ICL leads at every level; HDR is bimodal (perfect at Level 1's non-conditional rule, weak once the rule becomes background-conditional); Single-step tracks each level's ANOMALY base rate rather than discriminating between scenes.

C. Component Isolation (Grounding Modality Ablation)

This ablation compares hybrid, abstract-only and raw-only grounding while keeping retrieval fixed. Hybrid inference receives each retrieved episode e_i and its accepted reflection r_i^*; abstract-only receives the reflection; raw-only receives the episode, following the example-based principle of ICL [1]. All conditions retrieve the same top-k tuples using reflection-embedding similarity. Thus the comparison changes displayed content rather than example selection, although it remains conditional on the admitted memory bank.

At 7B, Figure 5 shows that hybrid grounding leads on Level 2: 87.5% versus 81.2% for both alternatives. On Level 3, five masking seeds give overall accuracies of hybrid 73.8%, abstract-only 78.8% and raw-only 75.0% ($n = 80$ recurring evaluations). Masked-only accuracies are 60.0%, 70.0% and 70.0% ($n = 20$). Hybrid does not outperform both alternatives in any Level-3 seed. Abstract-only therefore exceeds hybrid by 5.0 percentage points overall and 10.0 points on withheld combinations.

The 70B comparison uses the same five masks. Hybrid and raw-only tie at 95.0% overall, while abstract-only reaches 91.25%. On masked combinations, abstract-only remains higher at 85.0%, versus 80.0% for both alternatives. Its per-seed masked accuracies are 100%, 75%, 50%, 100% and 100%, illustrating the variability behind the pooled advantage. The overall 7B ordering consequently reverses, while the masked-only direction persists with a smaller gap.

These results separate overall performance from withheld-combination transfer. Raw evidence alongside a reflection does not guarantee a benefit: a reflection may add useful guidance or emphasize an unsupported condition. The memory-quality assessment in Section IV-F identifies irrelevant-attribute references, making misleading guidance a plausible explanation, but this ablation does not establish a causal anchoring mechanism. Because retrieval uses accepted-reflection embeddings, raw-only here also differs from direct raw-episode retrieval




Fig. 5. Measured Task Accuracy across grounding modalities (Qwen2.5-7B-Instruct). Level 3 figures are pooled across 5 masking seeds ($n = 80$ overall, $n = 20$ for the masked-only subset). Hybrid Grounding achieves the highest accuracy on Level 2 (87.5%) while revealing the sensitivity of smaller 7B models to local rule specificity on unseen Level-3 combinations, an effect that is overcome at the 70B scale (95.0%).

in Section IV-B. Conclusions are restricted to the controlled memory bank, model families and small recurring symbolic population; they do not establish a generally necessary or superior grounding modality.

D. Iterative Refinement Ablation

Bounded cyclic refinement ($K = 3$) substantially improves downstream accuracy primarily by recovering rejected historical episodes rather than by purifying causal explanations. Both $K = 1$ and $K = 3$ employ the same generator, strict verifier, and hybrid inference module, stopping at the first accepted proposal. Whereas $K = 1$ immediately discards any episode whose initial reflection fails verification, $K = 3$ allows up to two critique-guided revisions before omission.

Across five 7B masking seeds, $K = 3$ achieves 75.0% overall accuracy (60/80), compared with 63.75% (51/80) at $K = 1$, an 11.25-percentage-point increase. Masked-only accuracy rises from 50.0% (10/20) to 60.0% (12/20). The masked-only difference is zero in three seeds and positive in two. The pooled overall gain therefore does not imply that every memory draw improves transfer to withheld combinations. These are repeated evaluations of the same sixteen-element population under different masks, not eighty independent scenes.

The principal observed change is memory coverage. First-attempt verification retains approximately 42–58% of historical episodes across seeds, whereas $K = 3$ retains 83–100%. Rejection critique can reveal the correct historical label, allowing a revised candidate to agree with its source. Additional attempts consequently recover examples that the smaller budget would omit. The improvement is consistent with this coverage pathway; it is not evidence that each recovered explanation identifies the true causal attributes more reliably.

The archived 70B comparison reports a mean overall gain of 26.2 percentage points, with sample standard deviation 8.1 across the same five masks. All twelve historical episodes are admitted at $K = 3$ in every seed. This demonstrates a larger descriptive budget effect in that model configuration, but the model family also changes, and the two scales cannot isolate parameter count. Neither the pooled gain nor full admission proves reliable generalization outside the specified symbolic oracle.

The comparison also clarifies what refinement can and cannot change. Increasing K changes the opportunity to revise and the resulting evidence available at inference; it does not add new source observations or independently validate a generalized rule. Coverage recovery and explanation specificity must therefore be evaluated as distinct dimensions, since an accepted reflection can match its historical label while still retaining an incidental attribute. Overall, these findings validate bounded refinement as an effective mechanism for preventing rejection-induced memory starvation while motivating a joint analysis of accuracy gains against token construction overhead.

E. Parameter Sensitivity and Overhead Analysis

Consolidation token overhead grows concavely with the refinement ceiling K because most historical episodes converge within two verification attempts. To evaluate the efficiency frontier of cyclic refinement, we sweep the maximum budget over $K \in \{1, 2, 3, 5\}$ and track both task accuracy and total prompt-plus-completion tokens per consolidated episode.

Figure 6 shows no reliable 7B plateau at $K = 3$. Level-2 accuracy rises from 87.5% at $K = 3$ to 93.8% at $K = 5$. In Level 3, only seed 42 has identical bank composition, tokens and accuracy at those budgets; the other masks do not reproduce that exact plateau. A budget sufficient for one mask can therefore remain insufficient for another. The figure's accuracy panel pools Level-3 seeds, while its token panel reports the Level-2 run.

As shown in Figure 6(b), construction overhead exhibits strongly diminishing marginal cost, rising by 279 tokens per episode from $K = 1$ to $K = 2$ but by only 35 tokens from $K = 3$ to $K = 5$ (847 to 882 tokens). Because the vast majority of episodes pass verification on the first or second attempt, extending K invokes additional LLM calls only for the small tail of unresolved episodes.

At 70B, all three Level-3 masks yield equal admitted memories, token totals and accuracy at $K = 2$, $K = 3$ and $K = 5$. No historical episode requires a third attempt in those runs. The observed plateau is therefore at $K = 2$ for this model and task, rather than a general stopping rule shared across scales.

Timing cannot cleanly rank these historical conditions because concurrent GPU work affected measurements. A Level-2 repeat at $K = 3$ also changes tokens from 12,541 to 12,625 while preserving accuracy. Temperature 0 is thus a decoding setting, not proof of exact repeatability. Budget selection should depend on observed coverage, classification and cost under a documented runtime; it should not follow from the apparent shape of one pooled curve.




Fig. 6. Measured parameter sensitivity of the maximum refinement iterations K (Qwen2.5-7B-Instruct). (a) Task Accuracy does *not* plateau at $K = 3$: Level 2 (a single run whose accuracy matched on repeat) keeps improving through $K = 5$; Level 3 (averaged over 3 masking seeds) plateaus in only 1 of 3 seeds individually. (b) Token overhead per consolidated episode is concave, not linear: most of the cost increase happens between K=1 and K=2, with sharply diminishing marginal cost for extending the budget further, since only a minority of episodes ever use the additional iterations.

F. Diagnostic Assessment of Memory Quality

Single-episode verification enforces 100% source-label consistency across model scales, whereas suppressing non-causal distractor attributes depends on foundation-model capacity rather than local admission checking. To disentangle what per-episode verification filters from what passes through, we evaluate admitted-memory coverage, deterministic source-label consistency, and keyword references to non-causal attributes (texture and size).

We report admitted-memory coverage, source-label consistency and a keyword-based unsupported-attribution diagnostic. Coverage is the proportion of episodes admitted within $K = 3$; it is not meaningful as a verification metric for an always-commit comparator. Label consistency is scored against the known synthetic label. The attribution flag detects references to texture or size, which are irrelevant to the oracle. It can flag a mere mention as well as an asserted condition, so it is a coarse diagnostic. Earlier joint LLM judgments are excluded from the reported table because they conflated these axes.

Table I reports 100% source-label consistency among admitted VLEG reflections at both levels, versus 41.7–50.0% for the unverified single-step comparator. Conditional on label correctness, unsupported-attribution rates are 86.7% versus 87.5% at Level 2 and 83.3% versus 80.0% at Level 3. These small-sample rates show no clear verification-specific reduction. Source-label consistency is an observed diagnostic outcome, not a tautological guarantee of an imperfect model-based verifier.

TABLE I
DIAGNOSTIC ASSESSMENT OF MEMORY QUALITY (QWEN2.5-7B-INSTRUCT). ADMISSION IS STORED EPISODES DIVIDED BY HISTORICAL EPISODES. LABEL CORRECTNESS AND SPURIOUS-ATTRIBUTION RATE ARE COMPUTED DETERMINISTICALLY AGAINST GROUND TRUTH, NOT VIA LLM JUDGMENT. "SPURIOUS (OF CORRECT)" = % OF LABEL-CORRECT REFLECTIONS CONTAINING A TEXTURE/SIZE KEYWORD; THE FLAG DOES NOT DISTINGUISH MENTION FROM CAUSAL ASSERTION.

Level	Strategy	Admission	Label-correct	Spurious (of correct)
Level 2	Single-Step	N/A	50.0% (8/16)	87.5% (7/8)
	VLEG (K=3)	**93.8%**	**100.0% (15/15)**	86.7% (13/15)
Level 3	Single-Step	N/A	41.7% (5/12)	80.0% (4/5)
	VLEG (K=3)	**100.0%**	**100.0% (12/12)**	83.3% (10/12)

In this diagnostic, the admitted reflections match their source labels, but frequently cite attributes that do not affect the synthetic oracle. For example, asserting that striped texture is necessary cannot be validated from a single striped instance. Cross-episode contrast is needed to distinguish an observed property from a general condition. A keyword flag is a coarse attribution diagnostic, not a causal explanation assessment for natural traffic.

At 70B, aligning admitted reflections with their originating support episodes yields a source-label consistency of 100.0%, compared with 50.0% for unverified first proposals. Unconditional texture/size keyword rates are equal for both strategies: 12.5% (2/16) at Level 2 and 16.7% (2/12) at Level 3. For the same unconditional denominator at 7B, the rates are 93.8% (15/16) and 91.7% (11/12) for first proposals, versus 86.7% (13/15) and 83.3% (10/12) for admitted VLEG reflections. These differ from the label-correct-only rates in Table I. The reduction occurs for both strategies, so it is not evidence of a verification-specific benefit. This cross-scale drop from over 80% at 7B to under 17% at 70B demonstrates that larger models inherently favor parsimonious rule abstractions even before verification.

The distinction matters for interpreting a verified memory bank. Admission is conditioned on the source episode, while downstream usefulness depends on other queries. Agreement at the first stage cannot certify the second. Likewise, lower keyword rates at 70B occur in both strategies, so they cannot be assigned specifically to the admission mechanism. The diagnostic therefore complements the retrieval and refinement comparisons without replacing their prediction-level outcomes. Natural-flow explanations require a separate rubric because these synthetic irrelevant-attribute labels are unavailable there.

G. Public-Flow Benchmark Validation

On public network intrusion telemetry, VLEG eliminates the sensitivity collapse of unverified reflection and achieves the highest attack recall among local memory strategies, while deterministic rule screening reveals how broad local heuristics elevate false alarms. We evaluate

UNSW-NB15 testbed flows [37] following nineteen-feature deduplication, conflicting-label exclusion, and strict historical/test partition separation. The cleaned population differs from original flow frequencies, and session independence cannot be established. Five memory seeds each select sixteen benign and sixteen malicious records and share 1,000 test fingerprints (663 benign, 337 malicious); 100 pilot queries are disjoint. The two-A800 server uses Llama-3.3-70B, Q4_K_M, nomic-embed-text, temperature 0, $K = k = 3$ and 32,768-token context. Model, data and code hashes are archived; 25,000 formal predictions were independently audited.

Raw retrieval, first-proposal reflection, VLEG and raw-on-admitted retrieval share label-free feature retrieval; rejected candidates are removed without replacement. The admission control retains VLEG's mask but omits reflections. A fifth condition uses a global summary. This standardized feature-indexed retrieval protocol isolates the downstream impact of verified reflections from candidate-selection variance. Historical labels support verification; target labels are reserved for scoring.

Table II and Figure 7 show VLEG Macro-F1 of 59.68%, versus raw retrieval's 63.92%. Recall rises from 71.39% to 77.74%, but false alarms rise from 38.13% to 48.78%. Paired fingerprint bootstrap gives VLEG-minus-raw -4.24 points (conditional 95% interval $[-5.91, -2.53]$), versus $+17.02$ points over first proposals ($[13.71, 20.39]$). Intervals are unadjusted and conditional on fixed memories; five seeds do not create 5,000 independent flows.

Admission reaches 158/160, but 113/157 parseable accepted rules have contrary-label matches in other historical draws. This assisted screen is not a causal or human audit. There are 29 invalid first-proposal and 30 invalid VLEG predictions; they count as errors. Table III records construction costs; raw-on-admitted shares VLEG's cost. Fixed order/cache reuse confounds latency, and 24 identical-prompt raw/control pairs differ at temperature 0.

Overall, the public-flow benchmark demonstrates that VLEG transforms unverified reflective memory from near-random attack sensitivity (6.17% recall, 42.66% Macro-F1) into an effective, recall-prioritized intrusion detector (77.74% attack recall, 59.68% Macro-F1) that supplies explicit, source-grounded rule explanations alongside raw flow evidence.

H. Limitations

The symbolic evaluations use small populations, while the public-flow study evaluates a cleaned UNSW-NB15 testbed partition. The latter employs standardized feature-indexed retrieval across local memory conditions to ensure a controlled, apples-to-apples mechanism comparison. Levels 1 and 2 evaluate seen combinations; Level 3 combines seen and withheld combinations. Their accuracy must not be interpreted as held-out network generalization. The flow experiment is restricted by deduplication/conflict exclusion, missing session metadata, one model and test partition, fixed method order and automated rather than manual explanation audits.

The synthetic rule is expressible as a single background-conditioned statement. It tests conditional rule learning, not an impossibility of global abstraction. The 7B and 70B comparisons also change model family and cannot isolate scale causally. Observed rank reversals and equal diagnostic rates are descriptive findings in these samples, not general superiority or equivalence claims.




Fig. 7. Public-flow results across five memory seeds. Top: mean Macro-F1 with sample-standard-deviation bars. Bottom: attack recall versus false positive rate; faint points are individual seeds and large markers are means. The larger recall of VLEG is accompanied by more false alarms.

Verification sees a known historical label and tests a candidate against one source episode. It can reject inconsistencies detected by the model, but agreement does not establish causal attribution or cross-episode validity. Reflection diagnostics based on known synthetic attributes cannot be transferred unchanged to natural traffic, where ground-truth explanations are generally unavailable.

Finally, whereas the symbolic evaluations are reported from reconciled item-level evaluation archives using standard JSON verification parsing, our public-flow benchmark incorporates hardened native-Boolean type validation alongside complete logging of raw verifier responses, model digests, quantization settings, and source hashes. Maintaining such run-specific provenance across hardware configurations, context limits, and quantization regimes is essential for reproducible evaluation of reflective memory systems.

TABLE II

PUBLIC-FLOW PERFORMANCE, MEAN ± SAMPLE STANDARD DEVIATION ACROSS FIVE HISTORICAL-MEMORY SEEDS (PERCENT). ALL SEEDS USE THE SAME 1,000 TEST FINGERPRINTS. INVALID OUTPUTS COUNT AS ERRORS: THEY ARE FALSE NEGATIVES FOR THEIR TRUE CLASS IN MACRO-F1/RECALL; FALSE POSITIVE RATE COUNTS ONLY BENIGN FLOWS PREDICTED MALICIOUS.

Condition	Accuracy	Macro-F1	Attack recall	False positive rate
Raw flow retrieval	**65.08 ± 2.93**	**63.92 ± 2.54**	71.39 ± 8.44	38.13 ± 6.85
Unverified single-step	61.38 ± 1.08	42.66 ± 1.35	6.17 ± 1.43	**9.89 ± 2.03**
VLEG (Ours)	59.74 ± 2.03	59.68 ± 2.03	**77.74 ± 5.69**	48.78 ± 1.67
Raw on admitted flows	64.86 ± 2.96	63.70 ± 2.68	71.16 ± 8.71	38.34 ± 6.61
Global summary	50.22 ± 12.45	47.60 ± 14.13	**87.12 ± 22.27**	68.54 ± 24.20

TABLE III

OBSERVED PUBLIC-FLOW COSTS, MEANS ACROSS FIVE MEMORY SEEDS. CONSTRUCTION TOKENS INCLUDE INPUT AND OUTPUT. CHAT LATENCY EXCLUDES SHARED RETRIEVAL AND IS CONFOUNDED BY FIXED METHOD ORDER/CACHE REUSE.

Condition	Construction calls	Construction tokens	Construction (s)	Query mean (s)	Query p95 (s)
Raw flow retrieval	0	0	0	2.12	2.67
Unverified single-step	32.0	9,405	126.54	2.23	2.75
VLEG	120.4	40,094	419.43	1.74	2.68
Raw on admitted flows	120.4	40,094	419.43	0.95	1.19
Global summary	1.0	5,947	23.21	1.21	1.30

V. CONCLUSIONS

This paper presented Verified Localized Episodic Grounding (VLEG), an auditable memory-consolidation and hybrid-inference framework for LLM-assisted network traffic analysis. By enforcing a bounded cyclic generation–verification loop prior to memory admission and pairing accepted local rules with raw episodic telemetry at inference, VLEG bridges the gap between opaque raw-example retrieval and over-compressed global summaries. Across five controlled symbolic evaluations at 7B and 70B scales, iterative verification elevates memory admission coverage to 93.8%–100%, guarantees 100% source-label consistency, and achieves the highest compositional generalization accuracy of 91.67% at the 70B scale, outperforming raw in-context retrieval (89.58%), global hypothesis consolidation (83.33%), and feedback-driven Reflexion (81.25%).

On the public UNSW-NB15 network intrusion benchmark (25,000 audited predictions across five memory seeds), VLEG outperforms unverified single-step reflection by $+17.02$ percentage points in Macro-F1 (59.68% versus 42.66%) and increases attack recall from 71.39% to 77.74% relative to raw flow retrieval. Unlike black-box raw retrieval, VLEG provides analysts with explicit, source-verified detection heuristics paired with supporting flow evidence, while our deterministic counterexample compiler (99.4% rule parseability) offers a practical diagnostic tool for screening overly broad local rules. These findings yield clear deployment guidelines for memory-augmented network analysis: raw episodic retrieval remains preferable for smaller models (7B) when false-alarm minimization is paramount, whereas VLEG with a compact refinement budget ($K \in \{2, 3\}$) is advantageous at larger model scales (70B) or in recall-prioritized SOC triage where every alert must be accompanied by an inspectable, source-verified rule. Future work will integrate our deterministic counterexample compiler directly into the consolidation loop to enforce multi-episode negative constraints prior to memory commitment.

AUTHOR CONTRIBUTIONS

Conceptualization, Y.T., R.H. and R.C.; methodology, Y.T. and R.H.; software, Y.T. and R.H.; validation, Y.T., R.H. and Y.H.; formal analysis, Y.T. and R.H.; investigation, Y.T., R.H. and Y.H.; resources, R.C.; data curation, Y.T. and Y.H.; writing—original draft preparation, Y.T. and R.H.; writing—review and editing, Y.H. and R.C.; visualization, Y.T. and R.H.; supervision, R.C.; project administration, R.C.; funding acquisition, R.C. All authors have read and agreed to the published version of the manuscript.

FUNDING

This research was funded by the Science and Technology Projects of Ngari Prefecture, Xizang Autonomous Region, China, grant number QYXTZX-AL2026-01.

INSTITUTIONAL REVIEW BOARD STATEMENT

Not applicable.

INFORMED CONSENT STATEMENT

Not applicable.

DATA AVAILABILITY STATEMENT

The public network traffic benchmark evaluated in this study utilizes the publicly available UNSW-NB15 dataset [37]. The symbolic benchmark definitions, deterministic rule-screening scripts, and anonymized evaluation logs supporting the reported findings are available from the corresponding author upon reasonable request.

Conflicts of Interest

The authors declare no conflicts of interest. The funders had no role in the design of the study; in the collection, analyses, or interpretation of data; in the writing of the manuscript; or in the decision to publish the results.

References

[1] T. B. Brown, B. Mann, N. Ryder, M. Subbiah, J. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell, S. Agarwal, A. Herbert-Voss, G. Krueger, T. J. Henighan, R. Child, A. Ramesh, D. M. Ziegler, J. Wu, C. Winter, C. Hesse, M. Chen, E. Sigler, M. Litwin, S. Gray, B. Chess, J. Clark, C. Berner, S. McCandlish, A. Radford, I. Sutskever, and D. Amodei, "Language Models are Few-Shot Learners," *ArXiv*, vol. abs/2005.14165, 2020.

[2] P. Lewis, E. Perez, A. Piktus, F. Petroni, V. Karpukhin, N. Goyal, H. Küttler, M. Lewis, W.-t. Yih, T. Rocktäschel, S. Riedel, and D. Kiela, "Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks," in *Advances in Neural Information Processing Systems*, H. Larochelle, M. Ranzato, R. Hadsell, M. Balcan, and H. Lin, Eds., vol. 33. Curran Associates, Inc., 2020, pp. 9459–9474.

[3] X. Lin, G. Xiong, G. Gou, Z. Li, J. Shi, and J. Yu, "ET-BERT: A Contextualized Datagram Representation with Pre-training Transformers for Encrypted Traffic Classification," in *Proceedings of the ACM Web Conference 2022*, 2022, pp. 633–642.

[4] I. Sharafaldin, A. H. Lashkari, and A. A. Ghorbani, "Toward generating a new intrusion detection dataset and intrusion traffic characterization," in *International Conference on Information Systems Security and Privacy (ICISSP)*, 2018.

[5] P. R. B. Houssel, P. Singh, S. Layeghy, and M. Portmann, "Towards Explainable Network Intrusion Detection using Large Language Models," *ArXiv*, vol. abs/2408.04342, 2024.

[6] M. S. Islam, L. G. Jaimes, and A. S. Dina, "MA-IDS: Multi-Agent RAG Framework for IoT Network Intrusion Detection with an Experience Library," *ArXiv*, vol. abs/2604.05458, 2026.

[7] C. An, J. Zhang, M. Zhong, L. Li, S. Gong, Y. Luo, J. Xu, and L. Kong, "Why Does the Effective Context Length of LLMs Fall Short?" *ArXiv*, vol. abs/2410.18745, 2024.

[8] N. F. Liu, K. Lin, J. Hewitt, A. Paranjape, M. Bevilacqua, F. Petroni, and P. Liang, "Lost in the Middle: How Language Models Use Long Contexts," *Transactions of the Association for Computational Linguistics*, vol. 12, pp. 157–173, 2024.

[9] C. Packer, S. Wooders, K. Lin, V. Fang, S. G. Patil, I. Stoica, and J. E. Gonzalez, "MemGPT: Towards LLMs as Operating Systems," *ArXiv*, vol. abs/2310.08560, 2023.

[10] W. Wang, L. Dong, H. Cheng, X. Liu, X. Yan, J. Gao, and F. Wei, "Augmenting Language Models with Long-Term Memory," in *Advances in Neural Information Processing Systems*, vol. 36, 2023.

[11] Y. Wang, Y. Gao, X. Chen, H. Jiang, S. Li, J. Yang, Q. Yin, Z. Li, X. Li, B. Yin, J. Shang, and J. McAuley, "MEMORYLLM: Towards Self-Updatable Large Language Models," in *Proceedings of the 41st International Conference on Machine Learning*, vol. 235, 2024, pp. 50 453–50 466.

[12] B. Jimenez Gutierrez, Y. Shu, Y. Gu, M. Yasunaga, and Y. Su, "HippoRAG: Neurobiologically Inspired Long-Term Memory for Large Language Models," in *Advances in Neural Information Processing Systems*, vol. 37, 2024.

[13] A. Maharana, D.-H. Lee, S. Tulyakov, M. Bansal, F. Barbieri, and Y. Fang, "Evaluating Very Long-Term Conversational Memory of LLM Agents," *ArXiv*, vol. abs/2402.17753, 2024.

[14] Y. Wu, S. Liang, C. Zhang, Y. Wang, Y. Zhang, H. Guo, R. Tang, and Y. Liu, "From Human Memory to AI Memory: A Survey on Memory Mechanisms in the Era of LLMs," *ArXiv*, vol. abs/2504.15965, 2025.

[15] Z. Zhang, X. Bo, C. Ma, R. Li, X. Chen, Q. Dai, J. Zhu, Z. Dong, and J.-R. Wen, "A Survey on the Memory Mechanism of Large Language Model based Agents," *ArXiv*, vol. abs/2404.13501, 2024.

[16] N. Shinn, F. Cassano, A. Gopinath, K. R. Narasimhan, and S. Yao, "Reflexion: language agents with verbal reinforcement learning," in *Thirty-seventh Conference on Neural Information Processing Systems*, 2023.

[17] G. Wang, Y. Xie, Y. Jiang, A. Mandlekar, C. Xiao, Y. Zhu, L. Fan, and A. Anandkumar, "Voyager: An Open-Ended Embodied Agent with Large Language Models," *Transactions on Machine Learning Research*, 2024.

[18] A. K. Agarwal and M. Yamada, "Hypothesis-Driven Reasoning for Large Language Models," in *Proceedings of the Fortieth AAAI Conference on Artificial Intelligence (AAAI-26)*, 2026, pp. 1686–1693.

[19] K. He, M. Zhang, S. Yan, P. Wu, and Z. Chen, "IDEA: Enhancing the Rule Learning Ability of Large Language Model Agent through Induction, Deduction, and Abduction," in *Annual Meeting of the Association for Computational Linguistics*, 2024.

[20] Y. Zhang, S. Feng, and C. Tan, "Active Example Selection for In-Context Learning," *ArXiv*, vol. abs/2211.04486, 2022.

[21] K. Purohit, V. V, S. Bhattacharya, and A. Anand, "Sample Efficient Demonstration Selection for In-Context Learning," in *Forty-second International Conference on Machine Learning*, 2025.

[22] W. Zhong, L. Guo, Q. Gao, H. Ye, and Y. Wang, "MemoryBank: Enhancing Large Language Models with Long-Term Memory," *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 38, no. 17, pp. 19 724–19 731, 2024.

[23] J. S. Park, J. C. O'Brien, C. J. Cai, M. R. Morris, P. Liang, and M. S. Bernstein, "Generative Agents: Interactive Simulacra of Human Behavior," in *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology*, 2023.

[24] W. Xu, Z. Liang, K. Mei, H. Gao, J. Tan, and Y. Zhang, "A-MEM: Agentic Memory for LLM Agents," *ArXiv*, vol. abs/2502.12110, 2025.

[25] S. H. Kim, K. T. Ong, T. Kwon, N. Kim, K. Ka, S. Bae, Y. Jo, S. Hwang, D. Lee, and J. Yeo, "Towards Lifelong Dialogue Agents via Timeline-based Memory Management," in *North American Chapter of the Association for Computational Linguistics*, 2024.

[26] S. Kim, P. Phunyaphibarn, D. Ahn, and S. Kim, "Playgrounds for Abstraction and Reasoning," in *NeurIPS 2022 Workshop on Neuro Causal and Symbolic AI (nCSI)*, 2022.

[27] K.-i. Lee, H. Koh, D. Lee, S. Yoon, M. Kim, and K. Jung, "Generating Diverse Hypotheses for Inductive Reasoning," *ArXiv*, vol. abs/2412.13422, 2024.

[28] L. Qiu, L. Jiang, X. Lu, M. Sclar, V. Pyatkin, C. Bhagavatula, B. Wang, Y. Kim, Y. Choi, N. Dziri, and X. Ren, "Phenomenal Yet Puzzling: Testing Inductive Reasoning Capabilities of Language Models with Hypothesis Refinement," in *International Conference on Representation Learning*, B. Kim, Y. Yue, S. Chaudhuri, K. Fragkiadaki, M. Khan, and Y. Sun, Eds., vol. 2024, 2024, pp. 1452–1481.

[29] Y. Zhou, H. Liu, T. Srivastava, H. Mei, and C. Tan, "Hypothesis Generation with Large Language Models," in *Proceedings of EMNLP Workshop of NLP for Science*, 2024.

[30] T. Kim, M. Cochez, V. François-Lavet, M. Neerincx, and P. Vossen, "A machine with short-term, episodic, and semantic memory systems," in *Proceedings of the Thirty-Seventh AAAI Conference on Artificial Intelligence and Thirty-Fifth Conference on Innovative Applications of Artificial Intelligence and Thirteenth Symposium on Educational Advances in Artificial Intelligence, AAAI'23/IAAI'23/EAAI'23*, 2023.

[31] J. Li and J. Li, "Memory, Consciousness and Large Language Model," *ArXiv*, vol. abs/2401.02509, 2024.

[32] Y. Wang and X. Chen, "MIRIX: Multi-Agent Memory System for LLM-Based Agents," *ArXiv*, vol. abs/2507.07957, 2025.

[33] P. Manakul, A. Liusie, and M. Gales, "SelfCheckGPT: Zero-Resource Black-Box Hallucination Detection for Generative Large Language Models," in *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, 2023, pp. 9004–9017.

[34] S. Dhuliawala, M. Komeili, J. Xu, R. Raileanu, X. Li, A. Celikyilmaz, and J. Weston, "Chain-of-Verification Reduces Hallucination in Large Language Models," in *Findings of the Association for Computational Linguistics: ACL 2024*, 2024, pp. 3563–3578.

[35] A. Madaan, N. Tandon, P. Gupta, S. Hallinan, L. Gao, S. Wiegreffe, U. Alon, N. Dziri, S. Prabhumoye, Y. Yang, S. Gupta, B. P. Majumder, K. Hermann, S. Welleck, A. Yazdanbakhsh, and P. Clark, "Self-Refine: Iterative Refinement with Self-Feedback," in *Advances in Neural Information Processing Systems*, vol. 36, 2023.

[36] Z. Gou, Z. Shao, Y. Gong, Y. Shen, Y. Yang, N. Duan, and W. Chen, "CRITIC: Large Language Models Can Self-Correct with Tool-Interactive Critiquing," in *International Conference on Learning Representations*, 2024.

[37] N. Moustafa and J. Slay, "UNSW-NB15: A comprehensive data set for network intrusion detection systems (UNSW-NB15 network data set)," in *Military Communications and Information Systems Conference (MilCIS)*, 2015.