

# KELLAR-STUDIO'S

## AUDIO IDENTITY & SONIC LOGO SPECIFICATIONS

### 1. ACOUSTIC FRAMEWORK ARCHITECTURE

This master framework dictates the acoustic constraints, signal pathways, and normalization boundaries required to achieve consistent acoustic authority across distribution pipelines.

#### [1] SONIC SIGNATURE (INTRO/OUTRO)

- **Duration Parameter:** 2.5 to 3.0 seconds maximum run length execution.
- **Sub-Bass Sweep:** 30Hz to 80Hz linear frequency acceleration to generate localized physical pressure.
- **Transient Accent:** High-frequency "Electric Hertz" synth chime cluster anchored precisely at 5kHz.
- **Spatial Profile:** 90% wide stereo panoramic field tracking, collapsing into tight center-mono fields immediately on spoken dialogue onset.

#### [2] DIALOGUE POCKET & MUSIC DUCKING

- **Voiceover Priority Target:** -18 to -15 LUFS Integrated range for raw raw language captures.
- **Music Track Attenuation:** Structural ducking threshold configured between 12dB and 15dB during active speech phases.
- **Surgical Frequency Cleaving:** Dynamic EQ attenuation band mapped between 1kHz and 3.5kHz on background instrument arrangements, sidechained directly to vocal signals.

#### [3] ENGINEERING MASTER SPECIFICATIONS

- **Short-Form Delivery (Reels / TikTok / Shorts):** -14 LUFS Integrated | -1.0 dBTP True Peak safety limit.
- **Long-Form Master (YouTube Channels):** -14 LUFS Integrated | -0.1 to -1.0 dBTP flexible range limits.
- **Ecosystem Codec Target:** Render out strictly as 24-bit linear uncompressed PCM WAV containers mapped at a 48kHz sampling index.