

Development of a Belief Merging Framework for dlhex

Christoph Redl

May 31, 2010

Outline

- 1 Motivation
- 2 Reasons for Incompatibility
- 3 Task Definition
- 4 Architecture of the Belief Merging Framework
- 5 Using the Framework - Hands-on
- 6 Application Scenario
- 7 Summary

Motivation

Usage of multiple belief bases

- Usually we have more than one knowledge base

Motivation

Usage of multiple belief bases

- Usually we have more than one knowledge base
- In many applications, knowledge sources are often provided by third-parties

Motivation

Usage of multiple belief bases

- Usually we have more than one knowledge base
- In many applications, knowledge sources are often provided by third-parties
- ... but rarely synchronized

Motivation

Usage of multiple belief bases

- Usually we have more than one knowledge base
- In many applications, knowledge sources are often provided by third-parties
- ... but rarely synchronized

Combining the contents

- We do not want to restrict ourselves to one source

Motivation

Usage of multiple belief bases

- Usually we have more than one knowledge base
- In many applications, knowledge sources are often provided by third-parties
- ... but rarely synchronized

Combining the contents

- We do not want to restrict ourselves to one source
- Naive union can introduce contradictions

Motivation

Usage of multiple belief bases

- Usually we have more than one knowledge base
- In many applications, knowledge sources are often provided by third-parties
- ... but rarely synchronized

Combining the contents

- We do not want to restrict ourselves to one source
- Naive union can introduce contradictions
- Many different merging techniques

Motivation

Belief Revision

- Incorporation of knowledge into existing belief base

Motivation

Belief Revision

- Incorporation of knowledge into existing belief base
- AGM postulates: “minimal change”

Motivation

Belief Revision

- Incorporation of knowledge into existing belief base
- AGM postulates: “minimal change”

Belief Merging

- *Aggregation* of sources
- No single formula with absolute priority

Motivation

Belief Revision

- Incorporation of knowledge into existing belief base
- AGM postulates: “minimal change”

Belief Merging

- *Aggregation* of sources
- No single formula with absolute priority
- Variants of AGM postulates are reasonable:
informally, minimize differences between sources and merged belief base

Motivation

Belief Revision

- Incorporation of knowledge into existing belief base
- AGM postulates: “minimal change”

Belief Merging

- *Aggregation* of sources
- No single formula with absolute priority
- Variants of AGM postulates are reasonable:
informally, minimize differences between sources and merged belief base

Applications

- judgment aggregation

Motivation

Belief Revision

- Incorporation of knowledge into existing belief base
- AGM postulates: “minimal change”

Belief Merging

- *Aggregation* of sources
- No single formula with absolute priority
- Variants of AGM postulates are reasonable:
informally, minimize differences between sources and merged belief base

Applications

- judgment aggregation
- merging of decision diagrams

Motivation

Belief Revision

- Incorporation of knowledge into existing belief base
- AGM postulates: “minimal change”

Belief Merging

- *Aggregation* of sources
- No single formula with absolute priority
- Variants of AGM postulates are reasonable:
informally, minimize differences between sources and merged belief base

Applications

- judgment aggregation
- merging of decision diagrams
- fusion of business databases

Types of Incompatibility

Syntactic Incompatibility

- Sources are written in different formalisms
- Preprocessing step needed

Types of Incompatibility

Syntactic Incompatibility

- Sources are written in different formalisms
- Preprocessing step needed

Examples

- relational databases
- object-orientated databases
- RDF ontologies
- logic programs

Types of Incompatibility

Logic Inconsistencies

Union of data sets leads to **contradictions**:

$$\bigcup_i KB_i \models \perp$$

Types of Incompatibility

Logic Inconsistencies

Union of data sets leads to **contradictions**:

$$\bigcup_i KB_i \models \perp$$

likewise

constraint violation: $\bigcup_i KB_i \not\models C$

Types of Incompatibility

Logic Inconsistencies

Union of data sets leads to **contradictions**:

$$\bigcup_i KB_i \models \perp$$

likewise

constraint violation: $\bigcup_i KB_i \not\models C$

Example

name is the primary key; a constraint forces the height to be unique for each person.

(a)

<u>name</u>	height
Marge	1,78m
Homer	1,82m
Bart	1,67m

(b)

<u>name</u>	height
Marge	1,78m
Homer	1,82m
Bart	1,65m

Data Cleanness

- Remain after logic inconsistencies resolved
- Detection requires advanced algorithms: data cleansing

Data Cleaness

- Remain after logic inconsistencies resolved
- Detection requires advanced algorithms: data cleansing

Undesired artefacts concerning

- Differing naming conventions
e.g., academic degrees, addresses, ...
- Different entries referring to the same real-world object

Data Cleaness

- Remain after logic inconsistencies resolved
- Detection requires advanced algorithms: data cleansing

Undesired artefacts concerning

- Differing naming conventions
e.g., academic degrees, addresses, ...
- Different entries referring to the same real-world object

Example

Merging of address tables, one with and one without abbreviations

Logic Programs as Belief Bases

Given

$\pi = (P_1, \dots, P_n)$ vector of belief bases

Given as *logic programs* with answer sets $AS(P_i)$

Logic Programs as Belief Bases

Given

$\pi = (P_1, \dots, P_n)$ vector of belief bases

Given as *logic programs* with answer sets $AS(P_i)$

Answer sets of programs are considered to be the stored knowledge

Logic Programs as Belief Bases

Given

$\pi = (P_1, \dots, P_n)$ vector of belief bases

Given as *logic programs* with answer sets $AS(P_i)$

Answer sets of programs are considered to be the stored knowledge

To define

$\Sigma^C = (\Sigma_c^C, \Sigma_p^C)$ common signature

$\mu = (\mu_1, \dots, \mu_n)$ vector of mapping functions

$\omega = (\circ_1, \dots, \circ_m)$ merging operators

R merging plan

Common Signature and Mappings

Solve the problem of syntactic incompatibility

Common Signature and Mappings

Solve the problem of syntactic incompatibility

Common Signature

- $\Sigma^C = (\Sigma_c^C, \Sigma_p^C)$
- expressive enough to represent any of sources

Common Signature and Mappings

Solve the problem of syntactic incompatibility

Common Signature

- $\Sigma^C = (\Sigma_c^C, \Sigma_p^C)$
- expressive enough to represent any of sources

Mappings

- Let $\mathcal{A} = 2^{Lit_{\Sigma^C}}$ (set of potential answer sets over Σ^C)

Common Signature and Mappings

Solve the problem of syntactic incompatibility

Common Signature

- $\Sigma^C = (\Sigma_c^C, \Sigma_p^C)$
- expressive enough to represent any of sources

Mappings

- Let $\mathcal{A} = 2^{Lit_{\Sigma^C}}$ (set of potential answer sets over Σ^C)
- $\mu_i : \{AS(P_i)\} \rightarrow 2^{\mathcal{A}}$

Common Signature and Mappings

Solve the problem of syntactic incompatibility

Common Signature

- $\Sigma^C = (\Sigma_c^C, \Sigma_p^C)$
- expressive enough to represent any of sources

Mappings

- Let $\mathcal{A} = 2^{Lit_{\Sigma^C}}$ (set of potential answer sets over Σ^C)
- $\mu_i : \{AS(P_i)\} \rightarrow 2^{\mathcal{A}}$
- answer sets stay semantically equivalent!

Merging Operators

Resolve logic inconsistencies
(plus: may perform data cleansing tasks)

Merging Operators

Resolve logic inconsistencies
(plus: may perform data cleansing tasks)

$$\circ_i^{n,m} : \underbrace{2^{\mathcal{A}} \times \dots \times 2^{\mathcal{A}}}_{n \text{ times}} \times \underbrace{\mathcal{D}_1 \times \dots \times \mathcal{D}_m}_{\text{additional parameters}} \rightarrow 2^{\mathcal{A}}$$

Merging Operators

Resolve logic inconsistencies
(plus: may perform data cleansing tasks)

$$\circ_i^{n,m} : \underbrace{2^{\mathcal{A}} \times \dots \times 2^{\mathcal{A}}}_{n \text{ times}} \times \underbrace{\mathcal{D}_1 \times \dots \times \mathcal{D}_m}_{\text{additional parameters}} \rightarrow 2^{\mathcal{A}}$$

Example for a merging operator

The union operator $\circ_{\cup}^{2,0}$ is defined as follows:

$$\circ_{\cup}^{2,0} : 2^{\mathcal{A}} \times 2^{\mathcal{A}} \rightarrow 2^{\mathcal{A}}$$

$$\circ_{\cup}^{2,0}(SAS_1, SAS_2) = \{AS_1 \cup AS_2 \mid AS_1 \in SAS_1, AS_2 \in SAS_2, AS_1 \cup AS_2 \not\models \perp\}$$

(\circ_{\cup}^2 is binary, no additional parameters)

Merging Plans

A merging plan is **hierarchical** and defines

- the order
- of operators
- to be applied on which belief bases

Merging Plans


A merging plan is **hierarchical** and defines

- the order
- of operators
- to be applied on which belief bases


The result

- the set of answer sets delivered by the topmost operator

Example merging plan




Merging Input



Approach

Steps


- 1 designing a merging language
- 2 implementing the merging plan compiler
- 3 implementing external atoms (mergingplugin)



Approach

Steps

- 1 designing a merging language
- 2 implementing the merging plan compiler
- 3 implementing external atoms (mergingplugin)




Approach

Steps

- 1 designing a merging language
- 2 implementing the merging plan compiler
- 3 implementing external atoms (mergingplugin)

merging plan compiler

- translates merging plan into HEX program
- program makes use of **external atoms**
- answer sets = result of the merging plan




Approach

Steps

- 1 designing a merging language
- 2 implementing the merging plan compiler
- 3 implementing external atoms (mergingplugin)

merging plan compiler

- translates merging plan into HEX program
- program makes use of **external atoms**
- answer sets = result of the merging plan



mergingplugin

defines **external atoms** for:

- calling of nested HEX programs
- calling of merging operators

Advantages of the Framework

- Rapid prototyping

Advantages of the Framework

- Rapid prototyping
- Routine tasks like information flow management is done automatically

Advantages of the Framework

- Rapid prototyping
- Routine tasks like information flow management is done automatically
- Experiment with different merging plans and operators by parameterizing them

Advantages of the Framework

- Rapid prototyping
- Routine tasks like information flow management is done automatically
- Experiment with different merging plans and operators by parameterizing them
- Develop merging operators once, apply them in many scenarios

Using the Framework

Steps

- 1 Define your merging task “`merging.mp`”
- 2 Run the merging plan compiler (`mpcompiler`) on this input
- 3 Execute the result by `dlhex`

Using the Framework

Steps

- 1 Define your merging task “`merging.mp`”
- 2 Run the merging plan compiler (`mpcompiler`) on this input
- 3 Execute the result by `dlhex`
- 4 (filter the output since the translation of merging plans in HEX programs requires the derivation of some intermediate atoms)

Using the Framework

Steps

- 1 Define your merging task “`merging.mp`”
- 2 Run the merging plan compiler (`mpcompiler`) on this input
- 3 Execute the result by `dlhex`
- 4 (filter the output since the translation of merging plans in HEX programs requires the derivation of some intermediate atoms)

Typical call

■ Command-line:

```
$ mpcompiler merging.mp | dlhex --filter=a,b,c --
```

Using the Framework

Steps

- 1 Define your merging task “merging.mp”
- 2 Run the merging plan compiler (`mpcompiler`) on this input
- 3 Execute the result by `dlhex`
- 4 (filter the output since the translation of merging plans in HEX programs requires the derivation of some intermediate atoms)

Typical call

■ Command-line:

```
$ mpcompiler merging.mp | dlhex --filter=a,b,c --
```

■ Alternatively:

```
$ dlhex --merging --filter=a,b,c merging.mp
```

Merging plan language: `merging.mp`

[common signature]

predicate: a/0;

predicate: b/0;

predicate: c/0;

predicate: p/1;

predicate: q/3;

[belief base]

name:bb1;

mapping: "some_rule."; % query external source here

mapping: "q(X, Y, Z) :- &rdf[\"...\"](X, Y, Z).";

[belief base]

name:bb2;

source: "some_program.hex"; % or within this program

...

Merging plan language: `merging.mp` (ctn'd.)

```
[merging plan]
{
  operator: setminus;
  {
    operator: union;
    {
      operator: neg;
      {bb1};
    };
    {bb2};
    {bb3};
  };
  {
    operator: union;
    {bb4};
    {bb5};
  };
}
```

Dalal's Operator

Definition of implemented version

- Belief bases $K = (AS(P_1), \dots, AS(P_n))$
 \mathcal{A} = set of all potential answer sets

Dalal's Operator

Definition of implemented version

- Belief bases $K = (AS(P_1), \dots, AS(P_n))$
 \mathcal{A} = set of all potential answer sets
- Answer set distance function: $\underline{d} : \mathcal{A} \times \mathcal{A} \rightarrow \mathbb{R}$

Dalal's Operator

Definition of implemented version

- Belief bases $K = (AS(P_1), \dots, AS(P_n))$
 \mathcal{A} = set of all potential answer sets
- Answer set distance function: $\underline{d} : \mathcal{A} \times \mathcal{A} \rightarrow \mathbb{R}$
- Answer set to belief base-distances:

$$d(A, P_i) = \min_{J \in AS(P_i)} \underline{d}(A, J)$$

Dalal's Operator

Definition of implemented version

- Belief bases $K = (AS(P_1), \dots, AS(P_n))$
 \mathcal{A} = set of all potential answer sets
- Answer set distance function: $\underline{d} : \mathcal{A} \times \mathcal{A} \rightarrow \mathbb{R}$
- Answer set to belief base-distances:

$$d(A, P_i) = \min_{J \in AS(P_i)} \underline{d}(A, J)$$

- Aggregate function: $D : \mathbb{R}^n \rightarrow \mathbb{R}$

$$D^d(A, K) = D(d(A, P_1), \dots, d(A, P_n))$$

Dalal's Operator

Definition of implemented version

- Belief bases $K = (AS(P_1), \dots, AS(P_n))$
 \mathcal{A} = set of all potential answer sets
- Answer set distance function: $\underline{d} : \mathcal{A} \times \mathcal{A} \rightarrow \mathbb{R}$
- Answer set to belief base-distances:

$$d(A, P_i) = \min_{J \in AS(P_i)} \underline{d}(A, J)$$

- Aggregate function: $D : \mathbb{R}^n \rightarrow \mathbb{R}$

$$D^d(A, K) = D(d(A, P_1), \dots, d(A, P_n))$$

- $\circ^n(K) = \arg \min_{G \in \mathcal{A}: \text{consistent}} D^d(G, K)$

Fault Diagnosis

Finding an explanation for some observation

Definition

Propositional abduction problem (PAP): $\mathcal{P} = \langle V, H, M, T \rangle$

- V is a finite set of propositional variables
- $H \subseteq V$ is a set of hypothesis
- $M \subseteq V$ is the set of manifestations
- T is a consistent theory

Fault Diagnosis

Finding an explanation for some observation

Definition

Propositional abduction problem (PAP): $\mathcal{P} = \langle V, H, M, T \rangle$

- V is a finite set of propositional variables
- $H \subseteq V$ is a set of hypothesis
- $M \subseteq V$ is the set of manifestations
- T is a consistent theory

$S \subseteq H$ is a solution iff $T \cup S$ is consistent and $T \cup S \models M$

Fault Diagnosis

Finding an explanation for some observation

Definition

Propositional abduction problem (PAP): $\mathcal{P} = \langle V, H, M, T \rangle$

- V is a finite set of propositional variables
- $H \subseteq V$ is a set of hypothesis
- $M \subseteq V$ is the set of manifestations
- T is a consistent theory


$S \subseteq H$ is a solution iff $T \cup S$ is consistent and $T \cup S \models M$

Challenge: *multiple* experts with *different* explanations S_i


Task: Finding a group decision S_G s.t.

- S_G is a solution to \mathcal{P}
- S_G is as similar to $S_i \forall i$ as possible


Full Adder



Full Adder - Example interpretation



Full Adder - Malfunctioning



Full Adder


Implemented as logic program “fulladder.dl” (theory)
with observations “fault.obs”

Full Adder

Implemented as logic program “fulladder.dl” (theory)
with observations “fault.obs”

Suppose we have 3 experts with different hypotheses

1 $ab(haAnd1).ab(haXor1).ab(haAnd2).ab(haXor2).ab(faOr1).$




Full Adder

Implemented as logic program “fulladder.dl” (theory)
with observations “fault.obs”

Suppose we have 3 experts with different hypotheses

- 1 $ab(haAnd1).ab(haXor1).ab(haAnd2).ab(haXor2).ab(faOr1).$
- 2 $ab(haAnd1).ab(haAnd2).ab(haXor2).ab(faOr1).$
no $ab(haXor1)!$




Full Adder

Implemented as logic program “fulladder.dl” (theory)
with observations “fault.obs”

Suppose we have 3 experts with different hypotheses

- 1 $ab(haAnd1).ab(haXor1).ab(haAnd2).ab(haXor2).ab(faOr1).$
- 2 $ab(haAnd1).ab(haAnd2).ab(haXor2).ab(faOr1).$
no $ab(haXor1)!$
- 3 $ab(haAnd1).ab(haAnd2).ab(haXor2).ab(faOr1).$
no $ab(haXor2)!$



Full Adder


Implemented as logic program “fulladder.dl” (theory)
with observations “fault.obs”

Suppose we have 3 experts with different hypotheses

- 1 $ab(haAnd1).ab(haXor1).ab(haAnd2).ab(haXor2).ab(faOr1).$
- 2 $ab(haAnd1).ab(haAnd2).ab(haXor2).ab(faOr1).$
no $ab(haXor1)!$
- 3 $ab(haAnd1).ab(haAnd2).ab(haXor2).ab(faOr1).$
no $ab(haXor2)!$

(Minimal) Solutions

- 1 $AS(P_{J_1}) = \{\{ab(haXor1)\}, \{ab(haXor2)\}\}$
- 2 $AS(P_{J_2}) = \{\{ab(haXor2)\}\}$
- 3 $AS(P_{J_3}) = \{\{ab(haXor1)\}\}$



Full Adder - Merging individual decisions

Requirements

The group decision **must** be an explanation
and **should** be similar to the individual's

Full Adder - Merging individual decisions

Requirements

The group decision **must** be an explanation
and **should** be similar to the individual's

Distance function

I = individual explanation

G = group explanation

- 1 Penalize ignoring of individual beliefs, i.e.,

$$a \in I \wedge a \notin G$$

$$\neg a \in I \wedge \neg a \notin G$$

Full Adder - Merging individual decisions

Requirements

The group decision **must** be an explanation
and **should** be similar to the individual's

Distance function

I = individual explanation

G = group explanation

- 1 Penalize ignoring of individual beliefs, i.e.,
 $a \in I \wedge a \notin G$
 $\neg a \in I \wedge \neg a \notin G$
- 2 Penalize group beliefs unfounded for an individual, i.e.,
 $a \in G \wedge a \notin I$
 $\neg a \in G \wedge \neg a \notin I$

Full Adder - Merging individual decisions

Requirements

The group decision **must** be an explanation
and **should** be similar to the individual's

Distance function

I = individual explanation

G = group explanation

- 1 Penalize ignoring of individual beliefs, i.e.,
 $a \in I \wedge a \notin G$
 $\neg a \in I \wedge \neg a \notin G$
- 2 Penalize group beliefs unfounded for an individual, i.e.,
 $a \in G \wedge a \notin I$
 $\neg a \in G \wedge \neg a \notin I$
- 3 Penalize both (1) and (2), i.e.,
 $|I \Delta G|$

Full Adder

```
[common signature]
predicate:ab/1;
```

```
[belief base]
name:juror1;
dlvargs: "-FRmin fulladder.dl abnormal1.hyp fault.obs";
```

```
[belief base] name:juror2; ...
[belief base] name:juror3; ...
```

```
[merging plan]
{
operator: dalal; aggregate:"sum";
penalize: "ignoring";
constraints: "fulladder.dl"; constraints: "fault.obs";
{juror1}; {juror2}; {juror3};
}
```

Full Adder - Group Decision

Individual explanations

$$1 \quad AS(P_{J_1}) =$$

$$\{\{ab(haXor1)\}, \{ab(haXor2)\}\}$$

$$2 \quad AS(P_{J_2}) = \{\{ab(haXor2)\}\}$$

$$3 \quad AS(P_{J_3}) = \{\{ab(haXor1)\}\}$$

Possible group explanations

$$1 \quad E_1 =$$

$$\{ab(haXor1), ab(haXor2)\}$$

$$2 \quad E_2 = \{ab(haXor1)\}$$

$$3 \quad E_3 = \{ab(haXor2)\}$$

Full Adder - Group Decision

Individual explanations

$$1 \quad AS(P_{J_1}) =$$

$$\{\{ab(haXor1)\}, \{ab(haXor2)\}\}$$

$$2 \quad AS(P_{J_2}) = \{\{ab(haXor2)\}\}$$

$$3 \quad AS(P_{J_3}) = \{\{ab(haXor1)\}\}$$

Possible group explanations

$$1 \quad E_1 =$$

$$\{ab(haXor1), ab(haXor2)\}$$

$$2 \quad E_2 = \{ab(haXor1)\}$$

$$3 \quad E_3 = \{ab(haXor2)\}$$

Distances to Individuals

Penalizing ignoring only

	$AS(P_{J_1})$	$AS(P_{J_2})$	$AS(P_{J_3})$	Sum
E_1	0	0	0	0 \Leftarrow
E_2	0	1	0	1
E_3	0	0	1	1

Full Adder - Group Decision

Individual explanations

$$\mathbf{1} \quad AS(P_{J_1}) =$$

$$\{\{ab(haXor1)\}, \{ab(haXor2)\}\}$$

$$\mathbf{2} \quad AS(P_{J_2}) = \{\{ab(haXor2)\}\}$$

$$\mathbf{3} \quad AS(P_{J_3}) = \{\{ab(haXor1)\}\}$$

Possible group explanations

$$\mathbf{1} \quad E_1 =$$

$$\{ab(haXor1), ab(haXor2)\}$$

$$\mathbf{2} \quad E_2 = \{ab(haXor1)\}$$

$$\mathbf{3} \quad E_3 = \{ab(haXor2)\}$$


Distances to Individuals

Penalizing ignoring and unfounded group beliefs ($|I\Delta G|$)

	$AS(P_{J_1})$	$AS(P_{J_2})$	$AS(P_{J_3})$	Sum
E_1	1	1	1	3
E_2	0	2	0	$\mathbf{2} \Leftarrow$
E_3	0	0	2	$\mathbf{2} \Leftarrow$


Summary

■ Task: Merging of several belief bases




Summary

- Task: Merging of several belief bases
- Approach: Merging language
 - with **user-defined** merging operators
- merging input \Rightarrow compiler \Rightarrow dlvhex \Rightarrow answer sets



Summary

- Task: Merging of several belief bases
- Approach: Merging language
 - with **user-defined** merging operators
- merging input \Rightarrow compiler \Rightarrow dlvhex \Rightarrow answer sets



Advantages

- Develop merging operators only once or select one of the preinstalled ones (like Dalal)
- No need for manual re-merging after each change of the setting
- Try out several operators and evaluate which behaves best
- No routine tasks (like information flow between sources)
- User can focus on development and optimization of merging procedures in narrower sense!