AD 2. AERODROMES

OIGG AD 2.1 AERODROME LOCATION INDICATOR AND NAME

OIGG - RASHT / SARDAR-E-JANGAL / Secondary International Aerodrome

OIGG AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	*ARP coordinates and site at AD*	371924N 0493704E
2	*Direction and distance from (city)*	NE, 2 NM from Rasht
3	*Elevation / Reference temperature*	-37 FT / 31°C
4	*MAG VAR / Annual change*	5° E (2017) / Information not available
5	*AD Administration, address, telephone, telefax, telex, AFS*	Iran Airports & Air Navigation Company (IAC) Sardar-e-Jangal Airport Postal code: 4163935365 Rasht - Islamic Republic of Iran Tel: +9813 - 33727001-4, 33726974 Telefax: +9813 - 33720099 Telex: NIL AFS: OIGGYDYX
6	*Types of traffic permitted (IFR/VFR)*	IFR/VFR
7	*Remarks*	NIL

OIGG AD 2.3 OPERATIONAL HOURS

1	*AD Administration*	SAT to WED 0400-1200
2	*Customs and immigration*	O/R
3	*Health and sanitation*	O/R
4	*AIS Briefing Office*	NIL
5	*ATS Reporting Office (ARO)*	Service available by ATS
6	*MET Briefing Office*	NIL
7	*ATS*	0300-1700
8	*Fuelling*	0300 - 1700
9	*Handling*	Available during main carrier schedule flights, other times O/R
10	*Security*	H24
11	*De-icing*	0300 - 1700
12	*Remarks*	Other times O/R. PPR at least 72 HR before EOBT from OIGG

OIGG AD 2.4 HANDLING SERVICES AND FACILITIES

1	*Cargo - handling facilities*	NIL
2	*Fuel / oil types*	Jet A1
3	*Fuelling facilities/capacity*	Jet A1 : 2 trucks, 20000 litres, 1 truck, 45000 litres, 40 litres/sec No limitation
4	*De - icing facilities*	Available by main carrier, it will be done at eastern part of apron
5	*Hanger space for visiting aircraft*	NIL
6	*Repair facilities for visiting aircraft*	NIL
7	*Remarks*	NIL

OIGG AD 2.5 PASSENGER FACILITIES

1	*Hotels*	Available in the city
2	*Restaurants*	Available at AD and in the city
3	*Transportation*	Taxis and buses
4	*Medical facilities*	First aids and ambulance at AD, Hospital in the city
5	*Bank and Post Office*	Only bank is available
6	*Tourist Office*	Available in the city
7	*Remarks*	NIL

OIGG AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	*AD category for fire fighting*	CAT 7
2	*Rescue equipment*	Available in accordance with AD category for firefighting
3	*Capability for removal of disabled aircraft*	NIL
4	*Remarks*	NIL

OIGG AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	*Types of clearing equipment*	1 blower and 5 blades fitted into trucks
2	*Clearance priorities*	1- RWY 09/27 2- TWY C and apron (stand NR 107 and 106) 3- TWY A and apron (stand NR 105, 104, 103, 102 and 101) 4- TWY B
3	*Remarks*	NIL

OIGG AD 2.8 APRONS, TAXIWAYS

1	*Apron surface and strength*	Surface: Asphalt Strength: PCN 60/F/C/X/T
2	*Taxiway width, surface and strength*	Width: 23 M Surface: Asphalt Strength: PCN 60/F/C/X/T
3	*Altimeter checkpoints*	Information not available
4	*VOR checkpoints*	Coordinates: 371925.7N 0493703.8 E Radial: 145° ; Distance: 0.2 NM
5	*INS checkpoints*	Information not available
6	*Remarks*	NIL

OIGG AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	*Use of aircraft stand ID signs* *TWY guide lines and parking guidance system of aircraft stands*	NIL
2	*RWY and TWY markings and LGT*	RWY marking: Designation, THR, TDZ, centre line, edge & RWY end. RWY lighting: See OIGG AD 2.14 TWY marking: Centre line, edge, holding position at TWY/RWY intersection. TWY lighting: See OIGG AD 2.15
3	*Stop bars*	NIL
4	*Remarks*	NIL

OIGG AD 2.10 AERODROME OBSTACLES

In approach / TKOF areas			*In circling area and at AD*		*Remarks*
1			2		3
RWY/Area affected	*Obstacle type Elevation / HGT Markings/LGT*	*Coordinates*	*Obstacle type Elevation / HGT Markings/LGT*	*Coordinates*	
a	*b*	*c*	*a*	*b*	
09 / APCH 27 / TKOF	AD Perimeter wall -41 FT AMSL NIL	371933N 0493506E	DVOR antenna -7 FT AMSL LGTD	371934.8N 0493657.1E	
09 / APCH 27 / TKOF	AD Perimeter wall -41 FT AMSL NIL	371938N 0493507E	TWR building 104 FT AMSL LGTD	371919N 0493655E	
09 / APCH 27 / TKOF	LOC antenna -44 FT AMSL LGTD	371935.6N 0493510.0E	Mast 372 FT AMSL LGTD	371737N 0493544E	
09 / APCH 27 / TKOF	RVR antenna -14 FT AMSL NIL	371929N 0493527E	Mast 991 FT AMSL LGTD	372630N 0494948E	
27/APCH 09/TKOF	Mast -1 FT AMSL NIL	371926N 0493748E	Mast 695 FT AMSL LGTD	372435N 0500044E	

In approach / TKOF areas			*In circling area and at AD*		*Remarks*
1			2		3
RWY/Area affected	*Obstacle type Elevation / HGT Markings/LGT*	*Coordinates*	*Obstacle type Elevation / HGT Markings/LGT*	*Coordinates*	
a	*b*	*c*	*a*	*b*	
27/APCH 09/TKOF	Mast 1 FT AMSL NIL	371924N 0493746E	NDB mast 94 FT AMSL NIL	371913.9N 0493722.8E	
27/APCH 09/TKOF	GP antenna 17 FT AMSL LGTD	371933.5N 0493706.4E	Apron mast 47 FT AMSL NIL	371920N 0493718E	
27/APCH 09/TKOF	RVR antenna -5 FT AMSL NIL	371926N 0493701E	Mast 37 FT AMSL NIL	371918N 0493737E	

OIGG AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	*Associated MET Office*	Rasht
2	*Hours of service* *MET Office outside hours*	H24 --
9	*ATS units provided with information*	Rasht TWR

Note: Subject concerning item 3 to 8 and 10 not available.

OIGG AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	*TRUE BRG*	*Dimensions of RWY (M)*	*Strength(PCN) and surface of RWY and SWY*	*THR coordinates THR geoid undulation*	*THR elevation and highest elevation of TDZ of precision APP RWY*
1	2	3	4	5	6
09	093.81°GEO	2917 x 45	60/F/C/X/T Asphalt	371934.99N 0493521.19E GUND 5 FT	THR -51 FT
27	273.83°GEO	2917 x 45	60/F/C/X/T Asphalt	371928.69N 0493719.39E GUND 5 FT	THR -37 FT

Slope of RWY - SWY	*SWY dimensions (M)*	*CWY dimensions (M)*	*Strip dimensions (M)*	*OFZ*	*Remarks*
7	8	9	10	11	12
0.14% 0.14 %	150 x 45 150 x 45	150 x 150 150 x 150	NIL NIL	NIL NIL	-THR RWY 09 displaced 100 M Coordinates: 371934.78N 0493525.25E -AD Reference Code: 4D

OIGG AD 2.13 DECLARED DISTANCES

RWY Designator	*TORA (M)*	*TODA (M)*	*ASDA (M)*	*LDA (M)*	*Remarks*
1	2	3	4	5	6
09	2917	3067	3067	2817	NIL
27	2817	3067	3067	2917	NIL

OIGG AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	*APCH LGT type LEN INTST*	*THR LGT colour WBAR*	*VASIS (MEHT) PAPI*	*TDZ LGT LEN*	*RWY Centre Line LGT LEN, spacing, colour INTST*	*RWY edge LGT LEN, spacing colour, INTST*	*RWY End LGT colour WBAR*	*SWY LGT LEN colour*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*	*8*	*9*	*10*
09	*NIL*	*Green Supplemented by WBAR*	*PAPI Left/3° (58FT)*	*NIL*	*NIL*	*2917 M 60 M White, LIH*	*Red*	*Red 150 M*	*According to 100 M DTHR RWY 09, THR LGTs and WBAR are installed.*
27	*PALS CAT I Barrette type 900 M LIH*	*Green Supplemented by WBAR*	*PAPI Left/3° (58FT)*	*NIL*	*NIL*	*2917 M 60 M White, LIH*	*Red*	*Red 150 M*	*Sequential Flash Lighting System (SFLS) available for RWY 27 900M*

OIGG AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	*ABN location, characteristics and hours of operation*	At top of the AD control tower building, FLG G and W, EV 2 sec; HN and during IMC
2	*LDI location and LGT* *Anemometer location and LGT*	NIL TDZ RWY 27: 371925.3N 0493701.6E (120M from CL); information not available. TDZ RWY 09: 371928.8N 0493526.1E (190M from CL); information not available.
3	*TWY edge and centre line lighting*	Edge: All TWYs Centre line: NIL
4	*Secondary power supply/switch-over time*	Available Switch-over time: 10 - 15 sec
5	*Remarks*	NIL

OIGG AD 2.16 HELICOPTER LANDING AREA

NIL

OIGG AD 2.17 ATS AIRSPACE

1	*Designation and lateral limits*	Rasht CTR: A circle, radius 30 NM centred at 371934.9N 0493656.8 (DVOR/DME)	Rasht ATZ: A circle, radius 7 NM centred at 371924N 0493704E (ARP)
2	*Vertical limits*	FL 175	3000 FT AMSL
3	*Airspace classification*	D	
4	*ATS unit call sign* *Language(s)*	Rasht TWR English / Persian	
5	*Transition altitude*	4000 FT AMSL	
6	*Remarks*	Approach Service is provided by Rasht TWR on frequency 122.700 MHZ	

OIGG AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	*Call sign*	*Frequency*	*Hours of operation*	*Remarks*
1	2	3	4	5
TWR	Rasht Tower	122.700 MHZ 121.900 MHZ 121.500 MHZ	0300-1700 Other times O/R	TWR Service and APP Emergency frequency
ATIS (INFO)	Rasht information	126.200 MHZ		

OIGG AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid, CAT of ILS (For VOR/ILS, give VAR)	*ID*	*Frequency*	*Hours of operation*	*Site of transmitting antenna coordinates*	*Elevation of DME transmitting antenna*	*Remarks*
1	2	3	4	5	6	7
DVOR/DME (5° E / 2017)	RST	112.600 MHZ CH 73X	H24	371934.8N 0493657.1E	-42 FT	
LOC 27 ILS CAT I (5° E / 2017)	IRST	109.900 MHZ	H24	371935.6N 0493510.0E		
ILS GP RWY 27		333.800 MHZ	H24	371933.5N 0493706.4E		3° RDH 58 FT
ILS DME RWY 27	IRST	CH 36X	H24	371933.5N 0493706.2E	-38 FT	

DVOR/DME unusable in counter clockwise direction in the FLW area:
AT 10 NM:
1- 260°- 240°, BLW 5000 FT AMSL
2- 240°- 215°, BLW 6500 FT AMSL
3- 215°- 190°, BLW 8000 FT AMSL
4- 190°- 155°, BLW 9500 FT AMSL
5- 155°- 130°, BLW 9000 FT AMSL
6- 130°- 115°, BLW 6000 FT AMSL
AT 25 NM:
1- 280°- 260°, BLW 8000 FT AMSL
2- 260°- 235°, BLW 9000 FT AMSL
3- 235°- 170°, BLW 10500 FT AMSL
4- 170°- 160°, BLW 11000 FT AMSL
5- 160°- 130°, BLW 10000 FT AMSL
6- 130°- 90°, BLW 7000 FT AMSL
7- 40°- 340°, BLW 3000 FT AMSL
8- 340°- 300°, BLW 4000 FT AMSL
AT 40 NM:
1- 280°- 260°, BLW 10000 FT AMSL
2- 260°- 230°, BLW 11000 FT AMSL
3- 235°- 170°, BLW 11500 FT AMSL
4- 170°- 160°, BLW 12000 FT AMSL
5- 160°- 130°, BLW 10000 FT AMSL
6- 130°- 90°, BLW 7000 FT AMSL
7- 90°- 40°, BLW 2000 FT AMSL
8- 40°- 340°, BLW 3000 FT AMSL
9- 340°- 300°, BLW 5500 FT AMSL
10- 300°- 280°, BLW 6500 FT AMSL

OIGG AD 2.20 LOCAL TRAFFIC REGULATIONS

NIL

OIGG AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

OIGG AD 2.22 FLIGHT PROCEDURES

Traffic pattern is defined as below:

a. For fighter and heavy fix wing ACFT 1500 feet,
b. For other fix wing ACFT 1000 feet and
c. For helicopter 500 feet.

Note: see AD 1.1.

OIGG AD 2.23 ADDITIONAL INFORMATION

1- Strolling dogs observed on the movement area.

2- Intensive bird's accumulation exists in the movement area and in the vicinity of AD, particularly in winter period and in short final RWY 27.

3- Heavy aircraft are authorized to make 180° turn only at the end of RWY in use or at RWY turn Pad.

4- Isolated aircraft parking position located at TWY C.

OIGG AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome Chart – ICAO ---------- AD 2 OIGG ADC

Standard Departure Chart - Instrument - ICAO ---------- AD 2 OIGG SID 1-1

AD 2 OIGG SID 1-2

AD 2 OIGG SID 1-3

Arrival Chart - Instrument - ICAO ---------- AD 2 OIGG STAR 1-1

AD 2 OIGG STAR 1-2

AD 2 OIGG STAR 1-3

AD 2 OIGG STAR 1-4

AD 2 OIGG STAR 1-5

AD 2 OIGG STAR 1-6

Instrument Approach Chart – ICAO ---------- AD 2 OIGG IAC 1-1

AD 2 OIGG IAC 2-1

AD 2 OIGG IAC 2-2

AD 2 OIGG IAC 2-3

AD 2 OIGG IAC 2-4