AD 2. AERODROM ES

OIYY AD 2.1 AERODROME LOCATION INDICATOR AND NAME

OIYY - YAZD / SHAHID SADOOGHI International

OIYY AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	*ARP coordinates and site at AD*	315422N 0541635E
2	*Direction and distance from (city)*	W, 5.3 NM from Yazd
3	*Elevation / Reference temperature*	4054 FT / 39°C
4	*MAG VAR / Annual change*	3° E (2016) / Information not available
5	*AD Administration, address, telephone, telefax, telex, AFS*	Iran Airports & Air Navigation Company (IAC) Yazd / Shahid Sadooghi Airport Postal code: 89471-73789 Yazd - Islamic Republic of Iran Tel: +9835-37218082-4, 37217775 Telefax: +9835-37218474 Telex: NIL AFS: OIYYYDYX
6	*Types of traffic permitted (IFR/VFR)*	IFR/VFR
7	*Remarks*	Email: yazd@airport.ir

OIYY AD 2.3 OPERATIONAL HOURS

1	*AD Administration*	0330 – 1130
2	*Customs and immigration*	H24
3	*Health and sanitation*	O/R
4	*AIS Briefing Office*	NIL
5	*ATS Reporting Office (ARO)*	H24 (available by ATS)
6	*MET Briefing Office*	NIL
7	*ATS*	H24
8	*Fuelling*	H24
9	*Handling*	Available during main carrier schedule flights, other times O/R
10	*Security*	H24
11	*De-icing*	NIL
12	*Remarks*	NIL

OIYY AD 2.4 HANDLING SERVICES AND FACILITIES

1	*Cargo - handling facilities*	Available by Iran air company
2	*Fuel / oil types*	Jet A1 - JP4
3	*Fuelling facilities/capacity*	Jet A1: 2 trucks, 42000 liters, 65 liters/sec and 20000 liters, 35 liters/ sec, No limitation JP4: provided in 18 liters barrel
4	*De - icing facilities*	NIL
5	*Hanger space for visiting aircraft*	NIL
6	*Repair facilities for visiting aircraft*	NIL
7	*Remarks*	Refueling unit Tel: +9835-37218833

OIYY AD 2.5 PASSENGER FACILITIES

1	*Hotels*	Available in the city
2	*Restaurants*	Available at AD and in the city
3	*Transportation*	Taxis and buses
4	*Medical facilities*	Hospital in the city, First aids at A/D
5	*Bank and Post Office*	Only bank is available
6	*Tourist Office*	Available in the city & AD
7	*Remarks*	NIL

OIYY AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	*AD category for fire fighting*	CAT 7
2	*Rescue equipment*	Available in accordance with AD category for fire fighting
3	*Capability for removal of disabled aircraft*	Coordinator for removal of disabled Aircraft: Aeronautical Operation Deputy Tell: +9835-37227760 & +9835-31018000 Email: yazd@airport.ir Max capability: MD83
4	*Remarks*	CAT 9 available for those non- scheduled flights which get prior permission at least 72 hours before EOBT from Yazd AD

OIYY AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	*Types of clearing equipment*	One blade fitted into truck
2	*Clearance priorities*	Information not available
3	*Remarks*	Information not available

OIYY AD 2.8 APRONS, TAXIWAYS

1	*Apron surface and strength*	Apron1: Concrete, PCN69/R/B/W/T Apron2: Asphalt, PCN60/F/B/X/T
2	*Taxiway width, surface and strength*	TWY A: 30M, Concrete, PCN69/R/B/W/T TWY B, C: 30M, Asphalt, PCN60/F/B/X/T
3	*Altimeter checkpoint location and elevation*	Coordinates: 315403.21N 0541706.38 E Position: between Stand NR 6 and 7 Elevation: 4036.5FT (1230.34M)
4	*Remarks*	Apron dimensions: Apron1: 252 x 120 Apron2: 420 x 120

OIYY AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	*Use of aircraft stand ID signs, TWY guide lines and parking guidance system of aircraft stands*	Taxiing guidance signs at all intersection with TWY and RWY and at all holding positions. Guide lines at apron Nose-in guidance at aircraft stand
2	*RWY and TWY markings and LGT*	RWY: Designation, THR, TDZ, centre line, edge & RWY end marked RWY lighting: See OIYY AD 2.14 TWY: Centre line, edge marked TWY lighting: See OIYY AD 2.15
3	*Stop bars*	NIL
4	*Remarks*	NIL

OIYY AD 2.10 AERODROME OBSTACLES

In approach / TKOF areas			*In circling area and at AD*		*Remarks*
1			2		3
RWY/Area affected	*Obstacle type Elevation/ HGT Markings/LGT*	*Coordinates*	*Obstacle type Elevation / HGT Markings/LGT*	*Coordinates*	
a	b	c	a	b	
13/TKOF 31/APCH	BTS Antenna 4236 FT AMSL NIL	315224 N 0541831 E	Building (GP Shelter) 4060 FT AMSL NIL	315336 N 0541721 E	
13/TKOF 31/APCH	BTS Antenna 4179 FT AMSL NIL	315246 N 0541819 E	GP ANTENNA 4078 FT AMSL NIL	315335.9N 0541721.0E	
			VOR Antenna 4076 FT AMSL NIL	315351.6 N 0541657.9 E	
			Building 4168 FT AMSL NIL	315406N 0541354E	

In approach / TKOF areas			*In circling area and at AD*		*Remarks*
1			2		3
RWY/Area affected	*Obstacle type Elevation/ HGT Markings/LGT*	*Coordinates*	*Obstacle type Elevation / HGT Markings/LGT*	*Coordinates*	
a	b	c	a	b	
			BTS Antenna 4229 FT AMSL -	315231N 0541756E	
			Building 4203 FT AMSL -	315408N 0541512E	
			Building (LOC Shelter) 3983 FT AMSL -	315512N 0541531E	
			Building 4206 FT AMSL -	315259N 0541857E	

OIYY AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	*Associated MET Office*	Yazd
2	*Hours of service* *MET Office outside hours*	H24 --
9	*ATS units provided with information*	Yazd TWR

Note: Subject concerning item 3 to 8 and 10 not available.

OIYY AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	*TRUE BRG*	*Dimensions of RWY (M)*	*Strength(PCN) and surface of RWY and SWY*	*THR coordinates* *THR geoid undulation*	*THR elevation and highest elevation of TDZ of precision APP RWY*
1	2	3	4	5	6
13	132.99°GEO	4100 x 45	60/F/B/X/T Asphalt	315503.01N 0541538.37E GUND –10 FT	THR 3984 FT
31	313.01°GEO	4100 x 45	60/F/B/X/T Asphalt	315332.24N 0541732.47E GUND –10 FT	THR 4054 FT

Slope of RWY - SWY	*SWY dimensions (M)*	*CWY dimensions (M)*	*Strip dimensions (M)*	→ *RESA*	*OFZ*
7	8	9	10	11	12
0.5 %	201 x 45	201 x 150	300 x 4820	NIL	NIL
0.5 %	201 x 45	201 x 150		NIL	NIL

Remarks
13
-AD Code Letter /Number : 4E

OIYY AD 2.13 DECLARED DISTANCES

RWY Designator	*TORA (M)*	*TODA (M)*	*ASDA (M)*	*LDA (M)*	*Remarks*
1	2	3	4	5	6
13	4100	4301	4301	4100	NIL
31	4100	4301	4301	4100	NIL

OIYY AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	*APCH LGT type LEN INTST*	*THR LGT colour WBAR*	*VASIS (MEHT) PAPI*	*TDZ LGT LEN*	*RWY Centre Line LGT LEN, spacing, colour INTST*	*RWY edge LGT LEN, spacing colour, INTST*	*RWY End LGT colour WBAR*	*SWY LGT LEN colour*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*	*8*	*9*	*10*
13	*SALS 420M LIH*	*Green Supplemented by WBAR*	*PAPI Left / 3° (62 FT)*	*NIL*	*NIL*	*4100 M 60 M White, LIH*	*Red*	*201 M Red*	*NIL*
31	*PALS 900M LIH*	*Green Supplemented by WBAR*	*PAPI Left / 3° (62 FT)*	*NIL*	*NIL*	*4100 M 60 M White, LIH*	*Red*	*201 M Red*	*NIL*

OIYY AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	*ABN location, characteristics and hours of operation*	On top of the control tower building, FLG G and W, EV 2 sec HN and during IMC
2	*LDI location and LGT* *Anemometer location and LGT*	NIL
3	*TWY edge and centre line lighting*	Edge: All TWYs Centre line: NIL
4	*Secondary power supply/switch-over time*	Available Switch-over time: 10 - 15 sec
5	*Remarks*	NIL

OIYY AD 2.16 HELICOPTER LANDING AREA

NIL

OIYY AD 2.17 ATS AIRSPACE

1	*Designation and lateral limits*	Yazd CTR: A circle, radius 30 NM centred at 315351.6N 0541657.7E (VOR/DME)	Yazd ATZ: A circle radius 7 NM centred at 315422N 0541635E (ARP)
2	*Vertical limits*	FL 175	7000 FT AMSL
3	*Airspace classification*	D	
4	*ATS unit call sign* *Language(s)*	Yazd TWR English / Persian	
5	*Transition altitude*	12000 FT AMSL	
6	*Remarks*	APP Service is provided by Yazd TWR on 122.700 MHZ	

OIYY AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	*Call sign*	*Frequency*	*Hours of operation*	*Remarks*
1	2	3	4	5
TWR	Yazd Tower	122.700 MHZ	H24	APP Service
		121.900 MHZ	H24	For ground movements
		121.500 MHZ	H24	Emergency frequency
		257.800 MHZ	H24	Military aircraft
ATIS (INFO)	Yazd Information	126.250 MHZ	0200-2000	

OIYY AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid, CAT of ILS (For VOR/ILS, give VAR)	*ID*	*Frequency*	*Hours of operation*	*Site of transmitting antenna coordinates*	*Elevation of DME transmitting antenna*	*Remarks*
1	2	3	4	5	6	7
NDB	YZD	402 KHZ	H24	315413.3N 0541713.8E	4005 FT	
VOR/DME (3° E / 2016)	YZD	117.700 MHZ CH 124X	H24	315351.6N 0541657.7E	4047 FT	
TACAN *	YZD	CH 75X	H24	315307.2N 0541802.9E	4072 FT	* IRIAF
ILS/DME RWY 31	IYZD	CH 26X		315335.9N 0541721.0E		
ILS GP RWY 31	-	329.300 MHz		315335.9N 0541721.0E	4052 FT	
LOC 31 ILS CAT I (3° E / 2016)	IYZD	108.900 MHz		315510.3N 541529.2E		

TACAN unusable in FLW area beyond 25 NM:
1- 030°- 080°, BLW FL 160.
2- 150°- 250°, BLW FL 220

VOR/DME unusable in the following area clockwise direction:

a- At 20 DME ARC:
1- 010°- 020°, BLW 7000 FT AMSL.
2- 020°- 030°, BLW 9000 FT AMSL.
3- 030°- 050°, BLW 11000 FT AMSL.
4- 050°- 070°, BLW 9000 FT AMSL.
5- 070°- 090°, BLW 7000 FT AMSL.
6- 090°- 140°, BLW 6000 FT AMSL.

b- At 40 DME ARC:
1- 360°- 030°, BLW 11000 FT AMSL.
2- 030°- 040°, BLW 12000 FT AMSL.
3- 040°- 060°, BLW 13000 FT AMSL.
4- 060°- 080°, BLW 12000 FT AMSL.
5- 080°- 110°, BLW 10000 FT AMSL.
6- 110°- 140°, BLW 11000 FT AMSL.
7- 140°- 150°, BLW 13000 FT AMSL.
8- 150°- 160°, BLW 15000 FT AMSL.
9- 160°- 180°, BLW 16000 FT AMSL.
10- 180°- 230°, BLW 17000 FT AMSL.
11- 230°- 250°, BLW 16000 FT AMSL.
12- 250°- 270°, BLW 14000 FT AMSL.
13- 270°- 280°, BLW 10000 FT AMSL.
14- 280°- 310°, BLW 9000 FT AMSL.
15- 310°- 350°, BLW 7000 FT AMSL.
16- 350°- 360°, BLW 8000 FT AMSL.

→ ILS: Inner coverage (17NM) of LOC restricted to (+35, -20) due to mountain in clearance area.

OIYY AD 2.20 LOCAL TRAFFIC REGULATIONS

1. Helicopters flying over Yazd city shall maintain 2500 FT AGL or above.
2. Fuel dumping area is located on area with following specifications:
   between radial 360 and 030, 15 to 30 DME from YZD VOR/DME with following coordinates:
   322352N 0541455E, 321855N 0543628E, 320624N 0542641E and 320852N 0541556E.

OIYY AD 2.21 NOISE ABATEMENT PROCEDURES

1. For noise abatement, if condition permit, RWY 13 may be used for arrivals and RWY 31 may be used for departures due to residential area on final RWY31.

OIYY AD 2.22 FLIGHT PROCEDURES

1. Traffic pattern is defined as below:
   a. For fighter and heavy fixed wing ACFT 5600 feet,
   b. For other fixed wing ACFT 5100 feet and
   c. For helicopter 4600 feet.

Note: see AD 1.1.

2. Landing and departing in opposite direction of RWY- in -use is not authorized due to safety consideration, except for aircraft in emergency situation if so, requested by the pilot of ACFT encountering emergency condition.

→ 3. All arriving aircraft to Apron shall contact Apron management unit at TWY entrance, according to the following table:

Service Designation	APRON MANAGEMENT
Call sign	MARSHALLER
Frequency	121.900 MHZ
Hours of operation	H24
Remarks	In case, aircraft stand not available, Aircraft shall hold on TAXIWAY D

OIYY AD 2.23 ADDITIONAL INFORMATION

1- Strolling dogs exist on the movement area.
2- Heavy and medium aircraft are permitted to make 180° turn only at the end of RWY in use.
3- Isolated aircraft parking position located at holding bay number 3 at right side of RWY 31(P3).
4- Keeping and storing of dangerous goods are done at holding bay number 6 at right side of RWY 31(P6).

OIYY AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome Chart – ICAO ---------- AD 2 OIYY ADC

Parking / Docking Chart – ICAO ---------- AD 2 OIYY PDC

Aerodrome Obstacle Chart - ICAO Type A ---------- AD 2 OIYY AOC 1

Standard Departure Chart - Instrument – ICAO ---------- AD 2 OIYY SID 1-1
AD 2 OIYY SID 1-2
AD 2 OIYY SID 1-3
AD 2 OIYY SID 1-4
AD 2 OIYY SID 2-1
AD 2 OIYY SID 2-2
AD 2 OIYY SID 2-3
AD 2 OIYY SID 2-4

Standard Arrival Chart - Instrument – ICAO---------- AD 2 OIYY STAR 1-1
AD 2 OIYY STAR 1-2
AD 2 OIYY STAR 1-3

AD 2 OIYY STAR 1-4
AD 2 OIYY STAR 2-1
AD 2 OIYY STAR 2-2
AD 2 OIYY STAR 2-3
Instrument Approach Chart – ICAO ---------- AD 2 OIYY IAC 1-1
AD 2 OIYY IAC 2-1
AD 2 OIYY IAC 2-2
AD 2 OIYY IAC 2-3
AD 2 OIYY IAC 2-4
AD 2 OIYY IAC 2-5
AD 2 OIYY IAC 2-6
AD 2 OIYY IAC 2-7
AD 2 OIYY IAC 4-1